

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Catalog | October 2022



Altivar Machine ATV320

Variable speed drives


www.se.com

Life Is On Schneider Electric




Quick access to product information

Get technical information about your product




Each commercial reference presented in a catalog contains a hyperlink. Click on it to obtain the technical information of the product:

- Characteristics, Dimensions and drawings, Mounting and clearance, Connections and schemas, Performance curves
- Product image, Instruction sheet, User guide, Product certifications, End of life manual




Find your catalog



> With just 3 clicks, you can access the Industrial Automation and Control catalogs, in both English and French

> Consult digital automation catalogs at Digi-Cat Online




- Up-to-date catalogs
- Embedded product selectors,360° pictures
- Optimized search by commercial references

Select your training

> Find the right Training for your needs on our Global website

> Locate the training center with the selector tool, using this link



Life Is On Schneider Electric



Digital tools to quickly select your Altivar Machine ATV320 solution

Product selector for ATV320

- Easy selection of the ATV320 commercial reference
- Expand it with options and accessories
- Get the Bill of Material in standard format
- Drop it into the product cart
- Access technical information and documentation

Scan or click on the QR code

EcoStruxure™ Motor Control Configurator

- From your application, select your drive reference
- Expand it with coordinated combination, options, and accessories
- Convert into Bill of Material, add the product to the cart
- Directly access product documentation
- Save, rework, share your solution with unique ID

Scan or click on the QR code

EcoStruxure™ Motor Management Design

- From your project, perform electrical design calculation
- Compare direct-on-line, soft starter, and variable speed drive
- Verify starting feasibility from mechanical standpoint
- Verify that power factor and harmonics levels objectives are met
- Build a complete Motor Management solution: circuit breakers, soft starters, drives, contactors, MCC panels, power quality monitoring
- Get a summary report with calculations and recommended offers

Scan or click on the QR code

Life Is On | Schneider Electric



Altivar

Discover Altivar

Variable speed drives and soft starters

Altivar variable speed drives and soft starters deliver top performance in motor control applications across machines, processes, and buildings. With built-in intelligence, these smart connected devices gather and share data to improve operational efficiency, safety, and reliability.

Explore our offer

- Altivar Process
- Altivar Machine
- Altivar Building
- Altivar Soft Starters

Life Is On Schneider Electric



Green Premium™

Enhance sustainability with Altivar™ Machine drives

Superior environmental performance thanks to upgradability and modernization solutions.

Altivar Machine is **RoHS** and **REACH** compliant
- Transparent environment information
- Life Cycle Analysis, compliant with ISO14025
- Circular instructions

Altivar Machine drives brings key benefits to our machine-builders in achieving superior upgradable performance by enhancing its embedded functionality, performance of capacity, for both, hardware and software.

The additional power options and the firmware upgradability capabilities of the Altivar Machine help our customers to maximize the machine control continuity and operation, as well as reducing the operational expenses, by avoiding the change of their drive or the modification of the existing installation, as a retrofit.

Benefits

- Maximize production and energy efficiency
- Reduce your OPEX
- Easy scalability of your Automation system
- Future-ready solution for Industry 4.0
- Improve power quality of your system with a low investment
- Improve the safety, integration, and performance of your application
- Optimize your maintenance cost and the Drives Lifetime



...SUSTAINABILITY READY

Use the Motor Management tool to calculate **your energy savings**.

Green Premium™ Sustainable performance, by design

Programmable function & embedded Safety function

The embedded programmable function can be applied in flexible applications and user can update the Safety functions based on need as well. These 2 functions are all software base, it do not require any additional hardware for achieving it.

Options (Line choke, Motor choke, EMC filer, Regenerative kit)

The power options of Altivar Machine brings to customers the possibility to improve their installation's power quality and efficiency.

Communication & Wi-Fi Modules

The additional communication modules allow our customers to easily integrate Altivar Machine drives in their scalable Automation system. Together with the Wi-Fi access point, brings easy access to the real data provided by the drive, helping the digitalization and the easy integration of the drive in the Industry 4.0 technologies.

Firmware Update & Service expertise

Thanks to our global network of service experts, our customers have the possibility of upgrading the Drive's firmware and modernizing its hardware to extend the Drives lifetime.
As part of our circular ambition we are currently deploying a global take-back platform for End of Use products which are either refurbished to "as good as new" state in our agreed repair centers,or dismantled and recycled.

Experience our offer

For more information regarding the compatibility of the options, please visit us in se com/drives

General contents

Altivar Machine ATV320 variable speed drives

Introduction to EcoStruxure Machine . . . . . *page 2*

Altivar Machine offer for Original Equipment Manufacturers (OEM) . . . . . *page 4*

■ **Altivar Machine ATV320 Variable speed drives**

□ Machine solution ..... *page 6*
□ Applications ..... *page 6*
□ Presentation ..... *page 8*
□ Innovative functions ..... *page 10*
□ The offer ..... *page 12*
□ Description ..... *page 15*
□ Standards and certifications ..... *page 15*
□ References
- Drives with compact control block ..... *page 16*
- Drives with book control block ..... *page 18*
- Drives for harsh environment IP66/IP65 ..... *page 19*
- Accessories ..... *page 20*
- Mounting accessories ..... *page 20*
- Replacement parts ..... *page 23*

□ ATV Regenerative units ..... *page 24*

■ **Options**

□ Dialog and configuration tools
- DTM ..... *page 26*
- Simple Loader and Multi-Loader configuration tools ..... *page 27*
- Remote display terminal ..... *page 28*
- Remote graphic display terminal, accessories ..... *page 29*

□ Combinations: options for ATV320 drives
- Drive with compact control block ..... *page 32*
- Drive with book control block ..... *page 36*
- Option modules ..... *page 36*

□ Braking resistors ..... *page 38*
□ Line chokes ..... *page 40*
□ Motor chokes ..... *page 41*
□ Additional EMC input filters ..... *page 42*
□ Option module adapter ..... *page 44*
□ Speed monitoring module ..... *page 45*

■ **Communication buses and networks**

□ Presentation ..... *page 46*
□ Functions ..... *page 47*
□ References
- Modbus serial link ..... *page 47*
- CANopen machine bus ..... *page 48*
- Modbus TCP network and EtherNet/IP network ..... *page 50*
- PROFIBUS DP, DeviceNet bus, EtherCAT bus, POWERLINK network, ProfiNet network ..... *page 51*

■ **Motor starters** ..... *page 52*

■ **Dimensions**

□ Altivar Machine ATV320 Variable speed drives
- Drives with compact control block ..... *page 56*
- Drives with book control block ..... *page 58*

□ Line chokes, Motor chokes, Braking resistors, Additional EMC input filters ..... *page 60*

■ **Field services** ..... *page 61*

■ **Product reference index** ..... *page 63*

To be competitive in today's digital era, machine builders must be innovative. Smart machines, those that are better connected, more flexible, more efficient, and safe, are enabling machine builders to innovate in ways never before possible.

EcoStruxure, Schneider Electric's open, IoT-enabled architecture and platform, offers powerful solutions for the digital era. As part of this, EcoStruxure Machine brings powerful opportunities for machine builders and OEMs, empowering them to offer smart machines and compete in the new, digital era.

EcoStruxure Machine brings together key technologies for product connectivity and edge control on premises, and cloud technologies to provide analytics and digital services. EcoStruxure Machine helps you bring more innovation and added value to your customers throughout the entire machine life cycle.

Innovation at Every Level for Machines is full systems across three layers:

– Connected products
Our connected products for measuring, actuating, device level monitoring, and control adhere to open standards to provide unmatched integration opportunities and flexibility

– Edge Control
We are IIoT-ready with a proven set of tested and validated reference architectures that enable the design of end-to-end open, connected, and interoperable systems based on industry standards. Ethernet and OPC UA facilitates IT/OT convergence meaning machine builders reap benefits from web interfaces and cloud.

– Apps, Analytics & Services
Seamless integration of machines to the IT layer allows the collection and aggregation of data ready for analysis – for machine builders and end users alike this means increased uptime and the ability to find information faster for more efficient operations and maintenance.

These levels are completely integrated from shop floor to top floor. And we have cloud offers and end-to-end cybersecurity wrapped around.


EcoStruxure Machine makes it easier for OEMs/ machine builders to offer their customers smarter machines. The advent of smart machines is driven by the changing needs of end users:

– Evolving workforce
– Reducing costs
– Dynamic markets
– Shorter life cycles
– Prioritizing safety and cybersecurity

EcoStruxure Machine provides one solution for the whole machine life cycle:

– With Smart Design & Engineering the time to market is reduced by up to 30% using our automated engineering and the simulation capabilities
– During Commissioning & Operation of the machine, resources such as energy, material and loss can be improved, and with seamless integration to the IT world efficiency can be improved by up to 40%
– Smart Maintenance & Services reduces the time for corrective actions up to 50%

EcoStruxure™ Machine



* The Schneider Electric industrial software business and AVEVA have merged to trade as AVEVA Group plc, a UK listed company. The Schneider Electric and Life is On trademarks are owned by Schneider Electric and are being licensed to AVEVA by Schneider Electric.


Altivar Machine variable speed drives

Altivar Machine offer for Original Equipment Manufacturers

Application segments	General	**Material handling, packaging, textiles, hoisting, mechanical actuators, material working**			
	Specific	**Conveyors, carton packers, gantry cranes, woodworking, metal processing, fans, etc.**			
					
Degree of protection		IP20	IP20	IP66	IP65
Power range for 50..60 Hz supply	Single-phase 200...240V	0.18...2.2 kW/*0.25... 3 HP*	0.18...2.2 kW/*0.25... 3 HP*	0.18...2.2 kW/*0.25... 3 HP*	0.18...2.2 kW/*0.25... 3 HP*
	Three-phase 200...240V	0.18…15 kW/*0.25…20 HP*	-	-	
	Three-phase 380...500V	0.37…4 kW/*0.5…5 HP*	0.37…15 kW/*0.5…20 HP*	0.37…7.5 kW/*0.5…10 HP*	0.37…7.5 kW/*0.5…10 HP*
	Three-phase 525...600V	0.75…15 kW/*1…20 HP*	-	-	
Drive	Output frequency	0.1…599 Hz			
	Control type Asynchronous motor	U/F ratio (2 points, 5 points, energy saving, quadratic), Flux vector control without sensor (Standard and Energy saving)			
	Synchronous motor	Vector control without sensor			
	Motor sensor Integrated	-			
	as an option	RS422 (speed monitoring)			
	Overload torque performance	Up to 200% Tn of over torque, and 170% tn of braking torque for open loop motor control			
Functions	**Advanced functions**	■ Control of asynchronous and synchronous motors; including IE2, IE3 and PM motors in open loop ■ MachineStruxure integration in SoMachine ■ Operation in Velocity mode and Torque control (with current limitation) ■ Customizable and flexible application functions with ATV Logic (up to 50 function blocks) ■ Numerous application functions for targeted application segments ■ Embedded safety functions dedicated to targeted application segments			
	Integrated safety functions	STO (up to SIL3 / PLe), SS1, SLS, SMS, GDL			
	Number of preset speeds	16			
Number of integrated I/O	Analog inputs	3: 1 Bipolar differential ±10 V, 1 with Voltage 0...10 V and 1 with current (0-20 mA)			
	Digital inputs	6: 4 configurable (positive or negative logic), 1 with PTC probe input, 1x20kHz pulse input			
	Analog outputs	1: Configurable as voltage (0...10 V) or current (0-20 mA)			
	Digital outputs	1: Configurable as sink or source			
	Relay outputs	2: 1 with NO/NC contacts and 1 with NO contacts			
	Safety function inputs	1 + 4: 1 with STO and 4 configurable for safety functions from digital inputs			
Communication	Integrated	Single port compatible with CANopen and Modbus Serial line			
	Optional	Ethernet IP and Modbus TCP, CANopen RJ45 Daisy Chain, Sub-D, and screw terminals, PROFINET, Profibus DP V1, EtherCAT, DeviceNet and PowerLink			
Configuration and runtime tools		Integrated Display, DTM (Device Type Manager), SoMove software, simple loader (optional), Multiloader (optional), and remote graphic terminal (optional).			
Standards and certifications		EN 61800-5-1, EN 61800-3 (Environments 1 and 2, category C2, C3), EN 61800-5-2 up to SIL3 level, EN ISO 13849-1 up to PLe level, EN ISO 13849-2, EN 62061, EN 50495, EN 61800-9-2, EN IEC 63000, CSA 22.2N274, EN 61000-3-2, CSA 22N4 (ATV320●●●●●B)			
		CE, UKCA, ATEX, UL 508C, UL61800-5-1, CSA 22.2 N274, GOST, EAC, CTICK, SIL, NOM (ATV320●●●●●B), KC (ATV320●●●●●B, ATV320●●●●●C)			
References		**ATV320●●●●●C**	**ATV320●●●●●B**	**ATV320●●●●●W**	**ATV320●●●●●WS**

More technical information on www.se.com

Variable speed drives
Altivar Machine ATV320



I/O Scanner (Industrial Ethernet Manager)

Advanced Variable Speed drive solution - Altivar 320

The Altivar Machine ATV320 provides IP20 and IP6x variable speed drive for three-phase synchronous and asynchronous motors in open loop control, and incorporates functions suitable for the most common applications, including:

- Torque and speed accuracy at very low speed, high dynamic performance with flux vector control without sensor.
- Extended frequency range for high-speed motors.
- Parallel connection of motors and special drives using voltage/frequency ratio.
- Static speed accuracy and energy saving for open-loop synchronous motors.

The Altivar Machine ATV320 series focus on easy integration for simple and advanced machine requirements with proven motor control and connectivity.

It offers enhanced automation capabilities and performance for industrial machine applications:
- Effective control of asynchronous and permanent magnet motors
- Complete integration into any system architecture (Ethernet, CANopen, Profibus, etc.)
- Compact and book format for integration in a variety of different cabinet types
- Integrated safety function for compliance with functional safety standards
- Enhanced resistance to polluted atmospheres

By taking account of constraints on product setup and use right from the design stage, Schneider Electric simplifies the integration of the Altivar Machine ATV320 drive into industrial machines. It features more than 150 functions. It is robust, easy to install, and compliant with the Machinery Directive 2006/42/EC.

ATV320 is fully integrated inside Schneider Electric's **EcoStruxure Machine** through DTM. PLCopen-compliant libraries. **EcoStruxure Machine** can be used to develop, configure, and set up an entire machine in a single software environment. Using FDT/DTM technology, it is possible to configure, control, and diagnose Altivar Machine ATV320 drives directly in SoMachine and SoMove software by means of the same software brick (DTM).

With seamless integration under this platform, Altivar Machine ATV320 benefits from the advantage of shorter engineering and design times. Optional Ethernet-based communication capability makes it accessible to production data at any level of automation system.



Material handling application



Hoisting application

Applications

Altivar Machine ATV320 drives incorporate functions suitable for the most common applications, including:

Material handling

- Very quick response times on transmission of a command: 2 ms (± 0.5 ms)
- Reference via pulse input as analog input
- Control via built-in CANopen network or optional communication networks
- Position control via limit switches with time optimization at low speed
- Multiple parameter settings via parameter set switching
- Provide high protection version IP65/66 product, with/without vario swtich

Hoisting

- Brake control adapted for horizontal and vertical movement
- Brake feedback management
- Load measurement using weight sensor
- High-speed hoisting with rope slack
- Limit switch management
- Dedicated speed monitoring function with optional card
- Multiple motors/configurations
- High speed switching function
- DC sharing and optional compact design regenerative braking unit

Variable speed drives: page 16
Dialog, configuration tools: page 26
Combinations: page 32
Dimensions: page 56



Packing and packaging machines

Applications (continued)

Packaging machines

- Up to 50 Hz of the bandwidth
- Control via built-in CANopen network or optional communication networks
- Book format enables to save space inside enclosure
- Advanced synchronous open loop control achieve energy saving performance
- Direct mounting of short circuit breaker on drive without wiring



Material working application

Material working

- 5 integrated safety functions secure operation
- Control via built-in CANopen network or optional communication networks
- Fastest possible controlled stop on loss of line supply
- Motor thermal monitoring and protection function
- Torque limitation
- DC sharing and optional compact design regenerative braking unit(ATV regene)
- Very quick response times on transmission of a command: 2 ms (± 0.5 ms)
- 200% over torque ability, allow more dynamic response



Textile application

Textile

- High protection degree version: IP65/IP66
- High resolution of the digital speed reference
- Use of synchronous motor, irrespective of load, helps to assure speed accuracy and energy saving
- High bandwidth with high-performance speed loop
- Spooling function/ Traverse control
- DC sharing and optional compact design regenerative braking unit
- Fastest possible controlled stop on loss of line supply secure continuous working machine
- Control via built-in CANopen network or optional communication networks
- Book format enables to save space inside enclosure



Pumping

Pumping

- Dedicated motor control law for pumping and fan with optimized energy saving
- PID regulator with preset reference
- Multi motor parameter set
- ATV logic, programming function integrated in drive
- High protection degree enclosure
- Alarm management function
- Process load monitoring function
- Fault inhibition function,used in emergency situation such as smoke extraction.

General machine control

- ATV logic, programming function integrated in drive
- PID regulator
- 16 preset speed functions.
- Reference operation
- Line contactor and output contactor command
- Speed or torque control with current limitation
- Control via built-in CANopen network or optional communication networks
- DC bus management
- 6 motor control laws: Standard V/F,V/F 5 points, Sensorless vector control, Synchronous permanent magnet motors control, Variable torque, and Energy saving, allow user to adapt different machine behavior.





Presentation - ATV320 IP20 Product

The Altivar Machine ATV320 IP20 product is a variable speed drive for three-phase asynchronous and synchronous motors from 0.18 to 15 kW.
The Altivar Machine ATV320 drive is robust, simple to commission, and easy to integrate into different machine layouts and cabinets. It can also be integrated into commonly used automation architectures. Altivar Machine ATV320 variable speed drives are particularly suitable for applications involving simple industrial machines. Furthermore, Altivar Machine ATV320 embeds many practical functions so that advanced application requirements can be covered. Altivar Machine ATV320 is designed to improve machine performance and increase machine availability while reducing the total machine cost.

Flexible

There are 2 different formats for IP20 products, book and compact:
- The book format *(1)*, 45 and 60 mm *(1.77 and 2.63 in.)* wide, is designed to be mounted side-by-side to save significant space on the installation foot print.
- The compact format, 72 to 180 mm *(2.83 to 7.08 in.)* wide, is designed to be integrated in compact electrical cabinets (200 mm *(7.87 in.)* cabinet depth or less) or mounted directly on the machine frame.

Advanced connectivity

Advanced connectivity allows the Altivar Machine ATV320 to operate in commonly used automation architectures; CANopen and Modbus RTU communication protocols are embedded and various communication fieldbus options are offered based on:
- Modbus TCP, EtherNet/IP, PROFINET, EtherCAT, POWERLINK
- Modbus serial link, CANopen, ProfibusDP, DeviceNet.

Robust design

Altivar Machine ATV320 variable speed drives can operate in harsh environment conditions:
- Up to 50 °C/*122 °F* without derating
- Up to 60 °C/*140 °F* with derating without the need for an additional fan

The printed circuit boards are coated according to IEC 60721-3-3 class 3C3 for industrial environments and 3S2 for solid particles.

Effective motor control

Control of both asynchronous and synchronous motors is both simple and effective. Altivar Machine ATV320 offers +/- 10% accuracy of motor slip in open-loop control with asynchronous motors.

Functions dedicated to synchronous motors

Altivar Machine ATV320 variable speed drives integrate new functions for synchronous motors that are suitable for the majority of commercially-available motors.
- Simplified setting due to the reduced number of configuration parameters (4 maximum)
- Autotuning of the drive/motor combination
- High-frequency injection for high performance in open-loop mode

As standard, Altivar Machine ATV320 drives support to drive synchronous motor in open loop control. This motor control law could help customer to reduce energy consumption.
Each ATV320 drive has a corresponding synchronous motor pre-selected in the SoMove software. User could select and order synchronous motor from the software easily and reduce time to design.

(1) The book format products are up to 4 kW and compatible supply voltages are 200-240V single phase and 380-500V three phase.



ATV320U02M2W



ATV320U02M2WS

Presentation - ATV320 IP66/65 Product

The Altivar Machine ATV320 IP66/65 drive is a variable speed drive for three-phase asynchronous and synchronous motors from 0.18 to 7.5 kW. Altivar high IP,

- offers **washable drives** for harsh environments, if users want to clean the dust & chemical pollution outside of drives.
- meets EMC C2/C3 performance to suppress the emission effect on long cable application.
- has **no external fan**, it reduces operational TOC site.
- heavy duty embedded from -10 °C/*14 °F* to 50 °C/*122 °F* for operational frequency (without derating below 4kHz switching frequency).
- has **Integrated PLC and safety functions (SLS,SMS,SS1,GDL,STO)** that save the automation setup cost of hybrid automation system which is widely applied in material handling segment.

With flexibility and functionality, ATV320 IP66/65 is the only IP drives, that offers with **flexible panel building ability** to users.

Flexible

There are 2 different sizes for ATV320 IP66/65 products with different depths (W x H x D dimensions):

- For 0.18...4 kW (*0,25...5 HP*), size 1: 250 mm x 340 mm x (182 or 200 or 235 mm)
  9.84 in x 13.39 in x (7.17 or 7.87 or 9.25 in)
- For 5.5 ...7.5 kW (*7.5...10 HP*), size 2: 320 mm x 521 mm x (300 or 335 mm)
  12.60 in x 20.51 in x (11.81 or 13.19 in)

For higher IP protection offers enclosed with two types:

- IP66 drives without Vario disconnect switch
- IP65 drives with Vario disconnect switch

The IP66/65 drives provide higher environmental resistance, and open the possibility to design with the customized ground plate (VW3A9911 & VW3A9912) and front cover of the drive, also with 2 holes in the front reserved for integrating control and signaling units.

Altivar Machine ATV320 offers variety of supply possibilities:

- 200-240 V single phase: up to 2.2 kW
- 380-500 V three phase: up to 7.5kW

Advanced connectivity

Advanced connectivity allows the Altivar Machine ATV320 to operate in commonly used automation architectures; CANopen and Modbus RTU communication protocols are embedded and various communication fieldbus options are offered based on:

- Modbus TCP, EtherNet/IP, PROFINET, EtherCAT, POWERLINK
- Modbus serial link, CANopen, ProfibusDP, DeviceNet.

Robust design

Altivar Machine ATV320 variable speed drives can operate in harsh environment conditions:

- Up to 50 °C/*122 °F* without derating
- Up to 60 °C/*140 °F* with derating without the need for an additional fan

The printed circuit boards are coated according to IEC 60721-3-3 class 3C3 for industrial environments and 3S2 for solid particles.

Effective motor control

Control of both asynchronous and synchronous motors is both simple and effective. Altivar Machine ATV320 offers +/- 10% accuracy of motor slip in open-loop control with asynchronous motors.

Features dedicated for material handling solution

Simplified setting due to the reduced number of configuration parameters (4 maximum)

- 6 preset speed functions
- Multiple parameter settings via parameter set switching
- External fan-less design, 50°C without derating below.
- 3 analog inputs, VSD can act as signal monitors.
- DC injection for fast stop
- DC bus connection to safe energy
- Jog operation
- PID regulator
- Positioning by limit switches or sensors
- Parameter switching
- Automatic restart







ATV320 with customized design

References:
page 16

Innovative functions *(1)*

PF600367



Example of an application (scrolling billboard) requiring a typical ATV Logic sequence

PF600366



Example of an application requiring the use of safety functions

Application functions

Altivar Machine ATV320 variable speed drives feature 150 functions, including:
- Configurations: standard or customizable
- Application-specific functions for material handling, textiles, hoisting, mechanical actuators
- Adjustable switching frequency (adjusted motor current, reduced motor noise)
- Adjustable monitoring function to create “My Menu” function to obtain user-specific monitoring
- Ability to upload/download drive configurations with the power off

ATV Logic

ATV Logic is used to adapt Altivar Machine ATV320 variable speed drives to specific applications by means of customizable integrated control system functions.

The integrated control system functions featuring ATV Logic can be used to perform simple operations without adding further devices, which reduces costs.
ATV Logic is programmed via the SoMove configuration software (consult the SoMove catalog for more information) and provides access to the following functions:
- Arithmetical operations, Boolean operators, counters, timers, etc.
- Programming of up to 50 functions by an automated sequence
- Access to the drive’s internal variables
- Use internal function block such as timer,counter,and logic unit to achieve customized & advanced function as user wants.

Compatibility mode

ATV320 has a dedicate function of compatibility mode which enables customer to replace a legacy product ATV32 without changing PLC program. Machine builders will benefit for their maintenance and service request from their end users, regardless of the type of the network fieldbus connected. This function will reduced the down-time of machines and improved its productivity.

Safety functions

The Altivar Machine ATV320 range of variable speed drives provides integrated safety functions (according to standard IEC 61508) comparable with performance level “e” (PL e) according to standard ISO/EN 13849-1-2.

The Altivar Machine ATV320 drive software includes 5 safety functions that help machines meet safety requirements, whether or not they are used in conjunction with a Preventa safety module *(2)*:
- STO: Safe Torque Off
- SLS: Safely Limited Speed
- SS1: Safe Stop 1
- SMS: Safe Maximum Speed
- GDL: Guard Door Locking

These safety functions are configured using SoMove configuration software.
For more information, please refer to the SoMove catalog.

***Note**: To set up the safety functions, please refer to the ATV320 Safety Functions manual.*

Innovative Tool *(1)*

Altivar Efficiency Calculator

This tool calculates the level of energy efficiency of your variable speed drive according to the Ecodesign standard EN/IEC 61800-9-2.


Calculate your level of energy efficiency with the Altivar Efficiency Calculator

- **Drive Efficiency (CDM Complete Drive Module)**
  Drive performance is determined according to 8 operating points considering torque and speed


- **System Efficiency (PDS Power Drive System)**
  System performance is determined according to 8 operating points considering torque and speed. This includes the efficiency of the variable speed drive and its motor.

(1) Non-exhaustive list; please consult our website.
(2) Please refer to our machine safety web page


References:
page 16




Activation of the STO safety function




Activation of the SLS safety function



Activation of the SS1 safety function



Activation of the SMS safety function



Activation of the GDL safety function (example of stop type SS1)

Integrated safety functions *(1)*

Safe Torque Off (STO) safety function

This function brings the machine safely into a no-torque state and/or prevents it from starting accidentally.

Safely Limited Speed (SLS) safety function

The SLS integrated safety function can be initiated by activation of safety function inputs. This function prevents the motor from exceeding the specified speed limit. If the motor speed exceeds the specified speed limit value, safety function STO is triggered.

Safe Stop 1 (SS1) safety function

The SS1 integrated safety function causes a category 1 safe stop.
This function monitors the deceleration according to a dedicated deceleration ramp and safely shuts off the torque once standstill has been achieved.

Safe Maximum Speed (SMS) safety function

This function prevents the speed of the motor from exceeding the predefined speed limit.

- 2 different speed limits can be defined and can be selected by logic inputs.
- If the motor speed exceeds the predefined speed limit value, safety function STO is triggered.

Once the SMS function is configured, it is continuously active.

Guard Door Locking (GDL) safety function

This function allows you to release the guard door lock after specified delay when the motor power is turned off. The specified delay is chosen according to the type of stop.
The front door of the machine can be opened only after the motor is stopped; this function helps to ensure the safety of the machine operator.

Setting up the integrated safety functions

Setting up the integrated safety functions in the Altivar Machine ATV320 drive does not require any options or additional accessories.
The functions are connected directly to the drive's digital inputs and can only be configured using SoMove setup software.
For more information, please refer to the SoMove catalog.

(1) Please refer to the ATV320 Safety Functions manual.

References:
page 16



ATV320U02M2C...U07M2C



ATV320U11M2C...U22M2C
ATV320U04N4C...U15N4C



ATV320U02M2B...U07M2B
ATV320U04N4B...U15N4B



ATV320U11M2B...U22M2B
ATV320U22N4B...U40N4B



ATV320U07N4W...U40N4W
ATV320U07N4WS...U40N4WS



ATV320U55N4W...U75N4W
ATV320U55N4WS...U75N4WS



CANopen communication module with RJ45 connectors



CANopen communication module with SUB-D connector



CANopen communication module with connection via terminals

The offer

The Altivar Machine ATV320 range of variable speed drives covers motor power ratings from 0.18 kW/ *0.25 HP* to 15 kW/*20 HP* with 4 types of power supply in book and compact control block design:

- 200 V…240 V single-phase, 0.18 kW/*0.25 HP* to 2.2 kW/*3 HP* (**ATV320U●●M2B**, **ATV320U●●M2C**, **ATV320U●●M2W**, **ATV320U●●M2WS**)
- 200 V…240 V three-phase, 0.18 kW/*0.25 HP* to 15 kW/*20 HP* (**ATV320●●●M3C**)
- 380 V…500 V three-phase, 0.37 kW/*0.50 HP* to 15 kW/*20 HP* (**ATV320U●●N4C, ATV320●●●N4B**)
- 380 V…500 V three-phase, 0.37 kW/0.50 *HP* to 7.5 kW/10 HP (**ATV320●●●N4W, ATV320●●●N4WS**)
- 525 V…600 V three-phase, 0.75 kW/*1 HP* to 15 kW/*20 HP* (**ATV320●●●S6C**)

References suffix meaning:

- Ending with “B” indicate that the product has a book control block
- Ending with “C" indicate that the product has a compact control block and a compact format *(1)*
- Ending with "W" indicate the IP66 drives without Vario Switch.
- Ending with "WS" indicate IP65 drives with Vario Switch.

Altivar Machine ATV320 drives integrate the Modbus and CANopen communication protocols as standard. Both can be accessed via the RJ45 connector on the front of the drive. To simplify connection of the Altivar Machine ATV320 drive to the CANopen machine bus, 3 dedicated communication modules are available with different connectors:

- CANopen Daisy Chain module with 2 RJ45 connectors
- CANopen module with 9-way SUB-D connector
- CANopen module with 5-way terminal block

In addition to the Modbus and CANopen standard protocols, Altivar Machine ATV320 drives can be connected to the main industrial communication buses and networks by adding one of the following optional communication modules:

- Modbus/TCP - Ethernet/IP
- PROFIBUS DP V1
- DeviceNet
- EtherCAT
- POWERLINK
- PROFINET

Integrated EMC filters

Altivar 320, have built-in EMC filter in ATV320U●●M2B, ATV320U●●M2C, ATV320●●●N4B, ATV320●●●N4C and ATV320●●●W● drives to meet the EMC standard.

Drive	Maximum length of shielded cable *(2)(3)* according to	
	IEC/EN 61800-3 Category C2	IEC/EN 61800-3 Category C3
	m	m
ATV320●●●M2●	10	10
ATV320U04N4C...U15N4C	10	10
ATV320U22N4C...U40N4C	10	20
ATV320U04N4B...U15N4B	5	5
ATV320U22N4B...U40N4B	10	20
ATV320U55N4●...U75N4●	2	20
ATV320D11N4●...D15N4●	_	30
ATV320U02M2W●...U22M2W●	10	10
ATV320U04N4W●...U75N4W●	10	10

The EMC filter enables compliance with standard IEC/EN 61800-3, category C2 or C3 in environment 1 or 2 and to comply with the European Electromagnetic Compatibility Directive (EMC).

(1) For the book format, several drives can be mounted side-by-side to save space.
(2) If motors are connected in parallel, it is the total cable length that should be taken into account.
(3) The maximum motor cable lengths is at 4 kHz switching frequency.

EMC standard description				
IEC 61800-3 Category	**C1**	**C2**	**C3**	**C4**
Environment	1st environment	1st or 2nd environment (choice of the user)	2nd environment	
Supply voltage/current	< 1000 V	–	–	> 1000 V, or > 400 A or IT supply network
Knowledge and requirement	No requirements	Installation and commissioning by EMC expert only	EMC plan required	–

The EMC filter enables compliance with standard IEC/EN 61800-3, category C2 or C3 in environment 1 or 2 and to comply with the European Electromagnetic Compatibility Directive (EMC).

EMC standards		
Catergory	**Subcategory**	**Test standard**
Emission	Radiated noise	CISPR11 (EN55011)
	Conducted noise	CISPR11 (EN55011)
Immunity	Electrostatic Discharge (ESD) test	IEC61000-4-2
	Radioactive radio-frequency magnetic contactor field	IEC61000-4-3
	Electrical fast transient (EFT)/burst transients test	IEC61000-4-4
	Electrical Surge Test	IEC61000-4-5
	Immunity to conducted disturbances induced by radio-frequency fields	IEC61000-4-6
	Voltage dip/interruption of power	IEC61000-4-11

IEC 60068-2	
Description	**Test and endurance standards**
Temperature test	IEC 60068-2-2
Vibration test	IEC 60068-2-6
Schock test	IEC 60068-2-27
Shake test	IEC 60068-2-29

The offer (continued)

Accessories and external options


Accessories and external options are available with Altivar Machine ATV320 drives. The type of external accessories and options depends on the drive rating.

Accessories

- UL Type 1 conformity kits, plates for direct mounting on 35 mm/*1.38 in.* rails, etc.
- Bracket for direct mounting of GV2/ATV320U●●●●B circuit breaker
- Adapter for mounting the control module at 90°, for mounting the power module on its side, keeping the control module visible and accessible
- Daisy chain DC bus cordsets for daisy chain connection of the DC bus

External options

- Braking resistors
- Line chokes
- Motor chokes
- Additional EMC filters
- Adapter extension module for compact control block drive
- Speed monitoring module



ATV320 dialog and configuration tools

Dialog and configuration tools

Human-Machine interface

The 4-digit display **1** shows drive states, error codes, and parameter values.
The navigation button **2** is used to navigate through the menus, modify values, and change the motor speed in local mode.

HMI terminals

Altivar Machine ATV320 drives can be connected to a graphic display terminal(VW3A1111,VW3A1101) **3** or a remote display terminal **4**, which are available as options.
The HMI terminals can be mounted on an enclosure door with IP65 degree of protection. They provide the same level of access as the on-board Human-Machine interface.
The HMI terminal display in the majority of user languages, and provide a user-friendly environment for configuration, debugging or maintenance.

SoMove setup software


SoMove setup software is used to configure, adjust, debug (using the Oscilloscope function), and maintain Altivar Machine ATV320 drives in the same way as for other Schneider Electric drives and starters.
For more information, please refer to the SoMove catalog.


Simple Loader and Multi-Loader configuration tools

The Simple Loader tool **6** enables the configuration from one powered-up drive to be duplicated on another powered-up drive.
The Multi-Loader tool **5** enables configurations from a PC or drive to be copied and duplicated on another drive; the drives do not need to be powered up.
7 Direct cable connection doesn't affect Certification & Protection degree(IP level).
Green bar: Advanced conguration tool
The advanced keypad tool 5 enables configurations from a PC or drive to be copied and duplicated on another drive, also support for REMOTE/LOCAL operation.
See page 19.

References:
page 16

Variable speed drives
Altivar Machine ATV320







Description

1 Power terminals
2 Protective cover to block access to the power terminals 1 when closed
3 RJ45 communication port for access to integrated protocols: Modbus serial link and CANopen machine bus
4 Protective cover for access to the control terminals (also includes a label with a wiring diagram)
5 Control terminals for I/O connection:
■ 6 digital inputs:
□ 4 configurable for positive digital input (Sink) or negative digital input (Source)
□ 1 input configurable as a PTC probe input
□ 1 x 20 kHz pulse control input, 24 V ⎓, impedance 3.5 kΩ, sampling time 8 ms
■ 1 digital output:
□ 24 V ⎓, sampling time 2 ms, maximum voltage 30 V, maximum current 100 mA
■ 3 analog inputs:
□ 1 current analog input, by programming X and Y from 0 to 20 mA, impedance 250 Ω
□ 1 bipolar differential analog input ± 10 V, impedance 30 kΩ
□ 1 voltage analog input 0...10 V, impedance 30 kΩ, sampling time 2 ms
■ 1 analog output configurable as:
□ voltage analog output 0…10 V ⎓, minimum load impedance 470 Ω
□ current analog output 0…20 mA, maximum load impedance 800 Ω
■ 2 relay outputs:
□ 1 NC contact and 1 NO contact with common point
Minimum switching capacity 5 mA for 24 V ⎓, maximum switching capacity 3 A on resistive load, 2 A on inductive load for 250 V ∿ or 30 V ⎓
□ 1 NO contact, maximum switching capacity 5 A on resistive load
6 Removable motor power terminal block (allows quick disconnect and re-connect of motor cables during maintenance operations)
7 EMC mounting plate (integral part of the motor power terminal block 6). This plate is supplied with a cable guide support, which can be used if required.
8 Direct cable connection doesn't affect Certification & Protection degree(IP level).

Standards and certifications *(1)*

Altivar Machine ATV320 drives have been developed to conform to the strictest international standards and recommendations relating to industrial electrical control devices (IEC), in particular:
■ IEC 61800-5-1
■ IEC 61800-3:
□ EMC immunity: IEC 61800-3, Environments 1 and 2
□ Conducted emission compliance:
- IEC 61800-3, category C2, C3 with integrated EMC filter for ATV320●M2●, ATV320●N4W●, ATV320U04N4●●●●D15N4● drives
- IEC 61800-3, category C1, C2, C3 with additional EMC filter for ATV320●N4●, ATV320●M2● drives

■ EN ISO 13849-1/-2 category 3 (PL e)

Altivar Machine ATV320 drives are certified:
■ CE - LV EMC
■ CE - Machine
■ ATEX
■ UL 508C
■ UL61800-5-1
■ CSA 22.2 N274
■ CSA 22N4 (ATV320●●●●●B)
■ NOM (ATV320●●●●●B)
■ GOST
■ EAC
■ CTICK
■ KC (ATV320●●●●●B, ATV320●●●●●C)
■ SIL
They are CE marked according to the European low voltage (2014/35/UE) and EMC (2014/30/UE) directives.
They also comply with environmental directives (RoHS).

(1) A complete list of certifications and characteristics is available on our website.

References:
page 16

Variable speed drives
Altivar Machine ATV320
Drives with compact control block, IP20



ATV320U02M2C...U07M2C



ATV320U11M2C...U22M2C
ATV320U04N4C...U15N4C



ATV320U22N4C...
ATV320U40N4C



ATV320U55M3C

Drives with compact control block

Motor		Line supply				Altivar Machine ATV320				
Power indicated on rating plate *(1)*		Max. line current *(2) (3)*		Apparent power	Max. prospective line Isc *(4)*	Max. continuous output current (In) *(1)*	Max. transient current for 60s	Power dissipated at maximum output current (In) *(1)*	Reference *(1)*	Weight
		at U1	at U2	at U2						
kW	*HP*	A	A	kVA	kA	A	A	W		kg/ *lb*
Single-phase supply voltage: 200…240 V 50/60 Hz, with integrated EMC filter *(6)*										
0.18	*0.25*	3.4	2.8	0.7	1	1.5	2.3	17	ATV320U02M2C	0.800/ *1.278*
0.37	*0.5*	5.9	4.9	1.2	1	3.3	5	30	ATV320U04M2C	1.000/ *2.204*
0.55	*0.75*	7.8	6.6	1.6	1	3.7	5.6	33	ATV320U06M2C	1.100/ *2.425*
0.75	*1*	10.0	8.4	2	1	4.8	7.2	45	ATV320U07M2C	
1.1	*1.5*	13.7	11.5	2.8	1	6.9	10.4	61	ATV320U11M2C	1.600/ *3.527*
1.5	*2*	17.8	14.9	3.6	1	8	12	76	ATV320U15M2C	
2.2	*3*	24.0	20.2	4.8	1	11	16.5	99	ATV320U22M2C	
Three-phase supply voltage: 200…240 V 50/60 Hz, without integrated EMC filter										
0.18	*0.25*	2.0	1.7	0.7	5	1.5	2.3	15	ATV320U02M3C	0.800/ *1.278*
0.37	*0.5*	3.6	3.0	1.2	5	3.3	5	27	ATV320U04M3C	0.900/ *1.984*
0.55	*0.75*	4.9	4.2	1.7	5	3.7	5.6	31	ATV320U06M3C	1.000/ *2.204*
0.75	*1.0*	6.3	5.3	2.2	5	4.8	7.2	42	ATV320U07M3C	
1.1	*1.5*	8.6	7.2	3.0	5	6.9	10.4	58	ATV320U11M3C	1.400/ *3.086*
1.5	*2.0*	11.1	9.3	3.9	5	8	12	72	ATV320U15M3C	
2.2	*3.0*	14.9	12.5	5.2	5	11	16.5	91	ATV320U22M3C	
3.0	*3.0*	18.7	15.7	6.5	5	13.7	20.6	105	ATV320U30M3C	2.200/ *4.850*
4.0	*5.0*	23.8	19.9	8.3	5	17.5	26.3	140	ATV320U40M3C	
5.5	*7.5*	35.4	29.8	12.4	22	27.5	41.3	242	ATV320U55M3C	3.500/ *7.716*
7.5	*10.0*	45.3	38.2	15.9	22	33	49.5	293	ATV320U75M3C	3.600/ *7.937*
11.0	*15.0*	60.9	51.4	21.4	22	54	81	468	ATV320D11M3C	6.800/ *14.991*
15.0	*20.0*	79.7	67.1	27.9	22	66	99	551	ATV320D15M3C	6.900/ *15.212*

(1) These values are given for a nominal switching frequency of 4 kHz, for use in continuous operation. The switching frequency is adjustable from 2 to16 kHz. Above 4 kHz, derate the nominal drive current. The nominal motor current should not exceed this value (see derating curves in the Installation Manual).
(2) Typical value for a 4-pole motor and a maximum switching frequency of 4 kHz, with no line choke for max.
(3) Nominal supply voltage, min. U1, max. U2: 200 (U1)…240 V (U2), 380 (U1)…500 V (U2), 525(U1)...600(U2).
(4) If line Isc is greater than the values in the table, add line chokes.

Variable speed drives
Altivar Machine ATV320
Drives with compact control block, IP20



ATV320U07S6C



ATV320U15S6C



ATV320U55N4C

Drives with compact control block

Motor		Line supply				Altivar Machine ATV320				
Power indicated on rating plate *(1)*		Max. line current *(2) (3)*		Apparent power	Max. prospective line Isc *(4)*	Max. continuous output current (In) *(1)*	Max. transient current for 60s	Power dissipated at maximum output current (In) *(1)*	Reference *(1)*	Weight
		at U1	at U2	at U2						
kW	*HP*	A	A	kVA	kA	A	A	W		kg/ *lb*
Three-phase supply voltage: 380…500 V 50/60 Hz, with integrated EMC filter *(5) (6)*										
0.37	*0.5*	2.1	1.6	1.4	5	1.5	2.25	23	ATV320U04N4C	*1.200/ 2.646*
0.55	*0.75*	2.8	2.2	1.9	5	1.9	2.85	27	ATV320U06N4C	
0.75	*1*	3.6	2.8	2.4	5	2.3	3.45	32	ATV320U07N4C	
1.1	*1.5*	5	3.8	3.3	5	3	4.5	40	ATV320U11N4C	1.300/ *2.866*
1.5	*2*	6.4	4.9	4.2	5	4.1	6.15	56	ATV320U15N4C	
2.2	*3*	8.7	6.6	5.7	5	5.5	8.25	74	ATV320U22N4C	2.100/ *4.630*
3	*3*	11.1	8.4	7.3	5	7.1	10.65	93	ATV320U30N4C	
4	*5*	13.7	10.6	9.2	5	9.5	14.25	111	ATV320U40N4C	2.200/ *4.850*
5.5	*7.5*	20.7	14.5	12.6	22	14.3	21.45	195	ATV320U55N4C	2.200/ *4.850*
7.5	*10.0*	26.5	18.7	16.2	22	17.0	25.5	229	ATV320U75N4C	2.200/ *4.850*
11.0	*15.0*	36.6	25.6	22.2	22	27.7	41.6	370	ATV320D11N4C	6.800/ *14.991*
15.0	*20.0*	47.3	33.3	28.8	22	33.0	49.5	452	ATV320D15N4C	6.900/ *15.211*
Three-phase supply voltage: 525…600 V 50/60 Hz, without integrated EMC filter *(7)*										
0.75	*1*	1.5	1.4	1.5	5	1.7	2.6	34	ATV320U07S6C	1.300/ *2.866*
1.5	*2*	2.6	2.4	2.5	5	2.7	4.1	54	ATV320U15S6C	
2.2	*3*	3.7	3.2	3.4	5	3.9	5.9	77	ATV320U22S6C	2.000/ *4.409*
4	*5*	6.5	5.8	6.0	5	6.1	9.2	96	ATV320U40S6C	2.500/ *5.511*
5.5	*7.5*	8.4	7.5	7.8	22	9.0	13.5	148	ATV320U55S6C	3.500/ *7.716*
7.5	*10*	11.6	10.5	10.9	22	11.0	16.5	175	ATV320U75S6C	
11	*15*	15.8	14.1	14.7	22	17.0	25.5	267	ATV320D11S6C	6.500/ *14.330*
15	*20*	22.1	20.1	20.9	22	22.0	33.0	317	ATV320D15S6C	

(1) These values are given for a nominal switching frequency of 4 kHz, for use in continuous operation. The switching frequency is adjustable from 2 to16 kHz. Above 4 kHz, derate the nominal drive current. The nominal motor current should not exceed this value (see derating curves in the Installation Manual).
(2) Typical value for a 4-pole motor and a maximum switching frequency of 4 kHz, with no line choke for max.
(3) Nominal supply voltage, min. U1, max. U2: 200 (U1)…240 V (U2), 380 (U1)…500 V (U2), 525(U1)...600(U2).
(4) If line Isc is greater than the values in the table, add line chokes.
(5) Drives supplied with category C2 integrated EMC filter. This filter can be disconnected.
(6) Drives are supplied with an EMC plate, for assembly by the customer.
(7) A line choke is mandatory with ATV320●●●S6C drives. To be ordered separately, see page 40.

Variable speed drives
Altivar Machine ATV320
Drives with book control block, IP20



ATV320U02M2B...U07M2B
ATV320U04N4B...U15N4B



ATV320U11M2B...U22M2B
ATV320U22N4B...U40N4B



ATV320U55N4B



ATV320D15N4B

Drives with book control block

Motor		Line supply				Altivar Machine ATV320				
Power indicated on rating plate *(1)*		Max. line current *(2),(3)*		Apparent power	Max. prospective line Isc *(4)*	Max. continuous output current (In) *(1)*	Max. transient current for 60s	Power dissipated at maximum output current (In) *(1)*	Reference *(1)*	Weight
		at U1	at U2	at U2						
kW	*HP*	A	A	kVA	kA	A	A	W		kg/ *lb*
Single-phase supply voltage: 200…240 V 50/60 Hz, with integrated EMC filter *(5) (6)*										
0.18	0.25	3.4	2.8	0.7	1	1.5	2.3	19	ATV320U02M2B	2.400/ *5.291*
0.37	0.5	6	5	1.2	1	3.3	5	31	ATV320U04M2B	2.500/ *5.511*
0.55	0.75	7.9	6.7	1.6	1	3.7	5.6	35	ATV320U06M2B	
0.75	1	10.1	8.5	2	1	4.8	7.2	46	ATV320U07M2B	2.400/ *5.291*
1.1	1.5	13.6	11.5	2.8	1	6.9	10.4	62	ATV320U11M2B	2.900/ *6.393*
1.5	2	17.6	14.8	3.6	1	8	12	77	ATV320U15M2B	
2.2	3	23.9	20.1	4.8	1	11	16.5	98	ATV320U22M2B	
Three-phase supply voltage: 380…500 V 50/60 Hz, with integrated EMC filter *(5) (6)*										
0.37	0.5	2.1	1.6	1.4	5	1.5	2.3	23	ATV320U04N4B	2.500/ *5.511*
0.55	0.75	2.8	2.2	1.9	5	1.9	2.9	27	ATV320U06N4B	2.600/ *5.732*
0.75	1	3.6	2.7	2.3	5	2.3	3.5	31	ATV320U07N4B	
1.1	1.5	5	3.8	3.3	5	3	4.5	41	ATV320U11N4B	2.500/ *5.511*
1.5	2	6.5	4.9	4.2	5	4.1	6.2	56	ATV320U15N4B	
2.2	3	8.7	6.6	5.7	5	5.5	8.3	74	ATV320U22N4B	3.000/ *6.614*
3	3	11.1	8.4	7.3	5	7.1	10.7	93	ATV320U30N4B	
4	5	13.7	10.5	9.1	5	9.5	14.3	111	ATV320U40N4B	
5.5	7.5	20.7	14.5	12.6	22	14.3	21.45	195	ATV320U55N4B	7.500/ *16.534*
7.5	10	26.5	18.7	16.2	22	17	25.5	229	ATV320U75N4B	
11	15	36.6	25.6	22.2	22	27.7	41.6	370	ATV320D11N4B	8.700/ *19.180*
15	20	47.3	33.3	28.8	22	33	49.5	452	ATV320D15N4B	8.800/ *19.401*

(1) These values are given for a nominal switching frequency of 4 kHz, for use in continuous operation. The switching frequency is adjustable from 2 to16 kHz. Above 4 kHz, derate the nominal drive current. The nominal motor current should not exceed this value (see derating curves in the Installation Manual).
(2) Typical value for a 4-pole motor and a maximum switching frequency of 4 kHz, with no line choke for max. prospective line Isc (4).
(3) Nominal supply voltage, min. U1, max. U2: 200 (U1)…240 V (U2), 380 (U1)…500 V (U2), 525 (U1)…600 V (U2).
(4) If line Isc is greater than the values in the table, add line chokes.
(5) Drives supplied with category C2 integrated EMC ilter. This ilter can be disconnected.
(6) Connection in compliance with EMC standards:
- ATV320●●●M2B, ATV320U04N4B…ATV320U40N4B drives are supplied with an EMC plate. This is integral part of the power terminal; these 2 components cannot be separated.
- ATV320U55N4B…D15N4B drives are supplied with an EMC plate, for assembly by the customer.

Variable speed drives
Altivar Machine ATV320
IP66 drive without Vario and IP65 drive with Vario

ATV320_63440_CPMGU18024



ATV320U02M2W ...U40N4W

ATV320_63440_CPMGU17055B



ATV320U55N4W, ATV320U75N4W

ATV320_63440_CPMGU17056C



ATV320U02M2WS ...U40N4WS

ATV320_63440_CPMGU17060B



ATV320U55N4WS, ATV320U75N4WS

Drives for harsh environment IP66/IP65

Motor		Line supply				Altivar Machine ATV320				
Power indicated on rating plate *(1)*		Max. line current *(2) (3)*		Apparent power	Max. prospective line Isc *(4)*	Max. continuous output current (In) *(1)*	Max. transient current for 60s	Power dissipated at maximum output current (In) *(1)*	Reference *(1)*	Weight
		at U1	at U2	at U2						
kW	*HP*	A	A	kVA	kA	A	A	W		kg/ *lb*
Single-phase supply voltage: 200…240 V 50/60 Hz, with integrated EMC filter, IP66 *(5)*										
0.18	*0.25*	3.4	2.8	0.7	1	1.5	2.3	17	ATV320U02M2W	5.000/ *11.023*
0.37	*0.5*	5.9	4.9	1.2	1	3.3	5	30	ATV320U04M2W	5.100/ *11.243*
0.55	*0.75*	7.8	6.6	1.6	1	3.7	5.6	33	ATV320U06M2W	
0.75	*1*	10	8.4	2	1	4.8	7.2	45	ATV320U07M2W	
1.1	*1.5*	13.7	11.5	2.8	1	6.9	10.4	61	ATV320U11M2W	7.400/ *16.314*
1.5	*2*	17.8	14.9	3.6	1	8	12	76	ATV320U15M2W	
2.2	*3*	24	20.2	4.8	1	11	16.5	99	ATV320U22M2W	
Three-phase supply voltage: 380…500 V 50/60 Hz, with integrated EMC filter, IP66 *(5)*										
0.37	*0.5*	2.1	1.6	1.4	5	1.5	2.3	23	ATV320U04N4W	5.900/ *13.007*
0.55	*0.75*	2.8	2.2	1.9	5	1.9	2.9	27	ATV320U06N4W	
0.75	*1*	3.6	2.8	2.4	5	2.3	3.5	32	ATV320U07N4W	
1.1	*1.5*	5	3.8	3.3	5	3	4.5	40	ATV320U11N4W	6.000/ *13.227*
1.5	*2*	6.4	4.9	4.2	5	4.1	6.2	56	ATV320U15N4W	
2.2	*3*	8.7	6.6	5.7	5	5.5	8.3	74	ATV320U22N4W	7.700/ *16.975*
3	*3*	11.1	8.4	7.3	5	7.1	10.7	93	ATV320U30N4W	
4	*5*	13.7	10.6	9.2	5	9.5	14.3	111	ATV320U40N4W	7.800/ *17.196*
5.5	*7.5*	20.7	14.5	12.6	22	14.3	21.5	195	ATV320U55N4W	22.000/ *48.501*
7.5	*10*	26.5	18.7	16.2	22	17.0	25.5	229	ATV320U75N4W	
Single-phase supply voltage: 200…240 V 50/60 Hz, with integrated EMC filter, IP65, with vario *(5)*										
0.18	*0.25*	3.4	2.8	0.7	1	1.5	2.3	17	ATV320U02M2WS	5.400/ *11.904*
0.37	*0.5*	5.9	4.9	1.2	1	3.3	5	30	ATV320U04M2WS	5.500/ *12.125*
0.55	*0.75*	7.8	6.6	1.6	1	3.7	5.6	33	ATV320U06M2WS	5.500/ *12.125*
0.75	*1*	10.0	8.4	2.0	1	4.8	7.2	45	ATV320U07M2WS	
1.1	*1.5*	13.7	11.5	2.8	1	6.9	10.4	61	ATV320U11M2WS	7.800/ *17.196*
1.5	*2*	17.8	14.9	3.6	1	8	12	76	ATV320U15M2WS	
2.2	*3*	24.0	20.2	4.8	1	11	16.5	99	ATV320U22M2WS	
Three-phase supply voltage: 380…500 V 50/60 Hz, with integrated EMC filter, IP65, with vario *(5)*										
0.37	*0.5*	2.1	1.6	1.4	5	1.5	2.3	23	ATV320U04N4WS	6.300/ *13.889*
0.55	*0.75*	2.8	2.2	1.9	5	1.9	2.9	27	ATV320U06N4WS	
0.75	*1*	3.6	2.8	2.4	5	2.3	3.5	32	ATV320U07N4WS	
1.1	*1.5*	5.0	3.8	3.3	5	3	4.5	40	ATV320U11N4WS	6.400/ *14.109*
1.5	*2.0*	6.4	4.9	4.2	5	4.1	6.2	56	ATV320U15N4WS	
2.2	*3.0*	8.7	6.6	5.7	5	5.5	8.3	74	ATV320U22N4WS	8.100/ *17.857*
3.0	*3.0*	11.1	8.4	7.3	5	7.1	10.7	93	ATV320U30N4WS	
4.0	*5.0*	13.7	10.6	9.2	5	9.5	14.3	111	ATV320U40N4WS	8.200/ *18.077*
5.5	*7.5*	20.7	14.5	12.6	22	14.3	21.5	195	ATV320U55N4WS	22.700/ *50.044*
7.5	*10.0*	26.5	18.7	16.2	22	17.0	25.5	229	ATV320U75N4WS	

(1) These values are given for a nominal switching frequency of 4 kHz, for use in continuous operation. The switching frequency is adjustable from 2 to16 kHz. Above 4 kHz, derate the nominal drive current. The nominal motor current should not exceed this value (see derating curves in the Installation Manual).
(2) Typical value for a 4-pole motor and a maximum switching frequency of 4 kHz, with no line choke for max. prospective line Isc (4).
(3) Nominal supply voltage, min. U1, max. U2: 200 (U1)…240 V (U2), 380 (U1)…500 V (U2).
(4) If line Isc is greater than the values in the table, add line chokes.
(5) Drives supplied with category C2 integrated EMC filter. This filter can be disconnected.

Variable speed drives
Altivar Machine ATV320
Accessories

ATV320_63440_OPF16047



*GV2 / ATV320 direct mounting: **GV2L08** + (**VW3A9921** + **GV2AF5**) + **ATV320U07N4B***

Accessories

Description	For use with	Minimum order quantity	Reference	Weight kg/ *lb*
Components for mounting GV2 circuit breaker directly on ATV320 drive				
Bracket for GV2/ATV320 direct mounting Mechanical bracket for holding the GV2 circuit breaker in place when directly mounted on the ATV320 drive. Requires a GV2AF5 adapter plate for electrical connection, to be ordered separately	ATV320●●●M2B ATV320U04N4B...U40N4B	10	VW3A9921	0.075/ *0.165*
Adapter plate Provides the electrical link between the GV2 circuit breaker and the ATV320 drive when the GV2 is directly mounted on the ATV320. Requires a VW3A9921 bracket for direct mounting, to be ordered separately.	ATV320●●●M2B ATV320U02N4B...U40N4B	10	GV2AF5	0.016/ *0.035*
GV2 adaptor metal sheet	ATV320●●●M2W ATV320U04N4W…U40N4W	1	VW3A9922	5.900/ *13.007*
UL type 4X kit Indoor UL type 4X kit, support for harsh environment usage.	ATV320U02M2W..U40N4W ATV320U55N4W..U75N4W		VW3A9923X VW3A9924X	*0.15/* *0.33*
Mounting the control module at 90°				
Adapter for mounting the control module at 90° This is used to mount the power module on the side, keeping the control module visible and accessible.	ATV320●●●M2B ATV320U04N4B...U40N4B	1	VW3A9920	0.125/ *0.276*

Daisy chain connection of the DC bus *(1)*

The DC bus is connected in a daisy chain in the following cases:
■ Drives powered by the AC supply with parallel connection of the DC bus in order to balance the loads during braking phases between the drives; used in addition to braking resistors (see page 38)
■ Drives powered by the DC bus only
Requires the connection accessories listed below:

Description	Use		Length	Sold in lots of	Unit Reference	Weight kg/ *lb*
	From	To	m/*ft*			
Cordset *(1)* equipped with 2 connectors	ATV320●●●●M2B	ATV320●●●●M2B	0.1/ *0.33*	5	VW3M7101R01	–
	ATV320●●●●N4B	ATV320●●●●N4B				
Shielded cable	ATV320●●●●M2●	ATV320●●●●M2●	15/ *49.21*	1	VW3M7102R150	–
	ATV320●●●●N4●	ATV320●●●●N4●				
	ATV320●●●●M3C	ATV320●●●●M3C				
	ATV320●●●●S6C	ATV320●●●●S6C				
Connection kit for VW3M7102R150 cable	–	–	–	10	VW3M2207	–

(1) Setting up several devices on the DC bus requires special precautions; please refer to the Installation Manual.

PF080670A



VW3A980●

Accessories (continued)

Shielding connection clamp

Description	For use with	Sold in lots of	Unit Reference	Weight kg/ lb
Shielding connection clamps Attachment and earthing of the cable shielding Pack of 25 clamps including: for the cable length of 10 ■ 20 clamps for Ø 4.8 mm *(0.19 in.)* cable ■ 5 clamps for Ø 7.9 mm *(0.31 in.)* cable	ATV320●●●●●●	25	TM200RSRCEMC	–

DIN rail mounting kit

Description	For use with	Reference	Weight kg/ lb
Plates for mounting on DIN rail width 35 mm *(1.38 in.)*	ATV320U02M●C... ATV320U07M●C	VW3A9804	0.290/ *0.639*
	ATV320U11M●C... ATV320U22M●C ATV320U04N4C... ATV320U15N4C ATV320U07S6C... ATV320U15S6C	VW3A9805	0.385/ *0.849*

(1) Setting up several devices on the DC bus requires special precautions; please refer to the Installation Manual.


Variable speed drives
Altivar Machine ATV320
Accessories


PF080666A


VW3A9523


PF080667A

VW3A9524


ATV320_63440_CPSCT16007

VW3A9532


ATV320_63440_CPSCT16008

VW3A9533


ATV320_63440_CPMGU18011A

VW3A9911


ATV320_63440_CPMGU18012A

VW3A9912

Accessories (continued)

Description	For use with	Reference	Weight kg/ lb
UL Type 1 conformity kits Mechanical device for attaching to the lower part of the drive. For direct connection of cables to the drive via tubes or cable glands.	ATV320U02M2C...U07M2C ATV320U02M3C...U07M3C	VW3A95811	0.370/ *0.816*
	ATV320U11M2C...U22M2C ATV320U04N4C...U15N4C ATV320U07S6C...U15S6C	VW3A95812	0.440/ *0.970*
	ATV320U11M3C...U22M3C	VW3A95813	0.480/ *1.058*
	ATV320U22N4C...U40N4C ATV320U22S6C...U40S6C	VW3A95814	0.550/ *1.213*
	ATV320U30M3C...U40M3C	VW3A95815	0.580/ *1.279*
	ATV320U55M3C...U75M3C ATV320U55N4C...U75N4C ATV320U55S6C...U75S6C	VW3A95816	0.820/ *1.808*
	ATV320U55N4B...U75N4B	VW3A95817	1.410/ *3.109*
	ATV320D11M3C...D15M3C ATV320D11N4C...D15N4C ATV320D11S6C...D15S6C	VW3A95818	1.160/ *2.557*
	ATV320D11N4B... D15N4B	VW3A95819	1.680/ *3.704*


Mounting accessories

Description	For drives	Reference	Weight kg/ lb
EMC conformity kits These provide a connection compliant with EMC standards (for further information, please consult our website) The kit consists of: ■ The EMC plate ■ Clamps ■ Fixing accessories	ATV320U02M3C ATV320U04M3C ATV320U06M3C ATV320U07M3C	VW3A9523	0.170/ *0.374*
	ATV320U11M3C ATV320U15M3C ATV320U22M3C ATV320U07S6C ATV320U15S6C	VW3A9524	0.190/ *0.418*
	ATV320U30M3C ATV320U40M3C ATV320U22S6C ATV320U40S6C	VW3A9525	0.210/ *0.462*
	ATV320U55M3C...U75M3C ATV320U55N4C...U75N4C ATV320U55S6C...U75S6C	VW3A9532	0.200/ *0.440*
	ATV320D11M3C...D15M3C ATV320D11N4C...D15N4C ATV320D11S6C...D15S6C	VW3A9533	0.260/ *0.573*
EMC conformity kits	ATV320●●●M2W ATV320●●●M2WS ATV320U04N4W…U40N4W ATV320U04N4WS…U40N4WS	VW3A9535	–
	ATV320U55N4W...U75N4W ATV320U55N4WS...U75N4WS	VW3A9536	–
Full gland plate *Panel builder to modify	ATV320●●●M2W ATV320●●●M2WS ATV320U04N4W…U40N4W ATV320U04N4WS…U40N4WS	VW3A9911	–
Full gland plate *Panel builder to modify	ATV320U55N4W...U75N4W ATV320U55N4WS...U75N4WS	VW3A9912	–

Presentation: page 6
Dialog, configuration tools: page 26
Combinations: page 32
Dimensions: page 56

Variable speed drives
Altivar Machine ATV320
Replacement parts

F19_VENTILLATION_CPODA2016002



VZ3V1301

Replacement parts

Description	For use with	Reference	Weight kg/ *lb*
Fans			
Fan for variable speed drive	ATV320U11M3C...U40M3C	VZ3V1302	
	ATV320U11M2C…U22M2C ATV320U04N4C…U15N4C ATV320U07S6C…U15S6C	VZ3V1301	
	ATV320U02M2B...U07M2B ATV320U04N4B...U15N4B	VZ3V32A100	
	ATV320U11M2B...U22M2B ATV320U22N4B...U40N4B	VZ3V32B100	
	ATV320U55M3C…U75M3C ATV320U55N4B…U75N4B ATV320U55N4C…U75N4C ATV320U55S6C…U75S6C	VZ3V32C100	
	ATV320D11M3C…D15M3C ATV320D11N4B…D15N4B ATV320D11N4C…D15N4C ATV320D11S6C…D15S6C	VZ3V32D100	
	ATV320U04N4W...U15N4W ATV320U04N4WS...U15N4WS ATV320U11M2W...U22M2W ATV320U11M2WS...U22M2WS	VZ3V32066S2	
	ATV320U22N4W...U40N4W ATV320U22N4WS...U40N4WS	VZ3V32066S3	
	ATV320U55N4W...U75N4W ATV320U55N4WS...U75N4WS	VZ3V32066S4	
Other			
Removable motor power terminal block	ATV320U02M2B...U40N4B	VY1F32AB1001	
Pluggable fan connector	ATV320U02M2B...D15N4B ATV320●●●M2W● ATV320●●●N4W●	VY1F10007V21	
I/O control card	ATV320●●●●●C ATV320●●●M2W● ATV320●●●N4W●	VW3A36201	

Variable speed drives
Altivar Machine ATV320
Option: ATV Regenerative units

ATVRegen_63440_CPF.JR16009



ATVRD15N4

ATVRegen_63440_CPF.JR16010



ATVRU75N4

Presentation


The main function of the ATV Regen product is to provide an option to regenerate energy back to the AC supply for heavy braking applications such as Material Working, Materail Handling and Hoisting with easy setting.

This option should be associated with Altivar drives in the 400 V series such as Altivar 320. The braking unit harmonic performance is the same as that of standard drives.

Features:
- Chemical class 3C3 conforming to IEC/EN 60721
- Mechanical class 3S2 conforming to IEC/EN 60721
- -10..50 °C/*14...122 °F* without derating, up to 60 °C/*140 °F* with derating
- Mechanical class 3S2 conforming to IEC/EN 60721
- Built in EMC filter comply with standard IEC 61800-3

Wiring concept

Generic wiring




Life Is On Schneider Electric

Click to download
Altivar Regenerative Unit: Sizing Tool

Wiring concept (continued)

Several drives with one Regenerative unit




References

For drives *(1)*	IP	Regenerative unit reference	Weight kg/ *lb*
Supply voltage: 380…480 V 50/60 Hz			
ATV320U07N4●...U75N4●	20	ATVRU75N4	6.000/ *13.228*
ATV320D11N4●...D15N4●	20	ATVRD15N4	11.500/ *25.353*

(1) The sizing selection should refer to Altivar Regenerative unit, user manual

Variable speed drives
Altivar Machine ATV320
Option: Dialog and configuration tool



Altivar Machine DTM in SoMove software

DTM

Presentation

Using FDT/DTM technology it is possible to configure, control, and diagnose Altivar Machine drives directly in EcoStruxure Machine Expert and SoMove software by means of the same software brick (DTM).
FDT/DTM technology standardizes the communication interface between field devices and host systems. The DTM contains a uniform structure for managing drive access parameters.
The Altivar Machine ATV320 DTM library is a flexible, open, and interactive tool that can be used in a third-party FDT.
DTMs can be downloaded from our website.

Specific functions of the Altivar Machine ATV320 DTM

- Offline or online access to drive data
- Transfer of configuration files from and to the drive
- Customization (My Menu)
- Access to drive parameters and option cards
- Oscilloscope function
- Graphic interface to assist with configuration of the Altivar Machine ATV320
- Drive parameter monitoring
- Detected error and warning logs

Advantages of the DTM library in EcoStruxure Machine Expert

EcoStruxure Machine Expert is a single tool for configuration, setup, and diagnostics for the complete machine. It can be integrated in the fieldbus topology. EcoStruxure Machine Expert additionally offers Function Block library possibilities for Altivar Machine drives.

Advantages of the DTM library in SoMove

SoMove is a drive-oriented software environment.
It allows a wired connection directly to the drive Modbus serial port.

SoMove setup software

SoMove Lite setup software for PC is used to prepare drive configuration files.
The USB/RJ45 cable (reference **TCSMCNAM3M002P**) connects to the USB port of the PC running software and to the RJ45 port on the device.
For more information, refer to the SoMove catalog.

Variable speed drives
Altivar Machine ATV320
Option: Dialog and configuration tool

PF080629



VW3A8121

PF080628



VW3A8120

ATV320_63440_OPF16048



Con iguring an Altivar 320 in its packaging with multi loader tool VW3A8121

Simple Loader and Multi-Loader configuration tools

The Simple Loader tool enables one drive configuration to be duplicated and transferred to another drive (both drives must be powered up). It is connected to the drive RJ45 communication port.
The Multi-Loader tool enables a number of configurations from a PC or drive to be copied and loaded onto other drives (Altivar Machine ATV320 drives do not need to be powered up when using the Multi-Loader tool).

References

Description		Reference	Weight kg/*lb*
Simple loader tool Supplied with a cordset equipped with 2 RJ45 connectors	ATV320●●●●	VW3A8120	–
Multi loader tool Supplied with: - 1 cordset equipped with 2 RJ45 connectors - 1 cordset equipped with one type A USB connector and one mini B USB connector - 1 SD memory card - 1 female/female RJ45 adapter - 4 AA/LR6 1.5 V batteries - 1 anti-shock protector - 1 carrying handle	ATV320●●●●	VW3A8121	–
USB/RJ45 cable equipped with a USB connector and an RJ45 connector. For connecting a PC to the Altivar Machine ATV320. Length: 2.5 m *(8.20 ft.)*	ATV320●●●●	TCSMCNAM3M002P	–

Variable speed drives
Altivar Machine ATV320
Option: Dialog and configuration tool

PF095133



Remote display terminal with cover open

PF095131



Remote display terminal with cover closed

Remote display terminal

This terminal is used to locate the Human-Machine Interface of the Altivar Machine ATV320 drive remotely on the door of an enclosure with IP 54 or IP 65 protection degree.
It is used to:
- Control, adjust, and configure the drive remotely
- Display the drive status and error codes

Its maximum operating temperature is 50 °C/*122 °F*.

Description

1 4-digit display
2 Navigation ▲, ▼ and selection **ENT**, **ESC** keys
3 Motor local control keys:
- **RUN**: Starts the motor
- **FWD/REV**: Reverses the direction of rotation of the motor
- **STOP/RESET**: Stops the motor/clears detected errors

4 **MODE**: Operating mode selection key
5 Cover for access to the motor local control keys

References

Description	Degree of protection	Length	Reference	Weight
		m/ft		*kg/lb*
Remote terminals A remote-mounting cordset, VW3A1104R●●, is also required	IP 54	–	VW3A1006	0.250/ *0.551*
	IP 65	–	VW3A1007	0.275/ *0.606*
Remote-mounting cordsets equipped with 2 RJ45 connectors	–	1.0/ *3.28*	VW3A1104R10	0.050/ *0.110*
		3.0/ *9.84*	VW3A1104R30	0.150/ *0.331*

Presentation: page 6
Variable speed drives: page 16
Combinations: page 32
Dimensions: page 56

Variable speed drives
Altivar Machine ATV320
Option: Dialog and configuration tool




Remote graphic terminal



Portable use of the remote graphic terminal: 1 + 2 + 3



Using the remote graphic terminal on enclosure door: 1 + 2 + 4 (+ 5, if IP 65)



Example of connection via multidrop link

Remote graphic display terminal

This remote graphic display terminal, common across Schneider Electric's variable speed drive ranges, provides a user-friendly interface for configuration, debugging, and maintenance. In particular, it is possible to transfer and store up to 4 configurations.
For portable use or mounted on an enclosure door, it can also be connected to multiple drives (see page 28).
Its main functions are as follows:

- The graphic screen displays 8 lines of 24 characters of plain text.
- The navigation button provides quick and easy access to the drop-down menus.
- It is supplied with 6 languages installed (Chinese, English, French, German, Italian, and Spanish). The available languages can be modified using the Multi-Loader configuration tool (**VW3A8121**).

Its maximum operating temperature is 60 °C/*140 °F*, and it features IP 54 protection degree this can be increased to IP 65 when mounted on an enclosure door.

Description

1 Graphic display: 8 lines of 24 characters, 240 x 160 pixels, large digit display
2 Function keys (not operational on the Altivar 320)
3 **Navigation button:**
- Rotate ±: Goes to the next/previous line, increases/decreases the value
- Press: Saves the current value (**ENT**)
- **ESC** key: Aborts a value, parameter, or menu to return to the previous selection

4 Motor local control keys:
- **RUN**: Starts the motor
- **STOP/RESET**: Stops the motor/clears detected errors
- **FWD/REV**: Reverses the direction of rotation of the motor

References

Item no.	Description	Length m/*ft*	Reference	Weight kg/*lb*
1	**Remote graphic terminal** A remote-mounting cordset, VW3A1104R●●●, and an RJ45 adapter, VW3A1105, are required	–	VW3A1101	0.180/*0.396*
2	**Remote-mounting cordsets** equipped with 2 RJ45 connectors Remote operation of the ATV320 and the remote graphic display terminal VW3A1101	1.0/*3.28*	VW3A1104R10	0.050/*0.110*
		3.0/*9.84*	VW3A1104R30	0.150/*0.331*
		5.0/*16.40*	VW3A1104R50	0.250/*0.551*
		10/*32.81*	VW3A1104R100	0.500/*1.102*
3	**Female/female RJ45 adapter**	–	VW3A1105	0.010/*0.022*
4	**Door mounting kit** For mounting on enclosure door IP 54 degree of protection	–	VW3A1102	0.150/*0.331*
5	**Transparent door** Used to increase the degree of protection for door mounting kit VW3A1102 to IP 65 To be mounted on door mounting kit VW3A1102	–	VW3A1103	0.040/*0.088*

Additional accessories for multidrop connection

Item no.	Description		Unit reference	Weight kg/*lb*
6	**Modbus splitter box:** 10 RJ45 connectors and 1 screw terminal block		LU9GC3	0.500/*1.102*
7	**Modbus "T" tap-off**	With integrated cable (0.3 m/*0.98 ft*)	VW3A8306TF03	–
		With integrated cable (1.0 m/*3.28 ft*)	VW3A8306TF10	–
8	**Modbus line terminator**	For RJ45 connector R = 120 Ω, , C = 1 nf	VW3A8306RC **sold by lots of 2**	0.010/*0.022*

Item no	Description	Length m/ *ft*	Reference	Weight kg/*lb*
9	**Cordsets for Modbus serial link** equipped with 2 RJ45 connectors	0.3/*0.98*	VW3A8306R03	0.025/*0.055*
		1/*3.28*	VW3A8306R10	0.060/*0.132*
		3/*9.84*	VW3A8306R30	0.130/*0.287*

Example of connection via multidrop link

All the components described on this page enable a remote graphic display terminal to be connected to several drives via a multidrop link. This multidrop link is connected to the RJ45 port on the Modbus/CANopen communication port. See the example opposite.

Presentation: page 6 | Variable speed drives: page 16 | Combinations: page 32 | Dimensions: page 56

PF130899



Graphic display terminal VW3A1111

ATV340_63441_CPSCT16025



Detected fault: Red screen when there is a detected error

Graphic display terminal

This terminal can be:
- Connected and mounted on an enclosure door using a remote mounting accessory
- Connected to a PC to exchange files via a Mini USB/USB connection *(1)*
- Connected to several drives in multidrop mode (see page 29)

This terminal is used to:
- Control, adjust, and configure the drive
- Display current values (motor, I/O, and machine data)
- Display graphic dashboards such as the energy consumption monitoring dashboard
- Store and download configurations (several configuration files can be stored in the 16 MB memory)
- Duplicate the configuration of one powered-up drive on another powered-up drive
- Copy configurations from a PC or drive and duplicate them on another drive (the drives should be powered on for the duration of the duplication operations)

Other characteristics:
- Up to 24 languages (complete alphabets) covering the majority of countries around the world (languages can be removed, added and updated according to user requirements; consult the graphic display terminal page on our website)
- 2-color backlit display (white and red); if an error is detected, the red backlight is activated automatically (function can be disabled)
- Operating range: -15…50 °C/*+5…122 °F*
- Degree of protection: IP 65
- The Multipoint Screen feature of the Graphic Display Terminal **VW3A1111** must not be used with ATV320.
- The behavior of configuration tool is similar as VW3A1101, for more information please check ATV320 programming manual

Description

This Graphic Display Terminal is a local control unit which can be either plugged on the drive or mounted on the door of the wall-mounted or floor-standing enclosure. It has a cable with connectors, which is connected to the drive front Modbus serial link.
- STOP / RESET: Stop command / apply a Fault Reset.
- LOCAL / REMOTE: used to switch between local and remote control of the drive if one of the function keys displays [T/K] (FT), otherwise the key is unused.
  NOTE: To assign a function key (F1…F4) to the function LOCAL/REMOTE, go to [Command] (CTL-) menu and assign [F1 key assignment] (FN1) or … or [F4 key assignment] (FN4) to [T/K] (FT).
- ESC: used to quit a menu/parameter or remove the currently displayed value in order to revert to the previous value retained in the memory.
- F1 to F4: function keys used to access quick view, and submenus. Simultaneous press of F1 and F4 keys generates a screenshot file in the Graphic Display Terminal internal memory.
- Graphic display.
- Home: Used to access directly at the home page if the Graphic Display Terminal displays “Quick” on one of its function keys.
- Information: used to show the code of menus, submenus, and parameters if the Graphic Display Terminal displays “Code” on one of its function keys.
- RUN: executes the function assuming it has been configured.
- Touch wheel / OK: used to save the current value or access the selected menu/parameter. The touch wheel is used to scroll fast into the menus. Up/down arrows are used for precise selections, right/left arrows are used to select digits when setting a numerical value of a parameter.
- RJ45 Modbus serial port: used to connect the Graphic Display Terminal to the drive in remote control.
- Mini USB port: used to connect the Graphic Display Terminal to a computer.
- Battery (10 years service life. Type: CR2032). The battery positive pole points to the front face of the Graphic Display Terminal.


References

Description	Reference	Weight kg/ *lb*
Graphic display terminal	VW3A1111	0.200/ *0.441*

(1) Graphic display terminal used only as a handheld terminal.
(2) For ATV320 and VW3A111 firmware compatibility, please refer to Programming manual.



Door mounting kit for mounting graphic display terminal on enclosure door (front panel)



Door mounting kit for graphic display terminal (rear panel)

Accessories for graphic display terminal

■ Door mounting kit for mounting on enclosure door with IP 65/UL Type 12 protection rating as standard

The kit comprises:

- Tightening tool (also sold separately under the reference **ZB5AZ905**)
1 Cover plate to maintain IP 65 protection when there is no terminal connected
2 Mounting plate
3 RJ45 port for the graphic display terminal
4 Seal
5 Fixing nut
6 Anti-rotation pin
7 RJ45 port for connecting the remote-mounting cordset (10 m/*33 ft* maximum) Cordsets should be ordered separately depending on the length required.
8 Grounding connector

Drilling a hole with a standard Ø 22 tool, as used for a pushbutton, allows the unit to be mounted without the need for a cut-out in the enclosure (Ø 22.5 mm/*Ø 0.89 in.* drill hole).

References

Description	Length m/ *ft*	IP	Reference	Weight kg/ *lb*
Door mounting kit Order with remote mounting cordset VW3A1104R●●●	–	65/UL Type 12	VW3A1112	–
Tightening tool for door mounting kit	–	–	ZB5AZ905	0.016/ *0.035*
Remote-mounting cordset equipped with 2 RJ45 connectors	1/ *3.28*	–	VW3A1104R10	0.050/ *0.110*
	3/ *9.84*	–	VW3A1104R30	0.150/ *0.331*
	5/ *16.40*	–	VW3A1104R50	0.250/ *0.551*
	10/ *32.81*	–	VW3A1104R100	0.500/ *1.102*
kit for deport the ethernet RJ45 port in front face of the drive *(1)* Ø 22 RJ45 female/female adapter with seal	–	65	VW3A1115	0.200/ *0.441*

Configuration tools

Connection accessories

Description	Length m/ *ft*	Reference	Weight kg/ *lb*
SoMove setup software For configuring, adjusting and debugging the Altivar Machine drive.	–	*(2)*	–
USB/RJ45 cable equipped with a USB connector and an RJ45 connector. For connecting a PC to the drive. Length: 2.5 m	2.5/ *8.20*	TCSMCNAM3M002P	–

(1) Graphic display terminal used only as a handheld terminal.
(2) For ATV320 and VW3A111 firmware compatibility, please refer to Programming manual.

Variable speed drives

Altivar Machine ATV320

Combinations of options for Altivar 320 drives, IP20, compact format

Combinations of options for Altivar 320 drives														
Motor		**Drive**	**Accessories**					**Options**						
								Braking resistors						
kW	***HP***		**UL Type 1 conformity kits**	**Fan for variable speed drive**	**Shielding connection clamps**	**DIN rail kit**	**EMC conformity kits**	**IP20**	**IP65 - 0.75 m/ *29.53 in.* cable**	**IP65 - 3 m/ *118.11 in.* cable**	**Line chokes**	**Motor chokes**	**Additional EMC filters**	**Communication adapter card**
Drive with compact control block - single-phase supply voltage: 200…240 V 50/60 Hz														
0.18	*0.25*	**ATV320U02M2C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.37	*0.5*	**ATV320U04M2C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.55	*0.75*	**ATV320U06M2C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	–	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
0.75	*1*	**ATV320U07M2C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	–	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
1.1	*1.5*	**ATV320U11M2C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	–	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
1.5	*2*	**ATV320U15M2C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	–	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
2.2	*3*	**ATV320U22M2C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	–	VW3A7732	VW3A7603R07	VW3A7603R30	VZ1L018UM20	VW3A4553	VW3A31405	VW3A3600
Drive with compact control block - three-phase supply voltage: 200...240 V 50/60 Hz														
0.18	*0.25*	**ATV320U02M3C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	VW3A9523	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31402	VW3A3600
0.37	*0.5*	**ATV320U04M3C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	VW3A9523	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31402	VW3A3600
0.55	*0.75*	**ATV320U06M3C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	VW3A9523	VW3A7731	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31402	VW3A3600
0.75	*1*	**ATV320U07M3C**	VW3A95811	–	TM200RSRCEMC	VW3A9804	VW3A9523	VW3A7731	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31402	VW3A3600
1.1	*1.5*	**ATV320U11M3C**	VW3A95813	VZ3V1302	TM200RSRCEMC	VW3A9805	VW3A9524	VW3A7731	VW3A7605R07	VW3A7605R30	VW3A4552	VW3A4552	VW3A31404	VW3A3600
1.5	*2*	**ATV320U15M3C**	VW3A95813	VZ3V1302	TM200RSRCEMC	VW3A9805	VW3A9524	VW3A7731	VW3A7605R07	VW3A7605R30	VW3A4552	VW3A4552	VW3A31404	VW3A3600
2.2	*3*	**ATV320U22M3C**	VW3A95813	VZ3V1302	TM200RSRCEMC	VW3A9805	VW3A9524	VW3A7732	VW3A7603R07	VW3A7603R30	VW3A4553	VW3A4553	VW3A31404	VW3A3600
3	*4*	**ATV320U30M3C**	VW3A95815	VZ3V1302	TM200RSRCEMC	–	VW3A9525	VW3A7732	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4553	VW3A31406	VW3A3600
4	*5*	**ATV320U40M3C**	VW3A95815	VZ3V1302	TM200RSRCEMC	–	VW3A9525	VW3A7733	VW3A7604R07	VW3A7604R30	VW3A4554	VW3A4554	VW3A31406	VW3A3600
5.5	*7.5*	**ATV320U55M3C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7733	–	–	VW3A4554	VW3A4554	VW3A31407	VW3A3600
7.5	*10*	**ATV320U75M3C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7734	–	–	VW3A4554	VW3A4554	VW3A31407	VW3A3600
11	*15*	**ATV320D11M3C**	VW3A95818	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7735	–	–	VW3A4555	VW3A4556	VW3A31408	VW3A3600
15	*20*	**ATV320D15M3C**	VW3A95818	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7736 (IP24)	–	–	VW3A4555	VW3A4556	VW3A31408	VW3A3600
Drive with compact control block - three-phase supply voltage: 380...500 V 50/60 Hz														
0.37	*0.5*	**ATV320U04N4C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.55	*0.75*	**ATV320U06N4C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.75	*1*	**ATV320U07N4C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.1	*1.5*	**ATV320U11N4C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9804	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.5	*2*	**ATV320U15N4C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
2.2	*3*	**ATV320U22N4C**	VW3A95814	VZ3V320S3	TM200RSRCEMC	VW3A9805	–	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
3	*4*	**ATV320U30N4C**	VW3A95814	VZ3V320S3	TM200RSRCEMC	VW3A9805	–	VW3A7730	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
4	*5*	**ATV320U40N4C**	VW3A95814	VZ3V320S3	TM200RSRCEMC	VW3A9805	–	VW3A7731	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
5.5	*7.5*	**ATV320U55N4C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7731	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4553	VW3A4424	VW3A3600
7.5	*10.0*	**ATV320U75N4C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7732	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4554	VW3A4424	VW3A3600
11.0	*15.0*	**ATV320D11N4C**	VW3A95816	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7732	–	–	VW3A4554	VW3A4554	VW3A4425	VW3A3600
15.0	*20.0*	**ATV320D15N4C**	VW3A95816	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7733	–	–	VW3A4554	VW3A4555	VW3A4425	VW3A3600
Drive with compact control block - three-phase supply voltage: 525…600 V 50/60 Hz														
0.75	*1*	**ATV320U07S6C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	VW3A9524	VW3A7730	*VW3A7608R07*	VW3A7608R30	VW3A4551	VW3A4552	–	VW3A3600
1.5	*2*	**ATV320U15S6C**	VW3A95812	VZ3V1301	TM200RSRCEMC	VW3A9805	VW3A9524	VW3A7730	*VW3A7608R07*	VW3A7608R30	VW3A4551	VW3A4552	–	VW3A3600
2.2	*3*	**ATV320U22S6C**	VW3A95814	VZ3V320S3	TM200RSRCEMC	–	VW3A9525	VW3A7730	*VW3A7608R07*	VW3A7608R30	VW3A4551	VW3A4552	–	VW3A3600
4	*5*	**ATV320U40S6C**	VW3A95814	VZ3V320S3	TM200RSRCEMC	–	VW3A9525	VW3A7730	*VW3A7606R07*	VW3A7606R30	VW3A4552	VW3A4552	–	VW3A3600
5.5	*7.5*	**ATV320U55S6C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7731	*VW3A7604R07*	VW3A7604R30	VW3A4553	VW3A4552	–	VW3A3600
7.5	*10*	**ATV320U75S6C**	VW3A95816	VZ3V32C100	TM200RSRCEMC	–	VW3A9532	VW3A7732	*VW3A7604R07*	VW3A7604R30	VW3A4553	VW3A4553	–	VW3A3600
11	*15*	**ATV320D11S6C**	VW3A95818	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7732	–	–	VW3A4554	VW3A4554	–	VW3A3600
15	*20*	**ATV320D15S6C**	VW3A95818	VZ3V32D100	TM200RSRCEMC	–	VW3A9533	VW3A7732	–	–	VW3A4554	VW3A4554	–	VW3A3600

Variable speed drives

Altivar Machine ATV320

Combinations of options for Altivar 320 drives, IP66/IP65, compact format

Combinations of options for Altivar 320 drives														
Motor		**Drive**	**Accessories**					**Options**						
								Braking resistors						
kW	***HP***		**UL Type 1 conformity kits**	**Fan for variable speed drive**	**Shielding connection clamps**	**DIN rail kit**	**EMC conformity kits**	**IP20**	**IP65 - 0.75 m/ *29.53 in.* cable**	**IP65 - 3 m/ *118.11 in.* cable**	**Line chokes**	**Motor chokes**	**Additional EMC filters**	**Communication adapter card**
Drive with compact control block - single-phase supply voltage: 200…240 V 50/60 Hz, IP66 without Vario														
0.18	*0.25*	**ATV320U02M2W**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.37	*0.5*	**ATV320U04M2W**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.55	*0.75*	**ATV320U06M2W**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
0.75	*1*	**ATV320U07M2W**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
1.1	*1.5*	**ATV320U11M2W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
1.5	*2*	**ATV320U15M2W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
2.2	*3*	**ATV320U22M2W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7732	VW3A7603R07	VW3A7603R30	VZ1L018UM20	VW3A4553	VW3A31405	VW3A3600
Drive with compact control block - single-phase supply voltage: 200…240 V 50/60 Hz, IP66 with Vario														
0.18	*0.25*	**ATV320U02M2WS**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.37	*0.5*	**ATV320U04M2WS**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A31401	VW3A3600
0.55	*0.75*	**ATV320U06M2WS**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
0.75	*1*	**ATV320U07M2WS**	–	–	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A31401	VW3A3600
1.1	*1.5*	**ATV320U11M2WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
1.5	*2*	**ATV320U15M2WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A31403	VW3A3600
2.2	*3*	**ATV320U22M2WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7732	VW3A7603R07	VW3A7603R30	VZ1L018UM20	VW3A4553	VW3A31405	VW3A3600
Drive with compact control block - three-phase supply voltage: 380...500 V 50/60 Hz, IP66 without Vario														
0.37	*0.5*	**ATV320U04N4W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.55	*0.75*	**ATV320U06N4W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.75	*1*	**ATV320U07N4W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.1	*1.5*	**ATV320U11N4W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.5	*2*	**ATV320U15N4W**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
2.2	*3*	**ATV320U22N4W**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
3	*4*	**ATV320U30N4W**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
4	*5*	**ATV320U40N4W**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
5.5	*7.5*	**ATV320U55N4W**	–	VZ3V32066S4	TM200RSRCEMC	–	VW3A9536	VW3A7731	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4553	VW3A4424	VW3A3600
7.5	*10*	**ATV320U75N4W**	–	VZ3V32066S4	TM200RSRCEMC	–	VW3A9536	VW3A7732	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4554	VW3A4424	VW3A3600
Drive with compact control block - three-phase supply voltage: 380...500 V 50/60 Hz, IP66 without Vario														
0.37	*0.5*	**ATV320U04N4WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.55	*0.75*	**ATV320U06N4WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
0.75	*1*	**ATV320U07N4WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.1	*1.5*	**ATV320U11N4WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
1.5	*2*	**ATV320U15N4WS**	–	VZ3V32066S2	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A31404	VW3A3600
2.2	*3*	**ATV320U22N4WS**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
3	*4*	**ATV320U30N4WS**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7730	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
4	*5*	**ATV320U40N4WS**	–	VZ3V32066S3	TM200RSRCEMC	–	VW3A9535	VW3A7731	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A31406	VW3A3600
5.5	*7.5*	**ATV320U55N4WS**	–	VZ3V32066S4	TM200RSRCEMC	–	VW3A9536	VW3A7731	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4553	VW3A4424	VW3A3600
7.5	*10*	**ATV320U75N4WS**	–	VZ3V32066S4	TM200RSRCEMC	–	VW3A9536	VW3A7732	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4554	VW3A4424	VW3A3600

Variable speed drives

Altivar Machine ATV320

Combinations of options for Altivar 320 drives, IP20, book format, and option modules for ATV320 drives

Combinations of options for Altivar 320 drives

Motor		Drive	Accessories					Options						
								Braking resistors						
kW	*HP*		UL Type 1 conformity kits	Fan for variable speed drive	Shielding connection clamps	Bracket for GV2 direct mounting	DC bus connector kit	IP20	IP65 - 0.75 m/ *29.53 in.* cable	IP65 - 3 m/ *118.11 in.* cable	Line chokes	Motor chokes	Additional EMC filters	Communication adapter card
Drive with book control block - single-phase supply voltage: 200...240 V 50/60 Hz														
0.18	*0.25*	**ATV320U02M2B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A4420	–
0.37	*0.5*	**ATV320U04M2B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	–	VW3A4552	VW3A4420	–
0.55	*0.75*	**ATV320U06M2B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A4420	–
0.75	*1*	**ATV320U07M2B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7731	VW3A7608R07	VW3A7608R30	VZ1L007UM50	VW3A4552	VW3A4420	–
1.1	*1.5*	**ATV320U11M2B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A4421	–
1.5	*2*	**ATV320U15M2B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7731	VW3A7605R07	VW3A7605R30	VZ1L018UM20	VW3A4552	VW3A4421	–
2.2	*3*	**ATV320U22M2B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7732	VW3A7603R07	VW3A7603R30	VZ1L018UM20	VW3A4553	VW3A4426	–
Drive with book control block - three-phase supply voltage: 380...500 V 50/60 Hz														
0.37	*0.5*	**ATV320U04N4B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A4422	–
0.55	*0.75*	**ATV320U06N4B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A4422	–
0.75	*1*	**ATV320U07N4B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A4422	–
1.1	*1.5*	**ATV320U11N4B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A4422	–
1.5	*2*	**ATV320U15N4B**	–	VZ3V32A100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4551	VW3A4552	VW3A4422	–
2.2	*3*	**ATV320U22N4B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7608R07	VW3A7608R30	VW3A4552	VW3A4552	VW3A4422	–
3	*4*	**ATV320U30N4B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7730	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A4422	–
4	*5*	**ATV320U40N4B**	–	VZ3V32B100	TM200RSRCEMC	VW3A9921	VW3M2207	VW3A7731	VW3A7606R07	VW3A7606R30	VW3A4552	VW3A4552	VW3A4422	–
5.5	*7.5*	**ATV320U55N4B**	VW3A95817	VZ3V32C100	TM200RSRCEMC	–	–	VW3A7731	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4553	VW3A4424	–
7.5	*10*	**ATV320U75N4B**	VW3A95817	VZ3V32C100	TM200RSRCEMC	–	–	VW3A7732	VW3A7604R07	VW3A7604R30	VW3A4553	VW3A4554	VW3A4424	–
11	*15*	**ATV320D11N4B**	VW3A95819	VZ3V32D100	TM200RSRCEMC	–	–	VW3A7732	–	–	VW3A4554	VW3A4554	VW3A4425	–
15	*20*	**ATV320D15N4B**	VW3A95819	VZ3V32D100	TM200RSRCEMC	–	–	VW3A7733	–	–	VW3A4554	VW3A4555	VW3A4425	–

Option modules *(1) (2)*

Description	Reference	Page
Communication option modules		
CANopen Daisy Chain 2 x RJ45 communication module	**VW3A3608**	48
CANopen SUB-D9 communication module	**VW3A3618**	48
CANopen open style communication module	**VW3A3628**	49
Ethernet TCP/IP communication module	**VW3A3616**	50
EtherCAT 2 x RJ45 communication module	**VW3A3601**	51
Profibus DP communication module	**VW3A3607**	51
DeviceNet communication module	**VW3A3609**	51
POWERLINK communication module	**VW3A3619**	51
ProfiNet communication module	**VW3A3627**	51
Other option modules		
Speed monitoring card - RS422 - 5V	**VW3A3620**	45


(1) To use with ATV320 drives with a compact control block, the option module adapter is required (to be ordered separately).
(2) Only one module can be connected at once.

Minimum value of the resistor to be connected

Reference	Minimum Value	Reference	Minimum Value	Reference	Minimum Value
	Ω		Ω		Ω
ATV320U02M●●	40	ATV320D11M3C	5	ATV320U07N4●	80
ATV320U04M●●	40	ATV320D15M3C	5	ATV320D11N4●	16
ATV320U06M●●	40	ATV320U11N4●	54	ATV320D15N4●	16
ATV320U07M●●	40	ATV320U15N4●	54	ATV320U07S6C	96
ATV320U11M●●	27	ATV320U22N4●	54	ATV320U15S6C	64
ATV320U15M●●	27	ATV320U30N4●	54	ATV320U22S6C	64
ATV320U22M●●	25	ATV320U40N4●	36	ATV320U40S6C	44
ATV320U30M3C	16	ATV320U55N4●	27	ATV320U55S6C	27
ATV320U40M3C	16	ATV320U75N4●	27	ATV320U75S6C	23
ATV320U55M3C	8	ATV320U04N4●	80	ATV320D11S6C	24
ATV320U75M3C	8	ATV320U06N4●	80	ATV320D15S6C	24

Variable speed drives
Altivar Machine ATV320
Option: braking resistors

PF106005



VW3A7731

Presentation

Braking resistors allow Altivar Machine ATV320 drives to operate while braking to a standstill or during slowdown braking, by dissipating the braking energy. They enable maximum transient braking torque.
Depending on the drive rating, the following types of resistor are available:

- Enclosed model (IP 20 casing) designed to comply with the EMC standard and protected by a temperature-controlled switch
- Enclosed model (IP 65 casing) with cordset

***Note**: To optimize the size of the braking resistor, the DC buses on Altivar Machine ATV320 drives in the same application can be connected in parallel (see page 18).*

Applications

Machines with high inertia, driving loads, and machines with fast cycles.


References

Drive reference	Ohmic value	Average power available at 50 °C/*122 °F* *(1)*	Length of connection cable	Reference *(2)*	Weight
	Ω	W	m/*ft*		kg/*lb*
IP 20 resistors					
ATV320U02M●● ATV320U04M●● ATV320U04N4●...U30N4● ATV320U07S6C...U40S6C	100	100	–	VW3A7730	1.500/*3.307*
ATV320U06M●●...U15M●● ATV320U40N4● ATV320U55N4● ATV320U55S6C	60	160	–	VW3A7731	1.800/*3.968*
ATV320U22M● ATV320U30M3C ATV320U75N4● ATV320D11N4● ATV320U75S6C…D15S6C	28	300	–	VW3A7732	2.700/*5.952*
ATV320U40M3C ATV320U55M3C ATV320D15N4●	16	960	–	VW3A7733	3.800/*8.377*
ATV320U75M3C	10	960	–	VW3A7734	4.300/*9.480*
ATV320D11M3C	8	960	–	VW3A7735	4.500/*9.920*
ATV320D15M3C	5	1900	–	VW3A7736	18.000/*39.683*

(1) Load factor for resistors: the value of the average power that can be dissipated at 50 °C/122 °F from the resistor into the casing is determined for a load factor during braking that corresponds to the majority of normal applications:
- 2 s braking with a 0.6 Tn braking torque for a 40 s cycle
- 0.8 s braking with a 1.5 Tn braking torque for a 40 s cycle
(2) Recommended braking resistors when ATV320 is used with synchronous motor.

Variable speed drives
Altivar Machine ATV320
Option: braking resistors

PF106005



VW3A7608R●●

References (continued)


Drive reference	Ohmic value	Average power available at 50 °C/*122 °F* (1)	Length of connection cable	Reference (2)	Weight
	Ω	W	m/*ft*		kg/*lb*
IP 65 resistors					
ATV320U02M2●…U07M2● ATV320U04N4●…U22N4● ATV320U02M3C...U07M3C ATV320U07S6C...U22S6C	100	25	0.75/*2.46*	VW3A7608R07	0.410/*0.904*
			3.0/*9.84*	VW3A7608R30	0.760/*1.675*
ATV320U30N4●…U40N4● ATV320U40S6C	72	50	0.75/*2.46*	VW3A7606R07	0.930/*2.050*
			3.0/*9.84*	VW3A7606R30	1.200/*2.645*
ATV320U11M2● ATV320U11M3C ATV320U15M3C	72	25	0.75/*2.46*	VW3A7605R07	0.620/*1.367*
			3.0/*9.84*	VW3A7605R30	0.850/*1.874*
ATV320U55N4● ATV320U75N4● ATV320U55S6C ATV320U75S6C	27	100	0.75/*2.46*	VW3A7604R07	1.420/*3.131*
			3.0/*9.84*	VW3A7604R30	1.620/*3.571*
ATV320U22M2● ATV320U22M3C	27	50	0.75/*2.46*	VW3A7603R07	0.930/*2.050*
			3.0/*9.84*	VW3A7603R30	1.200/*2.645*


(1) Load factor for resistors: the value of the average power that can be dissipated at 50 °C/122 °F from the resistor into the casing is determined for a load factor during braking that corresponds to the majority of normal applications:- 2 s braking with a 0.6 Tn braking torque for a 40 s cycle- 0.8 s braking with a 1.5 Tn braking torque for a 40 s cycle.

(2) Recommended braking resistors when ATV320 is used with synchronous motor.

***Nota**: no optional IP65 braking resistors for ATV320U55S6C, ATV320U75S6C, ATV320D11S6C, ATV320D15S6C, and ATV320●●●M3C drives.*

Variable speed drives
Altivar Machine ATV320
Option: Line chokes





Presentation

Line chokes

Line chokes, also known as line reactors, provide improved immunity against overvoltages on the supply mains and can reduce harmonic distortion of the current produced by the drive.
The recommended chokes limit the line current. They have been developed in line with standard IEC 61800-5-1 (VDE 0160 level 1 high-energy overvoltages on the line supply).
The inductance values are defined for a voltage drop between 3% and 5% of the nominal line voltage. Values higher than this will cause loss of torque.
The use of line chokes is recommended in particular under the following circumstances:

- Supply mains with significant disturbance from other equipment (interference, overvoltages)
- Supply mains with voltage imbalance between phases > 1.8% of nominal voltage
- Drive supplied by a supply mains with very low impedance (in the vicinity of a power transformer 10 times more powerful than the drive rating)
- Installation of a large number of frequency inverters on the same supply mains
- Reduction of overloads on the cos φ correction capacitors, if the installation includes a power factor correction unit

The prospective short-circuit current at the point of connection of the drive must not exceed the maximum value indicated in the reference tables (see page 16). The use of chokes allows connection to the following supply mains:


- Max. Isc 22 kA for 200/240 V
- Max. Isc 65 kA for 380/500 V

References

Drive Reference	Line current, without choke		Line current, with choke		Choke	
	U min. *(1)*	U max. *(1)*	U min. *(1)*	U max. *(1)*	Reference	Weight
	A	A	A	A		kg/*lb*
Single-phase supply voltage: 200…240 V 50/60 Hz						
ATV320U06M2●	7.9	6.7	5.8	5.0	VZ1L007UM50	0.880/*1.940*
ATV320U07M2●	10.1	8.5	7.5	6.4		
ATV320U11M2●	13.6	11.5	11.0	9.4	VZ1L018UM20	1.990/*4.387*
ATV320U15M2●	17.6	14.8	14.3	12.2		
ATV320U22M2●	23.9	20.1	19.9	16.8		
Three-phase supply voltage:200…240 V 50/60 Hz						
ATV320U02M3C	2.0	1.7	1.0	0.9	VW3A4551	1.500/*3.307*
ATV320U04M3C	3.6	3.0	1.9	1.6		
ATV320U06M3C	4.9	4.2	2.7	2.3		
ATV320U07M3C	6.3	5.3	3.6	3.0		
ATV320U11M3C	8.6	7.2	5.0	4.2	VW3A4552	3.000/*6.613*
ATV320U15M3C	11.1	9.3	6.7	5.6		
ATV320U22M3C	14.9	12.5	9.4	7.9	VW3A4553	3.500/*7.716*
ATV320U30M3C	18.7	15.7	12.5	10.4		
ATV320U40M3C	23.8	19.9	16.3	13.8	VW3A4554	6.000/*13.228*
ATV320U55M3C	35.4	29.8	21.8	18.2		
ATV320U75M3C	45.3	38.2	29.1	24.2		
ATV320D11M3C	60.9	51.4	41.1	34.4	VW3A4555	11.000/*24.251*
ATV320D15M3C	79.7	67.1	54.7	45.6		
Three-phase supply voltage: 380…500 V 50/60 Hz						
ATV320U04N4●	2.1	1.6	1.1	0.9	VW3A4551	1.500/*3.307*
ATV320U06N4●	2.8	2.2	1.5	1.3		
ATV320U07N4●	3.6	2.7	1.9	1.6		
ATV320U11N4●	5.0	3.8	2.7	2.1		
ATV320U15N4●	6.5	4.9	3.5	2.7		
ATV320U22N4●	8.7	6.6	5.1	4.0	VW3A4552	3.000/*6.613*
ATV320U30N4●	11.1	8.4	6.6	5.2		
ATV320U40N4●	13.7	10.5	8.5	6.6		
ATV320U55N4●	20.7	14.5	11.5	9.3	VW3A4553	3.500/*7.716*
ATV320U75N4●	26.5	18.7	15.3	12.0		
ATV320D11N4●	36.6	25.6	21.8	17.8	VW3A4554	6.000/*13.228*
ATV320D15N4●	47.3	33.3	28.8	22.8		
Three-phase supply voltage: 525…600 V 50/60 Hz *(2)*						
ATV320U07S6C	–	–	1.5	1.4	VW3A4551	1.500/*3.307*
ATV320U15S6C	–	–	2,6	2.4		
ATV320U22S6C	–	–	3.7	3.2		
ATV320U40S6C	–	–	6.5	5.8	VW3A4552	3.000/*6.613*
ATV320U55S6C	–	–	8.4	7.5		3.500/*7.716*
ATV320D11S6C	–	–	15.8	14.1	VW3A4553	6.000/*13.228*
ATV320U75S6C	–	–	11.6	10.5		3.500/*7.716*
ATV320D15S6C	–	–	22.1	20.1	VW3A4554	6.000/*13.228*

(1) Nominal supply voltage
(2) ATV320●●●S6C drives must not be used without a Line choke

Variable speed drives
Altivar Machine ATV320
Option: Motor chokes



Presentation

Motor chokes

Motor chokes, also known as load reactors, can be inserted between the Altivar Machine ATV320 drive and the motor to:

- Limit the dv/dt at the motor terminals (500 to 1500 V/µs), for cables longer than 50 m/*164.04 ft*
- Filter interference caused by the opening of a contactor placed between the filter and the motor
- Reduce the motor ground leakage current
- Smooth the motor current wave form to reduce motor noise

References


For drives	Losses	Cable length *(1)*		Nominal current	Reference	Weight
		Shielded cable	Unshielded cable			
	W	m/*ft*	m/*ft*	A		kg/*lb*
Single-phase supply voltage: 200…240 V 50/60 Hz						
ATV320U02M2●…U15M2●	65	≤ 100/*328.08*	≤ 200/*656.17*	10	VW3A4552	3.000/*6.613*
ATV320U22M2●	75	≤ 100/*328.08*	≤ 200/*656.17*	16	VW3A4553	3.500/*7.716*
Three-phase supply voltage: 200…240 V 50/60 Hz						
ATV320U02M3C...U15M3C	65	≤ 100/*328.08*	≤ 200/*656.17*	10	VW3A4552	3.000/*6.613*
ATV320U22M3C ATV320U30M3C	75	≤ 100/*328.08*	≤ 200/*656.17*	16	VW3A4553	3.500/*7.716*
ATV320U40M3C...U75M3C	90	≤ 100/*328.08*	≤ 200/*656.17*	30	VW3A4554	6.000/*13.228*
ATV320D11M3C...D15M3C	260	≤ 100/*328.08*	≤ 200/*656.17*	107	VW3A4556	16.000/35.274
Three-phase supply voltage: 380…500 V 50/60 Hz						
ATV320U04N4●…U40N4●	65	≤ 100/*328.08*	≤ 200/*656.17*	10	VW3A4552	3.000/*6.613*
ATV320U55N4●	75	≤ 100/*328.08*	≤ 200/*656.17*	16	VW3A4553	3.500/*7.716*
ATV320U75N4● ATV320D11N4●	90	≤ 100/*328.08*	≤ 200/*656.17*	30	VW3A4554	6.000/*13.228*
ATV320D15N4●	80	≤ 100/*328.08*	≤ 200/*656.17*	60	VW3A4555	11.000/*24.251*
Three-phase supply voltage: 525…600 V 50/60 Hz						
ATV320U07S6C ATV320U15S6C ATV320U22S6C ATV320U40S6C ATV320U55S6C	65	≤ 100/*328.08*	≤ 200/*656.17*	10	VW3A4552	3.000/*6.613*
ATV320U75S6C	75	≤ 100/*328.08*	≤ 200/*656.17*	16	VW3A4553	3.500/*7.716*
ATV320D11S6C ATV320D15S6C	75	≤ 100/*328.08*	≤ 200/*656.17*	16	VW3A4554	6.000/*13.228*

(1) For an application with several motors connected in parallel, the total motor cable lengths must be added together. If a cable longer than that recommended is used, the filters may overheat.

Variable speed drives
Altivar Machine ATV320
Additional EMC filters



VW3A4422 + ATV320U04N4B



VW3A4424 + ATV320U55N4B

Presentation

Additional EMC Filter

The additional EMC input filters enable the drives to meet more stringent requirements;

- They are designed to reduce conducted emissions on the supply mains below the limits of standard IEC 61800-3 category C1 or C2.
- Enlarge the maximum motor cable length of IEC 61800-3 category C3

Mounting on ATV320●●●●B

- Depending on the model, additional EMC filters can be mounted beside or underneath the drive.
- They act as a support for the drives and are attached to them via tapped holes.

Mounting the filter on the side of the drive:

1 ATV320●●●M2B, ATV320U04N4B…U40N4B drive
2 Additional EMC filter

Mounting the filter underneath the drive:

3 ATV320U55N4B…U75N4B or ATV320D11N4B…D15N4B drive
4 Additional EMC filter

Mounting on ATV320●●●●C

Additional EMC filters can be mounted beside or underneath the ATV320●●●●●C drives, except for the ATV320●●●S6C drives.
They act as a support for the drives and are attached to them via tapped holes.

Use according to the type of supply mains

- Additional EMC filters can only be used on TN (neutral connection) and TT (grounded neutral) type systems.
- Standard IEC 61800-3, appendix D2.1, states that on IT systems (isolated or impedance grounded neutral), filters can cause permanent insulation monitors to operate in a random manner.
- The effectiveness of additional filters on this type of system depends on the type of impedance between neutral and ground, and therefore cannot be predicted.
- If a machine has to be installed on an IT system, one solution is to insert an isolation transformer and connect the machine locally on a TN or TT system.
- The radio interference input filters integrated in Altivar 320 drives can easily be disconnected by means of a selector switch without removing the drive.

Variable speed drives
Altivar Machine ATV320
Additional EMC filters

105586



VW3A31405

PF095115



VW3A4422

PF095117



VW3A4424

References

Additional EMC input filters

Corresponding drive Reference	Additional EMC input filter: Maximum length of shielded cable (1) (2) IEC 61800-3 (5) Category C3	Category C2	Category C1	In (3)	Losses (4)	Mounting the filter/ Book format	Reference	Weight
	m/*ft*	m/*ft*	m/*ft*	A	W			kg/*lb*
Single-phase supply voltage: 200…240 V 50/60 Hz								
ATV320U02M2C…U07M2C ATV320U02M2W…U07M2W ATV320U02M2WS…U07M2WS	100/328.08	50/*164.04*	20/*65.61*	9	3.7	–	VW3A31401	0.600/ *1.323*
ATV320U11M2C…U15M2C ATV320U11M2W…U15M2W ATV320U11M2WS…U15M2WS	100/328.08	50/*164.04*	20/*65.61*	16	6.9	–	VW3A31403	0.775/ *1.709*
ATV320U22M2C ATV320U22M2W ATV320U22M2WS	100/328.08	50/*164.04*	20/*65.61*	22	7.5	–	VW3A31405	1.130/ *2.491*
ATV320U02M2B…U07M2B	50/164.04	20/*65.61*	5/*16.40*	10.1	3.7	On the side	VW3A4420	0.600/ *1.323*
ATV320U11M2B…U15M2B	100/328.08	50/*164.04*	2/*65.61*	17.6	6.9	On the side	VW3A4421	0.775/ *1.709*
ATV320U22M2B	100/328.08	50/*164.04*	2/*65.61*	23.9	7.5	On the side	VW3A4426	1.130/ *2.491*
Three-phase supply voltage: 200…240 V 50/60 Hz								
ATV320U02M3C...U07M3C	5/*16.40*	5/*16.40*	1/*3.28*	7	2.6	–	VW3A31402	0.650/ *1.433*
ATV320U11M3C...U22M3C	5/*16.40*	5/*16.40*	1/*3.28*	15	9.9	–	VW3A31404	1.000/ *2.205*
ATV320U30M3C...U40M3C	5/*16.40*	5/*16.40*	1/*3.28*	25	15.8	–	VW3A31406	1.650/ *3.637*
ATV320U55M3C...U75M3C	5/*16.40*	5/*16.40*	1/*3.28*	47	19.3	–	VW3A31407	3.150/ *6.945*
ATV320D11M3C...D15M3C	5/*16.40*	5/*16.40*	1/*3.28*	83	35.2	–	VW3A31408	5.300/ *11.684*
Three-phase supply voltage: 380…500 V 50/60 Hz								
ATV320U04N4C…U15N4C ATV320U04N4W…U15N4W ATV320U04N4WS…U15N4WS	150/*492.12*	50/*164.04*	20/*65.61*	15	9.9	–	VW3A31404	1.000/ *2.205*
ATV320U22N4C…U40N4C ATV320U22N4W…U40N4W ATV320U22N4WS…U40N4WS	100/*328.08*	50/*164.04*	20/*65.61*	25	15.8	–	VW3A31406	1.650/ *3.637*
ATV320U04N4B…U40N4B	150/*492.12*	50/*164.04*	20/*65.61*	15	9.9	On the side	VW3A4422	0.900/ *1.984*
ATV320U55N4●…U75N4● ATV320U55N4W…U75N4W ATV320U55N4WS…U75WS	150/*492.12*	100/*328.08*	20/*65.61*	47	19.3	Underneath	VW3A4424	3.150/ *6.944*
ATV320U07N4B..ATV320U15N4B	150/*492.12*	100/*328.08*	20/*65.61*	6.5	N/A	Underneath	VW3A4461	–
ATV320U30N4B..ATV320U40N4B	150/*492.12*	100/*328.08*	20/*65.61*	13.7	N/A	Underneath	VW3A4462	–
ATV320D11N4B…D15N4B	150/*492.12*	100/*328.08*	20/*65.61*	49	27.4	Underneath	VW3A4425	4.750/ *10.472*
ATV320D11N4C…D15N4C	150/*492.12*	100/*328.08*	5/*16.40*	49	27.4	Underneath	VW3A4425	4.750/ *10.472*

(1) The filter selection tables give the maximum lengths for shielded cables connecting motors to drives. These maximum lengths are given as examples only, as they vary depending on the stray capacitance of the motors and the cables used. If motors are connected in parallel, it is the total length of all cables that should be taken into account.
(2) These values are given for a nominal switching frequency of 4 kHz.
(3) In: nominal filter current.
(4) Via heat dissipation, at the nominal filter current (In).
(5) Standard IEC 61800-3:
Environmental 1(Residential): C1 and C2
EN55011 Group 1:Class B and Class A
Environmental 2(Industrial): C3 and C4
EN55011 Group 2:Class A and N/A

Variable speed drives
Altivar Machine ATV320
Option: option module adapter



*Example of installing a communication module **3** (view of underside) on a drive with compact control block*

Presentation


Altivar Machine ATV320 drives are designed for use with option modules according to machine and application requirements; only one option module can be used with an Altivar Machine ATV320 at a time.
The option modules are compatible with all Altivar Machine ATV320 drives (see page 32).
The **VW3A3600** option module adapter is required to connect an option module to Altivar Machine ATV320 IP20 drives with a compact control block and ATV320 IP66/65 products. **ATV320●●●●●C** and ATV320 IP65/66 products **ATV320●●●●●W**/ **ATV320●●●●●WS**.

Compact control block

An adapter should be added to the Altivar Machine ATV320 drives with compact control block in order to connect communication and speed monitoring modules.
1 Communication adapter card
2 Slot for the communication or speed monitoring module
3 Communication module

References

Description	Reference	Weight kg/*lb*
Mechanical adapter for communication module - for ATV320 compact drive	VW3A3600	–




*Example of installing a communication module **6** (view of underside) on a drive with book control block*

Book control block

Altivar Machine ATV320 drives with a book control block have been designed to simplify connections to communication buses and networks by means of the following:
4 Integrated RJ45 communication port for Modbus/CANopen on the front
5 Slot for the communication module
6 Communication module

Variable speed drives
Altivar Machine ATV320
Option: speed monitoring module

PF130914



VW3A3620

Presentation

The VW3A3620 speed monitoring module is recommended for hoisting applications in OPEN loop control. .
This module helps to detect undesired load slip on hoisting applications by means of an external encoder. The variable speed drive manages the load slip according to the configuration parameters.

Functions

- The load slip frequency threshold represents the difference between the speed feedback and the output frequency.
- The load slip detection level can be adjusted so that the function can be used more efficiently.
- The load slip direction check allows the variable speed drive to check that movement is initiated in the desired direction.
- The load slip detection duration can be configured in order to optimize the use of the function according the changing mechanics.

The **VW3A3620** speed monitoring module helps to ensure that the actual motor speed is within the acceptable threshold settings and that movement is in the desired direction.


The variable speed drive will trigger a warning and the motor will stop either with a freewheel stop or via the brake logic control function (depending on the configuration) in the following cases:
- if the actual speed is different from the permitted speed reference threshold and this reaches the defined duration, or
- if the direction of motor rotation is not as expected

Speed monitoring module *(1)*


Description	Reference	Weight kg/*lb*
Speed monitoring module Port: One 6-way screw connector ■ RS422 ■ Input nominal voltage: 5 V	VW3A3620	0.300/ *0.660*

(1) To use with ATV320 drives with a compact control block, the option module adapter is required (to be ordered separately).

Variable speed drives
Altivar Machine ATV320
Communication buses and networks



Example of configuration on Modbus serial link



Example of configuration on CANopen machine bus

Presentation

Altivar Machine ATV320 drives are designed to meet the configuration requirements found in the main industrial communication installations.
The Modbus and CANopen communication protocols are integrated as standard and can be accessed directly via the RJ45 communication port located on the front of the book control block drive and underneath the front door of the compact control block drive.
ATV320 drives can also be connected to other industrial communication buses and networks by using one of the communication modules available as an option.
Communication modules are supplied in “cassette” format for ease of mounting/removal.

Modbus serial link *(1)*

The Modbus serial link is used for connecting the following HMI and configuration tools:
- Harmony HMI terminal
- Remote display terminal, remote graphic display terminal
- SoMove setup software, Simple Loader and Multi-loader configuration tools

CANopen machine bus *(1) (2) (3)*

The CANopen machine bus is used for integration into control system architectures, especially when combined with Modicon M241 and M251 logic controllers or Lexium 32 motion controllers.


Optimized solutions for connection to the CANopen machine bus

To simplify setting up the Altivar Machine ATV320 drive, 3 dedicated CANopen communication modules *(2)* are available depending on the connection and connector types:
- CANopen daisy chain module with 2 RJ45 connectors offering an optimized solution for daisy chain connection to the CANopen machine bus (see page 48)
- CANopen module for connection to the bus via 9-way SUB-D connector (see page 48)
- CANopen module for connection to the bus via terminals (see page 49)

Using one of the CANopen communication modules also reduces the installation dimensions compared to using **VW3CANTAP2** and **TSXCANTDM4** junction boxes.

Communication modules for industrial applications *(3)*

The following communication modules are available:
- Modbus TCP and EtherNet/IP
- PROFIBUS DP V1
- DeviceNet
- EtherCAT
- POWERLINK
- PROFINET



*Example of installing a communication module **3** (view of underside)*

Description

Altivar Machine ATV320 drives with book control block have been designed to simplify connections to communication buses and networks by means of the following:
1 Integrated RJ45 communication port for Modbus/CANopen on the front
2 Slot for the communication module
3 Communication module

Altivar Machine ATV320 drives with compact control block are equipped as standard with:
1 Integrated RJ45 communication port for Modbus/CANopen
The **VW3A3600** mechanical adapter for communication modules can be used to make more communication buses and networks available by inserting the corresponding module directly into the adapter.
2 Slot for the communication module
3 Communication module

(1) The Modbus serial link always uses the RJ45 communication port. If simultaneous use of the Modbus serial link and the CANopen machine bus is required, a CANopen communication module is needed.
(2) When one of the CANopen communication modules is inserted in the Altivar 320 drive, CANopen communication via the RJ45 communication port is disabled.
(3) The Altivar 320 drive can only take one communication module.


Functions:
page 47

References:
page 47


Variable speed drives
Altivar Machine ATV320
Communication buses and networks



Altivar 320 compact format drive with communication module in the option module adapter



Example of connection of an Altivar 320 compact format drive and a Harmony GTO HMI terminal via the Modbus serial link



Example of connection of an Altivar 320 book format drive and a Harmony GTO HMI terminal via the Modbus serial link

Functions

All Altivar Machine ATV320 drive functions can be accessed via the communication buses and networks:
- Control
- Monitoring
- Adjustment
- Configuration

The speed reference and command may come from different sources:
- digital input or analog I/O terminals
- Communication bus or network
- Remote display terminals

The ATV320 drive's advanced functions can be used to manage switching of these drive control sources according to the application requirements.
The communication periodic I/O data assignment can be selected using the network configuration software.
The ATV320 drive can be controlled:
- According to the CiA 402 native profile
- According to the I/O profile

Communication is monitored according to criteria specific to each protocol.
Regardless of protocol type, the reaction of the drive to a detected communication interruption can be configured as follows:
- Freewheel stop, stop on ramp, fast stop, or braked stop
- Maintain the last command received
- Fallback position at a predefined speed
- Ignore the detected error

Modbus serial link *(1)*

Connection accessories for remote Human-Machine Interface *(2)*

Description	Item no.	Length m/*ft*	Reference	Weight kg/*lb*
Cordsets for Modbus serial link equipped with 2 RJ45 connectors	1	0.3/*0.98*	VW3A8306R03	0.025/ *0.055*
		1.0/*3.28*	VW3A8306R10	0.060/ *0.132*
		3.0/*9.84*	VW3A8306R30	0.130/ *0.287*

(1) The Modbus serial link always uses the RJ45 communication port. If simultaneous use of the Modbus serial link and the CANopen machine bus is required, a CANopen communication module is needed.
(2) See page 28 for connection of a remote display terminal or remote graphic display terminal.
(3) Requires a 24 V ⎓ power supply. Please refer to the Harmony GTO catalog.

Presentation:
page 46


Variable speed drives
Altivar Machine ATV320
Communication buses and networks

PF095127




VW3A3608

Modicon M241 *(7)*



ATV320 Compact + VW3A3600 + VW3A3608 module

Modicon M251 *(7)*



ATV320 Book + VW3A3608 module


Optimized solution for daisy chain connection to the CANopen machine bus

PF095128



VW3A3618

HMI SCU *(7)*



ATV320 Book + VW3A3618 module

Example of connection to the CANopen machine bus via SUB-D connector

Compact drive communication adapter *(1)*

Description	Item no.	Length m/*ft*	Unit reference	Weight kg/*lb*
Communication module adapter for ATV320 Compact	1	–	VW3A3600	–

CANopen machine bus *(2)*

Description	Item no.	Length m/*ft*	Unit reference	Weight kg/*lb*
Connection with VW3A3608 CANopen daisy chain module (optimized solution for daisy chain connection to the CANopen machine bus)				
CANopen daisy chain communication module *(2) (3) (4)* Ports: 2 RJ45 connectors	2	–	VW3A3608	–
CANopen cordsets equipped with 2 RJ45 connectors	3	0.3/ *0.98*	VW3CANCARR03	0.050/ *0.110*
		1.0/ *3.28*	VW3CANCARR1	0.500/ *1.102*
CANopen line terminator for RJ45 connector	4	–	TCSCAR013M120	–
Connection via SUB-D connector with VWA3618 CANopen module				
CANopen communication module *(2) (3)* Port: 1 x 9-way male SUB-D connector	5	–	VW3A3618	–
CANopen cable Standard cable, CE marking Low smoke zero halogen Flame retardant (IEC 60332-1)	6	50/ *164.04*	TSXCANCA50	4.930/ *10.869*
		100/ *328.08*	TSXCANCA100	8.800/ *19.401*
		300/ *984.25*	TSXCANCA300	24.560/ *54.145*
CANopen cable Standard cable, UL certification, CE marking Flame retardant (IEC 60332-2)	6	50/ *164.04*	TSXCANCB50	3.580/ *7.892*
		100/ *328.08*	TSXCANCB100	7.840/ *17.284*
		300/ *984.25*	TSXCANCB300	21.870/ *48.215*
CANopen cable Cable for harsh environments *(5)* or mobile installations, CE marking Low smoke zero halogen Flame retardant (IEC 60332-1)	6	50/ *164.04*	TSXCANCD50	3.510/ *7.738*
		100/ *328.08*	TSXCANCD100	7.770/ *17.130*
		300/ *984.25*	TSXCANCD300	21.700/ *47.840*
CANopen IP 20 straight connector 9-way female SUB-D with line terminator that can be deactivated	7	–	TSXCANKCDF180T	0.049/ *0.108*
IP 20 CANopen right angle connector *(6)* 9-way female SUB-D with line terminator that can be deactivated	7	–	TSXCANKCDF90T	0.046/ *0.101*

*(1) Altivar Machine ATV320 products with a compact control block require the **VW3A3600** option module adapter in order to use any communication option modules.*
(2) The Modbus serial link always uses the RJ45 communication port. If simultaneous use of the Modbus serial link and the CANopen machine bus is required, a CANopen communication module is needed.
(3) The Altivar Machine ATV320 drive can only take one communication module.
(4) When one of the CANopen communication modules is inserted in the Altivar Machine ATV320 drive, CANopen communication via the RJ45 communication port on the front is disabled.
(5) Standard environment:
- *No particular environmental constraints*
- *Operating temperature between 5 and 60 °C/41 and 140 °F*
- *Fixed installation*

Harsh environment:
- *Resistance to hydrocarbons, industrial oils, detergents, solder splashes*
- *Relative humidity up to 100%*
- *Saline atmosphere*
- *Operating temperature between -10 and +70 °C/14 and 158 °F*
- *Significant temperature variations*

(6) Incompatible with side-by-side mounting.
(7) Please refer to the Modicon M241 catalog, Modicon M251 catalog, or the Harmony SCU catalog.
(8) Cable dependent on the type of controller or PLC; please refer to the corresponding catalog.


Presentation: page 46
Functions: page 47

LXM32_CP21043



VW3A3628

Modicon M251 *(4)*



Example of connection to the CANopen machine bus via screw terminals

CANopen machine bus (continued) *(1)(7)*

Description	Item no.	Length m/*ft*	Unit reference	Weight kg/*lb*
Connection via terminals with VW3A3628 CANopen open style module				
CANopen open style communication module *(2) (3)* Port: 1 x 5-way spring terminal block	8	–	VW3A3628	–
CANopen line terminator for spring terminal connector	9	–	TCSCAR01NM120	–
Other connection accessories and cordsets				
IP 20 CANopen cordsets equipped with 2 x 9-way female SUB-D connectors. Standard cable, CE marking Low smoke zero halogen Flame retardant (IEC 60332-1)	–	0.3/ *0.98*	TSXCANCADD03	0.091/ *0.201*
		1.0/ *3.28*	TSXCANCADD1	0.143/ *0.315*
		3.0/ *9.84*	TSXCANCADD3	0.295/ *0.650*
		5.0/ *16.40*	TSXCANCADD5	0.440/ *0.970*
IP 20 CANopen cordsets equipped with 2 x 9-way female SUB-D connectors. Standard cable, UL certification, CE marking Flame retardant (IEC 60332-2)	–	0.3/ *0.98*	TSXCANCBDD03	0.086/ *0.190*
		1.0/ *3.28*	TSXCANCBDD1	0.131/ *0.289*
		3.0/ *9.84*	TSXCANCBDD3	0.268/ *0.591*
		5.0/ *16.40*	TSXCANCBDD5	0.400/ *0.882*
IP 20 CANopen junction boxes equipped with: ■ 4 x 9-way male SUB-D connectors + screw terminal block for trunk cable tap link ■ Line terminator	–	–	TSXCANTDM4	0.196/ *0.432*
IP 20 CANopen junction boxes equipped with: ■ 2 screw terminal blocks for trunk cable tap link ■ 2 RJ45 connectors for connecting drives ■ 1 RJ45 connector for connecting a PC	–	–	VW3CANTAP2	0.480/ *1.058*


(1) The Modbus serial link always uses the RJ45 communication port. If simultaneous use of the Modbus serial link and the CANopen machine bus is required, a CANopen communication module is needed.
(2) The Altivar Machine ATV320 drive can only take one communication module.
(3) When one of the CANopen communication modules is inserted in the Altivar Machine ATV320 drive, CANopen communication via the RJ45 communication port is disabled.
(4) Please refer to the Modicon M251 catalog.
(5) Cable dependent on the type of controller or PLC; please refer to the corresponding catalog.
*(6) See page 48 for item "**6**".*
*(7) Altivar Machine ATV320 products with a compact control block require the **VW3A3600** option module adapter in order to use any communication option modules.*

Variable speed drives
Altivar Machine ATV320
Communication buses and networks




VW3A3616

Modicon M221*(4)*



ATV320 Compact + VW3A3600 + VW3A3616 module

Modicon M251*(4)*



ATV320 Book + VW3A3616 module

Example of connection on an EtherNet/IP network

Modbus TCP network and EtherNet/IP network *(1) (5)*

Description	Item no.	Length m/*ft* *(3)*	Reference	Weight kg/*lb*
Communication module				
Modbus TCP and EtherNet/IP network module For connection to the Modbus TCP network or EtherNet/IP network Ports: 2 RJ45 connectors ■ 10/100 Mbps, half duplex and full duplex ■ Embedded web server Requires cordsets 490NTW000●●/●●U or 490NTC000●●/●●U	2	–	VW3A3616	0.300/ *0.661*
ConneXium cordsets *(2) (3)*				
Straight shielded twisted pair cordsets equipped with 2 RJ45 connectors Conforming to EIA/TIA-568 category 5 and IEC 11801/EN 50173-1, class D standards	3	2.0/ *6.56*	490NTW00002	–
		5.0/ *16.40*	490NTW00005	–
		12/ *39.37*	490NTW00012	–
Crossed shielded twisted pair cordsets equipped with 2 RJ45 connectors Conforming to EIA/TIA-568 category 5 and IEC 11801/EN 50173-1, class D standards	4	5.0/ *16.40*	490NTC00005	–
		15/ *49.21*	490NTC00015	–
Straight shielded twisted pair cables equipped with 2 RJ45 connectors Conforming to UL and CSA 22.1 standards	3	2.0/ *6.56*	490NTW00002U	–
		5.0/ *16.40*	490NTW00005U	–
		12/ *39.37*	490NTW00012U	–
Crossed shielded twisted pair cordsets equipped with 2 RJ45 connectors Conforming to UL and CSA 22.1 standards	3	5.0/ *16.40*	490NTC00005U	–
		15/ *49.21*	490NTC00015U	–

(1) The Altivar Machine ATV320 drive can only take one communication module.
(2) For other ConneXium connection accessories, please refer to our website.
(3) Also available in 40 m/131.23 ft and 80 m/262.46 ft lengths (2).
(4) Please refer to the Modicon M221 catalog or Modicon M251 catalog.
*(5) Altivar Machine ATV320 products with a compact control block require the **VW3A3600** option module adapter (item 1) in order to use any communication option modules.*

Presentation: page 46
Functions: page 47

PF095130




VW3A3607

PROFIBUS DP V1 bus *(1)(2)*

Description	Reference	Weight kg/*lb*
PROFIBUS DP V1 communication module Port: 1 x 9-way female SUB-D connector Conforming to PROFIBUS DP V1 Profiles supported: ■ CiA 402 drive ■ Profidrive Offers several message handling modes based on DP V1	VW3A3607	0.140/ *0.308*

PF095140



VW3A3609

DeviceNet bus *(1)(2)*

Description	Reference	Weight kg/*lb*
DeviceNet communication module Port: 1 removable 5-way screw connector Profiles supported: ■ CIP AC DRIVE ■ CiA 402 drive	VW3A3609	–

PF102282



VW3A3601

EtherCAT bus *(1)(2)*

Description	Reference	Weight kg/*lb*
EtherCAT communication module Port: 2 RJ45 connectors	VW3A3601	–

PF095144



VW3A3619

POWERLINK network *(1)(2)*

Description	Reference	Weight kg/*lb*
Ethernet POWERLINK communication module Port: 2 RJ45 connectors	VW3A3619	0.300/ *0.660*

PF130913



VW3A3627

ProfiNet network *(1)(2)*

Description	Reference	Weight kg/*lb*
ProfiNet communication module Port: 2 RJ45 connectors	VW3A3627	0.300/ *0.660*

(1) The Altivar Machine ATV320 drive can only take one communication module.
*(2) Altivar Machine ATV320 products with a compact control block require the **VW3A3600** option module adapter in order to use any communication option modules.*

Presentation:
page 46

Functions:
page 47

Variable speed drives
Altivar Machine ATV320
Motor starters (circuit breaker + drive)
Supply voltage 200...240 V

Applications

Two types of combination are possible:

- Circuit breaker + variable speed drive: minimum combination. The circuit breaker can be mounted directly on **ATV320 book type less than 4kW** drives using the bracket for GV2/ATV320 direct mounting (**VW3A9921**) and the adapter plate (**GV2AF5**) (see page 18).
- Circuit breaker + contactor + variable speed drive combination. The circuit breaker provides protection against accidental short circuits, disconnection and isolation.

For ATV320●●●●●WS, circuit breaker can't be integrated inside.

For ATV320●●●●●W, the combination table of Circuit breaker, Rotary handle kit (GVAPB65S or GV2APN03), and Base plate (VW3A9922) is indicated in the installation manual.

Example:

ATV320U07N4W + GV2L08 + GVAPB65S +VW3A9922

ATV320U55N4W + GV2L22 + GV2APN03

GVAPB65S used below 4 kW, GV2APN03 used for 5.5 kW and 7.5 kW motor power.

A contactor can be used downstream of the drive to help ensure the motor is isolated on stopping. In this case, the contactor size should be category AC-3 depending on the associated motor, only for operation between 25 Hz and 500 Hz.

The Altivar Machine ATV320 drive is protected electronically against short circuits between phases and between phase and ground. It therefore provides continuity of service and thermal monitoring of the motor.

ATV320_63440_OPF16047



GV2 / ATV320 direct mounting:
GV2L08
+
*(**VW3A9921** + **GV2AF5**)*
(5) (6)
+
ATV320U07N4B

Motor starters: Circuit breaker + Drive

Standard power ratings of three-phase 4-pole 50/60 Hz motors *(2)*		Variable speed drive	Circuit breaker *(1)*	
		Reference *(3)*	Reference	Circuit breaker mounted directly on ATV320 *(4)*
kW	***HP***			
Single-phase supply voltage: 200…240 V 50/60 Hz				
0.18	*0.25*	**ATV320U02M2●**	**GV2L08** *(5)*	With accessories VW3A9921 + GV2AF5 *(6)*
0.37	*0.5*	**ATV320U04M2●**	**GV2L10** *(5)*	
0.55	*0.75*	**ATV320U06M2●**	**GV2L14** *(5)*	
0.75	*1*	**ATV320U07M2●**	**GV2L16** *(5)*	
1.1	*1.5*	**ATV320U11M2●**	**GV2L16** *(5)*	
1.5	*2*	**ATV320U15M2●**	**GV2L20** *(5)*	
2.2	*3*	**ATV320U22M2●**	**GV2L22** *(5)*	
Three-phase supply voltage: 200…240 V 50/60 Hz				
0.18	*0.25*	**ATV320U02M3C**	**GV2L07** *(5)*	–
0.37	*0.5*	**ATV320U04M3C**	**GV2L08** *(5)*	
0.55	*0.75*	**ATV320U06M3C**	**GV2L10** *(5)*	
0.75	*1*	**ATV320U07M3C**	**GV2L14** *(5)*	
1.1	*1.5*	**ATV320U11M3C**	**GV2L14** *(5)*	
1.5	*2*	**ATV320U15M3C**	**GV2L16** *(5)*	
2.2	*3*	**ATV320U22M3C**	**GV2L20** *(5)*	
3	*4*	**ATV320U30M3C**	**GV2L22** *(5)*	
4	*5*	**ATV320U40M3C**	**GV2L22** *(5)*	
5.5	*7.5*	**ATV320U55M3C**	**GV3L40** *(5)*	
7.5	*10*	**ATV320U75M3C**	**GV3L50** *(5)*	
11	*15*	**ATV320D11M3C**	**GV3L65** *(5)*	
15	*20*	**ATV320D15M3C**	**GV3L80**	

(1) GV2L, GV3L: TeSys magnetic motor circuit breakers; accessories (see page 55).
(2) The HP values given are NEC-compliant (National Electrical Code).
(3) For the complete reference, replace ● with B, C, W, WS version.
(4) The circuit breaker can be mounted directly only on the book format drive **ATV320U●●M2B** *and* ***ATV320U04N4B****…***U40N4B****.***
(5) GV●L●● circuit breaker reference are not UL compliant.To achieve UL Type E compliance GV●P●● thermal magnetic circuit breaker must be used.
(6) To be ordered separately (see page 17), see note (4) for compatibility.

Variable speed drives
Altivar Machine ATV320
Motor starters (circuit breaker + drive)
Supply voltage 380...600 V



ATV320U07S6C

Motor starters: Circuit breaker + Drive

Standard power ratings of three-phase 4-pole 50/60 Hz motors *(2)*		Variable speed drive	Circuit breaker *(1)*	
		Reference *(3)*	Reference	Circuit breaker mounted directly on ATV320 *(4)*
kW	***HP***			
Three-phase supply voltage: 380…500 V 50/60 Hz				
0.37	*0.5*	**ATV320U04N4●**	**GV2L07** *(5) (7)*	With accessories VW3A9921 + GV2AF5 *(6)*
0.55	*0.75*	**ATV320U06N4●**	**GV2L08** *(5) (7)*	
0.75	*1*	**ATV320U07N4●**	**GV2L08** *(5) (7)*	
1.1	*1.5*	**ATV320U11N4●**	**GV2L10** *(5) (7)*	
1.5	*2*	**ATV320U15N4●**	**GV2L14** *(5) (7)*	
2.2	*3*	**ATV320U22N4●**	**GV2L14** *(5) (7)*	
3	*4*	**ATV320U30N4●**	**GV2L16** *(5) (7)*	
4	*5*	**ATV320U40N4●**	**GV2L16** *(5) (7)*	
5.5	*7.5*	**ATV320U55N4●**	**GV2L22** *(5)*	–
7.5	*10*	**ATV320U75N4●**	**GV2L32** *(5)*	
11	*15*	**ATV320D11N4●**	**GV3L40** *(5)*	
15	*20*	**ATV320D15N4●**	**GV3L50** *(5)*	
Three-phase supply voltage: 525…600 V 50/60 Hz				
0.75	*1*	**ATV320U07S6C**	**GV3P13**	–
1.5	*2*	**ATV320U15S6C**	**GV3P13**	
2.2	*3*	**ATV320U22S6C**	**GV3P13**	
4	*5*	**ATV320U40S6C**	**GV3P13**	
5.5	*7.5*	**ATV320U55S6C**	**GV3P13**	
7.5	*10*	**ATV320U75S6C**	**GV3P18**	
11	*15*	**ATV320D11S6C**	**GV3P25**	
15	*20*	**ATV320D15S6C**	**GV3P32**	

(1) GV2L, GV3L: TeSys magnetic motor circuit breakers; accessories (see page 55).
(2) The HP values given are NEC-compliant (National Electrical Code).
(3) For the complete reference, replace ● with B, C, W, WS version.
(4) The circuit breaker can be mounted directly only on the book format drive **ATV320U●●M2B** *and* ***ATV320U04N4B*****…U40N4B**.
(5) GV●L●● circuit breaker reference are not UL compliant.To achieve UL Type E compliance GV●P●● thermal magnetic circuit breaker must be used.
(6) To be ordered separately (see page 17), see note (4) for compatibility.
(7) A GV2P TeSys thermal magnetic circuit breaker with the same rating can also be used with **ATV320U04N4●…U40N4●** *drives. The thermal release should then be set to maximum to inhibit this function.*

Variable speed drives
Altivar Machine ATV320
Motor starters (circuit breaker + contactor + drive)
Supply voltage 200...240 V

PF600335



PF600336



ATV320_63440_CPF16002



GV2L14
+
LC1D09
+
ATV320U07M3C

Motor starters: Circuit breaker + Contactor + Drive

Standard power rating of 50/60 Hz 4-pole motors *(3)*		Variable speed drive Reference *(4)*	Circuit breaker *(1)* Reference	Rating	LRM	Contactor *(2)* Reference *(5)*
kW	*HP*			*A*	*A*	
Single-phase supply voltage: 200…240 V 50/60 Hz						
0.18	*0.25*	**ATV320U02M2●**	**GV2L08** *(6)*	4	51	**LC1D09●●**
0.37	*0.5*	**ATV320U04M2●**	**GV2L10** *(6)*	6.3	78	**LC1D09●●**
0.55	*0.75*	**ATV320U06M2●**	**GV2L14** *(6)*	10	138	**LC1D09●●**
0.75	*1*	**ATV320U07M2●**	**GV2L16** *(6)*	14	170	**LC1D09●●**
1.1	*1.5*	**ATV320U11M2●**	**GV2L16** *(6)*	14	170	**LC1D09●●**
1.5	*2*	**ATV320U15M2●**	**GV2L20** *(6)*	18	223	**LC1D09●●**
2.2	*3*	**ATV320U22M2●**	**GV2L22** *(6)*	25	327	**LC1D09●●**
Three-phase supply voltage: 200…240 V 50/60 Hz						
0.18	*0.25*	**ATV320U02M3C**	**GV2L07** *(6)*	2.5	33.5	**LC1D09●●**
0.37	*0.5*	**ATV320U04M3C**	**GV2L08** *(6)*	4	51	**LC1D09●●**
0.55	*0.75*	**ATV320U06M3C**	**GV2L10** *(6)*	6.3	78	**LC1D09●●**
0.75	*1*	**ATV320U07M3C**	**GV2L14** *(6)*	10	138	**LC1D09●●**
1.1	*1.5*	**ATV320U11M3C**	**GV2L14** *(6)*	10	138	**LC1D09●●**
1.5	*2*	**ATV320U15M3C**	**GV2L16** *(6)*	14	170	**LC1D09●●**
2.2	*3*	**ATV320U22M3C**	**GV2L20** *(6)*	18	223	**LC1D09●●**
3	*4*	**ATV320U30M3C**	**GV2L22** *(6)*	25	327	**LC1D09●●**
4	*5*	**ATV320U40M3C**	**GV2L22** *(6)*	25	327	**LC1D09●●**
5.5	*7.5*	**ATV320U55M3C**	**GV3L40** *(6)*	40	560	**LC1D25●●**
7.5	*10*	**ATV320U75M3C**	**GV3L50** *(6)*	50	700	**LC1D32●●**
11	*15*	**ATV320D11M3C**	**GV3L65** *(6)*	65	910	**LC1D50●●**
15	*20*	**ATV320D15M3C**	**GV3L80**	80	1100	**LC1D65●●**

(1) GV2L, GV3L: TeSys magnetic motor circuit breakers; accessories (see page 55).
(2) Composition of TeSys contactors LC1D09/D18/D25/D32/D50/D65: 3 poles + 1 NO auxiliary contact + 1 NC auxiliary contact.
(3) The HP values given are NEC-compliant (National Electrical Code).
(4) For the complete reference, replace ● with B, C, W or WS.
(5) Replace ●● with the control circuit voltage reference given in the table below:

AC control circuit						
	Volts ∿	**24**	**48**	**115**	**230**	**230/240**
LC1D	50/60 Hz	B7	E7	FE7	P7	U7

For other voltages between 24 V and 660 V, or a DC control circuit, please refer to the TeSys catalog.

(6) GV●L●● circuit breaker reference are not UL compliant.To achieve UL Type E compliance GV●P●● thermal magnetic circuit breaker must be used.

Variable speed drives

Altivar Machine ATV320

Motor starters (circuit breaker + contactor + drive)

Supply voltage 380...600 V

PF600335



PF600336



ATV320_63440_OPF16032



ATV320_63440_OPF16016



GV2L14
+
LC1D09
+
ATV320U15N4B/ATV320U04N4C

Motor starters: Circuit breaker + Contactor + Drive

Standard power rating of 50/60 Hz 4-pole motors *(3)*		Variable speed drive	Circuit breaker *(1)*			Contactor *(2)*
		Reference *(4)*	Reference	Rating	LRM	Reference *(5)*
kW	*HP*			*A*	*A*	
Three-phase supply voltage: 380…500 V 50/60 Hz						
0.37	*0.5*	**ATV320U04N4●**	**GV2L07** *(6)*	2.5	33.5	**LC1D09●●**
0.55	*0.75*	**ATV320U06N4●**	**GV2L08** *(6)*	4	51	**LC1D09●●**
0.75	*1*	**ATV320U07N4●**	**GV2L08** *(6)*	4	51	**LC1D09●●**
1.1	*1.5*	**ATV320U11N4●**	**GV2L10** *(6)*	6.3	78	**LC1D09●●**
1.5	*2*	**ATV320U15N4●**	**GV2L14** *(6)*	10	138	**LC1D09●●**
2.2	*3*	**ATV320U22N4●**	**GV2L14** *(6)*	10	138	**LC1D09●●**
3	*4*	**ATV320U30N4●**	**GV2L16** *(6)*	14	170	**LC1D09●●**
4	*5*	**ATV320U40N4●**	**GV2L16** *(6)*	14	170	**LC1D09●●**
5.5	*7.5*	**ATV320U55N4●**	**GV2L22** *(6)*	25	327	**LC1D09●●**
7.5	*10*	**ATV320U75N4●**	**GV2L32** *(6)*	32	416	**LC1D18●●**
11	*15*	**ATV320D11N4●**	**GV3L40** *(6)*	40	560	**LC1D25●●**
15	*20*	**ATV320D15N4●**	**GV3L50** *(6)*	50	700	**LC1D32●●**
Three-phase supply voltage: 525…600 V 50/60 Hz						
0.75	*1*	**ATV320U07S6C**	**GV3P13**	13	182	**LC1D09●●**
1.5	*2*	**ATV320U15S6C**	**GV3P13**	13	182	**LC1D09●●**
2.2	*3*	**ATV320U22S6C**	**GV3P13**	13	182	**LC1D09●●**
4	*5*	**ATV320U40S6C**	**GV3P13**	13	182	**LC1D09●●**
5.5	*7.5*	**ATV320U55S6C**	**GV3P13**	13	182	**LC1D09●●**
7.5	*10*	**ATV320U75S6C**	**GV3P18**	18	252	**LC1D09●●**
11	*15*	**ATV320D11S6C**	**GV3P25**	25	350	**LC1D18●●**
15	*20*	**ATV320D15S6C**	**GV3P32**	32	448	**LC1D25●●**

(1) GV2L, GV3L: TeSys magnetic motor circuit breakers; accessories (see page 55).
(2) Composition of TeSys contactors LC1D09/D18/D25/D32: 3 poles + 1 NO auxiliary contact + 1 NC auxiliary contact.
(3) The HP values given are NEC-compliant (National Electrical Code).
(4) For the complete reference, replace ● with B, C, W, WS version.
(5) Replace ●● with the control circuit voltage reference given in the table below:

AC control circuit						
	Volts ∼	**24**	**48**	**115**	**230**	**230/240**
LC1D	50/60 Hz	B7	E7	FE7	P7	U7

For other voltages between 24 V and 660 V, or a DC control circuit, please refer to the TeSys catalog.

(6) GV●L●● circuit breaker reference are not UL compliant.To achieve UL Type E compliance GV●P●● thermal magnetic circuit breaker must be used.

Variable speed drives

Altivar Machine ATV320

Drives with compact control block

200…240 V Single-phase and Three-phase



IP20 drives with compact control block

Single-phase supply voltage: 200…240 V 50/60 Hz

Reference		W x H x D (1)	
		mm	in.
ATV320U02M2C		72 x 143 x 109	2.83 x 5.63 x 4.29
	With EMC plate	72 x 188 x 109	2.83 x 7.40 x 4.29
	With UL Type 1 conformity kit	72 x 195.5 x 109	2.83 x 7.70 x 4.29
ATV320U04M2C		72 x 143 x 128	2.83 x 5.63 x 5.04
	With EMC plate	72 x 188 x 128	2.83 x 7.40 x 5.04
	With UL Type 1 conformity kit	72 x 195.5 x 128	2.83 x 7.70 x 5.04
ATV320U06M2C ATV320U07M2C		72 x 143 x 143	2.83 x 5.63 x 5.63
	With EMC plate	72 x 188 x 143	2.83 x 7.40 x 5.63
	With UL Type 1 conformity kit	72 x 195.5 x 143	2.83 x 7.70 x 5.63
ATV320U11M2C ATV320U15M2C ATV320U22M2C		105 x 142 x 158	4.13 x 5.60 x 6.22
	With EMC plate	105 x 188 x 158	4.13 x 7.40 x 6.22
	With UL Type 1 conformity kit	105 x 210.5 x 158	4.13 x 8.29 x 6.22

Three-phase supply voltage: 200…240 V 50/60 Hz

Reference		W x H x D (1)	
		mm	in.
ATV320U02M3C		72 x 143 x 109	2.83 x 5.63 x 4.29
	With EMC plate	72 x 188 x 109	2.83 x 7.40 x 4.29
	With UL Type 1 conformity kit	72 x 195.5 x 109	2.83 x 7.70 x 4.29
ATV320U04M3C		72 x 143 x 128	2.83 x 5.63 x 5.04
	With EMC plate	72 x 188 x 128	2.83 x 7.40 x 5.04
	With UL Type 1 conformity kit	72 x 195.5 x 128	2.83 x 7.70 x 5.04
ATV320U06M3C ATV320U07M3C		72 x 143 x 138	2.83 x 5.63 x 5.43
	With EMC plate	72 x 188 x 138	2.83 x 7.40 x 5.43
	With UL Type 1 conformity kit	72 x 195.5 x 138	2.83 x 7.70 x 5.43
ATV320U11M3C ATV320U15M3C ATV320U22M3C		105 x 143 x 138	4.13 x 5.63 x 5.43
	With EMC plate	105 x 189 x 138	4.13 x 7.44 x 5.43
	With UL Type 1 conformity kit	105 x 210.5 x 138	4.13 x 8.29 x 5.43
ATV320U30M3C ATV320U40M3C		140 x 184 x 158	5.51 x 7.24 x 6.22
	With EMC plate	140 x 228 x 158	5.51 x 8.97 x 6.22
	With UL Type 1 conformity kit	140 x 236.5 x 158	5.51 x 9.31 x 6.22
ATV320U55M3C ATV320U75M3C		150 x 232 x 178	5.91 x 9.13 x 7.01
	With EMC plate	150 x 308 x 178	5.91 x 12.13 x 7.01
	With UL Type 1 conformity kit	150 x 316 x 178	5.91 x 12.44 x 7.01
ATV320D11M3C ATV320D15M3C		180 x 330 x 198	7.09 x 12.99 x 7.80
	With EMC plate	180 x 404 x 198	7.09 x 15.91 x 7.80
	With UL Type 1 conformity kit	180 x 410.5 x 198	7.09 x 16.16 x 7.80

(1) The total depth excludes the module adapter, + 20 mm/0.79 in. in depth if combined with the option module adapter.

Presentation: page 6
Variable speed drives: page 16
Combinations: page 32

Variable speed drives
Altivar Machine ATV320
Drives with compact control block
Three-phase supply voltage: 380…600 V



IP20 drives with compact control block

Three-phase supply voltage: 380…500 V 50/60 Hz

Reference		W x H x D *(1)* mm	*in.*
ATV320U04N4C ATV320U06N4C ATV320U07N4C ATV320U11N4C ATV320U15N4C		105 x 142 x 158	*4.13 x 5.60 x 6.22*
	With EMC plate	105 x 188 x 158	*4.13 x 7.40 x 6.22*
	With UL Type 1 conformity kit	105 x 210.5 x 158	*4.13 x 8.29 x 6.22*
ATV320U22N4C ATV320U30N4C ATV320U40N4C		140 x 184 x 158	*5.51 x 7.24 x 6.22*
	With EMC plate	140 x 228 x 158	*5.51 x 8.97 x 6.22*
	With UL Type 1 conformity kit	140 x 236.5 x 158	*5.51 x 9.31 x 6.22*
ATV320U55N4C ATV320U75N4C		150 x 232 x 178	*5.91 x 9.13 x 7.01*
	With EMC plate	150 x 308 x 178	*5.91 x 12.13 x 7.01*
	With UL Type 1 conformity kit	150 x 316 x 178	*5.91 x 12.44 x 7.01*
ATV320D11N4C ATV320D15N4C		180 x 330 x 198	*7.09 x 12.99 x 7.80*
	With EMC plate	180 x 404 x 198	*7.09 x 15.91 x 7.80*
	With UL Type 1 conformity kit	180 x 410.5 x 198	*7.09 x 16.16 x 7.80*

Three-phase supply voltage: 525…600 V 50/60 Hz

Reference		W x H x D *(1)* mm	*in.*
ATV320U07S6C ATV320U15S6C		105 x 142 x 158	*4.13 x 5.60 x 6.22*
	With EMC plate	105 x 188 x 158	*4.13 x 7.40 x 6.22*
	With UL Type 1 conformity kit	105 x 210.5 x 158	*4.13 x 8.29 x 6.22*
ATV320U22S6C ATV320U40S6C		140 x 184 x 158	*5.51 x 7.24 x 6.22*
	With EMC plate	140 x 228 x 158	*5.51 x 8.97 x 6.22*
	With UL Type 1 conformity kit	140 x 236.5 x 158	*5.51 x 9.31 x 6.22*
ATV320U55S6C ATV320U75S6C		150 x 232 x 178	*5.91 x 9.13 x 7.01*
	With EMC plate	150 x 308 x 178	*5.91 x 12.13 x 7.01*
	With UL Type 1 conformity kit	150 x 316 x 178	*5.91 x 12.44 x 7.01*
ATV320D11S6C ATV320D15S6C		180 x 330 x 198	*7.09 x 12.99 x 7.80*
	With EMC plate	180 x 404 x 198	*7.09 x 15.91 x 7.80*
	With UL Type 1 conformity kit	180 x 410.5 x 198	*7.09 x 16.16 x 7.80*


(1) The total depth excludes the module adapter, + 20 mm/0.79 in. in depth if combined with the option module adapter.

Variable speed drives

Altivar Machine ATV320

Drives with book control block

Single-phase 200…240 V and Three-phase 380…500 V



Drives with book control block

Single-phase supply voltage: 200…240 V 50/60 Hz

Reference		W x H x D	
		mm	*in.*
ATV320U02M2B		45 x 325 x 245	*1.77 x 12.8 x 9.65*
ATV320U04M2B			
ATV320U06M2B			
ATV320U07M2B			
ATV320U11M2B		60 x 325 x 245	*2.63 x 12.8 x 9.65*
ATV320U15M2B			
ATV320U22M2B			

Three-phase supply voltage: 380…500 V 50/60 Hz

Reference		W x H x D	
		mm	*in.*
ATV320U04N4B ATV320U06N4B ATV320U07N4B ATV320U11N4B ATV320U15N4B		45 x 325 x 245	*1.77 x 12.8 x 9.65*
ATV320U22N4B ATV320U30N4B ATV320U40N4B		60 x 325 x 245	*2.36 x 12.8 x 9.65*
ATV320U55N4B ATV320U75N4B		150 x 232 x 232	*5.91 x 9.13 x 9.13*
	With EMC plate	150 x 308 x 232	*5.91 x 12.1 x 9.13*
	With UL Type 1 conformity kit	155 x 314 x 240	*6.10 x 12.36 x 9.45*
ATV320D11N4B ATV320D15N4B		180 x 330 x 232	*7.09 x 13.0 x 9.13*
	With EMC plate	180 x 404 x 232	*7.09 x 15.91 x 9.13*
	With UL Type 1 conformity kit	185 x 408.5 x 250	*7.28 x 16.08 x 9.84*


Presentation: page 6
Variable speed drives: page 16
Combinations: page 32

Variable speed drives

Altivar Machine ATV320

IP66 drive without vario and IP65 drive with vario

Single-phase 200…240 V and Three-phase 380…500 V



IP66 drive without vario and IP65 drive with vario		
Single-phase supply voltage: 200…240 V 50/60 Hz		
Reference	**W x H x D**	
	mm	***in.***
ATV320U02M2W ATV320U02M2WS ATV320U04M2W ATV320U04M2WS ATV320U06M2W ATV320U06M2WS ATV320U07M2W ATV320U07M2WS	250 x 340 x 182	*9.84 x 13.39 x 7.17*
ATV320U11M2W ATV320U11M2WS ATV320U15M2W ATV320U15M2WS ATV320U22M2W ATV320U22M2WS	250 x 340 x 235	*9.84 x 13.39 x 9.25*
Three-phase supply voltage: 380…500 V 50/60 Hz		
Reference	**W x H x D**	
	mm	***in.***
ATV320U04N4W ATV320U04N4WS ATV320U06N4W ATV320U06N4WS ATV320U07N4W ATV320U07N4WS ATV320U11N4W ATV320U11N4WS ATV320U15N4W ATV320U15N4WS	250 x 340 x 200	*9.84 x 13.39 x 7.87*
ATV320U22N4W ATV320U22N4WS ATV320U30N4W ATV320U30N4WS ATV320U40N4W ATV320U40N4WS	250 x 340 x 235	*9.84 x 13.39 x 9.25*
ATV320U55N4W	320 x 521 x 300	*12.6 x 20.51 x 11.81*
ATV320U55N4WS	320 x 521 x 335	*12.6 x 20.51 x 13.19*
ATV320U75N4W	320 x 521 x 300	*12.6 x 20.51 x 11.81*
ATV320U75N4WS	320 x 521 x 335	*12.6 x 20.51 x 13.19*

Variable speed drives
Altivar Machine ATV320
Line chokes, Motor chokes, Braking resistors, and Additional EMC input filters

Line chokes

Reference	W x H x D	
	mm	*in.*
VW3A4551	100 x 135 x 60	*3.94 x 5.31 x 2.36*
VW3A4552 VW3A4553	130 x 155 x 90	*5.11 x 6.10 x 3.54*
VW3A4554	155 x 170 x 135	*5.90 x 6.69 x 5.31*
VW3A4555	180 x 210 x 160	*7.09 x 8.27 x 6.30*
VZ1L007UM50	60 x 100 x 95	*2.36 x 9.94 x 3.74*
VZ1L018UM20	85 x 120 x 105	*3.35 x 4.72 x 4.13*

Motor chokes

Reference	W x H x D	
	mm	*in.*
VW3A4552 VW3A4553	130 x 155 x 90	*5.11 x 6.10 x 3.54*
VW3A4554	155 x 170 x 135	*5.90 x 6.69 x 5.31*
VW3A4555	180 x 210 x 160	*7.09 x 8.27 x 6.30*
VW3A4556	270 x 210 x 180	*10.6 x 8.27 x 7.09*

Braking resistors

Reference	W x H x D	
	mm	*in.*
VW3A7603R07 VW3A7603R30	251 x 204 x 15.5	*9.88 x 8.03 x 0.61*
VW3A7604R07 VW3A7604R30	257 x 204 x 30	*10.11 x 8.03 x 1.18*
VW3A7605R07 VW3A7605R30	145 x 98 x 15.5	*5.70 x 3.85 x 0.61*
VW3A7606R07 VW3A7606R30	251 x 204 x 15.5	*9.88 x 8.03 x 0.61*
VW3A7608R07 VW3A7608R30	145 x 98 x 15.5	*5.70 x 3.85 x 0.61*
VW3A7730	105 x 295 x 100	*4.13 x 11.61 x 3.94*
VW3A7731	105 x 345 x 100	*4.13 x 13.58 x 3.94*
VW3A7732	175 x 345 x 100	*6.89 x 13.58 x 3.94*
VW3A7733	190 x 570 x 180	*7.48 x 22.44 x 7.09*
VW3A7734 VW3A7735	250 x 490 x 180	*9.84 x 19.29 x 7.09*
VW3A7736	485 x 410 x 485	*19.09 x 16.14 x 19.09*


Additional EMC input filters

Reference	W x H x D	
	mm	*in.*
VW3A31401 VW3A31402	72 x 195 x 37	*2.82 x 7.63 x 1.45*
VW3A31403	107 x 195 x 35	*4.2 x 7.63 x 1.37*
VW3A31404	107 x 195 x 42	*4.2 x 7.63 x 1.65*
VW3A31405	140 x 235 x 35	*5.48 x 9.2 x 1.37*
VW3A31406	140 x 235 x 50	*5.48 x 9.2 x 1.96*
VW3A31407	180 x 305 x 60	*7.09 x 12.01 x 2.36*
VW3A31408	245 x 395 x 80	*9.65 x 15.55 x 3.15*
VW3A4420	72 x 195 x 37	*2.82 x 7.63 x 1.45*
VW3A4421	107 x 195 x 35	*4.2 x 7.63 x 1.37*
VW3A4422	107 x 195 x 42	*4.2 x 7.63 x 1.65*
VW3A4424	180 x 305 x 60	*7.05 x 11.94 x 2.35*
VW3A4425	245 x 395 x 60	*9.59 x 15.46 x 2.35*
VW3A4426	140 x 235 x 35	*5.48 x 9.2 x 1.37*
VW3A4461	70 x 315 x 60	*2.75 x 12.4 x 2.36*
VW3A4462	78 x 315 x 75	*3.07 x 12.4 x 2.95*

Presentation: page 6
Variable speed drives: page 16
Combinations: page 32


Variable speed drives and soft starters

A whole world of Services for your drives and soft starters by Schneider Electric



Support and services offer by Schneider Electric

Variable speed drives and soft starters are an important part of your operation, with downtime having a significant impact on your business. Protecting that investment through comprehensive services means that you can continue to deliver optimally throughout the lifecycle of your drive and soft starter. Our range of services is designed to help you get more out of your drives and soft starters, your operation, and to improve your environmental impact.



Install

- **Extended Warranty** service helps you control your maintenance costs. Schneider Electric will provide a replacement drive and soft starter or repair the product on site during a period of one or three years more than the standard warranty, in all conditions covered by the extended warranty.
- **Start-up** service is the first essential step in maintenance and optimal operational performance of the drive or soft starter. Our comprehensive review checks up to 100 parameters and is especially designed for drives and soft starters in simple applications.
- **Commissioning** service ensures a reliable start for operations with more complex applications and drive systems. The unique requirements of your process need to be carefully considered to ensure efficient operations.

Operate

- **Preventive Maintenance** service performs predetermined maintenance actions according to a product-specific schedule. The work is carried out by certified technical experts following Schneider Electric instructions. This service minimizes unplanned downtime and extends your equipment lifetime.
- **Remote Technical Support** brings you expert product assistance over the phone, email, chat, or web for any technical questions relating to your drives and soft starters, including configuration, diagnostics, and maintenance. Our global support team is multi-lingual with support available up to R&D level experts if needed.
- **On-Site Expert Assistance** service offers you highly skilled field service experts to troubleshoot and resolve drive or soft starter equipment-related matters at your site, as a back-up source of expertise for your personnel.
- **Spare Part Management** service identifies and manages your critical spare parts either on your site or offsite. This service ensures that you have access to the spares you need without having to invest in capital to maintain the stock.

(1) Services available in countries that have the right structure and capabilities.

Variable speed drives and soft starters

A whole world of Services for your drives and soft starters by Schneider Electric

Support and services offer by Schneider Electric (continued)

Optimize

- **Training** service offers eLearning, classroom, and onsite training provision to enhance the technical installation, commissioning, and maintenance competencies of your personnel. Added competence translates into further process efficiency and reliability, as well as employee satisfaction.
- **EcoStruxure Asset Advisor** service enables you to move from reactive to predictive maintenance and access actionable insight provided by the advisor. The service predicts drive- and motor-related actions through connected devices and advanced algorithms monitored by Schneider Electric's experts.

Renew

- **Drive Revitalization** is an excellent choice if you prefer to use your aging drives longer and want to extend their service life with affordable and comprehensive inspection and replacement of all critical parts.
- **Drive and soft starter replacement** involves modernizing equipment by replacing the previous aged or obsolete product with a new one matched to the purpose. The service can be extended with engineering in case the device and process requires more advanced engineering.

Circular economy

- **Spare Parts** are available from our local, regional, and global stocks. Original equipment parts from Schneider Electric are reliable and easily available. They will help to keep your product in operation for longer.
- **Repair** allows you to extend the life of your drive or soft starter. The affected product can be replaced, or repaired on site or at our repair centers, depending on the type of product in question.
- **Fast Exchange by refurbished drive or soft starter** *(1)* gives a second life to inoperative drives or soft starters. In this case, we offer an immediate exchange with a replacement refurbished drive or soft starter and take back the product, repair it, and keep it ready for the next exchange.
- **Take-back and recycling** *(1)* is the last step to improve your environmental impact. Unrepairable products are dismantled, raw materials are collected and given a second life. Up to 85% of the product components can be recycled.



Service contracts secure recovery, availability, and outcome

Service contracts manage the safety and performance of your assets through well-defined maintenance plans tailored to your operational needs. The predefined service contract – Advantage Service Plan – and fully customizable "à la carte" service contract are built from the services in the "Operate" and "Optimize" phases and service levels defining availability, response, and lead times matching your particular needs. You will enjoy priority access to Schneider Electric support when you need it, as well as having an expert partner to plan the long-term evolution of your drives and soft starters.



mySchneider app

With the mySchneider app you have easy 24/7 access to product information and expert support. All registered users have access to additional features, such as real-time notifications, order tracking, product pricing, and availability. The mySchneider app is available for download from the IOS and Android app store.

Schneider Electric – helping you succeed

Schneider Electric, the leader in digital transformation of energy management and automation, has operations in more than 100 countries. With this global footprint we have certified field service representatives, regional expert and advanced level support up to product R&D to provide you the right support across the lifecycle of your drives and soft starters. Furthermore, we offer an extensive network of local and global repair centers and a logistics chain that underpins our ability to respond to your needs.

To order services or find out more, please contact your local Schneider Electric service center.

(1) Services available in countries that have the right structure and capabilities.

Product reference index

#

490NTC00005 50
490NTC00005U 50
490NTC00015 50
490NTC00015U 50
490NTW00002 50
490NTW00002U 50
490NTW00005 50
490NTW00005U 50
490NTW00012 50
490NTW00012U 50

A

ATV320D11M3C 12 16 20 32 36 52 56
ATV320D11N4B 12 18 20 36 53 55 58
ATV320D11N4C 12 17 20 32 36 53 55 56
ATV320D11S6C 12 17 20 32 36 53 55 56
ATV320D15M3C 12 16 20 32 36 52 56
ATV320D15N4B 12 18 20 36 53 55 58
ATV320D15N4C 12 17 20 32 36 53 55 56
ATV320D15S6C 12 17 20 32 36 53 55 56
ATV320U02M2B 12 18 20 36 52 58
ATV320U02M2C 12 16 20 32 36 52 56
ATV320U02M2W 12 19 20 34 36 52 59
ATV320U02M2WS 9 12 19 34 36 52 59
ATV320U02M3C 12 16 20 32 36 52 56
ATV320U04M2B 12 18 20 36 52 56
ATV320U04M2C 12 16 20 32 36 52 56
ATV320U04M2W 12 19 20 34 36 52 59
ATV320U04M2WS 12 19 34 36 52 59
ATV320U04M3C 12 16 20 32 36 52 56
ATV320U04N4B 12 18 20 36 53 55 58
ATV320U04N4C 12 17 20 32 36 53 55 56
ATV320U04N4W 12 19 20 34 36 53 55 59
ATV320U04N4WS 12 19 34 36 53 55 59
ATV320U06M2B 12 18 20 36 52 58
ATV320U06M2C 12 16 20 32 36 52 56
ATV320U06M2W 12 19 20 34 36 52 59
ATV320U06M2WS 12 19 34 36 52 59
ATV320U06M3C 12 16 20 32 36 52 56
ATV320U06N4B 12 18 20 36 53 55 58
ATV320U06N4C 12 17 20 32 36 53 55 56
ATV320U06N4W 12 19 20 34 36 53 55 59
ATV320U06N4WS 12 19 34 36 53 55 59
ATV320U07M2B 12 18 20 36 52 58
ATV320U07M2C 12 16 20 32 36 52 56
ATV320U07M2W 12 19 20 34 36 52 59
ATV320U07M2WS 12 19 34 36 52 59
ATV320U07M3C 12 16 20 32 36 52 56
ATV320U07N4B 12 18 20 36 53 55 58
ATV320U07N4C 12 17 20 32 36 53 55 56
ATV320U07N4W 12 19 20 34 36 53 55 59
ATV320U07N4WS 12 19 34 36 53 55 56
ATV320U07S6C 12 17 20 32 36 53 55 56
ATV320U11M2B 12 18 20 36 52 58
ATV320U11M2C 12 16 20 32 36 52 56
ATV320U11M2W 12 19 20 34 36 52 59
ATV320U11M2WS 12 19 34 36 52 59
ATV320U11M3C 12 16 20 32 36 52 56
ATV320U11N4B 12 18 20 36 53 55 58
ATV320U11N4C 12 17 20 32 36 53 55 56
ATV320U11N4W 12 19 20 34 36 53 55 59
ATV320U11N4WS 12 19 34 36 53 55 59
ATV320U15M2B 12 18 20 36 52 58
ATV320U15M2C 12 16 20 32 36 52 56
ATV320U15M2W 12 19 20 34 36 52 59

Product reference index

ATV320U15M2WS 12 19 34 36 52 59
ATV320U15M3C 12 16 20 32 36 52 56
ATV320U15N4B 12 18 20 36 53 55 58
ATV320U15N4C 12 17 20 32 36 53 55 56
ATV320U15N4W 12 19 20 34 36 53 55 59
ATV320U15N4WS 12 19 34 36 53 55 59
ATV320U15S6C 12 17 20 32 36 53 55 56
ATV320U22M2B 12 18 20 36 52 58
ATV320U22M2C 12 16 20 32 36 52 56
ATV320U22M2W 12 19 20 34 36 52 59
ATV320U22M2WS 12 19 34 36 52 59
ATV320U22M3C 12 16 20 32 36 52 56
ATV320U22N4B 12 18 20 36 53 55 58
ATV320U22N4C 12 17 20 32 36 53 55 56
ATV320U22N4W 12 19 20 34 36 53 55 59
ATV320U22N4WS 12 19 34 36 53 55 59
ATV320U22S6C 12 17 20 32 36 53 55 56
ATV320U30M3C 12 16 20 32 36 52 56
ATV320U30N4B 12 18 20 36 53 55 58
ATV320U30N4C 12 17 20 32 36 53 55 56
ATV320U30N4W 12 19 20 34 36 53 55 59
ATV320U30N4WS 12 19 34 36 53 55 59
ATV320U40M3C 12 16 20 32 36 52 56
ATV320U40N4B 12 18 20 36 53 55 58
ATV320U40N4C 12 17 20 32 36 53 55 56
ATV320U40N4W 12 19 20 34 36 53 55 59
ATV320U40N4WS 12 19 34 36 53 55 59
ATV320U40S6C 12 17 20 32 36 53 55 56
ATV320U55M3C 12 16 20 32 36 52 56
ATV320U55N4B 12 18 20 36 53 55 58
ATV320U55N4C 12 17 20 32 36 53 55 56
ATV320U55N4W 12 19 20 34 36 53 55 59
ATV320U55N4WS 12 19 34 36 53 55 59
ATV320U55S6C 12 17 20 32 36 53 55 56
ATV320U75M3C 12 16 20 32 36 52 56
ATV320U75N4B 12 18 20 36 53 55 58
ATV320U75N4C 12 17 20 32 36 53 55 56
ATV320U75N4W 12 19 20 34 36 53 55 59
ATV320U75N4WS 12 19 34 36 53 55 59
ATV320U75S6C 12 17 20 32 36 53 55 56
ATVRD15N4 24 25
ATVRU75N4 24 25

G

GV2AF5 20 52 53
GV2APN03 52
GV2L07 52 53 54 55
GV2L08 20 52 53 54 55
GV2L10 52 53 54 55
GV2L14 52 53 54 55
GV2L16 52 53 54 55
GV2L20 52 54
GV2L22 52 53 54 55
GV2L32 53 55
GV2P07 52 53 54 55
GV2P08 52 53 54 55
GV2P10 52 53 54 55
GV2P14 52 53 54 55
GV2P16 52 53 54 55
GV2P20 52 54
GV2P22 52 53 54 55
GV3L40 52 53 54 55
GV3L50 52 53 54 55
GV3L65 52 54
GV3L80 52 54
GV3P13 53
GV3P18 53
GV3P25 53
GV3P32 53
GV3P40 52 53 54 55
GV3P50 52 53 54 55
GV3P65 52
GV3P80 52 54
GVAPB65S 52

L

LC1D09B7 54 55
LC1D09E7 54 55
LC1D09FE7 54 55
LC1D09P7 54 55

Product reference index

LC1D09U7 54 55
LC1D18B7 55
LC1D18E7 55
LC1D18FE7 55
LC1D18P7 55
LC1D18U7 55
LC1D25B7 54 55
LC1D25E7 54 55
LC1D25FE7 54 55
LC1D25P7 54 55
LC1D25U7 54 55
LC1D32B7 54 55
LC1D32E7 54 55
LC1D32FE7 54 55
LC1D32P7 54 55
LC1D32U7 54 55
LC1D50B7 54
LC1D50E7 54
LC1D50FE7 54
LC1D50P7 54
LC1D50U7 54
LC1D65B7 54
LC1D65E7 54
LC1D65FE7 54
LC1D65P7 54
LC1D65U7 54
LU9GC3 29

T

TCSCAR013M120 48
TCSCAR01NM120 49
TCSMCNAM3M002P 26 27 31
TM200RSRCEMC 21 32 34 36
TSXCANCA100 48
TSXCANCA300 48
TSXCANCA50 48
TSXCANCADD03 49
TSXCANCADD1 49
TSXCANCADD3 49
TSXCANCADD5 49
TSXCANCB100 48
TSXCANCB300 48
TSXCANCB50 48
TSXCANCBDD03 49
TSXCANCBDD1 49
TSXCANCBDD3 49
TSXCANCBDD5 49
TSXCANCD100 48
TSXCANCD300 48
TSXCANCD50 48
TSXCANKCDF180T 48
TSXCANKCDF90T 48
TSXCANTDM4 49

V

VW3A1006 28
VW3A1007 28
VW3A1101 14 29
VW3A1102 29
VW3A1103 29
VW3A1104R10 28 29 31
VW3A1104R100 29 31
VW3A1104R30 28 29 31
VW3A1104R50 29 31
VW3A1105 29
VW3A1111 14 30
VW3A1112 31
VW3A1115 31
VW3A31401 32 43 60
VW3A31402 32 43 60
VW3A31403 32 43 60
VW3A31404 32 43 60
VW3A31405 32 43 60
VW3A31406 32 43 60
VW3A31407 32 43 60
VW3A31408 32 43 60
VW3A3600 32 34 44 46 48
VW3A3601 36 51
VW3A3607 36 51
VW3A3608 36 48
VW3A3609 36 51
VW3A3616 36 50
VW3A3618 36 48
VW3A3619 36 51
VW3A3620 36 45
VW3A36201 23
VW3A3627 36 51
VW3A3628 36 49
VW3A4420 36 43 60
VW3A4421 36 43 60
VW3A4422 36 42 43 60
VW3A4423 60
VW3A4424 36 42 43 60
VW3A4425 36 43 60
VW3A4426 43 60
VW3A4461 43 60
VW3A4462 43 60
VW3A4551 32 34 36 40 41 60
VW3A4552 32 34 36 40 41 60
VW3A4553 32 34 36 40 41 60
VW3A4554 32 34 36 40 41 60
VW3A4555 32 36 40 41 60
VW3A4556 32 41 60
VW3A7603R07 32 34 36 39 60
VW3A7603R30 32 34 36 39 60
VW3A7604R07 32 34 36 39 60
VW3A7604R30 32 34 36 39 60
VW3A7605R07 32 34 36 39 60
VW3A7605R30 32 34 36 39 60
VW3A7606R07 32 34 36 39 60
VW3A7606R30 32 34 36 39 60
VW3A7608R07 32 34 36 39 60
VW3A7608R30 32 34 36 39 60
VW3A7730 32 34 36 38 60
VW3A7731 32 34 36 38 60
VW3A7732 32 34 36 38 60
VW3A7733 32 36 38 60
VW3A7734 32 38 60
VW3A7735 32 38 60
VW3A7736 32 38 60
VW3A8120 27
VW3A8121 27 29
VW3A8306R03 29 47
VW3A8306R10 29 47
VW3A8306R30 29 47
VW3A8306RC 29
VW3A8306TF03 29
VW3A8306TF10 29
VW3A9523 22 32
VW3A9524 22 32
VW3A9525 22 32
VW3A9532 22 32
VW3A9533 22 32
VW3A9535 22 34
VW3A9536 22 34
VW3A95811 22 34
VW3A95812 22 34
VW3A95813 22 34
VW3A95814 22 34
VW3A95815 22 34
VW3A95816 22 34
VW3A95817 22 36
VW3A95818 22 34
VW3A95819 22 36
VW3A9804 21 32
VW3A9805 21 32
VW3A9911 9 22
VW3A9912 9 22
VW3A9920 20
VW3A9921 20 36 52 53
VW3A9922 20
VW3A9923X 20
VW3A9924X 20
VW3CANCARR03 48
VW3CANCARR1 48
VW3CANTAP2 49
VW3M2207 20 36
VW3M7101R01 20
VW3M7102R150 20
VY1F10007V21 23
VY1F32AB1001 23
VZ1L007UM50 32 34 36 40 60
VZ1L018UM20 32 34 36 40 60
VZ3V1301 23 32
VZ3V1302 23 32
VZ3V32066S2 23 34
VZ3V32066S3 23 34
VZ3V32066S4 23
VZ3V320S3 32

Product reference index

VZ3V32A100 23 36

VZ3V32B100 23 36

VZ3V32C100 23 32 36

VZ3V32D100 23 32 36

Z

ZB5AZ905 31

Life Is On | Schneider Electric



Learn more about our products at
www.se.com/drives

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric
Photos: Schneider Electric

Schneider Electric Industries SAS
Head Office
35, rue Joseph Monier - CS 30323
F-92500 Rueil-Malmaison Cedex
France

DIA2ED2160311EN
October 2022 - V9.0

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP