ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

**Artisan Technology Group**
(217) 352-9330 | sales@artisantg.com | artisantg.com

**Full-service, independent repair center**
with experienced engineers and technicians on staff.

**We buy your excess, underutilized, and idle equipment**
along with credit for buybacks and trade-ins.

**Custom engineering**
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

**Expert team | Trust guarantee | 100% satisfaction**

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Schneider Electric / Telemecanique XS530B1PAL2TF* at our website: *Click HERE*

# Product data sheet
## Characteristics

# XS530B1PAL2TF
## inductive proximity sensor XS1 - form 8 x 43 x 8 mm

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 71.22 USD



## Main

| | |
|---|---|
| Range of product | OsiSense XS |
| Series name | General purpose |
| Sensor type | Inductive proximity sensor |
| Sensor name | XS5 |
| Sensor design | Form 8 x 43 x 8 |
| Size | 8 mm |
| Body type | Fixed |
| Enclosure material | Nickel plated brass |
| Type of output signal | Discrete |
| Wiring technique | 3-wire |
| Discrete output function | 1 NO |
| [Us] rated supply voltage | 12...24 V DC |
| Switching capacity in mA | <= 200 mA |
| IP degree of protection | IP67 |

## Complementary

| | |
|---|---|
| Detection face | Lateral top |
| Detector flush mounting acceptance | Flush mountable |
| Material | Metal |
| Front material | PPS |
| Output circuit type | DC |
| Switching frequency | <= 2500 Hz |
| Marking | CE |
| Depth | 0.31 in (8 mm) |
| Height | 0.31 in (8 mm) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

| | |
|---|---|
| Product certifications | UL |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |

## Ordering and shipping details

| | |
|---|---|
| Category | 22490 - SENSORS-ULTRASONIC (XX5,6) |
| Discount Schedule | DS2 |
| GTIN | 00785901015895 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.39000000000000001 |
| Returnability | N |
| Country of origin | FR |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0814 - Schneider Electric declaration of conformity<br>Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

**Artisan Technology Group** is an independent supplier of quality pre-owned equipment

## Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

## We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

## Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP