

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Technical Datasheet
UNO*TEC* 2405 N



Switch Mode Power Supply
NFPG 1311G1001
(**UNO***TEC* **2405 N**)

1 Short Description

The **UNO***TEC* 2405N is a switch mode power supply of the latest generation, which is characterized by its high efficiency and minimum power loss. It features Power Boost and Hyper Boost function. The **UNO***TEC* N can be operated redundantly. Operation in series (2 units max.) and parallel operation (up to 5 devices) are possible. Because of modern architecture, it can work in temperatures up to 60 ° C without load reduction.

2 Technical Data

Input	
Nominal voltage	100-240 VAC -15% +10% 100-230 VDC -10 % + 8%
Network	TN-S, TN-C, TT, IT mains
Nominal frequency	50 / 60 Hz ±6 %
Nominal current	1,3 A @ 100 V AC 0,6 A @ 240 V AC
Efficiency	94,5 %
Power losses	6,88 W
No-load power lossos	1,8 W
Recommended external fuse max	20 A (T) in building installation
Recommended circuit breaker	B6 or C4
Output	
Voltage	24 VDC
Voltage adjustable	24-28 VDC / potentiometer in front plate
Residual Ripple	< 50 mV eff / rms
Spikes	< 200 mV ss / p-p
Nominal current	5 A (up to 60 °C)
Ride-through	≥ 30 ms
“Power boost“ current	7,5 A >. 4 s without voltage variation
“Hyper boost“ current	17,5 A > 20 ms
Short circuit current	After “power boost” follows constant current: 5 A
Switching in parallel	5 devices
Switching in series	2 devices
Output overload and short-circuit protected. With overload the output voltage begins to reduce. With over temperature the power supply switches off.	

J. Schneider Elektrotechnik GmbH
Helmholtzstraße13, 77652 Offenburg · Postfach 2327, 77613 Offenburg · Werner-von-Siemens-Straße 12, 77656 Offenburg
Tel +49 (0) 781 206 0 · Fax +49 (0) 781 253 18 · info@j-schneider.de · www.j-schneider.de · Amtsgericht Freiburg HRB 470458
Geschäftsführer: Dipl.-Betriebswirtin (BA) Bettina Schneider · Dipl.-Wirt,-Ing. (FH) Rolf Anti · UST-Ident-Nr. DE142532740

Reg.-Nr. 2750

Connection Input	
Type of connection	Spring clamp, push-in 2,5 mm²
Connection Input	
Type of connection	Spring clamp, push-in 2,5 mm²
Connection Alarm	
Type of connection	Spring clamp, push-in 2,5 mm²
Classification of climatic environmental conditions	Class 3K3 according to EN 60721
Relative humidity	5 ... 95%, no condensation
Environmental temperature	-25 ... +60 °C
Storage temperature	-40 ... +85 °C
MTBF according to DIN EN 61709:1999-01, SN 29500, DIN EN ISO 13849-1:2008-12	> 506 805h @ 40°C
Housing	
Dimensions	123 x 50 x 138 mm (H x W x D)
Weight	0,66 kg
Protection class	I
Protection class of the housing	IP 20
Pollution degree	2
Fixation	Snap-on mounting on DIN-rail
Fitting position	Vertical
Material	Metal

3 Norms and Standards

IEC / EN60950-1 SELV
EN 61204-3
EN 55011 Klasse B, Gruppe 1
EN 61000-3-2
EN 61000-3-3
EN 61000-4-2 ESD
EN 61000-4-3 HF-Feld
EN 61000-4-4 Burst
EN 61000-4-5 Surge
EN 61000-4-6 HF-asymm
EN 61000-4-11

CE-marking in compliance with EMC directive 2014/30/EU and low-voltage directive 2014/35/EU and Directive 2011/65/EU (RoHS Directive) of THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 8th of June 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (recast)

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP