



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

### 984/A120 Technical Specifications

#### Power Requirements

Integral Power Supply	
Input	20 - 30 Vdc @ 1A Full Load
Output	5 Vdc @ 2.5A to the I/O Bus
P120 AC Power Supply Module	
Input	95 - 270 Vac, 47/63 Hz
Output	24 Vdc @ 1A
P120 DC Power Supply Module	
Input	102...150 Vdc
Output	24 Vdc @ 1.5A

#### Environmental

Temperature, Operating	0 - 60°C
Humidity, Operating	0 - 95% non-condensing
Temperature, Storage	- 40 - +85°C, IEC 68-2-14
Humidity, Storage	0 - 95% non-condensing
Altitude	15,000 feet (4500 m)
Shock	30 G's, 11 msec, 3 pulses/axis
Vibration	10 - 57 Hz: 0.075 mm DA 57 - 150 Hz: 1 g

#### Dimensions

Height	5.6 in (142 mm)
Width	8.4 in (213 mm)
Depth	5 in (127 mm)
Weight	1.0-1.2 lb (455-540g)
Agency Approvals	UL, CSA, FM, CE

### Specially designed for space efficiency

Although the 984/A120 Compact offers the performance of a larger PLC, it is specifically designed for the micro-to-small application. Small in size, its packaging includes the CPU, built-in power supply, and up to 256 I/O in less than 1.5 square feet of panel space. With a depth of less than 5.5 inches, it will fit comfortably in an 8 inch deep panel enclosure.

The primary subrack houses the controller with built-in 24 Vdc power supply and an additional three slots for I/O modules. If required, an optional 120 Vac power converter can occupy one slot. Three additional expansion subracks can be connected, providing up to 18 slots for I/O modules. Subracks can be mounted side-by-side, with no additional hardware. Or they can be mounted in two tiers by using a single bus extension cable. DIN rail mounting makes for a fast, secure installation.

A full complement of discrete I/O modules is available in densities of 4, 8, or 16 points. Analog I/O, high speed counter/ position detection modules, and single axis servo motion control modules are also available.

### 984/A120 Compact Controllers

Controller Model	Memory (Words)				Scan Time	Ports			Input / Output Maximum			
	Logic*	Registers	Extended (6X)			Modbus Port	Modbus+ Port	I/O Series	Discrete I/O	Total Bits** I/O	Total Drops	# Local Racks
			Total	Scan								
PC-A984/A120 (CPU 120)	1.5k	1920	—	3.5k	5 ms/k	1	—	A120	256 any mix	512/512	1	4
PC-A984-130 (CPU 130)	4k	1920	—	6k	5 ms/k	1	—	A120	256 any mix	512/512	1	4
PC-A984-131 (CPU 131)	4k	1920	—	6k	5 ms/k	2	—	A120	256 any mix	512/512	1	4
PC-A984-141 (CPU 141)	8k	1920	—	10k	5 ms/k	2	—	A120	256 any mix	512/512	1	4
PC-A984-145 (CPU 145)	8k	1920	—	10k	5 ms/k	1	1	A120	256 any mix	512/512	1	4
PC-E984-241 (CPU 141)	8k	1920	—	10k	2.5 ms/k	2***	—	A120	256 any mix	512/512	1	4
PC-E984-245 (CPU 145)	8k	1920	—	10k	2.5 ms/k	1***	1	A120	256 any mix	512/512	1	4
PC-E984-251 (CPU 251)	16k	1920	24k	42k	2.5 ms/k	2***	—	A120	256 any mix	512/512	1	4
PC-E984-255 (CPU 255)	16k	1920	24k	42k	2.5 ms/k	1***	1	A120	256 any mix	512/512	1	4

\* Includes memory configuration and I/O Traffic Cop. (888 words minimum – 1k words maximum)

\*\* Includes analog in/out at 16 bits each plus discrete in/out at one bit each.

\*\*\* Comm port 1 supports XMIT Block, temporary Modbus Master



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)