ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Siemens / Potter & Brumfield PM-17DY-24* at our website: *Click HERE*

P&B

Mfr.'s Type	Coil			Contacts	
	Input	Res In Ohms	Nom. Power	Arrange-ment	Amp Rating
Enclosed Relay					
KAP-5AG-120	120	2,250	2VA	SPDT	10
KAP-5AY-24	24	472	1.2W	SPDT	10
KAP-11AY-24	24	85	2VA	DPDT	5
KAP-11AY-120	120	2,250	2VA	DPDT	10
KAP-11AG-24	24	85	1.2W	DPDT	5
KAP-11AG-120	120	2,250	1.2W	DPDT	10
KAP-11DY-12	12	120	2VA	DPDT	5
KAP-11DY-24	24	472	2VA	3PDT	10
KAP-11DY-110	110	10,000	1.2W	3PDT	5
KAP-11DG-24	24	472	1.2W	3PDT	10
KAP-11DG-110	110	10,000			
KAP-14AY-120	120	2,250			
KAP-14AG-120	120	2,250			
KAP-14DY-24	24	472			
KAP-14DG-12	12	120			
KAP-14DG-24	24	472			

KAP-5DG-24 "P" denotes polycarbonate cover with octal-style plug.
KAP-5AG-24 "A" denotes AC coil
KAP-5DG-24 "D" denotes DC coil
KA-5AY-24 "Y" denotes Ag contacts
KA-5AG-24 "G" denotes AgCdO contacts

Note: Open style KArelays mount via a # 6-32 threaded stud and a locating tab on .438 centers Tab requires .165" dia. clearance hole.
Enclosed KAP relays have a seated height of 2.281" and are 1.531" wide and 1.437" deep

KUHP Series Power Relays



FEATURES
- 20-30Arating
- Enclosed Case
- Various mounting options
- 3,750Vrms coil-to contact breakdown
- Class B coil construction
- Approximate Size 1.53" x 1.41" x 1.97"h

Mounting Options: Panel Mount, side or top mount

Mfr.'s Type	Coil			Contacts	
	Input	Res In Ohms	Nom. Power	Arrange-ment	Amp Rating
Enclosed Relay					
KUHP-5A51-24	24	72	2.7VA	SPDT	30
KUHP-5A51-120	120	1,700			
KUHP-5AT1-120	124	1,700	2.7VA	SPDT	30
KUHP-5D51-12	12	120	1.2W	SPDT	30
KUHP-5D51-24	24	472			
KUHP-5DT1-12	12	120	1.2W	SPDT	30
KUHP-5DT1-24	24	472			
KUHP-11A51-24	24	72	2.7VA	DPDT	20
KUHP-11AT1-120	120	1,700	2.7VA	DPDT	20
KUHP-11D51-12	12	120	1.2W	DPDT	20
KUHP-11D51-24	24	472			
KUHP-11DT1-12	12	120	1.2W	DPDT	30
KUHP-11DT1-24	24	472			

KUHP-11A51-24 "A" denotes AC coil
KUHP-11D51-24 "D" denotes DC coil
KUHP-11A51-120 "5" denotes side mtg. brackets. Mounts on 2.5" centers
KUHP-11AT1-120 "T" denotes top mtg. brackets. Mounts on 1.875" centers

S86/S87 Series Power Relays

FEATURES
- 20Arating
- Compact package
- Choice of two mounting brackets
- Class B coil construction
- Approximate Size 2.42" x 2.07" x 1.31"h

Mounting Options: Panel Mount .




Mfr.'s Type	Coil			Contacts	
	Input	Res In Ohms	Nom. Power	Arrange-ment	Amp Rating
S86R5A1B1D1-120	120	800	4.0VA	SPDT	20
S87R5A2B1D1-24	24	32			
S87R5A2B1D1-120	120	800	4.0VA	SPDT	20
S87R5A2B1D1-240	240	3,200			
S87R5D2B1D1-12	12	50	2.9W	SPDT	20
S87R5D2B1D1-24	24	200			
S86R11A1B1D1-120	120	800	4.0VA	DPDT	20
S87R11A2B1D1-24	24	32			
S87R11A2B1D1-120	120	800	4.0VA	DPDT	20
S87R11A2B1D1-240	240	3,200			
S87R11D2B1D1-24	24	128	4.5W	DPDT	20

S86R5A1B1D1-120 "A" denotes AC coil
S87R5D2B1D1-24 "D" denotes DC coil

S86 and S87 have identical electrical specifications, but their mounting dimensions and terminal locations differ.

PM Series Power Relays



FEATURES
- 25Arating
- 4PDT Arrangement
- High dielectric Strength
- Screw or quick connect terminals
- Approximate Size 3.39" x 2.66" x 2.72"h

Mounting Options: Panel Mount .


Mfr.'s Type	Coil			Contacts	
	Input	Res In Ohms	Nom. Power	Arrange-ment	Amp Rating
PM17AY-24	24	5			
PM17AY-120	120	120	14VA	4PDT	25
PM17AY-240	240	587			
PM-17DY-12	2	33			
PM-17DY-24	24	132	4.4W	4PDT	25
PM-17DY-110	110	2,760			
PMT17DY-24	24	132	4.4W	4PDT	25

PM -17DY-24 "PM denotes screw terminal type
PMT-17DY-24 "PMT" denotes .25" quick connect terminal type


PM Dust Covers

Mfr.'s Type	Description	Length	Width	Height
35D203	Plastic Cover	3.394 (86.21)	2.657 (67.49)	2.791 (69.06)
35D227	Metal Cover	5.313 (134.95)	3.831 (96.85)	3.813 (96.85)

35D227



35D203



Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP