ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *SMC Thermo-Con INR-244-639* at our website: *Click HERE*

Made to Order

Peltier-Type Thermoelectric Bath

Accurately controls the temperature of liquid in the bath.

Square type is newly added to the product lineup.

Temperature stability ±0.02°C to ±0.03°C

Compact, Lightweight 22 kg (INR-244-757)

Current consumption 3.5 A to 6 A

Power supply voltage 100 VAC to 240 VAC
(Except for some models)



Application Examples



INR-244-757

Temperature control of sample and reagent



Temperature control of source gas for MO-CVD or diffusion furnace



Related Products

◎Fluoropolymer piping equipment

Refer to the Best Pneumatics No. 9 for details.


Fittings ***LQ1/LQ3 Series***



Bore through connector ***LQHB Series***



Tubing ***TL/TLM Series***



◎Process gas equipment

Regulator **Best Pneumatics No. 10**



Diaphragm valve **Best Pneumatics No. 10**



Variations

Model		Usable constant temperature liquid	Cooling method	Cooling capacity	Tank capacity	Temperature range	Temperature stability
	INR-244-745 INR-244-733	Water Ethylene glycol aqueous solution Fluorinated fluid (Square type can be used only at normal temperature.)	Water-cooled	140 W	Approx. 10 L	0 to 60°C	±0.03°C
	INR-244-747 INR-244-736			320 W			
	INR-244-746 INR-244-734		Water-cooled	320 W	Approx. 23 L	0 to 60°C	±0.03°C
	INR-244-749 INR-244-748				Approx. 39 L		
	INR-244-757		Air-cooled	220 W	Approx. 17 L	0 to 60°C	±0.03°C
	HEBC002-WA10		Water-cooled	140 W	Approx. 3 L	−15 to 60°C	±0.02°C
	INR-244-696A			280 W	Approx. 5.5 L		

Peltier-Type Thermoelectric Bath Lineup



(INR-244-733)

Specifications	Square type, water-cooled			
Model	**INR-244-745**	**INR-244-733**	**INR-244-747**	**INR-244-736**
Cooling method	Peltier, Water-cooled		Peltier, Water-cooled	
Cooling capacity∗1	140 W (at 20°C Water)		320 W (at 20°C Water)	
Dimensions (W x D x H)	266 x 376 x 400 mm		266 x 376 x 400 mm	
Tank capacity (W x D x H)	216 x 216 x 250 mm (Approx. 10 L)		216 x 216 x 250 mm (Approx. 10 L)	
Weight	Approx. 15.5 kg		Approx. 16.5 kg	
Power supply voltage range	100 VAC to 240 VAC		100 VAC to 240 VAC	
Rated current (at 100 VAC)	3.5 A		5.5 A	
Liquid temperature range	0 to 60°C		0 to 60°C	
Temperature stability	±0.03°C		±0.03°C	
Communications	RS-232C	RS-485	RS-232C	RS-485
Safety standards	CE marking, UL (NRTL) standard, RoHS			



(INR-244-749)

Specifications	Square type, water-cooled			
Model	**INR-244-746**	**INR-244-734**	**INR-244-749**	**INR-244-748**
Cooling method	Peltier, Water-cooled		Peltier, Water-cooled	
Cooling capacity∗1	320 W (at 25°C Water)		320 W (at 25°C Water)	
Dimensions (W x D x H)	350 x 510 x 400 mm		350 x 510 x 550 mm	
Tank capacity (W x D x H)	300 x 350 x 250 mm (Approx. 23 L)		300 x 350 x 400 mm (Approx. 39 L)	
Weight	Approx. 21 kg		Approx. 25 kg	
Power supply voltage range	100 VAC to 240 VAC		100 VAC to 240 VAC	
Rated current (at 100 VAC)	5.5 A		5.5 A	
Liquid temperature range	0 to 60°C		0 to 60°C	
Temperature stability	±0.03°C		±0.03°C	
Communications	RS-232C	RS-485	RS-232C	RS-485
Safety standards	CE marking, UL (NRTL) standard, RoHS			



Specifications	Square type, air-cooled
Model	**INR-244-757**
Cooling method	Peltier, Air-cooled
Cooling capacity	220 W (at 25°C Water, Ambient temperature 25°C)
Dimensions (W x D x H)	350 x 460 x 395 mm
Tank capacity (W x D x H)	300 x 290 x 200 mm (Approx. 17 L)
Weight	Approx. 22 kg
Power supply voltage range	100 VAC to 240 VAC
Rated current (at 100 VAC)	6 A
Liquid temperature range	0 to 60°C
Temperature stability	±0.03°C
Communications	RS-232C
Safety standards	RoHS



Specifications	Round type, water-cooled/Remote controller	
Model	**HEBC002-WA10/HEBC002-WB10**	
Cooling method	Peltier, Water-cooled	
Cooling capacity∗1	140 W (at 25°C Water)	
Dimensions (W x D x H)	Liquid tank 200 x 207 x 332 mm	Controller 250 x 300 x 180 mm
Tank capacity	ø130 x 188 mm (Approx. 3 L)	—
Weight	Approx. 8.5 kg	Approx. 6.5 kg
Power supply voltage range	100 VAC to 240 VAC	
Rated current (at 100 VAC)	4 A	
Liquid temperature range	−15 to 60°C	
Temperature stability	±0.02°C	
Communications	RS-485/RS-232C	
Safety standards	CE marking, UL (NRTL) standard, RoHS	



Specifications	Round type, water-cooled/Remote controller	
Model	**INR-244-696A**	
Cooling method	Peltier, Water-cooled	
Cooling capacity∗1	280 W (at 25°C Water)	
Dimensions (W x D x H)	Liquid tank 240 x 240 x 350 mm	Controller 220 x 330 x 123 mm
Tank capacity	ø170 x 202 mm (Approx. 5.5 L)	—
Weight	Approx. 12 kg	Approx. 5 kg
Power supply voltage range	200 VAC to 220 VAC	
Rated current (at 200 VAC)	5 A	
Liquid temperature range	−15 to 60°C	
Temperature stability	±0.02°C	
Communications	RS-485	
Safety standards	RoHS	

∗1 Conditions: Facility water temperature 20°C, flow rate 5 L/min, ambient temperature 25°C

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP