ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Sony SSM-14N5U* at our website: ***Click HERE***

SONY

COLOR MONITOR

SSM-14N5U
SSM-20N5U

**TRINITRON®
COLOR
MONITOR**

- 14"/20" (Viewable area measured diagonally) Fine Pitch Trinitron Color Monitor
- Over 500 lines of horizontal resolution
- Accepts NTSC, PAL, SECAM, & NTSC4.43
- Accepts Composite and Y/C Inputs
- On Screen Menu Operation
- Built-in speaker for audio monitoring
- Auto beam current feedback for color stability
- Dark tint CRT for improved dynamic range



SONY SECURITY SYSTEMS
NOTHING ESCAPES US.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

SSM-14N5U
SSM-20N5U

TRINITRON COLOR MONITOR

FRONT VIEW



BACK VIEW



SPECIFICATIONS

SSM-14N5U/SSM-20N5U

Video Systems: NTSC, PAL, SECAM, NTSC4.43

Picture Tube:

SSM-14N5U: High Resolution, 14"(Viewable area measured diagonally) Fine Pitch Trinitron

SSM-20N5U: High Resolution, 20" (Viewable area measured diagonally) Fine Pitch Trinitron

Horiz. Resolution: 500 TV lines

Color Temperature: 6500° K

Linearity: Horizontal<8%, Vertical<7%

Inputs:

Video: Loop through BNC, Composite video, 1.0V p-p sync negative, Auto 75 Ohm termination*
Loop through Mini DIN 4-pin, S-Video
Y: 1V p-p Sync negative
C(NTSC) 0.286V p-p; C(PAL): 0.3V p-p
Auto 75 Ohm termination*

Audio: Loop through Phono, -5dBu, high impedance

Audio Power Out: 0.5W, monaural

Power requirements: AC 100 to 240 V, 50/60 Hz**

Power consumption:

SSM-14N5U: 80W

SSM-20N5U: 100W

Operating temperature: 32°F to 95°F (0°C to 35°C)

Dimensions (WHD):

SSM-14N5U: (13 5/8" x 13 3/8" x 16 5/16")
346 x 340 x 414mm

SSM-20N5U: (17 11/16" x 17 3/8" x 19 3/4")
449 x 441 x 502mm

Weight:

SSM-14N5U: 33 lbs. (15kg)

SSM-20N5U: 61 lbs. 10 ozs. (28kg)

Optional Accessories:

MB-502B: 19" rack mount kit for SSM-14N5U

SLR-103A: 19" slide rail kit for SSM-20N5U

*75 Ohm termination is automatically set to OFF when connection is made to the OUT connector.
**UL Listed for 120V AC 50/60Hz operation only.

© 1998 Sony Electronics Inc. All rights reserved.
Reproduction in whole or in part without written permission is prohibited.
All specifications are subject to change without notice.
Non-metric weights and measurements are approximate.

SONY

Sony Security Systems
Broadcast and Professional Group
1 Sony Drive
Park Ridge, New Jersey 07656-8003
TEL: (201) 358-4954 • FAX: (201) 358-4927

Printed in U.S.A. 11/98 S-SSM-14N5U/SSM20N5U

SONY SECURITY SYSTEMS

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP