



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



GPS Timing Board

Model TSAT-cPCI



- Complete GPS-synchronized timecode reader/generator system
- GPS, IRIG-A, IRIG-B, NASA36 timecode reader
- IRIG-B time code generator
- Time-Tag input
- Programmable start/stop time output and interrupt capability
- Freewheel capability
- High-performance, 2.5 ppm oscillator

The TSAT-cPCI provides high-accuracy timing functions on a plug-in board for the Compact PCI computer bus. The board has an on-board clock, which is kept in sync to an external timecode input. Several timing functions are derived from the on-board clock, including a programmable periodic pulse rate output ("heartbeat"), a programmable start/stop output ("match"), a selectable frequency output ("oscillator out," 1 kHz, 1, 5, or 10 MHz), and a time-stamping input ("time-tag").

The TSAT-cPCI includes an externally-mounted GPS antenna and 100-foot of antenna cable. The GPS satellites provide Coordinated Universal Time (UTC) accurate to within 1 micro-second, and also give position in latitude, longitude, and elevation. The board automatically syncs its on-board clock to the time transmitted by the GPS satellites. The board outputs a timecode signal, in IRIG-B format, which conveys the day, hour, minute, and seconds, and also has a 1 kHz carrier referenced to the on-board oscillator.

The TSAT-cPCI can be used as a stand-alone timecode generator. The computer programs the day, hour, minute and second. The board then continues to count from that time, using the on-board oscillator as the timebase reference. This is called "freewheeling."

The host computer communicates to the board through a set of memory-mapped registers. When the computer boots up, the board identifies itself to the Compact PCI bus by specifying the unique Subsystem Vendor ID. The host computer can then read the instantaneous time, command the board to set time, and/or to provide an interrupt at a periodic rate, at a specified time, and/or when a time-tag event occurs.

**PXI™****CompactPCI®**

Specifications

Timecode Input

Code Format (Autodetect)

IRIG-A (A132), IRIG-B (B122), NASA36

Amplitude

1.2 Vp-p min, 8.0 Vp-p max

Polarity

Detected automatically

Modulation Ratio

2:1 min, 3:1 typ, 4:1 max

Input Impedance

>10K Ohms

Timing Accuracy

Better than 25 ppm
(not suitable for tape playback)

Common Mode Voltage

Differential input, ± 100 V max

Timecode Output

Code Format (Autodetect)

IRIG-B (B122)

Amplitude (Adjustable)

4.0 Vp-p typical (0 V–20 Vp-p)
into ≥ 600 Ohm load

Modulation Ratio (Adjustable)

3:1

Output Impedance

50 Ohms

On-Board Clock

Resolution

1 μ S

Range

366:23:59:59:999999

Propagation Delay Correction

–999 μ S through +999 μ S
(1 μ S resolution)

Stability

Disciplined to timecode: 2×10^{-7}
Undisciplined: 1×10^{-6}

Accuracy

± 1 μ s max

Oscillator Output

Frequency

1 kHz, 1 MHz, 5 MHz, 10 MHz or Off
(software selectable)

Type

RS-422

Differential Output Voltage

2.5 Vp-p (1 MHz)
1.8 Vp-p (10MHz) into 120 Ohms

Timebase Accuracy

Same as on-board clock

Time-Tag Input

Input Voltage

–0.1 V min, +0.4 V max for logic 0
+2.2 V min, +5.1 V max for logic 1
Tags rising edge

Input Current

–600 μ A for logic 0
100 μ A for logic 1

Rise/Fall Time

150 nS max

Repetition Rate

2000 events per second maximum

Timing Resolution

1 μ S

Heartbeat Output

Output Voltage

High: 2.4 V min at 2.5 mA
Low: 0.4 V max at –2.5 mA

Wave Shape

Pulse

Pulse Width

100 nS, 330 nS, 1 μ S, 1 ms

Pulse Polarity

Software selectable

Range

200 nS to 65.5 seconds

Power-on Default Rate

Off

Match Input

Output Voltage

High: 3.8 V min at 6 mA
Low: 0.3 V max at –6 mA

Settability

1 μ S

In-Sync Flag Output

Type

Open Collector
External Pullup

Voltage

+27 VDC max

Current

–20 mA max

Polarity

Conducts to ground when board is
sync'd to GPS or timecode.

Bus Interface

Interface

PICMG 2.0 compliant

I/O Address

64 bytes

General

Size

H 106.7 mm, L 175.26 mm

Power (from cPCI bus)

+5 VDC @ 425 mA max
+12 VDC @ 225 mA max
–12 VDC @ 50 mA max

Operating Temperature

5° to +50° C (41° to +122° F)

Storage Temperature

–40° to +85° C (–40° to 185° F)

Connectors

Timing – DB15
GPS Antenna – HDB15

GPS Receiver/Antenna

Number of Satellites

12

Acquisition Time

<50 seconds

Reacquisition Time

<2 seconds

Frequency

1575 MHz (receive only)
(L1 band, C/A code [SPS])

Sync to UTC

Within ± 1.0 μ S max

Position

Horizontal: <9 m
Altitude: <18 m

Size

95 mm Dia., 72.5 mm H
(3.74" Dia., 2.85" H)

Pole Mount

1.00" I.D., 14 turns/inch straight
(not tapered)

Operating Temperature

–40° to +85° C (–40° to +185° F)

Storage Temperature

–55° to +105° C (–67° to +221° F)

Antenna Cable

Length

30.5 m ± 0.2 m (100' ± 8 ")

Maximum Length

92 m (300')

Cable Size

9 mm (0.35") O.D.

Connector Size

20 mm (0.79") (antenna end)
46 mm (1.80") (board end and
extension cable)

Options

–TRIM-CAB-D-D-100

100' extension cable for GPS antenna

–GPS Optic Isolator

Drivers

Major operating systems are supported.

Ordering Information

Model TSAT-cPCI (+ option #)

0709-TSAT-cPCI(E)

Specifications subject to change or improvement without notice.
Spectracom is a company of the Orolia Group. © 2009 Spectracom Corp.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com