ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Bel / Stratos SPLC-20-8-1-B-R6* at our website: ***Click HERE***

Stratos
SPLC-20-8-1-B-R6 Optical Transceiver

Connectivity for Business Critical Continuity™



Gigabit Ethernet
1x / 2x Fiber Channel Applications
850nm SFP – 2.125 / 1.25 / 1.0625 GBaud

Product Overview

The **Emerson Network Power Connectivity Solutions** SPLC-20-8-1-B-R6 pluggable transceiver module is a high performance integrated duplex data link for bi-directional communication over multimode optical fiber. It is compliant with the MSA Small Form Factor Pluggable (SFP) specification. The SPLC-20-8-1-B-R6 is specifically designed for high speed data links up to 2.125GBaud. The Stratos Lightwave SFP transceiver is a hot pluggable which allows a suitably designed enclosure to be changed from one type of external interface to another simply by plugging in a SFP having the alternative external interface. This optoelectronic transceiver module is a Class 1 Laser product compliant with FDA Radiation Performance Standards, 21 CFR Subchapter J. This component is also a Class 1 Laser compliant according to the International Safety Standard IEC-825-1.

Ordering Information

SPLC - 20 - 8 - 2M - B - R6

Key Features & Benefits

- 2.125GBaud Fiber Channel Compliant
- 1.25GBaud Gigabit Ethernet Compliant
- 1.0625GBaud Fiber Channel Compliant
- Compliant with MSA SFP Specification
- 100Ω AC Coupled CML Level Outputs
- Die Cast Metal Housing
- Serial ID Functionality
- Hot Pluggable
- Single +3.3V Power Supply
- RoHS Compliant

Module Specifications – Electrical: -5°C<Tc<+80°C; +3.0V<Vcc<+3.6V

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Supply Current	Icc		180	250	mA	Tc = 25°C, Vcc = +3.3V
Surge Current	Isurge			300 30	mA	-5°C<Tc<+80°C; +3.15V<Vcc<+3.45V Surge above steady value
Transmitter						
PECL/CML Inputs (Differential)		400		2500	mVpp	AC Coupled Inputs
Input Impedance (Differential)	Zin	85	100	115	Ω	Rin > 100K Ω @ DC
TX_DISABLE Input Voltage – High	ViH	2		3.45	V	
TX_DISABLE Input Voltage – Low	ViL	0		0.8	V	
TX_FAULT Output Voltage – High	VtoH	Vcc-0.5		Vcc+0.3	V	Io = 400μA; Host Vcc
TX_FAULT Output Voltage – Low	VtoL	0		0.8	V	Io = -4.0mA

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
Receiver						
CML Outputs (Differential)		400	800	1200	mVpp	AC Coupled Outputs
Output Impedance (Differential)	Zout	85	100	115	Ω	
RX_LOS Output Voltage – High	VroH	Vcc-0.5		Vcc+0.3	V	Io = 400µA; Host Vcc
RX_LOS Output Voltage – Low	VroL	0		0.8	V	Io = -4.0mA
Total Jitter	Tj			75 130	pS	2^7-1 PRBS @ 2.125GBaud 2^7-1 PRBS @ 1.25/1.0625GBaud
MOD_DEF (0:2)	VoH VoL	2.5 0		Vcc+0.3 0.5	V	

Module Specifications – Optical: -5°C<Tc<+80°C; +3.0V<Vcc<+3.6V

Parameter	Sym	MIN	Typ	MAX	Unit	Notes
50µm Core Diameter MMF		300 550	500 1000		m	BER<1.0E-12 @ 2.125GBaud BER<1.0E-12 @ 1.25/1.0625GBaud
62.5µm Core Diameter MMF		200 300	300 500		m	BER<1.0E-12 @ 2.125GBaud BER<1.0E-12 @ 1.25/1.0625GBaud
Transmitter						
Optical Center Wavelength	λ	830	850	860	nm	
Spectral Width	Δλ			0.85	nm	RMS
Optical Transmit Power	Popt	-9.5		-3	dBm	
Optical Modulation Amplitude	OMA	225			µW	pk-pk
Extinction Ratio	ER	9			dB	P1/P0
Relative Intensity Noise	RIN			-117	dB/Hz	
Total Jitter [pk-pk]	Tj			85 170	ps	2^7-1 PRBS @ 2.125 GigaBaud 2^7-1 PRBS @ 1.25/1.0625 GigaBaud
Output Rise/Fall Time	t_R, t_F			160 260	ps	20-80%; unfiltered @ 2.125GBaud 20-80%; unfiltered @ 1.25/1.0625GBaud
Receiver						
Optical Input Wavelength	λ	770		860	nm	
Optical Input Power	Pr	-17		0	dBm	BER<1.0E-12 @ 1.25/1.0625GBaud
Optical Modulation Amplitude	OMA	31			µW	pk-pk
Optical Return Loss	ORL	12			dB	
RX_LOS – Asserted	Pa	-29			dBm	Measured on transition – Low to High
RX_LOS – Deasserted	Pd			-17	dBm	Measured on transition – High to Low
RX_LOS – Hysteresis	Pa-Pd		1.5	5	dB	

For more information on this product consult the SPLC-20-8-1-B-R6 product data sheet.

IMPORTANT NOTICE
Stratos International, Inc. reserves the right to make changes to or discontinue any optical link product or service identified in this publication, without notice. Stratos International, Inc. recommends that its customers obtain the latest version of the publications to verify, before placing orders, that the information being relied on is current. Stratos International, Inc. warrants performance of its optical link products to current specifications in accordance with the Stratos International, Inc. standard warranty. Testing and other quality control techniques are utilized to the extent that Stratos International, Inc. has determined it to be necessary to support this warranty. Specific testing of all parameters of each optical link product is not necessarily performed on all optical link products. Stratos International, Inc. products are not designed for use in life support appliances, devices, or systems where malfunction of a Stratos International, Inc. product can reasonably be expected to result in a personal injury. Stratos International, Inc. customers using or selling optical link products for use in such applications do so at their own risk and agree to fully indemnify Stratos International, Inc. for any damages resulting from such improper use or sale. Stratos International, Inc. assumes no liability for Stratos International, Inc. applications assistance, customer product design, software performance, or infringement of patents or services described here in. Nor does Stratos International, Inc. warrant or represent that a license, either expressed or implied is granted under any patent right, copyright, or intellectual property right, and makes no representations or warranties that these products are free from patent, copyright, or intellectual property rights. Applications that are described herein for any of the optical link products are for illustrative purposes only. Stratos International, Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Emerson Network Power
Stratos Optical
1333 Gateway Drive, Suite 1007
Melbourne, FL 32901-2644
For product information:
www.stratosoptical.com
call (708) 457-2582 or 1-800-323-6858

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
2007 Emerson Electric Co.

pi-splc2081br6
August 7, 2009

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP