

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.


Visit our website - *Click HERE*

Struthers-Dunn
407 East Smith Street, Suite B
Timmonsville, SC 29161
Telephone: (843)346-4427
Fax: (843)346-4465
Email: info@struthers-dunn.com
Website: www.struthers-dunn.com

Item # 235ACX-3-120VAC, 235 Series - Adjustable Current Sensors

The 235 series current sensor combines solid state circuitry with a SPDT, 10 relay. Knob adjustable user settings detect AC current levels generally ranging from 1.5 to 15 amps. Quick connect terminals are standard with socket or side mounting.





Specifications | Sensing | Contacts | Coil | Dielectric Strength | Temperature | Life Expectancy | Miscellaneous

Specifications

Series	235
Nominal Input Voltage	120 VAC

Terminal Size	4.7 mm
Socket Mountable	Yes

Sensing

Current Sense Range	1.5 to 15 A
Repeatability (Constant voltage and temperature)	2%
Reset Time maximum	150 ms

Contacts

Contact Configuration	SPDT
Contact Material	Silver Alloy
Contact Rating	10 A
Contact Rating 120VAC Resistive	10 A
Contact Rating 28VDC Resistive	6 A
Contact Rating Motor 120VAC	1/3 hp
Contact Rating Motor 240VAC	1/2 hp
Minimum Contact Load	500 mW
Contact Resistance, Initial	100 milliohms max at 6VDC

Coil

Coils Available	AC
Power Consumption	2 VA
Transient Protection	Yes

Input Voltage Tolerance - AC	85% to 110% of nominal
Duty	Continuous

Dielectric Strength

Across Open Contacts	500 Vrms
Between Mutually Insulated Point	1500 Vrms
Insulation Resistance	1,000 Mohms min at 500VDC

Temperature

Operating	-20 to 55 °C -4 to 131 °F
Storage	-40 to 85 °C -40 to 185 °F

Life Expectancy

Electrical (full load)	200,000
Mechanical (no load)	5,000,000

Miscellaneous

Mounting Position	Any
Mating Socket	SK-SQB11-DS
Enclosure	Opaque Polycarbonate
Weight	4.4 oz 125 g

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP