

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

X8DTL-3F



ATX 12"x10" SAS Xeon Tylersburg ServerBoard

Key Features

1. Intel® Xeon® processor 5600/5500 series, with QPI up to 6.4 GT/s
2. Intel® 5500 (Tylersburg) Chipset
3. Up to 96GB** DDR3 1333/ 1066/ 800MHz ECC Registered DIMM / 24GB Unbuffered DIMM
4. Dual Intel® 82574L Gigabit Ethernet Controller
5. Broadcom 1068E 8-Port SAS Controller; RAID 0, 1, 10; RAID 5 optional
6. 6x SATA2 (3 Gbps) Ports via ICH10R Controller
7. 2 (x8) PCI-E 2.0 (1 in x16 slot), 1 (x4) PCI-E 2.0 (in x8 slot), 1 (x4) PCI-E (in x8 slot), 2x PCI 33MHz slots
8. Integrated Matrox G200eW Graphics
9. Integrated IPMI 2.0 with Dedicated LAN

Links & Resources

- Tested Memory List
- Tested HDD / SSD List
- Motherboard Manual
- Update Your BIOS
- IPMI Firmware
- Download the Latest Drivers and Utilities
- Download Driver CD

Specifications

Product SKUs - Discontinued SKU (EOL). Please contact sales-rep for alternative options.

MBD-X8DTL-3F -O	X8DTL-3F (Standard Retail Pack)
MBD-X8DTL-3F -B	X8DTL-3F (Bulk Pack)

Physical Stats

Form Factor	ATX
Dimensions	12" x 10" (30.5cm x 25.4cm)

Processor/Cache

CPU	Dual 1366-pin LGA Sockets Supports up to two **Intel® 64-bit Xeon®** processor(s) of the same type below: **Intel® Xeon®Processor 5600 Series (Westmere)** **Intel® Xeon®Processor 5500 Series (Nehalem-EP)**
QPI	up to 6.4 GT/s

System Memory

Memory Capacity	6x 240-pin DIMM slots Supports up to 96 GB** 1333 / 1066 / 800MHz DDR3 ECC Registered memory Supports up to 24 GB 1333 / 1066 / 800MHz DDR3 ECC / Non ECC Unbuffered memory Memory Mirroring supported
Memory Type	1333 / 1066 / 800MHz ECC Registered / ECC or Non ECC Unbuffered DDR3 SDRAM 72-bit, 240-pin gold-plated DIMMs
DIMM Sizes	1GB, 2GB, 4GB , 8GB** , 16GB**
Memory Voltage	1.5 V / 1.35 V
Error Detection	Corrects single-bit errors Detects double-bit errors (using ECC memory) Supports Intel® x4 and x8 Single Device Data Correction (SDDC)

On-Board Devices

Chipset	Intel® 5500 (Tylersburg) chipset ICH10R + IOH-24D
SAS	Broadcom SAS1068E RAID 0, 1, 10 support (Optional: AOC-IButton68) RAID 5 support
SATA	Intel ICH10R SATA 3.0Gbps Controller RAID 0, 1, 5, 10 support (Windows) RAID 0, 1, 10 support (Linux)

Chassis (Optimized for X8DTL-3F)

1U Chassis	CSE-512F-600B CSE-811L-600B CSE-811TQ-600B
2U Chassis	CSE-825TQ-560LPB CSE-826A-R1200LPB CSE-826E1-R800LPB CSE-826E2-R800LP CSE-826TQ-R800LPB
3U Chassis	CSE-833T-550B CSE-833T-650B CSE-833T-R760B CSE-835TQ-R800B CSE-835TQ-R920B CSE-836A-R1200B CSE-836E1-R800B CSE-836E2-R800B CSE-836TQ-R800B CSE-933E1-R760B CSE-933E2-R760B CSE-933T-R760B CSE-936A-R1200B CSE-936A-R900B CSE-936E1-R900
Tower / 4U Rackmount	CSE-745TQ-920B
Important Chassis Notes	To support the new generation Intel® Xeon® processor-based motherboards, a **Revision K** chassis is recommended for most models. Please talk to your sales representative or follow the link for details.

Expansion Slots

PCI-Express	2 (x8) PCI-E 2.0 (1 in x16 slot) 1 (x4) PCI-E 2.0 (in x8 slot) 1 (x4) PCI-E (in x8 slot)
PCI	2x 33MHz PCI slots

System BIOS

BIOS Type	32Mb SPI Flash EEPROM with AMI® BIOS
BIOS Features	Plug and Play (PnP) PCI 2.2 ACPI up to 3.0 USB Keyboard support

Management

Software	IPMI (Intelligent Platform Management Interface) v1.5 / 2.0 with KVM support SuperDoctor® III
Power Configurations	ACPI / ACPM Power Management

PC Health Monitoring

IPMI	▪ Support for Intelligent Platform Management Interface v.2.0 ▪ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support ▪ Winbond® WPCM450 BMC*
Network Controllers	▪ 2x Intel® 82574L Gigabit Ethernet Controllers ▪ Supports 10BASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output ▪ 1x Realtek RTL8201N PHY (dedicated IPMI)
Graphics	▪ Matrox G200eW
Super I/O	▪ Winbond® 83627DHG-P chip

Input / Output

SAS	▪ 8 SAS / SATA ports
Serial ATA	▪ Six Serial ATA ports ▪ Six SATA hard drives supported
LAN	▪ 2x RJ45 LAN ports ▪ 1x RJ45 Dedicated IPMI LAN port
USB	▪ 2x USB rear ports ▪ 1x USB on-board ▪ 2x USB internal headers ▪ Total 5 USB 2.0 Compliant
VGA	▪ 1x VGA Port
Keyboard / Mouse	▪ PS/2 keyboard and mouse ports
Serial Port / Header	▪ 1 Fast UART 16550 serial port ▪ 1 Fast UART 16550 serial header (Option)

Voltage	▪ Monitors for CPU Cores, +1.8V, +3.3V, +5V, +12V, +3.3V Standby, +5V Standby, VBAT, Memory, Chipset Voltages. ▪ 4-Phase-switching voltage regulator
FAN	▪ Total of six fan headers supporting up to 6 fans ▪ Six 4-pin fan headers ▪ 6x fans with tachometer status monitoring ▪ Support 3-pin fans (w/o speed control) ▪ Low noise fan speed control (4-pin fan only)
Temperature	▪ Monitoring for CPU and chassis environment ▪ Thermal Control for 6x fan connectors ▪ PECI
Other Features	▪ Chassis intrusion detection ▪ Chassis intrusion header

Operating Environment

Environmental Spec.	▪ Operating Temperature: 10° to 35° C (50° to 95°F) ▪ Non-operating Temperature: -40° to 70° C (-40° to 158° F) ▪ Operating Relative Humidity: 8% to 90% (non-condensing) ▪ Non-operating Relative Humidity: 5 to 95% (non-condensing)

OS Compatibility

• Please see our **OS Compatibility Chart**

Note: For optimized or compatible chassis, additional parts may be required, please check with Supermicro sales rep

Parts List

Parts List (Retail Pack)

	Part Number	Qty	Description
X8DTL-3F	MBD-X8DTL-3F -O	1	X8DTL-3F Motherboard
I/O Cable 1	CBL-0044L	8	57.5CM SATA FLAT S-S PBF
I/O Shield	MCP-260-00027-0N	1	STD I/O SHIELD FOR X8, H8, X7SB3 SERVER MB (3RD LAN + 4XLAN)
Manual	MNL-1076-QRG	1	X8DTL-3/I(F)/X8DTL-3/I-II QUICK REFERENCE GUIDE

Note: Items in a Standard Retail Package may differ from items in a Standard Bulk Package.

** Please check '**Tested Memory List**' for compatibility

Copyright © 2019 Super Micro Computer, Inc.
Information in this document is subject to change without notice.
Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP