

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Victor Data Systems MG-781E* at our website: *Click HERE*

EWS-SERIES Single output 15W ~ 1500W



CE (Low Voltage Directive) 3 year warranty

Model name

EWS 15-5

Name of series: EWS
Output power: 15
Nominal output voltage: 5

Features

- CE marking (Low Voltage Directive)
- 74 models, 15 ~ 1500W
- Wide input voltage range
  EWS15, 25, 50: 85 ~ 265VAC universal input
  EWS100, 150, 300, 600: 100/200VAC auto-selectable
  EWS1500: 100/200VAC user-selectable
- Wide output voltage range: ±20% (EWS300, 600, 1500)
- Output voltage programmable (EWS1500):
  0V to nominal output voltage by external control
- 3 year warranty

Specifications

1. Input voltage range	EWS15, 25, 50: 85 ~ 265VAC (47 ~ 440Hz), DC110 ~ 330V universal input EWS100, 150, 300, 600: 85 ~ 132VAC/170 ~ 265VAC (47 ~ 63Hz) auto-selectable EWS1500: 85 ~ 132VAC/170 ~ 265VAC (47 ~ 63Hz) user-selectable
2. Output voltage range	EWS15, 25, 50, 100, 150: ±10% EWS300, 600, 1500: ±20% (2V: –10 ~ +20%) EWS1500: ±20% or 0V to nominal output voltage × 120% by external control
3. Cooling	EWS15, 25, 50, 100, 150: Convection cooling, EWS300, 600, 1500: Forced air cooling by internal fan
4. Operating ambient temperature (Standard mounting)	–10 ~ +60°C (Output derating) EWS15, 25, 50/–10°C: 70%, 0 ~ + 50°C: 100%, +60°C: 50% EWS100,150/–10°C: 72%, 0 ~ +40°C: 120%, +50°C: 100%, +60°C: 48% EWS300, 600, 1500/–10°C: 70%, 0 ~ +50°C: 100%, +60°C: 70%
5. Withstand voltage	Input–output: 3.75kVAC, Input–FG: 2.5kVAC, Output–FG: 500VAC for 1 min.
6. Safety standard	Approved by UL1950, CSA950 (EWS300: approved by CSA234) and EN60950
7. EMI	Conforms to VCCI-class A and FCC class A
8. Functions	Over voltage protection, Over current protection, Remote sensing (EWS100 ~ 1500), Remote on/off control (EWS300 ~ 1500), Output current balancing (EWS300 ~ 1500)

Product lineup


Model name		Nominal output voltage	Max. output current	Max. output power	UL	CSA	EN
EWS15	EWS15-5	5V	3.0A	15W	○	○	○
	EWS15-6	6V	2.5A	15W	○	○	○
	EWS15-9	9V	1.7A	15.3W	○	○	○
	EWS15-12	12V	1.4A	16.8W	○	○	○
	EWS15-15	15V	1.1A	16.5W	○	○	○
	EWS15-18	18V	0.9A	16.2W	○	○	○
	EWS15-24	24V	0.7A	16.8W	○	○	○
	EWS15-28	28V	0.6A	16.8W	○	○	○
	EWS15-48	48V	0.35A	16.8W	○	○	○
EWS25	EWS25-5	5V	5.0A	25.0W	○	○	○
	EWS25-6	6V	4.2A	25.2W	○	○	○
	EWS25-9	9V	2.8A	25.2W	○	○	○
	EWS25-12	12V	2.2A	26.4W	○	○	○
	EWS25-15	15V	1.8A	27W	○	○	○
	EWS25-18	18V	1.5A	27W	○	○	○
	EWS25-24	24V	1.2A	28.8W	○	○	○
	EWS25-28	28V	1.0A	28W	○	○	○
	EWS25-48	48V	0.6A	28.8W	○	○	○
EWS50	EWS50-5	5V	10.0A	50.0W	○	○	○
	EWS50-6	6V	8.4A	50.4W	○	○	○
	EWS50-9	9V	5.6A	50.4W	○	○	○
	EWS50-12	12V	4.4A	52.8W	○	○	○
	EWS50-15	15V	3.6A	54.0W	○	○	○
	EWS50-18	18V	3.2A	57.6W	○	○	○
	EWS50-24	24V	2.4A	57.6W	○	○	○
	EWS50-28	28V	2.0A	56.0W	○	○	○
	EWS50-48	48V	1.2A	57.6W	○	○	○
EWS100	EWS100-5	5V	20A	100W	○	○	○
	EWS100-6	6V	16.7A	100.2W	○	○	○
	EWS100-9	9V	11.2A	100.8W	○	○	○
	EWS100-12	12V	8.4A	100.8W	○	○	○
	EWS100-15	15V	6.7A	100.5W	○	○	○
	EWS100-18	18V	5.6A	100.8W	○	○	○
	EWS100-24	24V	4.2A	100.8W	○	○	○
	EWS100-28	28V	3.6A	100.8W	○	○	○
	EWS100-48	48V	2.1A	100.8W	○	○	○


Model name		Nominal output voltage	Max. output current	Max. output power	UL	CSA	EN
EWS150	EWS150-5	5V	30A	150W	○	○	○
	EWS150-6	6V	25A	150W	○	○	○
	EWS150-9	9V	16.7A	150.3W	○	○	○
	EWS150-12	12V	12.5A	150W	○	○	○
	EWS150-15	15V	10A	150W	○	○	○
	EWS150-18	18V	8.4A	151.2W	○	○	○
	EWS150-24	24V	6.3A	151.2W	○	○	○
	EWS150-28	28V	5.4A	151.2W	○	○	○
	EWS150-48	48V	3.15A	151.2W	○	○	○
EWS300	EWS300-2	2V	60A	120W	○	Δ	Δ
	EWS300-5	5V	60A	300W	○	○	○
	EWS300-6	6V	50A	300W	○	Δ	Δ
	EWS300-9	9V	34A	306W	○	Δ	Δ
	EWS300-12	12V	27A	324W	○	○	○
	EWS300-15	15V	22A	330W	○	○	○
	EWS300-18	18V	18A	324W	○	○	○
	EWS300-24	24V	14A	336W	○	○	○
	EWS300-28	28V	12A	336W	○	○	○
	EWS300-48	48V	7A	336W	○	○	○
EWS600	EWS600-2	2V	120A	240W	○	○	Δ
	EWS600-5	5V	120A	600W	○	○	○
	EWS600-6	6V	100A	600W	○	○	Δ
	EWS600-9	9V	68A	612W	○	○	Δ
	EWS600-12	12V	53A	636W	○	○	○
	EWS600-15	15V	43A	645W	○	○	○
	EWS600-18	18V	35A	630W	○	○	Δ
	EWS600-24	24V	27A	648W	○	○	○
	EWS600-28	28V	23A	644W	○	○	Δ
	EWS600-48	48V	13A	624W	○	○	○
EWS1500	EWS1500-2	2V	300A	600W	○	○	○
	EWS1500-3.3	3.3V	300A	990W	○	○	○
	EWS1500-5	5V	300A	1500W	○	○	○
	EWS1500-10	10V	150A	1500W	○	○	○
	EWS1500-12	12V	125A	1500W	○	○	○
	EWS1500-15	15V	100A	1500W	○	○	○
	EWS1500-24	24V	63A	1512W	○	○	○
	EWS1500-48	48V	32A	1536W	○	○	○

- Request customer specification for further details of specifications, outline, characteristics, etc.
  Read the instruction manual before usage.
- Contact us about delivery before ordering.

○ : Safety standard approved
Δ : Conforms to safety standard

■ EWS15






●Recommended Noise Filter


MAW-1201-22 GO!! P134


●Recommended Power Supply Fixture GO!! P198

(Unit: mm)

■ EWS25








●Recommended Noise Filter


MAW-1201-22 GO!! P134


●Recommended Power Supply Fixture GO!! P198

(Unit: mm)

■ EWS50








●Recommended Noise Filter

MAW-1202-22 GO!! P134

●Recommended Power Supply Fixture GO!! P198

(Unit: mm)

■ EWS100




●Recommended Noise Filter

MB1206 GO!! P137

●Recommended Power Supply Fixture GO!! P198

(Unit: mm)

■ EWS150




●Recommended Noise Filter

MB1206 GO!! P137

●Recommended Power Supply Fixture GO!! P198

(Unit: mm)

■ EWS300



●Recommended Noise Filter

MB1210 GO!! P137


(Unit: mm)


EWS-SERIES

LAMBDA
DENSEI-LAMBDA

■ EWS600


●Recommended Noise Filter
MB1220
GO!!
P137







(Unit: mm)

■ EWS1500







(Unit: mm)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TDK:

EWS10018 EWS150-15 EWS150-5 EWS150-6 EWS15-6 EWS25-15 EWS25-28 EWS600-15 EWS600-2 EWS15-28

TDK-Lambda:

EWS10012 EWS10015 EWS10028 EWS10048 EWS1005 EWS1006 EWS1009 EWS1500-24 EWS150-12 EWS150-24 EWS150-28 EWS150-48 EWS15-12 EWS15-15 EWS15-24 EWS15-48 EWS15-5 EWS25-12 EWS25-24 EWS25-48 EWS25-5 EWS25-6 EWS300-12 EWS300-15 EWS300-24 EWS300-28 EWS300-48 EWS300-5 EWS300-6 EWS50-15 EWS50-24 EWS50-28 EWS50-48 EWS50-5 EWS50-6 EWS600-12 EWS600-24 EWS600-28 EWS600-48 EWS600-5 EWS600-6 EWS50-12 EWS10024

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP