

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

EEA & EEB Series

Including the EAS/EBS and EAH/EBH Models

UL Recognized
CSA Certified
VDE Approved



EEA2 / EEB2 — EEA1 / EEB1 — EEAP / EEBP

EEA Series

- Compact single stage EMI filter with IEC 60320-1 C14 inlet
- Two element circuit provides basic attenuation
- Same performance as the EF Series
- Available in three terminal configurations
- Supersedes EF Series

EEB Series

- Compact EMI filter with IEC 60320-1 C14 inlet
- Two element circuit provides extended attenuation
- Extended differential mode performance
- Available in three terminal configurations

EAS & EBS Models

- Same performance as EEA and EEB Series
- Snap–in mounting
- Spade terminals

EAH & EBH Models

- Same size as EEA and EEB
- Minimal leakage current suitable for medical applications
- Flange mounted
- Spade terminals

Specifications

Maximum leakage current each Line to Ground:

	EEA/EEB EAS/EBS	EAH/EBH
@ 120 VAC 60 Hz:	.22 mA	2 µA
@ 250 VAC 50 Hz:	.38 mA	5 µA

Hipot rating (one minute):

Line to Ground:	2250 VDC
Line to Line:	1450 VDC

Rated Voltage (max.): 250 VAC


Operating Frequency: 50/60 Hz

Rated Current: 1 to 10A

Operating Ambient Temperature Range (at rated current I_r): -10°C to +40°C

In an ambient temperature (T_a) higher than +40°C the maximum operating current (I_o) is calculated as follows: $I_o = I_r \sqrt{(85-Ta)/45}$

Electrical Schematic



Note 1: Not present in EAH / EBH versions

Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

EEA & EEB Series

Ordering Information

3 EEB 1


Output Styles
1 – .250 [*6.3*] spade terminals *(back)*
2 – .250 [*6.3*] spade terminals *(bottom)*
P – PC board pins

Series
EEA – Basic Inlet Filter
EAS – Snap-in EEA Filter
EAH – Medical EEA Filter
EEB – Extended EMI Performance
EBS – Snap-in EEB Filter
EBH – Medical EEB Filter


Current Rating
1, 3, 6, or 10A


Accessories

GA400: NEMA 5-15P to IEC 60320-1 C-13 line cord




FA601: Insulating Shroud





Available Part Numbers

EEA Models	EEB Models
1EEA1	1EEB1
1EEA2	1EEB2
1EEAP	1EEBP
3EEA1	3EEB1
3EEA2	3EEB2
3EEAP	3EEBP
6EEA1	6EEB1
6EEA2	6EEB2
6EEAP	6EEBP
10EEA1	10EEB1
10EEA2	10EEB2
10EEAP	10EEBP
EAS Models	**EBS Models**
1EAS1	1EBS1
3EAS1	3EBS1
6EAS1	6EBS1
10EAS1	10EBS1
EAH Models	**EBH Models**
1EAH1	1EBH1
3EAH1	3EBH1
6EAH1	6EBH1
10EAH1	10EBH1



EAS / EBS


Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to **te.com/help** **corcom.com**

EEA & EEB Series

Case Styles


EEA1, EEB1, EAH1 & EBH1



Typical Dimensions:

Mounting holes (2):	.132 [*3.35*] Dia. with .236 [*5.99*] Dia. x 90° countersink for #4 flathead screw
Line Inlet (1):	IEC 60320-1 C14
Load Terminals (2):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot


EEA2 & EEB2



Typical Dimensions:

Mounting holes (2):	.132 [*3.35*] Dia. with .236 [*5.99*] Dia. x 90° countersink for #4 flathead screw
Line Inlet (1):	IEC 60320-1 C14
Load Terminals (2):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot


EEAP & EEBP



Typical Dimensions:

Mounting holes (2):	.132 [*3.35*] Dia. with .236 [*5.99*] Dia. x 90° countersink for #4 flathead screw
Line Inlet (1):	IEC 60320-1 C14
PC board pins (3):	.031 [*.07*] square, ± .003 [*.07*]

EAS1 & EBS1



Typical Dimensions:


Line Inlet (1):	IEC 60320-1 C14
Load Terminals (2):	.250 [*6.3*] with .07 [*1.8*] Dia. hole
Ground Terminal (1):	.250 [*6.3*] with .07 x .16 [*1.8 x 3.8*] slot

Case Dimensions

Part No.	A (max.)	B (max.)	C (max.)	D ± .010 / ± .25	E (max.)
EEA1, EEB1, EAH1, EBH1	**2.15** *54.6*	**1.12** *28.4*	**0.81** *20.6*	**1.575** *40.01*	**1.98** *50.3*
EEA2, EEB2	**1.54** *39.1*	**1.12** *28.4*	**0.81** *20.6*	**1.575** *40.01*	**1.98** *50.3*
EEAP, EEBP	**1.54** *39.1*	**1.12** *28.4*	**0.81** *20.6*	**1.575** *40.01*	**1.98** *50.3*
EAS1, EBS1	**2.20** *55.88*	**1.15** *29.2*	**.96** *24.38*	**1.185** *30.10*	**1.41** *35.81*

Recommended Panel Cutouts


EEA, EEB, EAH, EBH



Tolerances ± .005 [*0.13*] unless otherwise noted

Note 1: EEA1, EEB1, EAH1, EBH1 can be front or back mounted
Note 2: EEA2, EEB2, EEAP and EEBP can be back mounted only


EAS, EBS



Front Mount only

Panel Thickness	G Dim. ± .002 [*.05*]
0.031 - 0.052 [*0.79 - 1.32*]	1.260 [*32.00*]
0.046 - 0.068 [*1.17 - 1.73*]	1.350 [*34.29*]

PC Board Layout



Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

EEA & EEB Series

Performance Data


Typical Insertion Loss

Measured in closed 50 Ohm system


Common Mode / Asymmetrical (L-G)
Differential Mode / Symmetrical (L-L)

EEA, EAS Models


1A




3A



6A




10A




EEB, EBS Models


1A




3A



6A




10A




EAH Models


1A




3A



6A




10A




EBH Models


1A




3A



6A



10A



Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

EEA & EEB Series

Performance Data *(continued)*

Minimum Insertion Loss

Measured in closed 50 Ohm system

Common Mode / Asymmetrical (Line to Ground)

Current Rating	Frequency – MHz .01	.05	.1	.15	.5	1	5	10	30
EEA / EAS Models									
1A	12	23	29	32	41	47	47	47	40
3A	-	10	15	19	30	36	48	50	47
6A	-	1	4	10	22	28	42	48	47
10A	-	1	3	5	14	20	32	38	47
EEB / EBS Models									
1A	12	23	29	32	41	47	47	47	40
3A	-	10	14	18	30	36	48	50	47
6A	-	1	4	10	22	28	42	48	47
10A	-	1	3	5	14	20	32	38	47
EAH Models									
1A	8	21	29	32	42	45	32	30	19
3A	-	5	10	15	25	27	30	27	22
6A	-	-	5	6	19	21	24	20	15
10A	-	-	1	5	9	12	12	12	12
EBH Models									
1A	8	21	29	32	42	45	32	25	19
3A	-	5	10	15	25	27	30	27	22
6A	-	-	5	8	17	20	24	23	18
10A	-	-	-	3	8	12	12	12	12

Differential Mode / Symmetrical (Line to Line)

Current Rating	Frequency – MHz .5	1	1.5	3	5	10	30
EEA / EAS Models							
1A	1	9	19	32	42	45	40
3A	2	4	6	20	35	45	40
6A	2	4	6	6	24	40	40
10A	1	4	5	5	5	30	40

	Frequency – MHz .01	.15	.5	1	3	5	10	30
EEB / EBS Models								
1A	1	3	14	23	41	47	50	44
3A	1	2	11	14	25	38	44	40
6A	1	2	10	14	20	33	42	40
10A	1	2	10	16	19	19	39	40

	Frequency – MHz 1	1.5	5	10	30
EAH Models					
1A	5	13	28	32	25
3A	4	6	20	27	28
6A	2	5	19	25	27
10A	1	5	15	22	27

	Frequency – MHz .15	.5	1	10	10	30
EBH Models						
1A	1	10	18	30	31	31
3A	1	10	18	30	31	31
6A	1	10	18	30	31	31
10A	1	10	18	30	31	31

Dimensions are in inches and millimeters unless otherwise specified. Values in italics are metric equivalents. Dimensions are shown for reference purposes only. Specifications subject to change.

For email, phone or live chat, please go to
te.com/help
corcom.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP