

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

TransEra GPIO Interface Model 650

Deutsch | Other GPIB Interfaces | GPIO Interfaces | Product Support

Attention: Final Stock ! Very limited supply !

A compatible replacement for this product is the **TAMS 62622**.



The TransEra GPIO interface cards were developed to give HTBasic (DOS Version) full compatibility with the HP Model 98622 GPIO interface.

HP 98622 GPIO Compatibility
Driver are available for HTBasic (all versions including Windows NT/2000). HTBasic currently supports all GPIO capabilities except DMA with a TRANSFER statement.

GPIO Cable
Because the TransEra Model 650 GPIO card uses a compatible connector, either an existing HP cable or a new cable may be used. A matching ten foot cable with a connector attached to one end and open wires on the other is available to fill various cable and interfacing needs.

Features
* Cable and software compatible with HP 98622 GPIO interface
* 16 logic programmable TTL data input lines
* 16 logic programmable open connector 30V data output lines
* Flexible communication
* Logic programmable handshake lines
* Peripheral or interface ready interrupts
* Four general purpose I/O lines
* Fits any AT I/O or HP 700 EISA slot
* Choice of 7 interrupt lines
* Selectable I/O address range
* Selectable DMA address range

Interface Description
The GPIO board provides 16 logic programmable open collector 30V data output lines and 16 TTL logic programmable data input lines. The input lines are tied to pull up termination resistors and have a maximum input voltage of 5.5 volts.
The handshaking lines consist of transfer start, transfer direction, peripheral acknowledge, and peripheral ready. Further control is accomplished with the peripheral reset and interrupt request lines. There are also an additional four general purpose lines that can be used for custom hand-shaking or general bit level I/O.

Specifications

- GPIB/ISA Interface, fits in any ISA 16 bit slot
- Compatible with SICL
- Connect to up to 14 GPIB instruments
- Compatible with ANSI C, HTBasic and HP BASIC for Windows
- Operating systems: Windows XP, 2000, NT4, 9x, DOS

Ordering Information

Order code	Description
HM 650	TransEra GPIO model 650 interface
H-AC0010	GPIO cable, length: 2m; 50-pin Centronics connector, one side open

© 1997-2020 Tech Soft GmbH, Germany. All rights reserved.

/

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP