

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Technobox 5933* at our website: ***Click HERE***

XMC Carrier / Adapter

XMC to PCI Express Adapter

This carrier is designed to adapt an XMC to an 8-lane PCI Express slot.

JN4 is provided for access to rear I/O, PN1 and PN2 are build options but only provide +3V, +5V, +12V and -12V to the XMC card and do not provide PCI signal connections.

Several activity LEDs located at the edge of the board give an indication of key XMC and PCI express signals and voltages.

The signals unique to the XMC standard such as GA[2..0], MVMRO and ROOT0 are supported by DIP switch settings.

The JTAG signals from the PCI bus and the PCI express bus are brought out to headers allowing users the option of connecting the two JTAG ports. The I2C connections for both buses are available on the same connector as well. These jumpers are populated by default.


A high quality 2.5 mm thick machined aluminum panel, with a 0.5 mm chamfered edge, is provided on the PCI board bracket. This mimics the mechanics of a XMC installed on a VMEbus board or other host environments and allows the XMC bezel to be firmly positioned on the board.

For access to the XMC P16 connector for user I/O, consider Technobox P/N 4821 which connects all P16 signals to 0.1 inch headers.

The A and C rows of a 96-pin DIN connector connect with the 64-pin user I/O connector (J4/P4) on the mezzanine card. This connection is specified by IEEE 1386 for the P2 connector on VMEbus boards and permits internal connection of rear I/O, should the PMC board support rear I/O connectivity.


Two variants (P/Ns 5934 and 5935) support 4X and 1X slots. Additonal variants (P/Ns 6065, 6066, and 6067) - based on 5V VPWR - are available and support 8X, 4X, and 1X respectivley.

An optional fan assembly (P/N 4936) is available that fits over two XMC-to-PCI express adapter boards and provides substantial forced-air cooling of high-power modules.





5933

- **Adapts an XMC to a PCIe Slot**
- **Supports 1X, 4X, 8X, and 16X PCIe Lanes**
- **Supports +5V or +12V for XMC VPWR**
- **JN4/PN4 General Purpose I/O**
- **2.5 Gb/s per Lane (each direction)**
- **LEDs for Key PCI and PCIe Signals and Voltages**
- **Headers Provide Access to JTAG and I2C signals**
- **Optional fan assembly to augment cooling**
- **Industrial temperature**
- **RoHS-compliant, Lead-free**



Technobox





Specifications

Temperature (Operating): -40 to 85 C

Temperature (Storage): -50 to +100 C

Altitude: Not specified or characterized (Typical similar equipment is at 15,000 ft.)

Humidity (Operating/Storage): 5% to 90% non-condensing

Vibration: Not specified or characterized

Shock: Not specified or characterized

MTBF: Can be provided upon request

Weight: 110 grams

Typical Power Dissipation: Negligible

Voltages Required: +12, +3.3 +/-5%

Size: 4.376 in (11.13 cm) x 8.1 in (20.57 cm)

Amperage: 8 amps (+12 or +5 VPWR), 4 amps (+3.3 VPWR)

Ordering Information

5933: Passive XMC to PCI Express Adapter +12VPWR - 8X
5934: Passive XMC to PCI Express Adapter +12VPWR - 4X
5935: Passive XMC to PCI Express Adapter +12VPWR - 1X
5944: Passive XMC to PCI Express Adapter +12VPWR - 16X
6065: Passive XMC to PCI Express Adapter +5VPWR - 8X
6066: Passive XMC to PCI Express Adapter +5VPWR - 4X
6067: Passive XMC to PCI Express Adapter +5VPWR - 1X
4936: Fan Assembly (optional)

Technobox, inc.®

Copyright © Technobox 2009

Technobox, Inc.
140 Mount Holly Bypass
Unit 1
Lumberton, NJ 08048
Tel: 609-267-8988 • Fax: 609-261-1011
www.technobox.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP