ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Tektronix 1103* at our website: *Click HERE*

Probe Power Supply

1103

FEATURES & BENEFITS

1103

Powers up to Two Probes
For Use with P6205, P6243, P6245, P6246, P6247, P6248, P6249, P6330, P6701B, P6703B, P5205, P5210, ADA400A and TCP202 on other than TEKPROBE BNC Interfaced Scopes*[1]
Overload Protected 1103

APPLICATIONS

High-speed Digital Systems Design
- ECL
- GaAs
- MOS: CMOS; FastCMOS; BiCMOS; TTL

Component Design/Characterization
- Amplitude levels
- Aberrations
- Propagation Delay and Timing
- Bandwidths and Rise Times

Educational Research
Manufacturing Engineering and Test

TEKPROBE BNC™ Interface

The 1103 is an accessory power supply that provides external power to TEKPROBE BNC Interface probes. The 1103 allows customers to use probes requiring TEKPROBE interface power with any oscilloscope or digitizer that does not provide TEKPROBE BNC power.

The 1103 offers two independently controlled channels consisting of a TEKPROBE BNC interface input, a voltage offset control (providing variable offset or no offset) and BNC signal output.

The offset control supplies a voltage, adjustable via the front panel control. This offset control is available for TEKPROBE BNC probes with this capability. These include: P6235, P6245, P6246, P6247, P6248, P6249 and P6330.

*[1] The characteristics for TEKPROBE BNC Interface probes are subject to change when used with the 1103 TEKPROBE Power Supply. Bandwidth, Rise-time, Propagation Delays will generally differ from the advertised probe only specification. These are dependent upon: 1) the cable length from the output BNC connector to the oscilloscope input, 2) the instrumentation input impedance the output BNC is being connected to, and 3) any additional adapters required to properly interface to the test instrumentation.

To use TEKPROBE BNC Interface probes on the 11800, CSA800, TDS8000, CSA8000 or any non-TEKPROBE BNC interface test instrumentation requires an 1103 TEKPROBE Power Supply, an SMA Male to BNC Female adapter, a 50 Ω BNC cable and if required a 50 Ω feedthrough termination.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Probe Power Supply

1103

CHARACTERISTICS

Output Voltage ±2% - +15 V, -15 V, +5 V, -5 V.

Output Current - 300 mA.

Outputs - Pin 1: n.c.

Pin 2: n.c.

Pin 3: +5 V.

Pin 4: +15 V.

Pin 5: Offset ±1 V.

Pin 6: -5 V.

Pin 7: -15 V.

Power Consumption - ≤35 W.

Physical Characteristics

	cm	in.
Depth	17.8	7
Width	15.8	6.2
Height	8.9	3.9
Weight	**kg**	**lb.**
Net	1.8	3.9

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP