



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Television Demodulators

► DS1000 Series



The Tektronix DS1000 Series Television Demodulators are the answer to cable operators, broadcasters and manufacturers that need a low-cost, high-performance demodulator. They support television standard M/N and B/G.

The DS1000 Series are full measurement-grade demodulators, with specifications better than demodulators twice their size. Input sensitivity and other specifications make the DS1000 Series ideal for use as a repeater or as the analog front end of an RF-to-digital conversion system in all-digital cable systems. It can also act as a precision set-top converter for making baseband measurements in the field.

The DS1000 Series are well suited for remote node monitoring. The addressable serial port allows remote control and status monitoring using computers and modems.

For a complete solution that includes a graphical display, the DS1000 Series can be combined with the 1740A Combination Waveform/Vector Monitor.

► Features & Benefits

Standards Supported:

- M/N (DS1001A/DS1001G)
- B/G (DS1002)

Tuning Range:

- 55.25 to 801.25 MHz (M/N)
- 48.25 to 860.25 MHz (B/G)

Stereo Sound: BTSC, Dual Tone, NICAM (System Dependent)

Zero Carrier Pulse for Depth of Modulation Measurements

Standard and User-defined Channel Tables

RF Ghost Canceling Processing (DS1001G Only)

RS-232/RS-485 I/O Port for Remote Control

Simultaneous Left and Right and SAP Audio Output Monitoring

Remote Monitoring of RF Input Level

Lower Power Dissipation for Increased Efficiency and Reliability

Dual Video Outputs

IF Inputs and Outputs

Front Panel Lock-out Feature

► Applications

Remote Node Monitoring

Operational Demodulation

Broadcast Demodulation

Television Demodulators

► DS1000 Series

Ghost Canceling

The DS1001G incorporates state-of-the-art ghost canceling technology which improves overall video quality by using a specialized ghost canceling test signal, pre-inserted into the television signal by broadcasters, to automatically null out annoying static or dynamic picture “ghosts” caused by RF signal reflections from large buildings, trucks or changing weather conditions.

Audio Support

Audio support includes BTSC stereo for system M/N (DS1001A) as well as both FM (mono & dual tone) and NICAM support for System B/G (DS1002). The DS1001A audio outputs are through special terminal-block connectors, which provide simultaneous outputs of Left, Right and SAP audio channels. The DS1002 audio output is through 2xLR connectors. These connectors can be configured in a variety of ways (depending on system), including: mono, SAP, stereo right and left, both right or both left. The DS1001A also has a 4.5 MHz intercarrier output for driving an external aural modulation monitor.

Remote Programming

The DS1000 Series supports remote programming via either RS-232 or RS-485 at 9600 baud. Most front-panel controls can be accessed via the port. The CSS50 software can automatically control the DS1000 Series, as well as a 2714/15 Spectrum Analyzer.


► Characteristics

		DS1001A/DS1001G (M/N)	DS1002 (B/G)
RF Section	RF Tuning Range	55.25 to 801.25 MHz (Under range to 53.75)	48.25 MHz to 860.25 MHz (Under range to 45.25 MHz)
	RF Sensitivity*1 (all)	0 to +30 dBmV, +60 to +90 dBµV	0 to +30 dBmV, +60 to +90 dBµV
	Return Loss (all)	>6 dB	>6 dB
	Input Impedance (all)	75 Ω	75 Ω
	Input Connector (all)	Female “F”	Female “F”
	Channel Tables (all)	User configurable	User configurable
IF Section	Visual IF Frequency	45.75 MHz	38.9 MHz
	Aural IF Frequency	41.25 MHz	33.4/33.16/33.05 MHz depending on sound system
	IF Output (all)	+51 dBmV/+111 dBµV (typical), BNC	+51 dBmV/+111 dBµV (typical), BNC
Quadrature Video Output	BNC Connector	Yes	Yes

		DS1001A/DS1001G (M/N)	DS1002 (B/G)
Video Section	Video Outputs	Two BNC connectors	Two BNC connectors
	4.5 MHz Inter-carrier Input and Output	Two BNC connectors	None
	Video Signal Output (all)	1 V _{p-p} baseband video (GCR 1 channel only)	1 V _{p-p} baseband video
	Video Signal-to-noise* ¹	>50 dB (NTC7-weighted)	>50 dB (unified-weighted)
	Frequency Response (18°C to 26°C)	±0.7 dB, 100 kHz to 3.58 MHz ±2 dB, 3.58 MHz to 4.1 MHz (typical)	±0.7 dB, 100 kHz to 4.43 MHz
	Group Delay Sound Trap Off	±50 ns, 100 kHz to 3.58 MHz	±60 ns, 100 kHz to 4.43 MHz
	Group Delay Reference Sound Trap On	FCC	Curve B
	Differential Gain (all)	<1.5% (<2.5% DS1001G typical)	<1.5%
	Differential Phase (all)	<1.5° typical (<2° DS1001G typical)	<1.5° typical
	Chroma/Luma Delay (all)	<40 ns	<40 ns
	Luminance Bar Amplitude (all)	<2%	<2% typical
	Luminance Bar Tilt (all)	<3% typical	<3% typical
	2T K-factor (all)	<2.5% (typical 1%)	<2.5% typical
	Line Time Distortion (all)	<3% typical	<3% typical
Audio Section	Audio Outputs	Terminal-block connectors (simultaneous outputs of Left, Right, SAP)	2xLR configurable (Auto Switching FM or NICAM, Auto Switching for Mono, Dual Sound & Stereo)
	Level (all)	0 dBm across 600 Ω	0 dBm across 600 Ω
	Frequency Response (all)	±0.5 dB, 50 Hz to 12 kHz (typical)	±0.5 dB, 50 Hz to 12 kHz (typical)
	THD (all)	<1% at 1 kHz* ²	<1% at 1 kHz* ²

*¹ Video signal to noise tested at +19 dBmV/+79 dBμV.

*² Audio THD tested with a blackburst video signal.



The DS1000 series television demodulator can be part of a total television monitoring system when coupled with a VM700T video measurement set.

Environmental Temperature –

Operating: +5°C to +35°C.
 Nonoperating: -20°C to +75°C.

Altitude –

Operating: 0 to 6,500 ft. (1981 m).
 Nonoperating: 0 to 50,000 ft. (4572 m).

Power

Source Power –

Voltage Range: 95 to 240 VAC.
 Line Frequency: 50/60 Hz.

Power Consumption – 30 VA maximum.

Physical Characteristics

Dimensions	mm	in.
Height	46	1.8
Width	206	8.1
Depth	440	17.3
Weight	kg	lb.
Net	2.2	4.8

Television Demodulators

▶ DS1000 Series

▶ Ordering Information

DS1001A

M/N Television Demodulator.

Includes: User's manual, power cord, special audio terminal block connectors.

DS1001G

M/N Ghost Canceling Television Demodulator.

Includes: User's manual, power cord, special audio terminal block connectors.

DS1002

B/G Television Demodulator.

Includes: User's manual, power cord.

International Power Cord Options

Opt. A1 – Universal Euro 220 V, 50 Hz.

Opt. A2 – UK 240 V, 50 Hz.

Opt. A3 – Australian 240 V, 50 Hz.

Opt. A4 – North American 240 V, 60 Hz.

Opt. A5 – Switzerland 220 V, 50 Hz.

Service Options

Opt. R3 – Repair warranty extended to cover 3 years.

Recommended Accessories

TVGF11A – Rackmount single DS1000 series in a 483 mm (19 in.) rack.

TVGF13 – Rackmount two half-rack instruments side-by-side in a 483 mm (19 in.) rack.

TVGF14 – Rackmount two half-rack instruments vertically in a 19 in. rack (use to combine DS1000 Series with a 1700 series monitor).

TVGF14 and 1700F02 – Portable case for two half-rack instruments.

Measurement Service Options

Contact your local Tektronix representative.

Contact Tektronix:

ASEAN Countries (65) 356-3900

Austria +43 2236 8092 262

Central Europe & Greece +43 2236 8092 301

Belgium +32 (2) 715 89 70

Brazil & South America 55 (11) 3741-8360

Canada 1 (800) 661-5625

Denmark +45 44 850 700

Finland +358 (9) 4783 400

France & North Africa +33 (0) 1 69 86 80 34

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-2275577

Italy +39 (02) 25086 1

Japan (Sony/Tektronix Corporation) 81 (3) 3448-3111

Mexico, Central America & Caribbean 52 (5) 666-6333

The Netherlands +31 (0) 23 569 5555

Norway +47 22 07 07 00

People's Republic of China 86 (10) 6235 1230

Poland +48 (0) 22 521 53 40

Republic of Korea 82 (2) 528-5299

Russia, CIS & The Baltics +358 (9) 4783 400

South Africa +27 11 254 8360

Spain +34 (91) 372 6055

Sweden +46 8 477 6503/4

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Updated October 30, 2001



For the most up-to-date product information visit our web site at www.tektronix.com

Copyright © 2001, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

12/01 HB/XBS

25W-11248-5



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com