

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Specifications

Number of Resistance Channels:	Two.
Type Resistors:	Two sets of programmable resistors, each set consisting of twelve (12) ¾ watt, twenty turn cermet potentiometers.*
Minimum Resistance Step:	Variable from 10 ohms to 100 ohms.*
Maximum Resistance Output:	Adjustable from 40,950 to 409,500 ohms.*
Maximum Input Voltage:	30 V_{RMS}, 42.2 V_{p-p}, 60 V DC.
Resistance Resolution:	Variable for 10 ohms to 100 ohms.*
Standard Step Size:	100 ohm minimum step size, factory calibration.
Resistance Accuracy:**	Variable resistors: ±0.3 ohms ±1% of programmed value, 10 ohms steps. ±0.3 ohms ±0.3% of programmed value, 100 ohm steps.
Resistance Differential Linearity:	Variable resistors, ±0.015 ohms ±2% of programmed value, 10 ohms steps. ±0.015 ohms ±0.6% of programmed value, 100 ohm steps.
Resistance Temperature Coefficient:	±0.01% of programmed value per degree C.
VXIbus Compatibility:	Fully compatible with the VXIbus Specification 1.3 for message-based instruments with the Halt switch in the ON position. The module meets or exceeds all VXIbus power, cooling, emissions and susceptibility specifications.
VXI Device Type:	VXI message based instrument.
VXI Protocol:	Word serial.
VXI Card Size:	C size, one slot wide.

* Standard values. Fixed or variable resistors of the user's choice may be substituted.

** Resistance accuracies assume a known offset resistance value and compensation for that offset value in programming. If no programming compensation is performed, add ±2.5 ohms to the accuracy specification.

Module-Specific Commands:	All module-specific commands and data are sent via the VXIbus Byte-Available command. All module-specific commands are made up of ASCII characters. Module-specific data may be in either ASCII or binary format.
VMEbus Interface:	Data transfer bus (DTB) slave - A16, D16 only.
Interrupt Level:	Switch selectable, levels 1 (highest priority) through 7 (lowest).
Interrupt Acknowledge:	D16; lower 8 bits returned are the logical address of the module.
VXIbus Protocol Events Supported:	VXIbus events are returned via VME interrupts. The following events are supported and returned to the VX4342 Module's commander: REQUEST TRUE (In an IEEE-488 system, this interrupt will cause a Service Request (SRQ) to be generated on the IEEE-488 bus.)
VXIbus Registers:	ID Device Type Status Control Protocol Response Data Low See Appendix A for definition of register contents.
ID Register Contents:	FFFC (Colorado Data Systems' manufacturer's ID)
Power Requirements:	All required dc power is provided by the power supply in the VXIbus mainframe.
Voltage:	+5 Volt supply: 4.75 V dc to 5.25 V dc.
Current (Peak Module, I_{PM}):	+5 Volt supply: 2.1A
Current (Dynamic Module, I_{DM}):	+5 Volt supply: 1.79 APP
Fuses:	Replacement fuse: Littlefuse P/N 273004
Cooling:	Provided by the fan in the VXIbus mainframe. The module will have a temperature rise of 10°C with 1.5 liters/sec of air and a pressure drop of 0.03 mm of H_2O.

Temperature, Ambient:	0°C to +50°C, operating. -40°C to +85°C, storage.
Humidity:	Less than 95% R.H. non-condensing, 0°C to +30°C. Less than 75% R.H. non-condensing, −30°C to +40°C. Less than 45% R.H. non-condensing, −40°C to +50°C.
VXI Bus Radiated Emissions:	Complies with the VXIbus Specification.
VXI Bus Conducted Emissions:	Complies with the VXIbus Specification.
Module Envelope Dimensions:	VXI C size. 262 mm x 353 mm x 30.5 mm (10.3 in x 13.9 in x 1.2 in)
Dimensions, Shipping:	When ordered with a Tek/CDS mainframe, this module will be installed and secured in one of the instrument module slots (slots 1 - 12). When ordered alone, the module's shipping dimensions are: 406 mm x 305 mm x 102 mm. (16 in x 12 in x 4 in).
Weight:	1 kg (2.2 lb).
Weight, Shipping:	When ordered with a Tek/CDS mainframe, this module will be installed and secured in one of the instrument module slots (slots 1-12). When ordered alone, the module's shipping weight is: 3.13 kg (3.5 lb).
Mounting Position:	Any orientation.
Mounting Location:	Installs in an instrument module slot (slots 1-12) of a C or D size VXIbus mainframe. (Refer to D size mainframe manual for information on required adapters.)
Front Panel Signal Connectors:	9 pin DE-9P connector (pins). Refer to Appendix B for connector pinouts.
Recommended Cable:	73A-719S Data Cable.
Equipment Supplied:	1 - VX4342 Module.
Optional:	73A-719S Analog Cable or 73A-784S Hooded Connector. Option 1M - MATE TMA.
Software Version:	V3.4

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP