

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

TELEDYNE
MICROWAVE SOLUTIONS
Everywhereyoulook™

PRELIMINARY

A2P2520

100 TO 2500 MHz SMA CASCADED AMPLIFIER

Typical Values	***A2P2520***
High Gain	***36.0 dB***
Low Noise Figure	***3.2 dB***
High Output Level	***0.5 Watt***
High Third Order I.P.	***+40 dBm***
High Reverse Isolation	***63 dB***

High Performance Thin Film
Power Pack SMA Package

SPECIFICATIONS*

Parameter	Typical	Guaranteed 0 to 50 °C	Guaranteed -55 to +85 °C
Frequency (Min.)	**50-2500 MHz**	**100-2500 MHz**	**100-2500 MHz**
Small Signal Gain (Min.)	36.0 dB	33.0 dB	32.0 dB
Gain Flatness (Max.)	±0.7 dB	±1.0 dB	±1.2 dB
Noise Figure (Max.)	3.5 dB	4.5 dB	5.0 dB
SWR (Max.) Input/Output	1.7:1	1.9:1	2.0:1
Power Output (Min.) @ 1dB comp.	+27.5 dBm	+26.5 dBm	+26.0† dBm
Reverse Isolation	63 dB	—	—
DC Current (Max.)	363 mA	370 mA	392 mA

* Measured in a 50-ohm system at +15 Vdc unless otherwise specified.
† Indicates minimum temperature at -55/+71 °C.

INTERMODULATION PERFORMANCE

Typical @ 25 °C	***A2P2520***
Second Order Harmonic Intercept Point	+59 dBm
Second Order Two Tone Intercept Point	+53 dBm
Third Order Two Tone Intercept Point	+38 dBm


ABSOLUTE MAXIMUM RATINGS

Storage Temperature	-62 to +125 °C
Maximum Case Temperature	+115 °C
Maximum DC Voltage	+16 Volts
Maximum Continuous RF Input Power	-4 dBm
Maximum Short Term Input Power (1 Minute Max.)	50 Milliwatts
Maximum Peak Power (3 µsec Max.)	0.5 Watt
Burn-in Temperature	+85 °C
Thermal Resistance[1] (θjc)	+14 °C/Watt
Junction Temperature Rise Above Case (Tjc)	+60.0 °C

[1] Thermal resistance is based on total power dissipation.

A2P2520

Power Pack SMA Case
(two-stage)



DIMENSIONS ARE IN INCHES [MILLIMETERS]

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP