



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

APPENDIX A - SPECIFICATIONS

MEASUREMENTS

Roughness

R_a, Arithmetic Average
Max R_a, Maximum of 19 overlapping sections
R_q, Root-Mean-Square (RMS)
R_p, Maximum Height
R_v, Maximum Depth
R_t, Maximum Peak-to-Valley
R_z, Ten-Point Height
R_{3z}, Six-Point Height

Waviness

W_a, Arithmetic Average
W_q, Root-Mean-Square
W_p, Maximum Height
W_v, Maximum Depth
W_t, Maximum Peak-to-Valley

Topography

TIR
Height
Average Height

Total Indicator Run-out
Height between two points (Step Height)
Average height of all data points between the measurement cursors relative to the leveled baseline (Delta Average Mode).

Cut Off Filter

mm	inch	mm	inch
.0045	.0002	0.45	.018
.008	.0003	0.8	.03
.014	.0006	1.4	.055
.025	.001	2.5	.1
.045	.002	4.5	.18
.08	.003	8.0	.3
.14	.006	14.0	.55
.25	.01	25.0	1.0

PROFILING PERFORMANCE

	Metric	English
Scan Length	210 mm	8.2 in. maximum.
Scan Speed	1 μ m/s to 25 mm/s	0.04 mil/s to 1 in./s

Sampling Rate	50, 100, or 200/s nominal	
Vertical Range		
At 1Å (0.004 μin.) Resolution:	± 6.5 μm	± 0.25 mil maximum.
At 25Å (0.1 μin.) Resolution:	± 150 μm + 20/-280 μm + 280/-20 μm	± 6 mil maximum + 0.8/-11 mil or + 11/-0.8 mil
Vertical Linearity, entire range	± 0.5%	± 0.5%
Horizontal Resolution	Metric	English
At 1 μm/s scan speed	0.01 μm (100Å)	0.4 μin.
Scan Method	Moving stage, stationary stylus	
Stylus Control	Programmable Force: Range 1.0 - 100 mg Resolution 0.1 mg Full retract between scans Programmable descent rate	

REPEATABILITY AND STABILITY

Step Height Repeatability

13 μm (± 6.5 μm) range
300 μm (± 150 μm) range

0.001 μm (10Å) maximum standard deviation
0.005 μm (50Å) maximum standard deviation
Note: The Step Height Repeatability has been verified using step height standards from VLSI Standards with a sequence of fifty 10 s measurements at a single position.

Base Line Stability

Time
Distance

0.02 μm (200Å) maximum TIR for a 100-s scan.
0.2 μm (2000Å) maximum TIR on a profile length of 130 μm verified on a 1/20 optical flat.

Measurement Environment

Floor vibration below 0.2 mG
Audio noise below 80 dB
Ambient temperature range 16-26° C
Maximum rate of change 2° C/hour

MEASUREMENT CONTROL

Manual/Single Scan Mode	Continuous or segmented scan, from recipe.
Keylock with three Modes	Position 1: Run a single recipe or sequence without modification. Position 2: Run any recipe or sequence without modification. Position 3: Unlocked. All functions available including interlock setting.
Repeat and Average Mode	Scan repeated up to ten times and averaged.
Automatic Sequence Mode	Up to 100 recipes and locations combined into a sequence of recipes (optional).

SAMPLE HANDLING

Motorized X-Y	Two programmable locations (Standard Config.) Unlimited programmability (Automatic Config.)								
Manual Control	Via trackball or keyboard								
Maximum Sample Size	<table> <thead> <tr> <th>Metric</th> <th>English</th> </tr> </thead> <tbody> <tr> <td>254 x 254 mm</td> <td>10 x 10 in.</td> </tr> <tr> <td colspan="2">Note: 355 x 355 mm (14 x 14 in.) with side panel removed</td> </tr> <tr> <td colspan="2">Note: Stylus can access any part of a 210-mm (8.2-in.) round sample without sample repositioning.</td> </tr> </tbody> </table>	Metric	English	254 x 254 mm	10 x 10 in.	Note: 355 x 355 mm (14 x 14 in.) with side panel removed		Note: Stylus can access any part of a 210-mm (8.2-in.) round sample without sample repositioning.	
Metric	English								
254 x 254 mm	10 x 10 in.								
Note: 355 x 355 mm (14 x 14 in.) with side panel removed									
Note: Stylus can access any part of a 210-mm (8.2-in.) round sample without sample repositioning.									
<i>Open Frame Configuration</i>	<table> <tbody> <tr> <td colspan="2">Without Removable Isolation Hood:</td> </tr> <tr> <td>480 x 480 mm</td> <td>19 x 19 in.</td> </tr> <tr> <td colspan="2">With Removable Isolation Hood:</td> </tr> <tr> <td>430 x 430 mm</td> <td>17 x 17 in.</td> </tr> </tbody> </table> <p>Note: Inside space of hood is 743 mm (29.25 in.) X, 556 mm (23.1 in.) Y. A 480-mm (19-in.) sample has full 210 mm (8.2 in.) of scan or positioning motion in the X direction but only 100 mm (4 in.) in the Y direction.</p> <p>Note: Stage Table: 243 x 243 mm (9.57 x 9.57 in.) with switchable vacuum to handle wafer sizes of 100 mm (4 in.) to 200 mm (8 in.). Accomodates</p>	Without Removable Isolation Hood:		480 x 480 mm	19 x 19 in.	With Removable Isolation Hood:		430 x 430 mm	17 x 17 in.
Without Removable Isolation Hood:									
480 x 480 mm	19 x 19 in.								
With Removable Isolation Hood:									
430 x 430 mm	17 x 17 in.								

Tencor P-2 sample locators.

Note: The stylus can access, without sample repositioning, one 210-mm (8.2-in.) diameter area or a 145-mm (5.7-in.) square area. Also, the stylus can access 86% of a 355-mm (14-in.) or 73% of a 430-mm (17-in.) square sample when the sample is moved to each of four or five positions respectively.

Maximum Sample Weight	2.2 kg	5 lb
Throat Depth	228 mm	9 in.
Throat Height, incl. Rotary Stage	63.5 mm	2.5 in.
X,Y Maximum Travel	210 mm	8.2 in.
Stylus and Sample Programmed Position Repeatability (1 σ)	2 μ m	0.08 mil
X,Y Positioning Speed	Variable up to: 25 mm/s	1 in./s
Manual Stage Rotation	Unlimited rotation. Can be set with six detents (four at 90 ^o , two at \pm 45 ^o)	
Motorized Stage Rotation Angle Resolution	0.001 degrees	
Position Repeatability (1 σ)	4 μ m (at 4 in. from center)	0.16 mil
Leveling	Electronic leveling of traces is standard. Automatic mechanical leveling of sample with Motorized Level and Rotation Option	
Vacuum Hold-Down of Sample	Standard with either of the rotating stages	
Custom Fixturing Interface Standard Precision Locator	Six mounting holes, 8-32 on 3.6-in. diameter B. C. (See Appendix F, "Ordering Information.")	

DATA STORAGE

Hard Disk	40 Mbytes. Stores up to 6000 scans at 1000 points each.
Diskette	1.4 Mbyte, 3.5 in. Data storage limited to approximately 100 recipes and 200 scans at 1000 points each. (300 scans per diskette dedicated to data.)
Storage Requirements	DOS Operating System: approx. 80 Kbytes Tencor P-2 Program: approx. 500 Kbytes Recipe: approx. 140 bytes Scan Data (incl. graphs): Approx. 240 bytes + 250 bytes/s of scan time (e.g., 20 s scan time: 4240 bytes).

DATA ANALYSIS

Interactive Graph	Two cursor read-out. Cursors move independently or in tandem.
Delta Average Mode	Each cursor is expandable into a region for measurement or leveling.
Zoom Box Data Expansion	Portion of a graph can be magnified.
Data Catalog	Immediate data retrieval and display from catalog.
Database Manager Option	For each recipe in a given sequence: data table with statistics of mean, standard deviation, minimum, maximum, and range for up to 20 surface analysis parameters. Recall or purge data saved on disk using up to seven user-labeled identifiers in addition to recipe and sequence identifiers, dates. Data can be formatted for PC-AT compatible programs.
Metric/English Units	Parameters displayed in preprogrammed metric or English units; independent selection of horizontal and vertical parameters.

EQUIPMENT SPECIFICATIONS

Processor	8038620-MHz controller, PC/AT compatible, runs MS-DOS Operating System, version 3.3.
Screen	Displays magnified image of the sample or output data. Initial data trace or cross-hair identification of stylus location relative to stage can be superimposed on sample image. 33 cm (13 in.) diagonal High resolution: 640 x 350 pixels Color data display, user-selectable colors Variable image magnification: 150 - 600X standard. 60 - 240X optional, factory only. Motorized zoom with keyboard control Filtered illumination of sample (Yellow-red wavelength only)
Console	Built-in keyboard and trackball to program and operate instrument.
Remote Keyboard	Removable keyboard enabling use of PC/AT software (Automatic Configuration only).
Real Time Clock	Battery-backed clock provides date and time of day.

PHYSICAL SPECIFICATIONS

Tencor P-2 without Wafer Handler

Dimensions	Metric	English
Width	57 cm	22.5 in.
Height	75 cm	29.3 in.
Depth	78 cm	30.6 in.
 <i>Open Frame Configuration</i>		
Width (with hood)	75 cm	29.3 in.
(without hood)	57 cm	22.5 in.
Depth	90 cm	35.6 in.
Note: Feet will fit on a 76-cm (30-in.) deep table.		
Hood Door Opening	55 cm	21.9 in.
Overall Width (with hood)	75 cm	29.3 in.
(without hood)	57 cm	22.5 in.

Weight		
Instrument	118 kg	260 lb
Shipping Weight	197 kg	435 lb
<i>Open Frame Configuration</i>		
Instrument Weight	127 kg	280 lb
<i>Tencor P-2 with Wafer Handler</i>		
Dimensions	Metric	English
Width	117 cm	46.0 in.
Height	154 cm	61.0 in.
Depth	78 cm	30.6 in.
Weight		
Instrument	231 kg	510 lb
Shipping Weight	354 kg	780 lb
Electrical	90-130 V, 50/60 Hz	
	180-260 V, 50/60 Hz	
	Power requirements: 150 VA	



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com