

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

The Embedded I/O Company

TEWS TECHNOLOGIES

TIP250

8 Mbytes Flash Memory

Version 1.0

User Manual

Issue 1.2

October 2008

TEWS TECHNOLOGIES GmbH
Am Bahnhof 7
25469 Halstenbek, Germany
www.tews.com
Phone: +49-(0)4101-4058-0
Fax: +49-(0)4101-4058-19
e-mail: info@tews.com

TEWS TECHNOLOGIES LLC
9190 Double Diamond Parkway,
Suite 127, Reno, NV 89521, USA
www.tews.com
Phone: +1 (775) 850 5830
Fax: +1 (775) 201 0347
e-mail: usasales@tews.com

TIP250-10

8 Mbytes Flash Memory

This document contains information, which is proprietary to TEWS TECHNOLOGIES GmbH. Any reproduction without written permission is forbidden.

TEWS TECHNOLOGIES GmbH has made any effort to ensure that this manual is accurate and complete. However TEWS TECHNOLOGIES GmbH reserves the right to change the product described in this document at any time without notice.

TEWS TECHNOLOGIES GmbH is not liable for any damage arising out of the application or use of the device described herein.

Style Conventions

Hexadecimal characters are specified with prefix 0x, i.e. 0x029E (that means hexadecimal value 029E).

For signals on hardware products, an ‚Active Low' is represented by the signal name with # following, i.e. IP_RESET#.

Access terms are described as:

W	Write Only
R	Read Only
R/W	Read/Write
R/C	Read/Clear
R/S	Read/Set

©2001 -2008 by TEWS TECHNOLOGIES GmbH

All trademarks mentioned are property of their respective owners.

Issue	Description	Date
1.0	First Issue	December 2001
1.1	Added MTBF Value	January 2002
1.2	Added Weight New Address TEWS LLC	October 2008

Table of Contents

1 PRODUCT DESCRIPTION 6
2 TECHNICAL SPECIFICATION 7
3 ID PROM CONTENTS 8
4 IP ADDRESSING 9
4.1 I/O Addressing 9
4.1.1 Flash Control Register (FCR) 9
4.1.2 Flash Status Register (FSR) 10
4.1.3 Interrupt Vector Register (IVR) 10
4.2 Memory Addressing 10
5 HINTS 11
5.1 Flash Memory 11
5.2 JTAG Connector 11

Table of Figures

FIGURE 1-1 : BLOCK DIAGRAM....6
FIGURE 2-1 : TECHNICAL SPECIFICATION....7
FIGURE 3-1 : ID PROM CONTENTS....8
FIGURE 4-1 : REGISTER SET....9
FIGURE 4-2 : FLASH CONTROL REGISTER....9
FIGURE 4-3 : FLASH STATUS REGISTER....10
FIGURE 4-4 : INTERRUPT VECTOR REGISTER....10
FIGURE 4-5 : MEMORY STRUCTURE....10
FIGURE 5-1 : TYPICAL FLASH ACCESS TIMES....11
FIGURE 5-2 : JTAG CONNECTOR....11

1 Product Description

The TIP250 is an IndustryPack compatible module that offers an easy and reliable way to implement 8 Mbytes of Flash memory. The TIP250 is ideal for holding application code, operating system software or data.

Two AM29LV033 devices (32 Mbit, x 8 organized) are used to provide 1 bank of 8 Mbytes (16 bit wide) Flash memory, which is divided, into 64 sectors of 128 Kbytes (16 bit wide).

Access to the TIP250 Flash memory occurs within the IP memory space. After power-on the TIP250 starts up in read only mode. The IP I/O space holds the Flash Control Register, the Flash Status Register and the Interrupt Vector Register.




Figure 1-1 : Block Diagram

2 Technical Specification

IP Interface		
Interface	Single Size IndustryPack® Logic Interface compliant to ANSI/VITA 4-1995	
ID ROM Data	Format I	
I/O Space	Used, with no wait states	
Memory Space	8 MByte, with 1 wait state	
Interrupts	Only INTREQ0# is used	
DMA	Not supported	
Clock Rate	8 MHz	
Module Type	Type I	
On Board Devices		
Memory	8 MBytes Flash Memory (4 Mbit x 16), implemented by two AM29LV033 (or compatible). Organized as 64 sectors of 128 KBytes Min. erase and program cycle endurance: 1 000 000	
I/O Interface		
no connection to the IP I/O connector		
Power Requirements	160 mA typical @ +5V DC	
Physical Data		
Temperature Range	Operating Storage	-40 °C to +85 °C -55°C to +125°C
MTBF	407000 h MTBF values shown are based on calculation according to MIL-HDBK-217F and MIL-HDBK-217F Notice 2; Environment: G_B 20°C. The MTBF calculation is based on component FIT rates provided by the component suppliers. If FIT rates are not available, MIL-HDBK-217F and MIL-HDBK-217F Notice 2 formulas are used for FIT rate calculation.	
Humidity	5 – 95 % non-condensing	
Weight	25 g	

Figure 2-1 : Technical Specification

3 ID PROM Contents

Address	Function	Contents
0x01	ASCII ‘I’	**0x49**
0x03	ASCII ‘P’	**0x50**
0x05	ASCII ‘A’	**0x41**
0x07	ASCII ‘C’	**0x43**
0x09	Manufacturer ID	**0xB3**
0x0B	Model Number	**0x30**
0x0D	Revision	**0x10**
0x0F	Reserved	**0x00**
0x11	Driver-ID Low - Byte	**0x00**
0x13	Driver-ID High - Byte	**0x00**
0x15	Number of bytes used	**0x0C**
0x17	CRC	**0xFD**

Figure 3-1 : ID PROM Contents

4 IP Addressing

The control registers of the TIP250 are accessible in the IP I/O Space.

The Flash memory of the TIP250 is accessible in the IP MEM Space.

4.1 I/O Addressing

The complete register set of the TIP250 is accessible in the I/O space of the IP.

Address	Symbol	Description	Size (Bit)	Access
0x01	FCR	Flash Control Register	8	R/W
0x03	FSR	Flash Status Register	8	R/W
0x05	IVR	Interrupt Vector Register	8	R/W

Figure 4-1 : Register Set

4.1.1 Flash Control Register (FCR)

Read/Write Register to control basic features of the TIP250.

Bit	Symbol	Description	Access	Reset Value
7	F_RST	Reset flash memory Writing a “1” forces the Flash Memory into reset. A subsequently written "0" terminates the reset. Reset forces the flash memory into read-only state. Refer to the AM29LV033 data sheet for more details.	R/W	0
6	WP	Write Protect (active high) 0 = no write protection 1 = write protected (default after Reset)	R/W	1
5	INT_EN	Interrupt Enable 0 = interrupt disabled 1 = An interrupt is generated on IP INTREQ0# when the flash memory's state changes from BUSY to READY during WRITE or ERASE commands. Any write to the FSR clears the pending interrupt.	R	0
4:0	-	reserved	R	-

Figure 4-2 : Flash Control Register

4.1.2 Flash Status Register (FSR)

Read/Write register. A read displays status information. Any write to the FSR clears the pending interrupt.

Bit	Symbol	Description	Access	Reset Value
7:6	-	reserved	R	-
5	INTSTAT	Interrupt Status 0 = no pending interrupt 1 = interrupt is pending	R	0
4	RDY/BSY#	Flash Ready / Busy# signal if the flash devices 0 = Flash is busy 1 = Flash is ready	R	1
3:0	-	reserved	R	-

Figure 4-3 : Flash Status Register

4.1.3 Interrupt Vector Register (IVR)

Read/Write register. This register is cleared automatically during IP Reset. The Interrupt Vector must be loaded by software.

Bit	Symbol	Description	Access	Reset Value
7:0	INTVEC	Interrupt Vector loaded by software	R/W	0x00

Figure 4-4 : Interrupt Vector Register

4.2 Memory Addressing

Two AM29LV033 devices (each organized as 32 Mbit x 8) are used to provide 1 bank of 8 Mbytes (16 bit wide) Flash memory, which is divided into 64 sectors of 128 Kbytes (16 bit wide). Access to the TIP250 Flash memory occurs within the IP memory space. Refer to AM29LV033 datasheet for command sequence details.




Figure 4-5 : Memory Structure

5 Hints

No Configuration like e.g. Jumper setting is necessary for the TIP250.

5.1 Flash Memory

The 8 MByte (4 MBit x 16) Flash Memory of the TIP250 is implemented by two AM29LV033 (or compatible) Flash devices.

Typical access times:

Bank erase time	typ. 45 s
Sector erase time	typ. 0.7 s
Word programming time	typ. 9 µs
Bank programming time	typ. 36 s

Figure 5-1 : typical Flash access times

5.2 JTAG Connector

For factory programming of the on board CPLD, the TIP250 has a JTAG connector.

This connector is only for factory use. See figure below for location of the JTAG connector.




Figure 5-2 : JTAG Connector

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP