ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Tews Technologies TPCE260-10R* at our website: ***Click HERE***

The Embedded I/O Company

TEWS TECHNOLOGIES

TPCE260

PCI Express PMC Carrier

Version 1.0

User Manual

Issue 1.0.1

August 2014

TEWS TECHNOLOGIES GmbH
Am Bahnhof 7 25469 Halstenbek, Germany
Phone: +49 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19
e-mail: info@tews.com www.tews.com

TPCE260-10R

PCI Express PMC Carrier, 5V PCI VI/O, +12V Power Supply from PCIe Connector

TPCE260-11R

PCI Express PMC Carrier, 3.3V PCI VI/O, +12V Power Supply from PCIe Connector

TPCE260-20R

PCI Express PMC Carrier, 5V PCI VI/O, +12V Power Supply via PCIe Graphics Power Connector, 2 x 5.25" to 6-pin adapter cable included

TPCE260-21R

PCI Express PMC Carrier, 3.3V PCI VI/O, +12V Power Supply via PCIe Graphics Power Connector, 2 x 5.25" to 6-pin adapter cable included

This document contains information, which is proprietary to TEWS TECHNOLOGIES GmbH. Any reproduction without written permission is forbidden.

TEWS TECHNOLOGIES GmbH has made any effort to ensure that this manual is accurate and complete. However TEWS TECHNOLOGIES GmbH reserves the right to change the product described in this document at any time without notice.

TEWS TECHNOLOGIES GmbH is not liable for any damage arising out of the application or use of the device described herein.

Style Conventions

Hexadecimal characters are specified with prefix 0x, i.e. 0x029E (that means hexadecimal value 029E).

For signals on hardware products, an ‚Active Low' is represented by the signal name with # following, i.e. IP_RESET#.

Access terms are described as:

W	Write Only
R	Read Only
R/W	Read/Write
R/C	Read/Clear
R/S	Read/Set

©2014 by TEWS TECHNOLOGIES GmbH

All trademarks mentioned are property of their respective owners.

Issue	Description	Date
1.0.0	Initial Issue	May 2011
1.0.1	General Revision	August 2014

Table of Contents

1 PRODUCT DESCRIPTION 6
2 TECHNICAL SPECIFICATION 7
3 HANDLING AND OPERATING INSTRUCTIONS 8
3.1 ESD Protection 8
3.2 PCI Bus Signaling Voltage and Keying 8
3.3 Power Limits for PMC Modules 8
3.4 Installation of PMC Modules 8
4 PCIE-TO-PCI BRIDGE 9
4.1 PCI Configuration Registers 9
4.1.1 PCIe-to-PCI Bridge Configuration Space Header 9
4.2 PCI Bus Device Number Mapping 10
4.3 PCI Clock Frequency 10
5 PMC INTERFACE 11
5.1 PMC BUSMODE[4:1] Signals 11
5.2 PCI Signaling Voltage 11
5.2.1 V_I/O Configuration 11
5.2.2 Voltage Keying Configuration 12
5.3 Power Limits for PMC Modules 13
5.4 Installation of a PMC Module 13
6 PIN ASSIGNMENTS 14
6.1 PMC J11 / P11 14
6.2 PMC J12 / P12 15
6.3 PMC J14 / P14 16
6.4 X4 VG64 Rear-I/O Connector 17

List of Figures

FIGURE 1-1 : BLOCK DIAGRAM....6
FIGURE 5-1 : PCI SIGNALING VOLTAGE CONFIGURATION RESISTORS....11
FIGURE 5-2 : PMC VOLTAGE KEYING....12

List of Tables

TABLE 2-1 : TECHNICAL SPECIFICATION....7
TABLE 4-1 : PCIE-TO-PCI BRIDGE CONFIGURATION SPACE HEADER....9
TABLE 4-2 : PCI BUS DEVICE NUMBER MAPPING....10
TABLE 5-1 : TPCE260 PMC BUSMODE[4:1] SIGNALS....11
TABLE 5-2 : TPCE260 PCI SIGNALING VOLTAGE FACTORY DEFAULTS....11
TABLE 5-3 : PCI SIGNALING VOLTAGE CONFIGURATION RESISTORS....11
TABLE 5-4 : PCI SIGNAL VOLTAGE CONFIGURATION MATRIX....12
TABLE 5-5 : CURRENT LIMITS FOR THE PMC MODULES....13
TABLE 6-1 : PMC J11/P11 PIN ASSIGNMENT....14
TABLE 6-2 : PMC J12/P12 PIN ASSIGNMENT....15
TABLE 6-3 : PMC J14/P14 PIN ASSIGNMENT....16
TABLE 6-4 : X4 VG64 PIN ASSIGNMENT....17

1 Product Description

The TPCE260 is a standard height PCI Express Revision 1.1 compatible module that provides one slot for a single-width PMC module used to build modular, flexible and cost effective I/O solutions for all kinds of applications like process control, medical systems, telecommunication and traffic control. The TPCE260 is a versatile solution to upgrade well known PMC I/O solutions to the PCI Express signaling standard.

The bridging between the system host board and the PMC slot is handled by the transparent PCIe-to-PCI Bridge PI7C9X111SL from Pericom.

The PCI bus side of the bridge allows 32-bit PCI accesses with either 33 MHz or 66 MHz. Both 3.3V (TPCE260-x1R) and 5V (TPCE260-x0R) PCI I/O signaling voltages are supported.

The TPCE260 supports PMC front panel I/O and also PMC P14 Rear I/O through a VME P2 style connector (IEC 60603-2, Type C). The I/O mapping of P14 complies with VITA-35 (“PMC P4 to VME-P2, Rows A-C mapping”).

The PCIe edge card connector provides +12V and +3.3V. All TPCE260-xx variants use the +3.3V solely to power the PCIe-to-PCI Bridge. The TPCE260-1xR uses the +12V of the PCIe edge card connector to generate all four power supply voltages for the PMC slot (+3.3V, +5V, +12V and -12V). According to the PCIe specification, a PCIe x1 card is limited to 6W on the +12V which allows to operate most of the available 32-bit 33/66 MHz PMC modules on the TPCE260-1xR.

For PMC modules with increased power requirements, the TPCE260-2xR offer a PCIe Graphics Power Connector to supply the +12V for generating all the power supply voltages for the PMC slot providing a power of up to 25W.




Figure 1-1 : Block Diagram

2 Technical Specification

Mechanical and Electrical Interfaces		
PCI Express	PCI Express x1, Revision 1.1 Standard Height Full Length	
PCI (PMC Slot)	PCI Mezzanine Card (PMC) Interface conforming to IEEE P1386/P1386.1 Single Size PCI Rev. 3.0 compliant 33/66 MHz / 32-Bit PCI 3.3V and 5V PCI Signaling Voltage	
PMC Interface		
Number of PMC Slots	1	
PMC I/O Access	PMC Front Panel I/O PMC P14 Back I/O through VG64 Right Angle Male Connector	
On Board Devices		
PCI Express to PCI Bridge	PI7C9X111SL (Pericom)	
Physical Data		
Power Requirements	250mA typical @ +3.3V DC 50mA typical @ +12V DC **Additional power is required by the PMC Module!**	
Maximum Power for PMC Slot	TPCE260-1xR: 3 A maximum @ +3.3V DC 2 A maximum @ +5V DC 200 mA maximum @ +12V DC 200 mA maximum @ -12V DC TPCE260-2xR: 5 A maximum @ +3.3V DC 5 A maximum @ +5V DC 200 mA maximum @ +12V DC 200 mA maximum @ -12V DC	
Temperature Range	Operating Storage	-40°C to +85°C -40°C to +85°C
MTBF	TPCE260-1xR: 664000 h TPCE260-2xR: 582000 h MTBF values shown are based on calculation according to MIL-HDBK-217F and MIL-HDBK-217F Notice 2; Environment: G_B 20°C. The MTBF calculation is based on component FIT rates provided by the component suppliers. If FIT rates are not available, MIL-HDBK-217F and MIL-HDBK-217F Notice 2 formulas are used for FIT rate calculation.	
Humidity	5 – 95 % non-condensing	
Weight	TPCE260-1xR: 99 g TPCE260-2xR: 101 g	

Table 2-1 : Technical Specification

3 Handling and Operating Instructions

3.1 ESD Protection



The TPCE260 is sensitive to static electricity. Packing, unpacking and all other handling of the TPCE260 has to be done in an ESD/EOS protected Area.

3.2 PCI Bus Signaling Voltage and Keying



Be sure that the TPCE260 PCI bus signal voltage configuration matches the TPCE260 PMC slots keying pin configuration.

If PMC modules are plugged into a PCI environment where the PCI signaling voltage does not match, damage to the equipment could occur, voiding product warranties.

Refer to the chapter "PCI Signaling Voltage" for details.

3.3 Power Limits for PMC Modules



The PCIe specification limits the power for PCIe add-in cards. These limitations have implications for the use of PMC modules.

Refer to the chapter "Power Limits for PMC Modules" for details.

3.4 Installation of PMC Modules



Before mounting PMC Modules on the TPCE260, be sure that the system is powered off.

Also, follow the installation instructions in the "PMC Interface" chapter.

3.5 Installation of TPCE260-2xR



For the TPCE260-2xR variants, it is imperative to always connect a PCI Express VGA power connector to the TPCE260, even if no PMC is mounted.

4 PCIe-to-PCI Bridge

4.1 PCI Configuration Registers

4.1.1 PCIe-to-PCI Bridge Configuration Space Header

PCI CFG Register Address	PCI Configuration Registers				Initial Values (Hex Values)
	31 24	23 16	15 8	7 0	
0x00	Device ID		Vendor ID		E111 12D8
0x04	Status		Command		0010 0000
0x08	Class Code			Revision ID	060400 02
0x0C	BIST	Header Type	Primary Latency Timer	Cacheline Size	00 01 00 00
0x10	Reserved				-
0x14	Reserved				-
0x18	Secondary Latency Timer	Subordinate Bus Number	Secondary Bus Number	Primary Bus Number	00 00 00 00
0x1C	Secondary Status		I/O Limit	I/O Base	02A0 01 01
0x20	Memory Limit		Memory Base		0000 8000
0x24	Prefetchable Memory Limit		Prefetchable Memory Base		0001 8001
0x28	Prefetchable Base Upper 32-Bit				00000000
0x2C	Prefetchable Limit Upper 32-Bit				00000000
0x30	I/O Limit Upper 16-Bit		I/O Base Upper 16-Bit		0000 0000
0x34	Reserved			Capability Pointer	000000 80
0x38	Expansion ROM Base Address				00000000
0x3C	Bridge Control		Interrupt Pin	Interrupt Line	00 00 01 00

Table 4-1 : PCIe-to-PCI Bridge Configuration Space Header

4.2 PCI Bus Device Number Mapping

The PCI bus device number of the PMC slot is defined by configuration type translation of the PCI-Express to PCI Bridge.

By default, the PMC slot is mapped to the bus device number 0x0.

PCI Bus Device Number (HEX)	PCI AD Line used as PMC IDSEL	Purpose
0x0	16	Default IDSEL for PMC Slot
0x1 0x2 0x3	17 18 19	Not used on TPCE260
0x4	20	Optional IDSEL for PMC Slot
0x5 - 0xF	21 - 31	Not used on TPCE260

Table 4-2 : PCI Bus Device Number Mapping

4.3 PCI Clock Frequency

The TPCE260 supports 66 MHz PCI clock frequency. The actual PCI clock frequency on the TPCE260 is configured by the plugged PMC module. If the plugged PMC module supports 66 MHz operation, the PCI bus will operate with 66 MHz; otherwise it will operate with 33 MHz.

5 PMC Interface

5.1 PMC BUSMODE[4:1] Signals

The BUSMODE[4:1]# signals are defined in the IEEE1386 (CMC) specification and allow a host to identify the used mezzanine card type. The TPCE260 supports PMC cards only.

The TPCE260 indicates the “PMC only” support with the signal levels presented in the table below. The PMC card should decode these signals and drive out a logic “0” on BUSMODE1#.

Signal	Logic Level
BUSMODE4#	Pulled LOW
BUSMODE3#	Pulled LOW
BUSMODE2#	Pulled HIGH

Table 5-1 : TPCE260 PMC BUSMODE[4:1] Signals

5.2 PCI Signaling Voltage

PMC modules are specified either for 3.3V only, 5V only or universal (3.3V or 5V) PCI signaling voltage operation.

The TPCE260 onboard V_I/O voltage level defines the PCI signaling voltage level for the TPCE260 PCI bus. A voltage keying pin indicates the voltage level and prevents incompatible PMC modules from being plugged onto the carrier.

TPCE260	V_I/O Configuration	5V Keying Pin	3.3V Keying Pin
-x0	5V	Installed	Not Installed
-x1	3.3V	Not Installed	Installed

Table 5-2 : TPCE260 PCI Signaling Voltage Factory Defaults

5.2.1 V_I/O Configuration

The V_I/O signaling voltage level is configured by three resistors. To change the voltage level, these resistors must be soldered to the appropriate soldering terminals. They are grouped and labeled appropriately.



Figure 5-1 : PCI Signaling Voltage Configuration Resistors

TPCE260 V_I/O	Populated Resistors	Unpopulated Resistors
5V	R500, R501, R502	R300, R301, R302
3.3V	R300, R301, R302	R500, R501, R502

Table 5-3 : PCI Signaling Voltage Configuration Resistors

5.2.2 Voltage Keying Configuration

To prevent a PMC module from being plugged into a PMC system with a different PCI signaling voltage, the PMC specification defines a voltage keying system with keying pins (on the PMC carrier board) and keying holes (on the PMC module).

PMC modules supporting only 5V PCI signaling voltage provide a single keying hole for the 5V keying pin.

PMC modules supporting only 3.3V PCI signaling voltage provide a single keying hole for the 3.3V keying pin.

Universal PMC modules supporting both 3.3V and 5V PCI signaling voltages provide keying holes for both voltage keying pins.

In certain system configurations it may be necessary to remove the keying pin from one location and assemble it at the other keying pin location.




Figure 5-2 : PMC Voltage Keying

Use the following table to identify the required TPCE260 voltage keying for the actual PMC modules that are to be used.

PMC PCI Signaling Voltage Capability	TPCE260 V_I/O Configuration	TPCE260 5V Keying Pin	TPCE260 3.3V Keying Pin
3.3V only	3.3V	Not Installed	Installed
3.3V or 5V	3.3V	Not Installed	Installed
	5V	Installed	Not Installed
5V only	5V	Installed	Not Installed

Table 5-4 : PCI Signal Voltage Configuration Matrix

5.3 Power Limits for PMC Modules

The following current limits have to be taken into account when choosing the appropriate TPCE260 for the power requirements of the PMC module.

TPCE260	Voltage	Current Limits
TPCE260-1xR	+3.3V	3 A
	+5V	2 A
	+12V	200 mA
	-12V	200 mA
TPCE260-2xR	+3.3V	5 A
	+5V	5 A
	+12V	200 mA
	-12V	200 mA

Table 5-5 : Current Limits for the PMC Modules

5.4 Installation of a PMC Module

The PMC modules are mounted to the TPCE260 prior to installation into the system.

If the PMC has a front panel, first remove the cover from the PMC front panel cut-out of the TPCE260. Install the PMC at an angle so that the PMC front panel penetrates the PMC front panel cut-out. Then rotate down to mate with the PMC connectors on the TPCE260. If the PMC has no front panel, simply plug in the PMC, and leave the cover in the PMC front panel cut-out of the TPCE260.

After the PMC module has been installed, it can be mounted on the TPCE260 using the mounting screws that come with the PMC module. There are four screw mounting locations, two at the PMC front panel and two at the standoffs near the PMC bus connectors.

Before installing a PMC module, be sure that the power supply for the TPCE260 is turned off.

The components are Electrostatic Sensitive Devices (ESD). Use an anti-static mat connected to a wristband when handling or installing the components.

WARNING!!!

Be sure that the TPCE260 PCI bus signaling voltage (V_I/O) configuration matches the TPCE260 PMC slots keying pin configuration.

Be sure that the used PMC modules match the TPCE260 PCI bus signaling voltage and PMC slot keying pin configuration.

If PMC modules are plugged into a PCI environment where the PCI signaling voltage does not match, damage to the equipment could occur, voiding product warranties.

6 Pin Assignments

6.1 PMC J11 / P11

Pin	Signal		Signal	Pin
1	TCK		-12V	2
3	GND		INTA#	4
5	INTB#		INTC#	6
7	BUSMODE1#		+5V	8
9	INTD#		PCI-RSVD	10
11	GND		3.3Vaux	12
13	CLK		GND	14
15	GND		GNT#	16
17	REG#		+5V	18
19	V (I/O)		AD[31]	20
21	AD[28]		AD[27]	22
23	AD[25]		GND	24
25	GND		C/BE[3]#	26
27	AD[22]		AD[21]	28
29	AD[19]		+5V	30
31	V (I/O)		AD[17]	32
33	FRAME#		GND	34
35	GND		IRDY#	36
37	DEVSEL#		+5V	38
39	GND		LOCK#	40
41	PCI-RSVD		PCI-RSVD	42
43	PAR		GND	44
45	V (I/O)		AD[15]	46
47	AD[12]		AD[11]	48
49	AD[09]		+5V	50
51	GND		C/BE[0]#	52
53	AD[06]		AD[05]	54
55	AD[04]		GND	56
57	V (I/O)		AD[03]	58
59	AD[02]		AD[01]	60
61	AD[00]		+5V	62
63	GND		REQ64#	64

Table 6-1 : PMC J11/P11 Pin Assignment

6.2 PMC J12 / P12

Pin	Signal		Signal	Pin
1	+12V		TRST#	2
3	TMS		TDO	4
5	TDI		GND	6
7	GND		PCI-RSVD	8
9	PCI-RSVD		PCI-RSVD	10
11	BUSMODE2#		+3.3V	12
13	RST#		BUSMODE3#	14
15	+3.3V		BUSMODE4#	16
17	PME#		GND	18
19	AD[30]		AD[29]	20
21	GND		AD[26]	22
23	AD[24]		+3.3V	24
25	IDSEL		AD[23]	26
27	+3.3V		AD[20]	28
29	AD[18]		GND	30
31	AD[16]		C/BE[2]#	32
33	GND		PMC-RSVD	34
35	TRDY#		+3.3V	36
37	GND		STOP#	38
39	PERR#		GND	40
41	+3.3V		SERR#	42
43	C/BE[1]#		GND	44
45	AD[14]		AD[13]	46
47	M66EN		AD[10]	48
49	AD[08]		+3.3V	50
51	AD[07]		PMC-RSVD	52
53	+3.3V		PMC-RSVD	54
55	PMC-RSVD		GND	56
57	PMC-RSVD		PMC-RSVD	58
59	GND		PMC-RSVD	60
61	ACK64#		+3.3V	62
63	GND		PMC-RSVD	64

Table 6-2 : PMC J12/P12 Pin Assignment

6.3 PMC J14 / P14

The PMC J14 / P14 connector routes the PMC I/O lines directly to its appropriate pins. The actual signal assignment is PMC specific.

Pin	Signal		Signal	Pin
1	I/O 1		I/O 2	2
3	I/O 3		I/O 4	4
5	I/O 5		I/O 6	6
7	I/O 7		I/O 8	8
9	I/O 9		I/O 10	10
11	I/O 11		I/O 12	12
13	I/O 13		I/O 14	14
15	I/O 15		I/O 16	16
17	I/O 17		I/O 18	18
19	I/O 19		I/O 20	20
21	I/O 21		I/O 22	22
23	I/O 23		I/O 24	24
25	I/O 25		I/O 26	26
27	I/O 27		I/O 28	28
29	I/O 29		I/O 30	30
31	I/O 31		I/O 32	32
33	I/O 33		I/O 34	34
35	I/O 35		I/O 36	36
37	I/O 37		I/O 38	38
39	I/O 39		I/O 40	40
41	I/O 41		I/O 42	42
43	I/O 43		I/O 44	44
45	I/O 45		I/O 46	46
47	I/O 47		I/O 48	48
49	I/O 49		I/O 50	50
51	I/O 51		I/O 52	52
53	I/O 53		I/O 54	54
55	I/O 55		I/O 56	56
57	I/O 57		I/O 58	58
59	I/O 59		I/O 60	60
61	I/O 61		I/O 62	62
63	I/O 63		I/O 64	64

Table 6-3 : PMC J14/P14 Pin Assignment

6.4 X4 VG64 Rear-I/O Connector

The PMC J14 / P14 I/O connector routes the PMC I/O lines to the VG64 Right Angle Male, Type C connector compliant to VITA-35 (“PMC P4 to VME-P2, Rows A-C mapping”). The actual signal assignment of the PMC J14 / P14 connector is PMC specific.

Pin	Signal		Signal	Pin
c1	I/O 1		I/O 2	a1
c2	I/O 3		I/O 4	a2
c3	I/O 5		I/O 6	a3
c4	I/O 7		I/O 8	a4
c5	I/O 9		I/O 10	a5
c6	I/O 11		I/O 12	a6
c7	I/O 13		I/O 14	a7
c8	I/O 15		I/O 16	a8
c9	I/O 17		I/O 18	a9
c10	I/O 19		I/O 20	a10
c11	I/O 21		I/O 22	a11
c12	I/O 23		I/O 24	a12
c13	I/O 25		I/O 26	a13
c14	I/O 27		I/O 28	a14
c15	I/O 29		I/O 30	a15
c16	I/O 31		I/O 32	a16
c17	I/O 33		I/O 34	a17
c18	I/O 35		I/O 36	a18
c19	I/O 37		I/O 38	a19
c20	I/O 39		I/O 40	a20
c21	I/O 41		I/O 42	a21
c22	I/O 43		I/O 44	a22
c23	I/O 45		I/O 46	a23
c24	I/O 47		I/O 48	a24
c25	I/O 49		I/O 50	a25
c26	I/O 51		I/O 52	a26
c27	I/O 53		I/O 54	a27
c28	I/O 55		I/O 56	a28
c29	I/O 57		I/O 58	a29
c30	I/O 59		I/O 60	a30
c31	I/O 61		I/O 62	a31
c32	I/O 63		I/O 64	a32

Table 6-4 : X4 VG64 Pin Assignment

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP