

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*


The Embedded I/O Company

TPMC630 Reconfigurable FPGA with 64 TTL I/O / 32 Diff. I/O

Application Information

The TPMC630 is a standard single-width 32 bit PMC module providing a user configurable FPGA with 300,000 (TPMC630-1x) or 600,000 (TPMC630-2x) system gates. All local signals from the PCI controller are routed to the FPGA.

The TPMC630-x0x has 64 ESD-protected TTL lines, the TPMC630-x1x provides 32 differential I/O lines using EIA-422 / EIA-485 compatible, ESD-protected line transceivers. The TPMC630-x2x provides 32 TTL and 16 differential I/Os. All lines are individually programmable as input or output. The receivers are always enabled, which allows determining the state of each I/O line at any time. This can be used as read back function for lines configured as outputs. Each TTL I/O line has a pull-up resistor. The pull-up voltage is selectable to be either +3.3V or +5V. The differential I/O lines are terminated by 120Ω resistors.



The FPGA is configured by a serial Flash. The Flash device is in-system programmable via driver software over the PCI bus. An in-circuit debugging option is available via an optionally mountable JTAG header (on the backside of the board) for readback and real-time debugging of the FPGA design (using Xilinx “ChipScope”).

A programmable clock generator supplies up to six different clock frequencies between 200 kHz and 166 MHz. All outputs are available at the FPGA, one clock source is in addition used as the local clock signal for the PCI controller. The clock generator settings are stored in an EEPROM and can be changed by the driver software through PCI9030 GPIO pins.

The configuration EEPROM of the PCI controller can also be modified by the driver software, to adapt address spaces etc.

User applications can be developed using the design software ISE WebPACK which can be downloaded free of charge from www.xilinx.com.


The TPMC630 provides front panel I/O via a HD68 SCSI-3 type connector and rear panel I/O via P14.

For First Time Users the Engineering Documentation TPMC630-ED is recommended. The Engineering Documentation includes TPMC630-DOC, schematics, data sheets / application notes of the components and well documented sample VHDL source code.

Software Support (TPMC630-SW-xx) for different operating systems is available.

Technical Information

- Standard single-width 32 bit PMC module conforming to IEEE P1386.1
- PCI 2.1 compliant interface
- 3.3V and 5V PCI Signaling Voltage
- Board size: 149 mm x 74 mm
- TPMC630-1x: Xilinx XC2S300E-6 Spartan-IIE FPGA configured by serial Flash XCF02S
  TPMC630-2x: Xilinx XC2S600E-6 Spartan-IIE FPGA configured by serial Flash XCF04S
- Flash device in-system programmable
- 32 bit PCI target interface by PLX PCI9030
- FPGA clock options:
  - Local clock oscillator
  - PLL programmable clock generator (200 KHz – 166 MHz), 6 clock outputs connected to FPGA
- I/O lines
  - 64 TTL I/O (-10), 32 differential I/O (-11) or 32 TTL I/O and 16 differential I/O (-12)
  - TTL signaling voltage (maximum current: +/-32mA) or EIA-422/-485 signaling level
  - direction individually programmable
- I/O access:
  64 I/O lines on HD68 front connector, parallel to up to 64 I/O lines on rear connector P14
- Operating temperature: -40°C to +85°C



TEWS TECHNOLOGIES GmbH keeps the right to change technical specification without further notice. 09/2009
All trademarks mentioned are property of their respective owners.

TEWS TECHNOLOGIES GmbH
Am Bahnhof 7 25469 Halstenbek, Germany
Phone: +49 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19
e-mail: info@tews.com www.tews.com

Order Information

RoHS Compliant

TPMC630-10R	64 TTL Inputs/Outputs, XC2S300E-6 Spartan-IIE FPGA
TPMC630-11R	32 Differential Inputs/Outputs, XC2S300E-6 Spartan-IIE FPGA
TPMC630-12R	32 TTL Inputs/Outputs and 16 Differential Inputs/Outputs, XC2S300E-6 Spartan-IIE FPGA
TPMC630-20R	64 TTL Inputs/Outputs, XC2S600E-6 Spartan-IIE FPGA
TPMC630-21R	32 Differential Inputs/Outputs, XC2S600E-6 Spartan-IIE FPGA
TPMC630-22R	32 TTL Inputs/Outputs and 16 Differential Inputs/Outputs, XC2S600E-6 Spartan-IIE FPGA

None RoHS Compliant

TPMC630-10	None RoHS compliant version of TPMC630-10R
TPMC630-11	None RoHS compliant version of TPMC630-11R
TPMC630-12	None RoHS compliant version of TPMC630-12R
TPMC630-20	None RoHS compliant version of TPMC630-20R
TPMC630-21	None RoHS compliant version of TPMC630-21R
TPMC630-22	None RoHS compliant version of TPMC630-22R

Documentation

TPMC630-DOC	User Manual
TPMC630-ED	Engineering Documentation, includes TPMC630-DOC

Software

TDRV004-SW-25	Integrity Software Support
TDRV004-SW-42	VxWorks Software Support (Legacy and VxBus-Enabled Software Support)
TDRV004-SW-65	Windows XP/XPE/2000 Software Support
TDRV004-SW-72	LynxOS Software Support
TDRV004-SW-82	LiNUX Software Support
TDRV004-SW-95	QNX 6 Software Support

For other operating systems please contact TEWS.

Related Products

TA304	Cable Kit for modules with HD68 SCSI-3 type connector
TPIM003	PIM I/O Module with HD68 SCSI-3 type connector and special pin assignment

TEWS TECHNOLOGIES GmbH keeps the right to change technical specification without further notice. 09/2009
All trademarks mentioned are property of their respective owners.

TEWS TECHNOLOGIES GmbH
Am Bahnhof 7 25469 Halstenbek, Germany
Phone: +49 (0) 4101 4058 0 Fax: +49 (0) 4101 4058 19
e-mail: info@tews.com www.tews.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP