ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Thermo / HAAKE C10* at our website: ***Click HERE***

HAAKE Phoenix
HAAKE C/DC
HAAKE EK



Circulators, Cryostats, Coolers

Analyze • Detect • Measure • Control™

Thermo
ELECTRON CORPORATION

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Temperature Control Technology from Thermo El

HAAKE Phoenix – HAAKE C/DC – HAAKE EK

Thermo Electron Corporation is an industry leader in laboratories all over the world and continually drives new standards for circulators, cryostats, immersion coolers and water recirculators.

The HAAKE Phoenix range of circulators is the latest innovation resulting from our philosophy develop and implement advanced technology that is also visually attractive and easy to use.

HAAKE Phoenix products incorporate innovative and design-conscious materials such as aluminum, polymers or glass. The simple operation of the HAAKE Phoenix circulators and their large monitors with easily visible displays demonstrates on dedication to user-friendliness.

Our products are certified according to ISO 9001. All units have the CE-mark.

CFC-free refrigerants have been used for many years as proof of Thermo's commitment to the environment.

All units can be recycled easily.

Find out more about the advanced features and flexibility of the HAAKE circulator ranges from Thermo Electron Corporation in the next few pages.



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

ectron Corporation –

Simple to Operate

The menu structure for all digital units enables intuitive operation. The simple allocation of the individual functions to the operating keys.

Innovative Control

High temperature accuracy and the ability to reach the set temperature quickly even under difficult conditions is made possible by the new Fuzzy-Star control system.

Many Additional Functions

Additional functions such as the Real Temperature Adjustment (RTA), the Fault Identification System (FIS), the External Temperature Control (ETC) and the Turbulence Reduction System (TRS) make operation easier for the user.

Flexible Communication

Connecting the units to PCs or within networks is simple due to a range of different interfaces: RS232C, RS485, I/O, multifunctional port, Profibus.

Extensive Range of Accessories

Insert racks, lift plates, hoses or software are just some of the optional accessories which can be used to adapt the units to suit a wide range of applications.

+ + ExtraPlus-Rating + +

The more functions the circulators have, the more ExtraPlus points they get. On page 35 you see which functions related to the points.

Your Guide to the Products

In this brochure we have grouped the circulator lines separately and have described them in detail including extensive technical specifications. The ExtraPlus features of the units are included on the last two pages.

Immersion and Bridge Circulators

Introduction HAAKE C/DC-Line 4

Immersion Circulators HAAKE C/DC 5

Introduction HAAKE Phoenix-Line 6

Bridge Circulators HAAKE Phoenix 7

Open-bath Circulators

Open-bath Circulators HAAKE C/DC up to 100°C (water) with integral baths 8

Open-bath Circulators HAAKE C/DC up to 60°C (water) with polyacrylic bath 9

Open-bath Circulators HAAKE C/DC up to 100°C (water) with stainless steel bath ..... 10 – 11

Open-bath Circulators HAAKE C/DC up to 200°C (water and oil) with stainless steel bath ..... 12 – 13

Heating Circulators

Heating Circulators HAAKE C/DC ..... 14 – 15

Open-bath and Heating Circulators HAAKE Phoenix ..... 16 – 17

Refrigerated Circulators and Cryostats

Refrigerated Circulators HAAKE C/DC ..... 18 – 19

Refrigerated Circulators HAAKE Phoenix ..... 20 – 21

Cryostats ..... 22 – 24

Shaking Waterbath HAAKE SWB25 25

Flow-through Cooler / Immersion Cooler ..... 26 – 27

Water Recirculators ..... 28 – 29

Tubings / Bath Liquids ..... 30 – 31

Software HAAKE ThermStar95plus 32

Pt100 Sensors / Level controller Replenishing Device 33

Description of Functions 34

ExtraPlus-Rating System 35

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The HAAKE C/DC circulators are inexpensive units with a high power capacity. These circulators are small, slimline units which can be used for a wide range of standard applications. A powerful pump and a heating capacity of up to 2000 watts enable the safe temperature control of applications up to 200°C. Digital displays with user-preset temperatures are available for simple operation.

There are five different models:

HAAKE C10: Analog unit up to 100°C, 1.5 kW heating capacity

HAAKE DC10: Inexpensive digital unit up to 100°C, 2kW heating capacity

HAAKE DC30: Digital unit with RS232C up to 200°C, 2kW heating capacity


HAAKE DL30: Same as DC30, however with 200 mm immersion depth

HAAKE DC50: Same as DC30, however with connection for Pt100 sensor and external control

Highlights


- Powerful pumps with Turbulence Reduction System (TRS)
- Simple operation due to separate display panels for menu selection and temperature (except for C10)
- Microprocessor with PID control (except for C10)
- Resolution of the digital display for the set and actual temperature optionally 0.1 or 0.01°C
- Real Temperature Adjustment (RTA)
- Saving of 3 user-defined fixed temperatures with their respective RTA values
- The reason for a unit fault is shown on the display via the Fault Identification System (FIS)
- RS 232C interface (except for C10, DC10), optional RS485 interface with the DC50
- External Temperature Control (ETC) for external systems (for DC50 only)
- Connection for an external Pt100 sensor (for DC50 only)





TRS (Turbulence Reduction System)

2-level-switching to avoid turbulence in open baths or to enable careful filling of external systems.



The HAAKE C/DC immersion circulators are used for the temperature control of baths up to 50 liters. They can be attached to bath walls with a thickness of up to 25 mm using a bracket clamp. A pivotal nozzle ensures even mixing and a good temperature distribution within the entire bath. The minimum depth of the bath must be 150 or 200 mm. The TRS feature can be used to avoid turbulence in the open bath.

Comes with
Screw clamp for bath wall thickness up to 25 mm and **pivotal.**
C10: plus **checking thermometer** 0 to 100°C, division 0.5°C

Optional accessories	**Order-No.**
Tap water cooling coil (C10, DC10, DC30 und DC50)	**333-0590**
Tap water cooling coil (DL30)	**333-0593**
Software ThermStar95plus	(s. P. 32)
Bath liquids	(s. P. 30-31)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Technical specifications acc. to DIN 12876		C10	DC10	DC30	DC50	DL30
Working temperature with tap water cooling with other cooling	°C °C °C	25..100 20..100 -30..100	25..100 20..100 -30..100	25..200 20..200 -50..200	25..200 20..200 -50..200	25..200 20..200 -50..200
Temperature accuracy	+/-K	0.04	0.02	0.01	0.01	0.01
Heater capacity 230 V / 115 V	kW	1.5/1.0	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2
Pump: Pressure / Flow rate max.	mbar / L/min	300/17	300/17	300/17	300/17	300/17
Immersion depth from..to	mm	75..145	75..145	85..145	85..145	85..190
Overall dimensions: WxLxH	cm	9.5x15x32	10x16.5x32	10x16.5x32	10x16.5x32	10x16.5x37
Net weight	kg	3	3	3.2	3.2	3.6
Total wattage 230V / 115V	VA	1550/1050	2050/1250	2050/1250	2050/1250	2050/1550
Order-No. for 230V / 50..60Hz for 115V / 60Hz		425-1001 425-1002	426-1001 426-1002	426-3001 426-3002	426-5001 426-5002	427-3001 427-3002
ExtraPlus-Rating (see page 35)		+	+ +	+ + +	+ + + +	+ + +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



HAAKE Phoenix Series

Innovative materials combined with sophisticated technology and advanced design form the basis of the HAAKE Phoenix circulators.

The simple operation of the units is ensured by the large graphic display that incorporates plain text dialog and a simple user interface. The Phoenix circulators come equipped with a powerful pressure and suction pump, feature a heating capacity of up to 3000 W and a maximum bath temperature of +280°C and are thus ideally suited to meet the extreme technical specifications that many applications require.

HAAKE Phoenix circulators are available in two versions:

Basic version HAAKE Phoenix 1
(P1) with a 2 kW (230V) heating capacity, up to 250°C.

Full version HAAKE Phoenix 2
(P2) with a 3 kW (230V) heating capacity, up to 280°C and with additional functional features.

Highlights

- Large monitor with plain text display and Fault Identification System (FIS)
- FuzzyStar control with neural adaptation
- Very powerful combined pressure and suction pump with automatic speed recognition and TRS
- Display resolution of 0.01°C
- Flexible interface concept
- Direct value setting at the display via numeric input
- Up to 10 ramp programs with a maximum of 30 segments (for P2)
- 4 savable fixed temperatures
- Real Temperature Adjustment (RTA) for integration in QS systems
- External Temperature Control (ETC) with connection for an external Pt100 sensor as standard
- User can choose from 6 different dialog languages (German, English, French, Italian, Spanish, Japanese)
- Permanent display of date and time
- 3-point calibration function (for P2)
- External analog box (optional)
- Profibus interface (optional)

A more detailed explanation of the individual fetaures and the ExtraPlus-Rating system can be found on page 35.



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The units are fitted onto bath vessels with a maximum volume of 100 l.

The bridge can be adjusted to fit widths between 320 and 800 mm and is thus suitable for use with a wide range of different bath sizes.

The powerful combined pressure and suction pump enables a good heat exchange in the bath and the simultaneous temperature control of an external unit?




Comes with

Connections for **tubing** with 8 and 12 mm i. Ø.

Optional accessories	Order-No.
External analog box	**333-0685**
230V Power supply for analog box	**333-0705**
Software ThermStar95plus	**091-2950**
	(s. P. 32)
Tubes and **Bath liquids**	(s. P. 30-31)
Immersion cooler	(s. P. 26-27)
Pt100-sensors	(s. P. 33)


Profibus-interface on request.



Technical specifications acc. to DIN 12876		P1-H70	P2-H70
Working temperature range	°C	30...250	30...280
with tap water cooling	°C	20...250	20...280
with other cooling	°C	-75...250	-90...280
Temerature accuracy	+/- K	0.01	0.01
Heater capacity 230V / 115V	kW	2.0 / 1.2	3.0 / 1.2
Pump: Pressure max. Flow rate max. Suction max. Flow rate max.	mbar l/min mbar l/min	560 24 380 22	560 24 380 22
Width of the bath bridge from…to	mm	320...800	320...800
Immersion depth from…to	mm	70...150	70...150
Overall dimensions WxLxH	cm	32x17x36	32x17x36
Total wattage 230V / 115V	VA	2100 / 1250	3100 / 1250
Net weight	kg	6.1	6.1
Order-No. for 230V / 50-60Hz Order-No. for 115V / 60Hz		440-0511 440-0512	441-0511 441-0512
ExtraPlus-Rating (see page 35)		**+ + + + +**	**+ + + + + +**

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HAAKE C/DC open-bath circulators very rigid baths made from modified polyphenyleneoxide (PPO) that are thermally resistant up to 100 °C. Used with the temperature control units C10 and DC10,they are inexpensive open-bath circulators to be used with water as the heat transfer liquid. The baths have integrated grips and supports. They are fitted with bridge plates for locating the temperature control unit.
A range of accessories is available to adapt the units to suit specific applications.




Comes with
Directable **nozzle**
All C10-combinations include a **checking thermometer** 0 to 100°C, division 0.5°C.


Optional accessories	Order-No.
Tap water cooling coil	**333-0589**
Instead of water cooling, an **immersion cooler EK20** can be used with baths P14 and P21 (see page 26/27)	
Set for external circulation to upgrade the baths	**333-0586**
Lifting platform for C10-P14 and DC10-P14	**333-0583**

Optional accessories	Order-No.
Lifting platform for C10-P21 and DC10-P21	**333-0582**
Plastic balls as **floating bath** cover (recommended above 60°C)	**827-0310**
Bath cover for P5	**333-0618**
Bath cover for P14	**333-0619**
Bath cover for P21	**333-0620**
Racks for bath P5 (fits 2 in the bath) for: 18 tubes, 16 mm Ø	**333-0500**
26 **micro centrifuge tubes**, 1.5 ml, 10 mm Ø	**333-0501**
6 **centrifuge tubes**, 50 ml, 30 mm Ø	**333-0502**


Optional accessories	Order-No.
Basic rack without inserts (fits 1x into P14; 2x in P21)	**333-0129**




inserts for tubs into basic rack
for 86 of 10 mm Ø **333-0130**




for 46 of 16 mm Ø **333-0131**



for 23 of 25 mm Ø **333-0132**



without holes **333-0151**



plastic snappers to reduce the hole Ø in the nserts from
16 to 3..10 mm, 50 pieces **333-0134**
25 to 6..17 mm, 25 pieces **333-0135**





Technical specifications acc. to DIN 12876		C10-P5	DC10-P5	C10-P14	DC10-P14	C10-P21	DC10-P21
Working temperature range with tap water cooling with other cooling	°C °C °C	25..100 20..100 0..100	25..100 20..100 0..100	22..100 20..100 0..100	22..100 20..100 0..100	22..100 20..100 0..100	22..100 20..100 0..100
Temperature accuracy	+/-K	0.04	0.02	0.04	0.02	0.04	0.02
Heater capacity 230V /115V	kW	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2
Pump: Pressure / Flow rate max.	mbar / l/min	300/17	300/17	300/17	300/17	300/17	300/17
Bath opening: WxLxD	cm	13x17x16	13x17x16	30x19x16	30x19x16	30x38x16	30x38x16
Bath volume	l	3..5	3..5	8..14	8..14	13..21	13..21
Overall dimensions: WxLxH	cm	16x33x36	16x33x36	33x38x36	33x38x36	33x54x36	33x54x36
Net weight	kg	4.8	4.8	6	6	6.3	6.3
Total wattage 230V / 115V	VA	1550/1050	2050/1250	1550/1050	2050/1250	1050/1050	2050/1250
Order-No. for 230V / 50..60Hz for 115V / 60Hz		425-1821 425-1822	426-1821 426-1822	425-1831 425-1832	426-1831 426-1832	425-1841 425-1842	426-1841 426-1842
ExtraPlus rating (see page 35)		+	+ +	+	+ +	+	+ +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Open-Bath Circulators
C10- and DC10-W12P,
C10- and DC10-W18P

These transparent baths allow clear viewing during processing.

A water cooling coil is necessary for working temperatures below 25°C. These units can also be adapted for external circulation by adding a pump set.

Open-Bath Circulators
with a built-in recirculation pump
C10-W5P, DC10-W5P

These circulators used for the simultaneous temperature control of external systems such as a photometer and the insertion of flasks or test tubes within the circulator's own bath.


A powerful, two-stage pressure pump is available as a standard feature.



Comes with

C10-W5P and DC10-W5P:
Each 2 **nozzles** for tubing with 8 and 12 mm i. Ø, **set for externalcir-culation** and **tap water cooling coil.**
C10-W5P: plus **checking thermometer** 0 bis 100°C
W12P and W18P: **Bath bridge** to fix the circulator onto the bath and a **directable nozzle.**

Optional accessories	Order-No.
Tap water **cooling coil** for W12P/W18P	**333-0589**
Plastic balls as **floating bath cover**	**827-0310**
Lifting platforms	
for W12P	**333-0583**
for W18P	**333-0582**
Set for external circulation for W12P/W18P	**333-0586**
Reservoir drain for W12P/W18P	**333-0499**
Racks for W5P-bath (to be used max. 3 per bath) for:	
18 tubes, 16 mm Ø	**333-0500**
26 **micro centrifuge tubes**, 1.5 ml, 10 mm Ø	**333-0501**
6 **centrifuge tubes**, 50 ml, 30 mm Ø	**333-0502**



Technical specifications acc. to DIN 12876		C10-W5P	DC10-W5P	C10-W12P	DC10-W12P	C10-W18P	DC10-W18P
Working temperature range with tap water cooling with other cooling	°C °C °C	30..60 20..60 0..60	30..60 20..60 0..60	25..60 20..60 0..60	25..60 20..60 0..60	25..60 20..60 0..60	25..60 20..60 0..60
Temperature accuracy	+/-K	0.04	0.02	0.04	0.02	0.04	0.02
Heater capacity 230V / 115V	kW	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2
Pump: Pressure / Flow rate max.	mbar/l/min	300/12.5	300/12.5	300/17	300/17	300/17	300/17
Bath opening: WxLxD	cm	12x24x15	12x24x15	30x17x15	30x17x15	30x34x15	30x34x15
Bath volume	l	4..6	4..6	8..12	8..12	12..19	12..19
Overall dimensions: WxLxH	cm	17x40x34	17x40x34	31x34x34	31x34x34	31x51x34	31x51x34
Net weight	kg	6	6.2	7	7.2	8.2	8.4
Total wattage 230V / 115V	VA	1550/1050	2050/1250	1550/1050	2050/1250	1550/1050	2050/1250
Order-No. for 230V / 50..60Hz for 115V / 60Hz		425-1051 425-1052	426-1051 426-1052	425-1121 425-1122	426-1121 426-1122	425-1181 425-1182	426-1181 426-1182
ExtraPlus-Rating (see page 35)		+	+ +	+	+ +	+	+ +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The high-quality stainless steel used on the bath interior and exterior is characteristic of these circulators. The handles and drain nozzle enable easy handling.

The temperature control units C10 and DC10 are suitable for used with water or a mixture of water and anti-freeze. A large range of accessories such as an immersion cooler, a set for external circulation, test tube racks or lift plates can be used to quickly adapt the circulator for different applications.

The bath depth for all baths is 200 mm to allow both large and long objects to be placed within. The units V15/B and V26/B are fitted with a compressor cooling unit, i.e. are independent of tap water and are therefore environmentally friendly.


Comes with
Bath bridge to attached the circulator onto the bath and a directable nozzle.
All C10-combinations include a **checking thermometer** 0 to 100°C, division 0.5°C.

Optional accessories	Order-No.
Tap water **cooling coil**	**333-0589**
Instead of water cooling, an immersion cooler EK20 or EK30 can be used (see page 26/27)	
Set for external circulation to upgrade the baths	**333-0586**
Lifting platform	
for W15, V15	**333-0583**
for W26, V26	**333-0582**
for W46	**333-0584**
Bath cover out of s/s (fits 1 x onto W15, V15; 2 x onto W26, V26; 4 x onto W46)	**333-0225**
Plastic balls as floating bath cover	**827-0310**
Reservoir drain	**333-0499**




Baths with angled clamps are also available for more budget-conscious customers.

Optional accessories	Order-No.
Basic rack without inserts (fits 1 x into W15, V15; 2 x into W26, V26; 4 x into W46)	**333-0129**




inserts for tubes into basic rack


for 86 of 10 mm Ø **333-0130**




for 46 of 16 mm Ø **333-0131**



for 23 of 25 mm Ø **333-0132**



without holes **333-0151**



plastic snappers to reduce the hole Ø in the inserts from

16 to 3..10 mm, 50 pieces **333-0134**

25 to 6..17 mm, 25 pieces **333-0135**






Technical specifications acc. to DIN 12876		C10-V15/B	DC10-V15/B	C10-V26/B	DC10-V26/B	C10-W15/B
Working temperature range with tap water cooling with other cooling	°C °C °C	-5..100 – –	-5..100 – –	-10..100 – –	-10..100 – –	25..100 20..100 -30..100
Temperature accuracy	+/-K	0.04	0.02	0.04	0.02	0.04
Heater capacity 230V / 115V	kW	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2	1.5/1.0
Cooling capacity at 20°C	W	200	200	250	250	–
Pump: Pressure / Flow rate max.	mbar/l/min	300/17	300/17	300/17	300/17	300/17
Bath opening: WxLxD	cm	30x17.5x20	30x17.5x20	30x35x20	30x35x20	30x17.5x20
Bath volume	l	11..15	11..15	19..26	19..26	11..15
Overall dimensions: WxLxH	cm	36x59x40	36x59x40	36x75x40	36x75x40	34x36x40
Net weight	kg	26.1	26.1	31	31	8.3
Total wattage 230V / 115V	VA	1900/1400	2400/1600	2000/1500	2500/1700	1550/1050
Order-No. for 230V / 50..60Hz for 115V / 60Hz		425-1531 425-1532	426-1531 426-1532	425-1561 425-1562	426-1561 426-1562	425-1161 425-1162
ExtraPlus-Rating (see page 35)		+	+ +	+	+ +	+

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



DC10-W19/B	C10-W26/B	DC10-W26/B	DC10-W46/B
25..100 20..100 -30..100	23..100 20..100 -30..100	23..100 20..100 -30..100	22...100 20..100 -30..10
0.02	0.04	0.02	0.02
2.0/1,2	1.5/1.0	2.0/1.2	2.0/1.2
–	–	–	–
300/17	300/17	300/17	300/17
30x35x15	30x35x20	30x35x20	30x70x20
12..19	19..26	19..26	35..46
34x54x35	34x56x40	34x56x40	36x95x40
9	10.9	10.9	23.3
2050/1250	1550/1050	2050/1250	2050/1250
426-1191 426-1192	425-1261 425-1262	426-1261 426-1262	426-1461 426-1462
+ +	+	+ +	+ +



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The temperature control unit is attached to the bath vessel by means of a bath bridge. The bridge is equipped with openings designed for the subsequent attachment of an immersion cooler, cooling coil and circulation set for temperature controlling external systems. The units used with the DL30 have an especially large filling range. This enables the frequent exchange of objects with a large volume without triggering level alarms.

The integrated TRS (Turbulence Reduction System) avoids excessive turbulence in the bath via a reduction of the flow rate. Full capacity is available if required.

The units V15/B and V26/B are fitted with a compressor cooling unit, i.e. are independent of tap water and are therefore environmentally friendly.


Comes with

Bath bridge to fix the circulator onto the bath and a directable nozzle




Pumpset (optional)

Optional accessories	Order-No.
Lifting platforms	
for W13, W15 and V15	**333-0583**
for W19, W26, V26	**333-0582**
for W46	**333-0584**
for W45	**333-0581**
Reservoir drain	**333-0499**
Set for external circulation to upgrade the baths for DC30-Combinationen	**333-0586**
for DL30-Combinationen	**333-0625**
Basic rack without inserts (fits 1 x into W13, W15, V15; 2 x into W19, W26, W45; 4 x into W46)	**333-0129**




inserts for tubes into basic rack


for 86 of 10 mm Ø **333-0130**



for 46 of 16 mm Ø **333-0131**



for 23 of 25 mm Ø **333-0132**



without holes **333-0151**



Optional accessories	Order-No.
plastic snappers to reduce the hole Ø in the inserts from	
16 to 3..10 mm, 50 pieces	**333-0134**
25 to 6..17 mm, 25 pieces	**333-0135**





Tap water **cooling coil** for DC30-Combinationen	**333-0589**
Tap water **cooling coil** for DL30-Combinationen	**333-0595**
Instead of water cooling, an immersion cooler EK20 or EK30 can be used (see page 26/27)	
bath cover made from stainless steel (fits 1 x onto W13, W15, V15; 2 x onto W19, W26, V26; 4 x onto W46)	**333-0225**
bath cover made from stainless steel (fits 2 x onto W45)	**333-0648**



Lifting platform (optional)

Technical specifications acc. to DIN 12876		DL30-V15/B	DL30-V26/B	DC30-W13/B	DL30-W15/B
Working temperature range with tap water cooling with other cooling	°C °C °C	-5..150 – –	-10..150 – –	25..200 20..200 -50..200	25..200 20..200 -50..200
Temperature accuracy	+/-K	0.01	0.01	0.01	0.01
Heater capacity 230V / 115V	kW	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2
Cooling capacity at 20 °C	W	200	250	–	–
Pump: Pressure / Flow rate max.	mbar / l /min	300/17	300/17	300/17	300/17
Bath opening: WxLxD	cm	30 x 17.5 x 20	30 x 35 x 20	30 x 17.5 x 15	30 x 17.5x 20
Bath volume	l	8..15	14..26	7..12	8..15
Overall dimensions: WxLxH	cm	36 x 59x 40	36 x 75 x 40	34 x 36 x 35	34 x 36 x 40
Net weight	kg	27	32	8.8	9
Total wattage 230V / 115V	VA	2400/1500	2500/1700	2050/1250	2050/1250
Order-No. for 230V / 50..60Hz for 115V / 60Hz		427-3531 427-3532	427-3561 427-3562	426-3141 426-3142	427-3161 427-3162
ExtraPlus-Rating (see page 35)		**+++**	**+++**	**+++**	**+++**

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



	DC30-W19/B	DL30-W26/B	DL30-W46/B	DL30-W45/B
	25..200 20..200 -50..200	23..200 20..200 -50..200	22..200 20..200 -50..200	22..200 20..200 -50..200
	0.01	0.01	0.01	0.01
	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2
	–	–	–	–
	300/17	300/17	300/17	300/17
	30 x 35 x 15	30 x 35 x 20	30 x 70 x 20	30 x 35 x 30
	12..19	14..26	27..46	30..42
	34 x 54 x 35	34 x 54 x 40	36 x 95 x 40	36 x 54 x 51
	9	11.2	24	23
	2050/1250	2050/1250	2050/1250	2050/1250
	426-3191 426-3192	427-3261 427-3262	427-3461 427-3462	427-3451 427-3452
	+++	+++	+++	+++



HAAKE DC30-W26/B with cooler HAAKE EK30

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

These space-saving heating circulators are used to control temperatures in smaller external systems such as density meters, viscometers, photometers, refractometers or similar devices. A powerful pressure pump provides a good heat exchange with closed systems and thus optimum temperature accuracy.

The available bath opening also allows samples to be inserted into the circulator's own bath. Various bath volumes and depths cover a wide application range. The interior and exterior of the bath vessels are made from stainless steel for easy cleaning and durability. The bath P5 is made from polyphenyleneoxide (PPO). A built-in water cooling coil enables temperature control down to 2°C...3°C above the cooling water temperature.

The HAAKE DC- and DL-Class

- Robust PID control
- Double display
- 3 fixed temperatures
- RS232C interface (RS485 option)
- RTA / FIS / ETC / TRS


Comes with

Each 2 **nozzles** for tubins with 8 and 12 mm i. Ø, a **tap water cooling coil** and a **bath cover.**

C10-P5/U, C10-B3:
plus **checking thermometer**
0 to 100°C, division 0,5°C.


Optional accessories	Order-No.
Rack for 20 tubes/ 16 mm Ø for B3-bath	**333-0456**


Optional accessories	Order-No.
Racks for bath B5, B7	
18 tubes, 16 mm Ø	**333-0500**
26 **micro centrifuge tubes**, 1.5 ml, 10 mm Ø	**333-0501**
6 **centrifuge tubes**, 50 ml, 30 mm Ø	**333-0502**
Universal **hose nozzle** for tubing of 3 to 6 mm i. Ø	**832-0275**
Reservoir **drain**	**333-0499**



Software for DC30, DL30, DC50 (s. P. 32)

Choose the **necessary tubes, bath liquids** or **Pt 100 sensors** on pages 30/31/32.





Technical specification acc. to DIN 12876		C10-P5/U	DC10-P5/U	C10-B3	DC10-B3	DC30-B3	DC50-B3
Working temperature range with tap water cooling with other cooling	°C °C °C	25..100 20..100 0..100	25..100 20..100 0..100	32..100 20..100 -30..100	32..100 20..100 -30..100	32..200 20..200 -50..200	32..200 20..200 -50..200
Temperature accuracy	+/-K	0.04	0.02	0.04	0.02	0.01	0.01
Heater capacity 230V / 115V	kW	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2	2.0/1.2	2.0/1.2
Pump: Pressure / Flow rate max.	mbar/ l/min	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5
Bath opening: WxLxD	cm	13x17x16	13x17x16	13x10x15	13x10x15	13x10x15	13x10x15
Bath volume	L	5	5	3	3	3	3
Overall dimensions: WxLxH	cm	16x33x36	16x33x36	20x30x37	20x30x37	20x30x37	20x30x37
Net weight	kg	5.2	5.4	7.1	7.3	7.3	7.4
Total wattage 230V / 115V	VA	1550/1050	2050/1250	1550/1050	2050/1250	2050/1250	2050/1250
Order-No. for 230V / 50..60Hz for 115V / 60Hz		425-1851 425-1852	426-1851 426-1852	425-1701 425-1702	426-1701 426-1702	426-3701 426-3702	426-5701 426-5702
ExtraPlus-Rating (see page 35)		+	+ +	+	+ +	+ + +	+ + + +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



	DC30-B5	DC50-B5	DL30-B7	DC50-B7	DL30-B12	DC50-B12
	32..200 20..200 -50..200	32..200 20..200 -50..200	30..200 20..200 -50..200	30..200 20..200 -50..200	28..200 20..200 -50..200	28..200 20..200 -50..200
	0.01	0.01	0.01	0.01	0.01	0.01
	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2
	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5
	14x15x15	14x15x15	13x10x20	13x10x20	22x14x20	22x14x20
	4.5	4.5	7	7	12	12
	21x36x38	21x36x38	23x36x44	23x36x44	32x38x44	32x38x44
	8.5	8.5	9.5	9.5	13.2	13.2
	2050/1250	2050/1250	2050/1250	2050/1250	2050/1250	2050/1250
	426-3801 426-3802	426-5801 426-5802	427-3811 427-3812	426-5811 426-5812	427-3821 427-3822	426-5821 426-5822
	+++	++++	+++	++++	+++	++++



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The HAAKE Phoenix heating circulators are designed for temperature controlling external systems. The bath opening also enables the immersion of samples within the circulator bath. All units have a stainless steel bath and can be used up to 280°C. The powerful pump guaran-tees a good heat exchange and optimum temperature accuracy.

Innovative
The pump automatically adapts itself to the viscosity of the bath liquid used due to the automatic speed recognition function. This guarantees constant pressure and flow rate conditions over a wide temperature range.



P1-B5 / P2-B5
Compact heating circulators with a 5-liter bath, ideal for temperature controlling small open or closed systems with short heating up times and thus quick reaction times.



P1-B7 / P2-B7
Slim-line heating circulators with a deep 7-liter bath for temperature controlling open and closed sys-tems; high temperature accuracy for medium-size external systems.



P1-B12 / P2-B12
Heating circulators with a 12-liter bath suitable for external systems with high volume variations; use as open-bath circulator also possible due to the large bath opening.

Technical specification acc. to DIN 12876		P1-B5	P2-B5	P1-B7	P2-B7
Working temperature range	°C	32...250	32...280	30...250	30...280
with tap water cooling	°C	20...250	20...280	20...250	20...280
with other cooling	°C	-60...250	-60...280	-60...250	-60...280
Temperature accuracy	+/- K	0.01	0.01	0.01	0.01
Heater capacity 230V / 115V	kW	2.0/1.2	3.0/1.2	2.0/1.2	3.0/1.2
Pump: Pressure max. Flow rate max. Suction max. Flow rate max.	mbar l/min mbar l/min	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22
Bath opening WxLxD	cm	14x14.5x15	14x14.5x15	13x10x20	13x10x20
Bath volume max.	l	4.5	4.5	7	7
Overall dimensions WxLxH	cm	24x38x44	24x38x44	25x38x50	25x38x50
Total wattage 230V / 115V	VA	2100/1250	3100/1250	2100/1250	3100/1250
Net weight	kg	10.2	10.2	11.8	11.8
Order-No. for 230V / 50-60Hz Order-No. for 115V / 60Hz		440-0051 440-0052	441-0051 441-0052	440-0071 440-0072	441-0071 441-0072
ExtraPlus-Rating (see page 35)		+ + + + +	+ + + + + +	+ + + + +	+ + + + + +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com




P1-W26 / P2-W26
Combined open-bath and heating circulators with a 42-liter bath. Extra deep bath (300 mm) for large objects,simultaneous temperature control of external systems.



P1-W45 / P2-W45
Combined open-bath and heating circulators with a 26-liter bath.Large bath opening for direct temperature control of objects, simultaneous temperature control of external systems.



Additional pump
If the capacity of the integrated circulator pump would not be high enough for temperature controlling an external system, this booster pump can provide up to 3 bar pressure.



Comes with
Each 2 **nozzles** for tubings with 8 and 12 mm i. Ø
Bath cover for B5, B7, B12
Tap water cooling coil for B5, B7, B12

Optional accessories	Order-No.
Tap water cooling coil for baths W26 und W45	**333-0677**
Universal **hose nozzle** for tubing of 3 bis 6 mm i. Ø	**001-3718**
Reservoir **drain**	**333-0499**
Bath cover made from stainless steel (fits 2 x onto W45)	**333-0648**
Bath cover made from stainless steel (fits 2 x onto W26)	**333-0225**
External analog box	**333-0685**
230V Power supply for analog box	**333-0705**
Software ThermStar95plus	(s. P. 32)
Tubing and bath liquids	(s. P. 30-31)
Pt100 sensors	(s. P. 33)
Additional heater B7 bath	**333-0741**
Additional heater B12 cooling	**333-0743**
Solenoid valve control for tap water cooling	**333-0744**
Additional pump	**333-0746**
Profibus interface	on request

P1-B12	P2-B12	P1-W26	P2-W26	P1-W45	P2-W45
28...250	28...280	28...250	28...280	28...250	28...280
20...250	20...280	20...250	20...280	20...250	20...280
-60...250	-60...280	-60...250	-60...280	-60...250	-60...280
0.01	0.01	0.01	0.01	0.01	0.01
2.0/1.2	3.0/1.2	2.0/1.2	3.0/1.2	2.0/1.2	3.0/1.2
560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22
22x14x20	22x14x20	30x35x20	30x35x20	30x35x30	30x35x30
12	12	26	26	42	42
34x38x50	34x38x50	35x54x44	35x54x44	36x54x55	36x54x55
2100/1250	3100/1250	2100/1250	3100/1250	2100/1250	3100/1250
13	13	11	11	19	19
440-0121 440-0122	441-0121 441-0122	440-0261 440-0262	441-0261 441-0262	440-0451 440-0452	441-0451 441-0452
+++++	++++++	+++++	++++++	+++++	++++++

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


The powerful refrigerated circulators in the HAAKE C/DC class are available either in a space-saving vertical version or an ergonomic flat version. The K10 does not require more space than a sheet of DIN A4 paper at the bench. The units K10, K15 and K20 are primarily used at room temperature. The units also feature efficient heat removal even at high temperatures and enable the temperature controlling of external closed liquid circuits at temperatures well below 0°C. Unit selection depends mainly on the required cooling capacity and the desired temperature range.

Note:
The units K10, K15 and K20 can be combined with all circulator heads from C10 to DC50.

Comes with
Each 2 **nozzles** for tubings with 8 and 12 mm i. Ø and a **bath cover.**
C10-K10, C10-K15 and C10-K20: plus **checking thermometer** 0 to 100°C, division 0,5°C.

Optional accessories	Order-No.
Universal **hose nozzle** for tubing of 3 to 6 mm i. Ø	**832-0275**
Reservoir **drain**	**333-0499**
Software for DC30, DC50 (see Page 32)	
Trolly with castors for K35, K40, K41, K50	**333-0508**


Optional accessories	Order-No.
Rack for 20 tubes, 16 mm Ø for K10	**333-0456**



Racks for K15 and K20	
18 tubes, 16 mm Ø	**333-0500**
26 **micro centrifuge tubes**, 1.5 ml, 10 mm Ø	**333-0501**
6 **centrifuge tubes**, 50 ml, 30 mm Ø	**333-0502**
Choose the **necessary tubes, bath liquids** and **Pt-100 sensor** for DC50-units on pages 30/31/33.	



Sealed bath cover with K10, K15 and K20



Technical specifications acc. to DIN 12876		C10-K10	DC10-K10	C10-K15	DC10-K15
Working temperature range	°C	-10..100	-10..100	-28..100	-28..100
Temperature accuracy	+/-K	0.04	0.02	0.04	0.02
Heater capacity 230V / 115V	kW	1.5/1.0	2.0/1.2	1.5/1.0	2.0/1.2
Cooling capacity at 20°C at 0°C at -20°C	W W W	240 70 –	240 70 –	300 200 70	300 200 70
Pump: Pressure / Flow rate max.	mbar/ l/min	300/12.5	300/12.5	300/12.5	300/12.5
Bath opening: WxLxD	cm	13x10x15	13x10x15	13x10x15	13x10x15
Bath volume max.	l	3	3	4.5	4.5
Overall dimensions: WxLxH	cm	19.5x36x57	19.5x36x57	39x46x41	39x46x41
Net weight	kg	22.7	22.7	30.8	30.8
Total wattage 230V / 115V	VA	1800/1300	2300/1500	1900/1400	2400/1600
Order-No. for 230V / 50Hz for 220V / 60Hz for 115V / 60Hz		425-1641 425-1641 425-1642	426-1641 426-1641 426-1642	425-1501 425-1501 425-1502	426-1501 426-1501 426-1502
ExtraPlus rating (see page 35)		+	+ +	+	+ +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



DC30-K15	C10-K20	DC10-K20	DC30-K20	DC50-K35	DC50-K40	DC50-K41	DC50-K50
-28..150	-28..100	-28..100	-28..150	-35..200	-40..150	-40..150	-47..200
0.01	0.04	0.02	0.01	0.01	0.01	0.01	0.01
2.0/1.2	1.5/1.0	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2	2.0/1.2
300 200 70	320 205 75	320 205 75	320 205 75	400 300 150	700 550 300	1000 750 400	850 700 500
300/12.5	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5	300/12.5
13x10x15	13x10x15	13x10x15	13x10x15	22x14x15	29x15x15	29x15x20	22x14x15
4.5	4.5	4.5	4.5	8	12	15	8
39x46x41	23x46x58	23x46x58	23x46x58	38x46x68	38x46x74	38x46x74	38x46x74
31.1	29.8	29.8	30.1	37	43	50	46
2400/1600	1900/1400	2400/1600	2400/1600	2500/1700	2550/ –	2600/ –	2650/ –
426-3501 426-3501 426-3502	425-1601 425-1601 425-1602	426-1601 426-1601 426-1602	426-3601 426-3601 426-3602	426-5351 426-5351 426-5352	426-5401 426-5409 –	426-5411 426-5419 –	426-5491 426-5499 –
+++	+	++	+++	++++	++++	++++	++++


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The HAAKE Phoenix refrigerated circulators feature. FuzzyStar control with neural adaptation, the tried-and-tested energy management system. External connection options greatly extend the application range.

All units are characterized by their simple operation and represent the optimum combination of design and functionality.

The refrigerated circulators are especially suited for the temperature control of open and closed temperature control circuits due to their powerful pressure and suction pump.

Innovative:
The pump automatically adapts itself to the viscosity of the bath liquid due to the automatic speed recognition function.
This guarantees constant pressure and flow rate conditions over a wide temperature range.



Comes with
nozzles
for tubings with 8 and 12 mm i. Ø
Bath cover

Optional accessories	Order-No.
Universal **hose nozzle** for tubing of 3 bis 6 mm i. Ø	**001-3718**
Reservoir **drain**	**333-0499**
Trolley with castor for C30P, C35P, C40P, C41P, C50P	**333-0678**
External analog box	**333-0685**
230V Power supply for analog box	**333-0705**
Software ThermStar95plus	(s. P. 32)
Tubes and bath liquids	(s. P. 28–29)
Pt100 sensors	(s. P. 32)
Additional heater for C25P	**333-0741**
Additional heater for C30P, C35P, C50P	**333-0745**
Additional heater for C40P, C41P	**333-0742**
Additional pump	**333-0746**



Optional accessory: Additional heater ZH1 to accelerate heating-up

Technical specifications acc. to DIN 12876		P1-C25P	P2-C25P	P1-C30P	P2-C30P
Working temperature range	°C	-28...150	-28...150	-30...200	-30...200
Temperature accuracy	+/- K	0.01	0.01	0.01	0.01
Heater capacity 230V / 115V	kW	2.0 / 1.2	2.0 / 1.2	2.0 / –	2.0 / –
Cooling capacity at 20°C 0°C -20°C	W W W	300 200 70	300 200 70	800 620 450	800 620 450
Pump: Pressure max. Flow rate max. Suction max. Flow rate max.	mbar l/min mbar l/min	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22
Bath opening WxLxD	cm	13x10x15	13x10x15	22x14x20	22x14x20
Bath volume max.	l	4.5	4.5	12	12
Overall dimensions WxLxH	cm	26x48x63	26x48x63	40x51x77	40x51x77
Total wattage 230V / 115V	VA	2450 / 1650	2450 / 1650	2600 / –	2600 / –
Net weight	kg	26.3	26.3	46	46
Order-No. for 230V / 50Hz Order-No. for 220V / 60Hz Order-No. for 115V / 60Hz		440-0251 440-0251 440-0252	441-0251 441-0251 441-0252	440-0301 440-0309 –	441-0301 441-0309 –
ExtraPlus-Rating (see page 35)		+ + + + +	+ + + + + +	+ + + + +	+ + + + + +

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



P1-C25P / P2-C25P
Compact refrigerated circulators down to -28°C with a small 4.5 liter bath for rapid cooling.
300 watt cooling capacity at 20°C.



P1-C30P / P2-C30P
Refrigerated circulators for high loads down to -30°C, reliable cooling even at high ambient temperatures.
800 watt cooling capacity at 20°C.



P1-C35P / P2-C35P
Refrigerated circulators with a wide temperature range from -35°C to +200°C. 400 watt cooling capacity at 20°C.



P1-C40P / P2-C40P
Refrigerated circulators with a large bath opening, down to -40°C ideal for the simultaneous temperature control internally and externally.
700 watt cooling capacity at 20°C.



P1-C41P / P2-C41P
High power refrigerated circulators down to -40°C. High cooling capacity for applications under 0°C.
1000 watt cooling capacity at 20°C.



P1-C50P / P2-C50P
Refrigerated circulators for extreme low temperatures down to -50°C. Inexpensive cooling alternative to a cryostat. 850 watt cooling capacity at 20°C.

P1-C35P	P2-C35P	P1-C40P	P2-C40P	P1-C41P	P2-C41P	P1-C50P	P2-C50P
-35...200	-35...200	-40...150	-40...150	-40...150	-40...150	-50...150	-50...150
0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01
2.0 / 1.2	2.0 / 1.2	2.0 / –	2.0 / –	2.0 / -	2.0 / -	2.0 / -	2.0 / -
400 300 150	400 300 150	700 550 300	700 550 300	1000 750 400	1000 750 400	850 700 500	850 700 500
560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22	560 24 380 22
22x14x15	22x14x15	29x15x15	29x15x15	29x15x20	29x15x20	22x14x15	22x14x15
8	8	12	12	15	15	8	8
40x51x71	40x51x71	40x51x71	40x51x71	40x51x77	40x51x77	40x51x77	40x51x77
2500 / 1700	2500 / 1700	2550 / –	2550 / –	2600 / –	2600 / –	2650 / –	2650 / –
40	40	41	41	45	45	46	46
440-0351 440-0359 440-0352	441-0351 441-0359 441-0352	440-0401 440-0409 –	441-0401 441-0409 –	440-0411 440-0419 –	441-0411 441-0419 –	440-0501 440-0509 –	441-0501 441-0509 –
+++++	++++++	+++++	++++++	+++++	++++++	+++++	++++++

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Cryostats application and selection

Very low temperatures are best reached with both P2-CT90L and -W, the P1/P2-C75P and the DC50-K75 cryostats. The P2-CT50L and -W both delivera high cooling capacity.

The cryostats are cooled by powerful, quiet compressors. The cooling circuits are either air-cooled (K75, C75P, CT50L, CT90L) or water-cooled (CT50W, CT90W).

The powerful, water-cooled units are equipped with a water flow limiter. The water consumption is kept low, thus considerably reducing operating costs.

The cooling capacity for all HAAKE Phoenix cryostats is controlled by a fuzzy logic-supported energy management system.

The floor-based units are fitted with stable, adjustable castors.

The cryostats HAAKE DC50-K75 and P1/P2-C75P are suitable for location either under or on the lab table.

HAAKE Phoenix cryostats

The most user-friendly cryostat baths available to handle a wide range of applications.

The Phoenix cryostats come equipped with a powerful pressure and suction pump, feature a cooling capacity of up to 5000 W, and are thus ideally suited to meet the extreme technical specifications that many applications require. Phoenix circulators are available in two versions:

- Basic version Phoenix 1 (P1) with a 1 kW heating capacity
- Full version Phoenix 2 (P2) with 1 to 3 kW heating capacity and with additional functional features

HAAKE Phoenix P1-C75P / P2-C75P

- Compact cryostat down to -75°C
- Unit can be placed on the lab table
- 280 W cooling capacity at 20°C

HAAKE Phoenix P2-CT50L

- Cryostat with high capacity down to -50°C
- Air-cooled floor-based unit
- Ideal for direct temperature control in the bath
- 2500 W cooling capacity at 20°C
- Large bath volume (24 l)

HAAKE Phoenix P2-CT50W

- Cryostat with big power down to -50°C
- Water-cooled floor-based unit
- 5000 W cooling capacity at 20°C
- Large bath volume (24 l)

HAAKE Phoenix P2-CT90L

- Cryostat with high capacity down to -90°C
- Air-cooled floor-based unit
- Ideal for direct temperature control in the bath
- 1650 W cooling capacity at 20°C

HAAKE Phoenix P2-CT90W


- Cryostat with big power down to -90°C
- Water-cooled floor-based unit
- 1900 W cooling capacity at 20°C
- 200 W cooling capacity at -80°C

HAAKE Phoenix P2-CT80L

- Compact cryostat down to -80°C
- Excellent price-performance ratio
- 800 W cooling capacity at 20°C

Technical specification acc. to DIN 12876		DC50-K75	P1-C75P	P2-C75P	P2-CT80L	P2-CT50L
Working temperature range	°C	-75..100	-75..100	-75..100	-80..100	-50..100
Temperature accuracy	+/-K	0.05	0.02	0.02	0.1	0.1
Heater capacity	kW	1.5	1.0	1.0	1.0	2.0
Cooling at 20°C / 0°C at -20°C / -40°C at -60°C / -80°C	W W W	280 / 220 180 / 130 50 / –	280 / 220 180 / 130 50 / –	280 / 220 180 / 130 50 / –	800 / 750 700 / 600 500 / 50	2500/1750 1100 / 300 –
Pump: Pressure / Flow rate max. Suction / Flow rate max.	mbar/ l/min mbar/ l/min	300 / 12.5 – / –	560 / 24 380 / 22	560 / 24 380 / 22	560 / 24 380 / 22	560 / 24 380 / 22
Bath opening: WxLxD	cm	13x10x20	13x10x20	13x10x20	22x14x20	22x27x20
Bath volume	l	6	6	6	12	24
Overall dimensions: WxLxH	cm	38x46x72	40x51x77	40x51x77	42x66x102	50x75x109
Net weight	kg	65	68	68	107	125
Total wattage	VA	2450	2500	2500	2500	3300
Order-No. for 230V / 50Hz for 220V / 60Hz for 380V / 3Ph / 50Hz for 220V / 3Ph / 60Hz		426-5751 – – –	440-0751 440-0759 – –	441-0751 441-0759 – –	441-0801 441-0809 – –	– – 446-0503 446-0504
ExtraPlus-Rating (see page 35)		++++	+++++	++++++	++++++	++++++

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



	P2-CT50W	P2-CT90L	P2-CT90W
	-50..100	-90..100	-90..100
	0.1	0.1	0.1
	3.0	2.0	2.0
	5000 / 3000 1900 / 800 –	1650 / 1500 1300 / 1150 600 / 170	1900 / 1700 1500 / 1300 700 / 200
	560 / 24 380 / 22	560 / 24 380 / 22	560 / 24 380 / 22
	22x27x20	22x15x20	22x15x20
	24	15	15
	50x75x109	50x90x109	50x90x109
	180	190	185
	5800	5300	5300
	– – 447-0503 447-0504	– – 448-0903 448-0904	– – 449-0903 449-0904
	++++++	++++++	++++++

HAAKE DC50 cryostats are used for a wide range of standard applications.
A powerful pump enables the temperature control of small, closed external systems.

The unit can be set by a push-button keypad. The read-out is shown via two separate display panels.

HAAKE DC50-K75

- Compact cryostat down to -75°C with a temperature accuracy of ± 0.05 K
- Unit can be placed on the lab table
- 280 W cooling capacity at 20°C
- 130 W cooling capacity at -40°C




Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

HAAKE DC50 Highlights

- Powerful pumps with Turbulence Reduction System (TRS)
- Simple operation due to separate display panels for menu selection and temperature
- Microprocessor control with PID control
- Resolution of the digital display for the set and actual temperature optionally 0.1 or 0.01°C
- Real Temperature Adjustment (RTA)
- Ability to save 3 user-defined fixed temperatures with their respective RTA values
- The reason for a unit fault is shown on the display via the Fault Identification System (FIS)
- RS 232C interface, optional RS485
- External Temperature Compensation (ETC) for controlling external systems with connection for an external Pt100 sensor

HAAKE Phoenix Highlights

- FuzzyStar control with neuronal adaptation
- Easy operation of the units due to a large monitor with plain text display and direct value setting
- Very powerful combined pressure and suction pump with automatic speed recognition for the precise temperature control of external objects
- 4 savable fixed temperatures
- Flexible interface concept: RS232C (standard), multifunctional output (standard), RS485 (for P2), Profibus (optional for P2)
- External Temperature Control (ETC) with connection for an external Pt100 sensor as standard
- User can choose from 6 different dialog languages
- Permanent display of date and time
- Up to 10 ramp programs with a maximum of 30 segments (for P2)
- 3-point calibration function (for P2)




Comes with


Each 2 **nozzles** for tubings with 8 and 12 mm i. Ø

Reservoir drain for CT50L, CT50W, CT80L, CT90L and CT90W


Optional accessories	Order-No.
Rack for DC50-K75, P1-C75P and P2-C75P for:	
18 tubes, 16 mm Ø	**333-0500**
26 **micro centrifuge tubes**, 1.5 ml, 10 mm Ø	**333-0501**
6 **centrifuge tubes**, 50 ml, 30 mm Ø	**333-0502**



Universal hose nozzle for tubing of 3 bis 6 mm i. Ø for Phoenix-Cryostats	**001-3718**



Software ThermStar95plus Programming temperature set values and ramp programs for cryostats via PC under Win95, 98 or NT	**091-2950**
Universal hose nozzle for tubing of 3 bis 6 mm i. Ø for DC50-K75	**832-0275**
Reservoir drain for DC50-K75, P1-C75P and P2-C75P	**333-0499**



Trolley with castors for DC50-K75	**333-0508**
Trolley with castors for P1-C75P and P2-C75P	**333-0678**


Choose the necessary tubes, bath liquids and Pt100 sensors on pages 30, 31 and 33.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The SWB25 features a high safety level for constant operation in addition to very accurate temperature control (PID control). Shaking frequency and temperature are adjusted via a keypad and digital display. The heater and control sensor are located underneath the bath, thus guaranteeing easy cleaning.

The fluid level can vary from 50 mm to 180 mm to acemmodate sample vessels of differing heights. A second shaking carriage (optional) can be inter-changed quickly and easily.

The transparent plastic gable-shaped bath cover (optional) prevents water spillage due to turbulence formation. It is particularly recommended for temperatures above 70 °C.





SWB25 with test tube rack

Technical specification acc. to DIN 12876		SWB25
Working temperature range with tap water cooling	°C °C	22..90 20..90
Temperature accuracy	+/-K	0.2
Heater capacity 230V / 115V	kW	1.5/1.5
Type of control		PID
Overtemperature protection		adjustable
Bath opening: WxLxD	cm	50x30x20
Bath volume	L	8..26
Shaking amplitude	mm	15
Shaking frequency (cont. adj.)	min^{-1}	20..200
Overall dimensions: WxLxH	cm	65x34x26
Net weight	kg	18
Total wattage 230V / 115V	VA	1600/1600
Order-No. for 230V / 50..60Hz for 115V / 60Hz		375-0001 375-0002




SWB25 with swivelling gabled cover

Comes with


One **Shaking carriage plate** without clamps

Optional accessories	Order-No.
Tap water **cooling coil**	**000-8581**




Swivelling roof-shaped **cover** (transp.) **333-0642**

Basic rack without inserts for each 2 of the following inserts **333-0259**




Inserts for tubes into basic rack


for 86 of 10 mm Ø **333-0130**




for 46 of 16 mm Ø **333-0131**



for 23 of 25 mm Ø **333-0132**




without holes **333-0151**



Clamps to fix beakers or flasks onto the shaking carriage plate or the basic rack.

flask cont. (ml)	glas Ø (mm)	no. per carriage plate	
25	42	40	**000-8732**
50	51	32	**000-1980**
100	64	18	**000-1982**
250	85	12	**000-1990**
500	105	8	**000-1994**
1000	131	5	**000-1995**



Spare schaking carriage plate 000-8384

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

These coolers are ideal for the following applications:

- to cool smaller volumes down to -90°C,
- to remove reaction heat or
- to replace tap water cooling

The lowest reachable temperature depends upon:

- the quantity of liquid
- the type of liquid and its viscosity
- the bath insulation

Flow-Through Cooler HAAKE DK15
This cooler is used in the liquid circuit of a heating circulator. Heat is removed from the liquid as it flows through the cooler.

Immersion Coolers HAAKE EK20/EK30
Used together with the open-bath circulators, these coolers provide an alternative to tap water cooling. The lowest attainable temperature and the cooling down times are illustrated in the diagrams.

The EK20 is designed for baths with a 15 cm depth and the EK30 for baths with a depth of at least 20 cm.


Vessels can of othersizes also be cooled. End temperatures of -25°C resp. -30°C can be reached in a 5 l Dewar vessel.

Immersion Cooler HAAKE EK45
This multi-purpose cooler has its own controller with digital temperature display, reaching temperatures down to -45°C in a 5 l Dewar vessel. The controller enables temperature accuracy of approx. 1°C to 2°C. Improvement is possible using a stirrer.

Immersion Cooler HAAKE EK90
This unit is designed for working temperatures down to -90°C. The cooling coil is flexible and can therefore be adapted to suit virtually any bath shape. The minimum diameter of the vessel to be cooled is 110 mm.

Comes with
EK45 and EK90:
Electronic controller and Pt100 sensor (Ø 6 mm, 50 mm long, cabel 2.5 m long).

Optional accessories	Order-No.
Trolley with castors for EK90	**333-0508**
Holder to fix a cooler EK20, EK30 or EK45 onto a wall with a thickness up to 25 mm	**333-0602**




Technical specification acc. to DIN 12876		DK15	EK20	EK30	EK45	EK90
Working temperature range	°C	-15..150	-25..150	-30..150	-45..40	-90..40
Cooling at 20°C	W	300	300	400	350	300
at -10°C	W	150	150	250	250	280
at -40°C	W	–	–	–	50	170
at -60°C	W	–	–	–	–	100
Hose length	cm	–	150	150	150	150
Cooling coil dimensions (Ø x L)	mm	–	81 x 145	81 x 195	81 x 195	13 x 900
Smallest bending radius	mm	–	–	–	–	40
Connecting nozzles for hoses	mm Ø	12 and 8	–	–	–	–
Overall dimensions: WxLxH	cm	23x46x38	23x46x38	23x46x38	23x46x38	38x46x49
Net weight	kg	22	22	23	30	60
Total wattage	VA	160	160	270	300	750
Order-No. for 230V / 50..60Hz		106-1151	322-1201	323-1301	328-1451	329-1901
for 115V / 60Hz		106-1152	322-1202	323-1302	328-1452	–


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com




Cooling time with the EK20



Cooling time with the EK30



Cooling time with the EK45 und EK90



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Tap water is still used far too often when measuring instruments, distillation equipment or rotary evaporators need to be cooled. This method is not only environmentally damaging, but it is also technically unsound. The presence of minerals and bacteria create problems with scaliry and contamination.

Water recirculators are both an economical and ecologically sensible alternative to wasting tap water for cooling purposes.

Haake TC water recirculators are available in 5 different cooling capacity models up to 5 kW.

A variable pump and accessories program fits the units to your application. Ask for our special water recirculator brochure.



HAAKE TC water recirculators are flexible:
You can combine the available pumps and cooling compressors to suit your requirements. They are also available in two versions.

HAAKE TC water recirculators are economical:
They do more than save tap water. Short pay-back periods are guaranteed by their excellent cost/benefit ratio.

HAAKE TC water recirculators are safe and reliable:
The units are designed and manufactured according to EN 61010. A variety of safety elements guarantee reliable operation.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

This low cost mini-cooler is specially designed to remove of up to 240 watts heat from connected analysis instruments, apparatus or any thermic processes.

The water recirculator HAAKE WKL 26 is a small-scale unit which can be situated practically anywhere. A high level of noise reduction is attained due to the quiet-running compressor.




HAAKE WKL 26 Highlights

- The working temperature can be variably adjusted.
- The control accuracy is approx. ± 1.1K.
- The powerful pump is designed for hoses with an inner diameter of 8 to 12 mm.
- A long unit service life as the switching on and off of the compressor is avoided.
- Small and compact, the unit base takes up roughly the surface area of a DIN A4 sheet of paper.
- The ventilation grid can be removed for easy cleaning of the liquifier fins.
- All parts which come into contact with the bath liquid are made from stainless steel.
- The compressor circuit and circulation pump do not require maintenance.
- A drainage opening for easy water changing.
- A combined temperature and water level indicator is available as an optional accessory.
- The unit is CFC-free and has the CE-mark.

Comes with:

Each 2 nozzles for tubes with 8 and 12 mm Inside-Ø

Description	Order-No.
Combined temperature and liquid level indicator	333-0567



Technical Specifications		WKL 26
Working temperature range	°C	-10 to 30
Temperature accuracy	± K	1.1
Cooling capacity at 20°C Refrigerant (CFC-free)	W	240 R 134a
Pump capacity Pressure max. Flow rate max.	 mbar l/min	 300 12
Bath volume Filling opening	l mm	3 45 Ø
Dimensions Base area Height	 mm mm	 200x340 490
Weight	kg	22
Total wattage max.	VA	450
Max. ambient Temperature	°C	5 - 40
Order-No. for 230V / 50Hz for 115V / 60Hz		 386-0001 386-0002

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Hoses
All circulators and cryostats are always delivered with nozzles for tubings with an inner Ø of 8 and 12 mm. The tubings and insulation (if applicable) have to be ordered separately and should be selected according to the application.

Description	Order-No.
Insulated **metal tubing** made from stainless steel with M16x1 unions on both ends. To be used from -50 to +300°C.	
50 cm long	**333-0292**
100 cm long	**333-0293**
150 cm long	**333-0294**
coupling to connect 2 tubings to each other	**001-2560**
coupling for circulation set C-/DC-line	**333-0302**
Insulated **metal tubing** made from stainless steel with M16x1 unions on both ends. Especially for the low temperature range -90..105°C	
100 cm long	**333-0578**
150 cm long	**333-0579**
coupling to connect 2 tubings to each other	**001-2560**
coupling for circulation set C-/DC-line	**333-0302**
PVC tubing to be used only with water	
8 mm i. ø; per meter	**082-0745**
12 mm i. ø; per meter	**082-0304**
Viton tubing for a temperature range of -60 to + 200°C	
8 mm i. ø; per meter	**082-1214**
12 mm i. ø; per meter	**082-1215**
Silicone tubing for a temperature range of -30 to + 220°C (not to be used with any silicone oil.)	
8 mm i. ø; per meter	**082-0663**
12 mm i. ø; per meter	**082-0664**
Perbunan tubing for a temperature range of -40 to + 100°C	
8 mm i. ø; per meter	**082-0172**
12 mm i. ø; per meter	**082-0173**
Foam rubber insulation for PVC, Viton, silicone and Perbunan tubings	
for tubings with 8 mm i. Ø; per meter	**806-0373**
for tubings with 12 mm i. Ø; per meter	**806-0374**



Bath Liquids
The carefully selected and proven heat transfer liquids offer the following advantages:

- Eliminates health hazards and minimizes unpleasant odors.
- High resistance against aging while retaining a low viscosity with a low corrosive tendency.

Note: A good ventilation is recommended when working at temperatures > 200°C.

1. Viscosity

For optimum temperature accuracy it is very important that the heat transfer liquid be of low viscosity.

2. Fire Point

Flammable thermal liquids can ignite when a specified temperature is surpassed. The usage of bath liquids is limited to a temperature level 25°C below the fire point as defined by the EN 61010.

3. Selection

Silicone oils (Sil):
Carry a low risk of inflammation, do not give off unpleasant odors and have a long service life.

Synthetic thermal liquids (Synth):
Are mainly produced on a hydrocarbon basis and exhibit a low viscosity within the recommended working temperature range.

4. Application Range

Working temperature range:
This is the range within which the circulator can be operated optimally over a longer period of time. The maximum viscosity is approx. 5 mPas.

Operating temperature range:
The circulator may be operated only within this range over a longer period of time under certain conditions. Viscosity may rise to a maximum of 30 mPas. The pump capacity no longer matches the specifications made in the brochure.

Heating range:
Long-term temperature control this range is not permissible as the pump motor's excess temperature protection may switch off the pump.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Application range		Sil 100	Sil 180	Sil 300	Synth 20*)	Synth 60	Synth 200	Synth 260
Fire point	°C	>100	> 225	>325	n.a.	70	>235	275
Viscosity	at 20 °C [mPas]	3	11	200	<1	2	100	140
Density	at 20 °C [kg/dm³]	0.89	0.93	1.08	0.77	0.76	0.86	1.03
Spec. heat capacity	[kJ / kg x K]	1.67	1.51	1.56	n.a.	2.1	1.96	2
Temperature ranges **Heating-up range** **operating temperature range** **working temperature range**	300°C 250°C 200°C 150°C 100°C 50°C 0°C -50°C -100°C	75	200	300	-28	45	210	250
Color		transparent colorless	transparent colorless	transparent colorless	transparent colorless	transparent colorless	transparent light brown	transparent colorless
Reacts with		Silicone	Silicone	Silicone	Light-metals Zinc	Rubber Silicone	Copper Lightmetal Bronze	Copper Lightmetal Bronze
Order-No. for 10 l Container		**999-0202**	**999-0204**	**999-0206**	**999-0208**	**999-0210**	**999-0226**	**999-0214**
Order-No. for 5 l Container		**999-0201**	**999-0203**	**999-0205**	**999-0207**	**999-0209**	**999-0225**	**999-0213**

EC-Safety Data Sheets will be delivered together with each container of liquid.

*) Cannot be exported; use methylecyclohexane as bath liquid

n.a. not applicable

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Application Software for all HAAKE Phoenix and HAAKE DC Line Circulators

HAAKE Phoenixline or a HAAKE DC30, DL30 or DC50 circulators can be connected to a PC and controlled with Windows 95, 98 or NT.

Highlights of HAAKE ThermStar95plus:

- Simple operation due to the clear alignment of program options via a register card system.
- Selection between ramp function, just data recording and an online mode with set value setting.
- Simultaneous control of up to eight circulators.
- Online-graph with zoom function and display of internal, external and set temperature- and time values.
- Temperature ramp programs with up to 99 segments and 99 repetitions.
- Time setting down to the last second with a maximum of 23h:59min:59s per segment.
- Long distance diagnosis possible with recorded service data.
- Export of measured values as ASCII-file.
- 5 operating languages possible
- Automatic identification of connected circulator.
- Circulator connection to Intranet / Internet available (remote control).
- Monitoring of various circulators via Intranet from one location.

Hard- und Software requirements:

- A HAAKE Phoenix line circulator or a HAAKE DC30, DL30 or DC50 model.
- A PC with the operating system Windows 95, 98 or NT and a CD-ROM drive.
- At least one available RS232C interface port with a suitable connecting cable (9-pole SUB-D at both ends).


Contents of delivery:

- Software package HAAKE ThermStar95plus on CD-ROM with hardware protection device (dongle) and additional program
- operating instructions

Order-No. 091-2950

Note:
HAAKE ThermStar95plus can also be used with older HAAKE F/N line circulators (F6, F8, N6, N8).

A demo-version ThermPlot95plus can be downloaded free-of-charge from www.thermo.com.




Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Pt100-Sensor


The following sensors are available for external temperature control applications (ETC-System) with circulators and cryostats.

Description	Order-No.
Sensor TT for Phoenix units Pt100 sensor in closed protection tube made from stainless steel 18/8, 150 mm long, ø 3 mm, cable length 3 m, up to 600°C	**333-0429**
Sensor DTT for DC50 units Pt100 sensor in closed protection tube made from stainless steel 18/8, 150 mm long, ø 3 mm, cable length 3 m, up to 600°C	**333-0613**
Sensor ST for Phoenix units as sensor TT, 27 mm long, ø 3 mm, with thread M 10x1, cable length 3 m, up to 600°C	**333-0428**
Sensor DST for DC50 units as sensor TT, 27 mm long, ø 3 mm, with thread M 10x1, cable length 3 m, up to 600°C	**333-0612**
Sensor HT for Phoenix units as sensor TT, only to be used with the T-piece 001-1766, cable length 3 m, up to 600°C	**333-0423**
T-Piece for the sensor HT to be mounted into HAAKE metal tubing connections	**001-1766**


TT + DTT



ST + DST




HT




Level Control

All circulators and cryostats equipped with a combined pressure and suction pump can be used for the temperature control of external open baths. Tubing mounts with integrated level control are fitted for this purpose to make sure that the external bath will not overflow.

Description	Order-No.
Tubing mount for the level control in the external bath with screw clamp:	**333-0587**



Description	Order-No.
Tubing mount built into bath cover for level control in the circulator bath when temperature controlling external open vessels. For units with bath:	
B7, C25P	**333-0609**
B5	**333-0610**
B12	**333-0603**
C30P, C35P, C50P	**333-0591**
C40P, C41P	**333-0608**



Replenishing Device

This device enables the user to transfer evaporated water into a bath circulator automatically. The water loss will be compensated in small amounts to avoid temperature shocks and drifts.

The device comprises a controller and a float switch. The float switch has to be mounted into the bath cover of the circulator.

Description	Order-No.
Automatic replenishing device AN2 for 230 V/50..60 Hz/60 VA	**333-0752**
Holder for AN2 in bath bridge H62 and H73	**333-0762**
Holder for AN2 in bath cover B3, B7, K10, K15, K20, C25P	**333-0764**
Holder for AN2 in bath cover B5	**333-0765**
Holder for AN2 in bath cover B12, K35, K50, C30P, C35P, C50P	**333-0757**
Holder for AN2 in bath cover K40, K41, C40P, C41P	**333-0759**



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

This glossary contains the most important terms used to describe the features of HAAKE circulators.



1 PID^{++}-control

This robust control system is specially developed for HAAKE DC circulators and adapted to each respective unit. No customer adjustments are necessary.

2 FuzzyStar-control system with neural adaptation

This intelligent control system is included in all Phoenix circulators designed for the special demands of temperature control. This range incorporates a Fuzzy Logic control system combined with a system identification feature via neural networks.

Advantages:

- Quick heating and cooling
- Exact control without fluctuations
- Extremely robust control compensation in case of system changes
- High level of adaptability to sint a variety of applications
- Energy saving due to integrated cooling management
- Phoenix units sense your application needs and automaticaly adapt for optimal results

3 TRS system

The pump capacity can be reduced with the Turbulence Reduction System (TRS) to avoid heavy turbulence in open baths.

4 ETC system with external sensor connection

The External Temperature Control (ETC) handles the temperature control of external systems when an external Pt100 is con-nected. The inlet temperature in the circulator is adapted so that the set temperature in the external system is maintained precisely. A Pt100 sensor is used for this purpose.

5 Direct dialog via LCD graphic display

Phoenix circulators are equipped with a large LCD graphic display that shows the necessary operating steps in plain text. The selection of menu options is carried out via the direct assignment of the functions to keys.

6 HAAKE RTA system

The Real Temperature Adjustment (RTA) enables the difference between the actual temperature displayed and the real temperature in the bath or external system to be compensated for. To do this, the temperature difference must be measured once and entered into the circulator as a correction value. The correction of the display is then carried out automatically.



7 Safety classes NFL and FL

Units with safety elements classified according to NFL (Non Flammable Liquids) can be used only with water or water and antifreeze. Units with elements classified according to FL (Flammable Liquids) can be used with the recommended bath liquids.

8 HAAKE FIS system

The Fault Identification System (FIS) ensures that the cause for an alarm is clearly shown on the display. All safety-relevant parts are switched off.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

ExtraPlus Rating System

Each circulator has been given an individual ExtraPlus rating. This rating can be found at the bottom of the specification table in the product description.

Have you already chosen your circulator?
You can now cross-reference the ExtraPlus rating with the specifications in the corresponding column of the table on this page and see which features your circulator has.

Are you looking for a circulator with special features?
Select the desired features in the first column of the table on this page, and you can then determine which ExtraPlus rating your circulator should have.
Phoenix line circulators with a rating of 5 and 6 ExtraPlus can be found on pages with HAAKE Phoenix circulators. Circulators with a rating of 1 and 4 stars can be found on pages with HAAKE C/DC-line circulators.

Rating	+	++	+++	++++	+++++	++++++
Control and Technology						
Stable On/Off-Control	✔					
1 Advanced PID++-Control		✔	✔	✔		
2 FuzzyStar®-Control with neural adaption					✔	✔
Energy management of cooling					✔	✔
3 TRS-system / flow rate reduction	✔	✔	✔	✔	✔	✔
Self-adapting pump					✔	✔
4 External sensor connection with ETC-system				✔	✔	✔
Microprocessor and digital electronics		✔	✔	✔	✔	✔
Operation						
Analog setting and fine adujustment	✔					
Touch pad front panel with double display		✔	✔	✔		
5 Direct dialog on LCD-graphic display					✔	✔
Display selection (°C, °F, K)					✔	✔
Digital Display resolution (0.1 / 0.01 °C)		✔	✔	✔	✔	✔
Simultaneous SET/ACTUAL display				✔	✔	✔
Green 7-segment LED-display		✔	✔	✔		
Selection Languages				✔	✔	✔
User-defined fixed temperatures (storable)		✔	✔	✔	✔	✔
6 RTA-system for internal temperature		✔	✔	✔	✔	✔
6 RTA-system for external temperature				✔	✔	✔
High temperature limitation		✔	✔	✔	✔	✔
Low temperature limitation		✔	✔	✔	✔	✔
Continous display of date and time					✔	✔
Time for Start/Stop						✔
Number of saveable programs					1	10
3-point calibration						✔
Safety						
7 Safety elements acc. to NFL	✔	✔				
7 Safety elements acc. to FL			✔	✔	✔	✔
Variable overtemperature protection	✔	✔	✔	✔	✔	✔
Fixed low liquid level protection			✔	✔	✔	✔
Pump and motor overload protection	✔	✔	✔	✔	✔	✔
Control sensor monitoring		✔	✔	✔	✔	✔
Measuring and external sensor monitoring				✔	✔	✔
Cooling circuit overload protection					✔	✔
Optical alarm	✔	✔	✔	✔	✔	✔
Acoustical alarm			✔	✔	✔	✔
8 FIS		✔	✔	✔	✔	✔
Communication						
RS 232C interface			✔	✔	✔	✔
RS 485 interface				optional		✔
Profibus interface						optional
LIMS-compatible				optional		✔
Remote alarm connection						✔
External Start/Stop/Alarm						✔
Rating	**+**	**++**	**+++**	**++++**	**+++++**	**++++++**

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

International/Germany
Thermo Electron (Karlsruhe) GmbH
Dieselstr. 4
76227 Karlsruhe
Tel. +49(0)721 40 94-444

Benelux
Thermo Electron B.V.
Meerenakkerplein 31
5652 BJ Eindhoven
Tel. +31(0)40 2300236

France
Thermo Electron S.A.
16 Avenue du Québec - Silic 765
91963 Courtaboeuf Cedex
Tel. +33(0)1 60 92 48 00

Great Britain
Thermo Electron UK
Temperature Control Business
Ion Path, Road Three
Winsford, Cheshire CW7 3GA
Tel. +44(0)1606 548749

Thermo Electron UK
Material Characterization Business
Emerald Way
Stone Business Park, Stone
Staffordshire ST15 OSR
Tel. +44(0)17858-13648

USA
Thermo Electron
25 Nimble Hill Rd.
Newington, NH 03801
Tel. 603-430-6329

info@thermohaake.com

623-1063

©HAAKE /Nov. 2003

www.thermo.com/tc

Analyze • Detect • Measure • Control™

Thermo ELECTRON CORPORATION

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP