ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Toshiba MG75J2YS40* at our website: *Click HERE*

TOSHIBA GTR MODULE SILICON N CHANNEL IGBT


MG75J2YS50

HIGH POWER SWITCHING APPLICATIONS.


MOTOR CONTROL APPLICATIONS.

- The Electrodes are Isolated from Case.
- High Input Impedance.
- Includes a Complete Half Bridge in One Package.
- Enhancement-Mode.
- High Speed : $t_f = 0.30\mu s$ (Max.) ($I_C = 75A$)
  $t_{rr} = 0.15\mu s$ (Max.) ($I_F = 75A$)
- Low Saturation Voltage
  : $V_{CE\,(sat)} = 2.70V$ (Max.) ($I_C = 75A$)

EQUIVALENT CIRCUIT



Unit in mm



JEDEC	—
EIAJ	—
TOSHIBA	2-94D1A

Weight : 202g (Typ.)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Emitter Voltage		V_{CES}	600	V
Gate-Emitter Voltage		V_{GES}	±20	V
Collector Current	DC	I_C	75	A
	1ms	I_{CP}	150	
Forward Current	DC	I_F	75	A
	1ms	I_{FM}	150	
Collector Power Dissipation (Tc = 25°C)		P_C	390	W
Junction Temperature		T_j	150	°C
Storage Temperature Range		T_{stg}	−40~125	°C
Isolation Voltage		V_{Isol}	2500 (AC 1 min.)	V
Screw Torque (Terminal / Mounting)		—	3 / 3	N·m

961001EAA2


● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

http://store.iiic.cc/

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I_{GES}	$V_{GE}=\pm20V$, $V_{CE}=0$	—	—	±500	nA
Collector Cut-off Current		I_{CES}	$V_{CE}=600V$, $V_{GE}=0$	—	—	1.0	mA
Gate-Emitter Cut-off Voltage		$V_{GE\ (off)}$	$I_C=7.5mA$, $V_{CE}=5V$	5.0	7.0	8.0	V
Collector-Emitter Saturation Voltage		$V_{CE\ (sat)}$	$I_C=75A$, $V_{GE}=15V$	—	2.10	2.70	V
Input Capacitance		C_{ies}	$V_{CE}=10V$, $V_{GE}=0$, f=1MHz	—	7100	—	pF
Switching Time	Turn-on Delay Time	$t_{d\ (on)}$	Inductive Load $V_{CC}=300V$ $I_C=75A$ $V_{GE}=\pm15V$ $R_G=18\Omega$ (Note 1)	—	0.08	0.16	μs
	Rise Time	t_r		—	0.12	0.24	
	Turn-on Time	t_{on}		—	0.40	0.80	
	Turn-off Delay Time	$t_{d\ (off)}$		—	0.20	0.40	
	Fall Time	t_f		—	0.15	0.30	
	Turn-off Time	t_{off}		—	0.50	1.00	
Forward Voltage		V_F	$I_F=75A$, $V_{GE}=0$	—	2.10	2.80	V
Reverse Recovery Time		t_{rr}	$I_F=75A$, $V_{GE}=-10V$ $di/dt=100A/\mu s$	—	0.08	0.15	μs
Thermal Resistance		$R_{th\ (j-c)}$	Transistor Stage	—	—	0.32	°C / W
			Diode Stage	—	—	0.69	

Note 1 Switching Time Test Circuit & Timing Chart




961001EAA2'


● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
● The information contained herein is subject to change without notice.

http://store.iiic.cc/


I_C – V_{CE}




I_C – V_{CE}




I_C – V_{CE}




V_{CE} – V_{GE}



V_{CE} – V_{GE}




V_{CE} – V_{GE}




http://store.iiic.cc/


I_C – V_{GE}




V_{CE}, V_{GE} – Q_G




t_{on}, $t_{d\,(on)}$, t_r – I_C




t_{on}, $t_{d\,(on)}$, t_r – R_G



t_{off}, $t_{d\,(off)}$, t_f – I_C




t_{off}, $t_{d\,(off)}$, t_f – R_G




http://store.iiic.cc/


I_F – V_F




t_{rr}, I_{rr} – I_F




C – V_{CE}




$R_{th\,(t)}$ – t_w



SAFE OPERATING AREA



REVERSE BIAS SOA



http://store.iiic.cc/

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP