ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Tracewell TTX400-3U-1S-24* at our website: *Click HERE*

Tracewell Systems

CompactPCI POWER SUPPLY

TTX400-3U-1S-24

350 Watt, 3U, 1 Slot, 24VDC Input, CompactPCI Power Supply

The TTX Series from Tracewell Power offers a wide variety of form factors, utilizing a new topology which provides excellent power density and high efficiency. The single slot, 3U package delivers 350 watts of continuous output at 50°C with 400LFM air flow and efficiency greater than 80%. Power supply cooling is achieved by a heat sink which is positioned directly in the air stream for optimum heat dissipation. Rugged design and construction has been verified by HALT (Highly Accelerated Life Test) testing.



Specifications

- 24 VDC input (range 18 - 36 VDC)
- Output Voltages:

  V1: +5V@30A V3: +12V@5A

  V2: +3.3V@45A V4: -12V@0.5A

  V1 + V2 cannot exceed 70A
- 350 Watt output maximum
- Efficiency exceeds 80%
- Hot Swap, N+1 redundant
- V1, V2, V3 Single wire active current share up to 8 supplies
- Standard 47pin Positronic connector
- No minimum load on all outputs
- PICMG 2.11 R1.0 Compliant
- Remote sense on V1, V2, V3
- Reverse input polarity protection
- Over voltage, current, temperature protection

Safety & Emissions Features (pending)

- UL, cUL, CE
- FCC part 15, class A
- CISPR 22 (EN-55022) level A radiated
- GR-1089 conducted

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Tracewell Systems

CompactPCI POWER SUPPLY

TTX400-3U-1S-24

Output Voltage and Current

CONFIGURATION NUMBER	MAXIMUM TOTAL POWER	+5V	+3.3V	+12V	-12V
		V1	V2	V3	V4
TTX400-3U-1S-24	350W	30A	45A	5A	0.5A

V1 + V2 cannot exceed 70A

Input Specifications

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Voltage DC		18	24	36	VDC
Efficiency	Nominal DC, full load		80		%
Inrush Current			1		Amps
Input Protection	Reverse Polarity				
Input Current			18		Amps
No-Load Input Current			0.75		Amps

Output Specifications

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Minimum Load	On all outputs	0			Amps
Output Power				350	Watts
Output Regulation	Line, load, cross :5V, 3.3V, +12V		±1.5		%
	Line, load, cross : -12V		±3		%
PARD (ripple and noise)	20 MHz bandwidth 3.3V, 5V			50	mV*
	20 MHz bandwidth ±12V			120	mV*
Voltage Adjust Range	For 5V, 3.3V, ±12V outputs		2		%
Remote Sense	Compensates for distribution voltage drop		0.5		Volts
Current Share	Active current share		10		%
Overshoot/Turn On			0		%
Turn-On Delay	Input to power good		350		mS
Initial Setting Accuracy	For 5V, 3.3V, +12V outputs		1		%
Maximum Output Capacitance	Contact factory		TBD		uF

* mV pk-pk or 1%, whichever is greater

Feature Characteristics

PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Switching Frequency			500		KHz
Output Voltage Remote Sense Range			0.5		Volts
Output Over-Voltage Protection	Nominal		120		%
Output Over-Current Protection			140		%
Over-Temperature Shutdown			113		°C
Weight			1.01		Lbs.

Environmental Specifications

PARAMETER	CONDITIONS				
Operating Temperature	At full power	-40		50	°C
Storage Temperature		-40		85	°C
Humidity	Non-condensing		95		%

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Tracewell Systems


CompactPCI POWER SUPPLY

TTX400-3U-1S-24

Connector


PIN #	FUNCTION
1	V1 Out
2	V1 Out
3	V1 Out
4	V1 Out
5	V1 & V2 RTN
6	V1 & V2 RTN
7	V1 & V2 RTN
8	V1 & V2 RTN
9	V1 & V2 RTN
10	V1 & V2 RTN
11	V1 & V2 RTN
12	V1 & V2 RTN
13	V2 Out
14	V2 Out
15	V2 Out
16	V2 Out
17	V2 Out
18	V2 Out
19	V3 RTN
20	V3 Out
21	V4 Out
22	Signal RTN
23	Reserved
24	V4 RTN
25	Reserved

PIN #	FUNCTION
26	Reserved
27	EN# Enable
28	Reserved
29	Reserved
30	V1 Remote Sense
31	Reserved
32	Reserved
33	V2 Remote Sense
34	Sense RTN
35	V1 Current Share
36	V3 Remote Sense
37	Reserved
38	DEG# Degrade
39	INH# Inhibit
40	Reserved
41	V2 Current Share
42	FAL# Fail Signal
43	Reserved
44	V3 Current Share
45	Chassis Ground
46	+DC Input
47	-DC Input



Dimensions





Notes: 1) All dimensions are in inches (mm)
2) Keying per IEEE 1101.10

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Tracewell Systems

CompactPCI POWER SUPPLY

TTX400-3U-1S-24

Controls/Indicators

CONTROL/INDICATOR	CHARACTERISTIC
Green LED on	Input OK, Power supply is delivering power
Red LED on / Green LED on	Fault on secondary side, OVP, over temperature, current limiting
Red LED on / Green LED flash	DC input is present but the power supply is inhibited, or not enabled, or handle switch is not engaged
Degrade/Overtemp	Transitions low when unit is within 10°C of shutdown, Unit shuts down when internal temperature exceeds limits. Recycle power. Open collector
Enable	Active low input turns on power supply
Inhibit	Active low input turns off power supply
Fail	Active low output indicates fault condition. Open collector

Standards Compliance (pending)

APPROVAL	
UL, cUL, CE	
FCC Part 15, Class A	
CISPR 22 (EN-55022) level A radiated	
GR-1089 conducted	

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

ISO 9001-2000


PRELIMINARY DATA

Tracewell Systems


CompactPCI POWER SUPPLY

TTX400-3U-1S-24

Single Slot Power Backplane



Single Slot, 100mm power backplane
TTX-PB-1S-3U-S47-DC



PIN #	FUNCTION	PIN #	FUNCTION
1	V3 SHARE	11	V1 SENSE
2	FAL #	12	SENSE RTN
3	V2 SHARE	13	DEG #
4	RTN	14	V1 ADJ
5	V1 SHARE	15	V2 ADJ
6	INH #	16	V1
7	V3 SENSE	17	Res.
8	EN #	18	Res.
9	V2 SENSE	19	V3
10	SENSE RTN	20	Res.

*Male AMP Connector: Hard Wired 102398-8
Ribbon Cable 499252-2

S1 DIP SWITCH



1 Res.	ON	low
	OFF	high
2 Res.	ON	low
	OFF	high
3 Res.	ON	low
	OFF	high
4 INH #	ON	power off
	OFF	power on

5 V3	ON	local
	OFF	remote
6 V2	ON	local
	OFF	remote
7 V1	ON	local
	OFF	remote
8 RTN	ON	local
	OFF	remote

TTX Family of Products - 24VDC, 48VDC, Power Backplanes



3U, 1 slot



3U, 2 slot




1 slot 3U backplane 47 pin connector



6U, 1 slot



6U, 2 slot



1 slot 6U backplane single 47 pin connector



1 slot 6Ubackplane dual 47pin connector

note: data subject to change without notice

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP