

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*


ECONOMICAL SINGLE POINT BENDING BEAM LOAD CELLS

ESP SERIES

MADE IN USA

CAPACITY RANGES:
6, 10, 15, 20, 25, 30,
35 Kg.

The ESP Series is a economical, high accurate single point bending beam load cell. It is ideal for OEM applications such as electronic scales and weighing machines. The single point bending beam design is highly resistant to eccentric loading allowing direct mounting to the scale base and weighing platform. The ESP Series features a moisture proof sealant.




Specifications

Rated Output (R.O.):	2 mV/V nominal
Nonlinearity:	0.02% of R.O.
Hysteresis:	0.02% of R.O
Nonrepeatability:	0.02% of R.O.
Zero Balance:	±1% of R.O.
Compensated Temp. Range:	14°F to 104°F
Safe Temp. Range:	14°F to 140°F
Temp. Effect on Output:	0.002% of Load/°F
Temp. Effect on Zero:	0.002% of R.O./°F
Terminal Resistance:	350 ohms nominal
Excitation Voltage:	10 VDC (20 VDC max.)
Safe Overload:	150% of R.O.
Max. Weighing Platform Size:	11.8" x 11.8"

Model	Capacity Kg.	Capacity lb	A	Weight oz
ESP-6	6	13	1.181	7.1
ESP-10	10	22	1.181	7.1
ESP-15	15	33	1.181	7.1
ESP-20	20	44	1.181	7.1
ESP-25	25	55	1.575	9.2
ESP-30	30	66	1.575	9.2
ESP-35	35	77	1.575	9.2


Dimensions in Inches



Wiring Color Code (WCC1)

4 Conductor

Internal Temperature Compensation and Balance Network Not Shown



OPT-TEDS Plug & Play Option

AD9 (9 PIN "D" Series) Connector attached to the end of a Load Cell or Torque sensor cable with a TEDS (Transducer Electronic Data Sheet) EEPROM. Used with a Smart Plug & Play IEEE 1451.4 Compliant instrument, (shown on right), the Load Cell and Instrument will self calibrate. This option is a real time saver. Read additional article...



Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP