ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Ugo Basile 37400-001* at our website: *Click HERE*

UGO BASILE
Via G. Borghi 43, 21025 COMERIO – VA- ITALY
www.ugobasile.com

DYNAMIC PLANTAR AESTHESIOMETER

Cat. No. 37400

MECHANICAL STIMULATION

ASSESSMENT OF ANIMAL SENSITIVITY TO LIGHT TOUCH OF THE PAW

NEW INSTRUMENT, featuring:-

- Computer compatibility : direct connection to a PC (via optional 52010 software)
- Read-out : multifunction graphic display
- Print-out : by incorporated thermal printer



GENERAL

The 37400 Dynamic Plantar Aesthesiometer is a new instrument for the assessment of "touch sensitivity" on the plantar surface of the rodents.

Somesthetic (mechanical) stimulation has a long history of effective clinical use to diagnose pathologies of hyper- or hypo- aesthesia, brought about by drugs, neural pathology or experimental lesions, etc., in model and experimental systems using laboratory animals.

The instrument basically consists of:

- a movable touch-stimulator unit
- a framed metal mesh
- a two-compartment animal enclosure
- a microprocessor controlled electronic unit, provided with graphic LCD display, serial port (RS232) and thermal printer

The electronic unit, enclosed into a tiltable cylindrical case of original design, has an internal memory for data storage, scrolling screen review and optional output to PC.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

DYNAMIC PLANTAR AESTHESIOMETER

Cat. No. 37400

UGO BASILE
Via G. Borghi 43, 21025 COMERIO – VA- ITALY
www.ugobasile.com

OPERATION

The rat, mouse or other small rodent moves about freely in one of the compartments of the enclosure, positioned on the metal mesh surface.

After cessation of exploratory behaviour, the operator places the touch-stimulator below the target area of the animal paw, using the adjustable angled-mirror to position the filament.

Pressing START key provided at both sides of the handle of the touch-stimulator vessel, invokes the following automatic sequence:

a. an electrodynamic actuator of proprietary design lifts a straight metal filament;
b. the filament touches the plantar surface and begins to exert an upward force below the threshold of feeling;
c. the force increases (at the preset application rate), until a stop signal is attained, either the animal removing the paw or the point at which greatest preset force is met .



The actuator filament (0.5mm diameter) produces force over the entire range of all typical aesthesiometer test devices.

Paw withdrawal reflex is automatically recorded using two metrics: the latency until withdrawal, in seconds, and the force at which paw was withdrawn, in grams.

BASIC SPECIFICATIONS

Starting	: via keys on the touch-stimulator vessel
Force range	: 0 to 50.0 grams, in 0.5 g steps
Force increasing rate	: adjustable in the interval 1 to 20 seconds, in 1 s steps
Filament travel	: 12 mm
Latency time	: read-out on graphic display, in 0.1s steps
Connection to PC	: through DELTA 9-pin connector

DATA ACQUISITION

The 37400 microprocessor controlled and features direct PC output. Internally-stored data can be routed via a 9-pin D-type con-nector to the PC serial port (RS232).

Data output is managed by 52050-06 Data Acquisition Software Package (Windows® based), which enables the research worker to store the data into individual files, ready to be easily managed by most statistical analysis packages available on the market. Ask for details!

ORDERING INFORMATION

37400	DYNAMIC PLANTAR AESTHESIOMETER, complete with following standard accessories:
37400-001	Microprocessor controlled electronic unit
37400-002	Touch stimulator, complete with filament actuator and adjustable angled-mirror
37400-003	Platform with supporting columns
37400-005	Framed metal mesh
37400-006	Two-compartment animal enclosure
37400-305	Package of 10 Heat Sensitive Paper Rolls
37400-302	Instruction manual
37400-321	Set of two 0.5 mm diam. stainless-steel filaments and two calibration weights (5 & 50 g)
37400-324	4-Space Partition for Animal-Enclosure
37400-326	6-Space Partition for Animal-Enclosure
E-WP008	Mains Cord

Set of 2 fuses for either 230V or 115V operation

Physical

Power Requirements		: 115 or 230 V, 50/60 Hz 20 W max.
Dimensions:	Electronic Unit	: cm 26(w) x 13(d) x 12(h)
	Assembled Platform	: cm 50(w) x 32(d) x 40(h)
Total Weight		: Kg. 10.20
Shipping Weight		: Kg. 18.50 approx.

BIBLIOGRAPHY

- L. Ramer et alia: "Rho-Kinase Inhibition Enhances Axonal plasticity and Attenuates Cold Hyperalgesia after Dorsal Rhizotomy" J. Neuroscience, 24 (48), 10796-10805, 2004
- E. Escribano et alia: "Rapid Human Skin Permeation and Topical Anaesthetic Activity of a New Amethocaine Microemulsion" Skin Pharmacol. Physiol., 18, 294-300, 2004
- G. Villetti et alia: "Antinociceptive Activity of the N-Methyl-D-aspartate Receptor Antagonist N-(2-Indanyl)-glycinamide Hydrochloride (CHF3381) in Experimental Models of Inflammatory and Neuropathic Pain" J. Pharmacol. Exper. Therap., 306, 804-814, 2003
- M. Isabel Arévalo et alia: "Thermal Hyperalgesia and Light Touch Allodynia After Intradermal Mycobacterium butyricum Administration in Rat" Inflammation, 27 (5), 293-299, 2003

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP