



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

LS2, LS3, LS6 SHUTTER SPECIFICATIONS



Vincent Associates 803 Linden Avenue, Rochester, NY 14625
 web www.uniblitz.com e-mail vincentassociates@uniblitz.com toll-free 800.828.6972

FEATURES

- Three aperture sizes available
 2mm diameter - Model LS2
 3mm diameter - Model LS3
 6mm diameter - Model LS6
- Laser energy ratings up to 5W/mm² with "Z" or "ZM" shutter blade coating options
- Exposure repetition rates from DC - 400Hz
- Electronic synchronization available

The UNIBLITZ[®] LS series shutters are especially well suited for laser use, with applications including low level chopping, pulse gating, selection, and modulation to 400Hz. Precision exposure control in the areas of holography and microscopy are additional application that benefit from the precise, repeatable characteristics of the LS shutter series.

For information on typical laser damage thresholds see "OPTICAL" information in our "COMPARISON SPECIFICATION" sheet. For further information see our application note "LASER APPLICATION REFERENCE" sheet in the resource section of our web site, www.uniblitz.com

The LS shutter series is comprised of three models. The model LS2 features a 2mm aperture, with typical rise time of 300µsec. The LS3 and LS6 models feature a 3mm and 6mm aperture, respectively. All three styles are offered mounted in a black anodized aluminum housing, and are equipped with the electronic synchronization system. In addition to the standard housing illustrated on the opposite side, several customized microscope and video mounts are available as options for use with this series. Additional information can be found in the data sheets entitled "MICROSCOPE, VIDEO, and UNIVERSAL MOUNTING SYSTEMS".

ELECTRICAL

| | |
|---------------------------|---------|
| Coil Resistance | 48 ohms |
| Pulse Voltage to Open | +65VDC |
| Hold Voltage ¹ | +10VDC |

MECHANICAL

| | |
|---|--|
| Wgt. Cased | 7.41 oz (.211 kg) |
| Operating Temp. | 0°C to +80°C |
| Max. Opening Bounce | 15% |
| Max. Closing Bounce | 5% |
| Max. Frequency of Operation (CONT/BURST) ² | LS2: 100 Hz /400 Hz LS3: 50 Hz / 200 Hz LS6: 20 Hz /150 Hz |
| Number of Blades | LS2: 1 LS3/6: 2 |


TIMING

Typical timing values (msec.) using UNIBLITZ drive equipment and measured with UNIBLITZ shutters equipped with standard TEFLON[®] coated shutter blades.

TYPICAL PULSE INPUT TO CONTROLLER

SHUTTER STATE

TYPICAL ELECTRONIC SYNCHRONIZATION OUTPUT FROM CONTROLLER



(Timing in msec.)

| | LS2 | LS3 | LS6 |
|--|-----|-----|-----|
| O-A Delay time on opening after current is applied | 0.7 | 1.0 | 1.0 |
| A-C Transfer time on opening | 0.3 | 0.5 | 0.7 |
| O-C Total opening time | 1.0 | 1.5 | 1.7 |
| B-F Min. equivalent exp. time | 1.1 | 1.5 | 1.5 |
| C-E Min. dwell time with min. input pulse | 0.7 | 0.8 | 0.8 |
| E-G Transfer time on closing | 0.5 | 0.6 | 0.8 |
| A-G Total window time | 1.5 | 1.9 | 2.3 |

| | | | |
|-----------------------------|------|------|------|
| MET: Min. exposure time | 1.0 | 2.0 | 2.0 |
| TEP: Typical exposure pulse | >1.7 | >2.3 | >2.5 |

The question regarding enhancement of shutter speed with the application of user supplied lubricants has been repeatedly asked. It is our experience that lubricating the shutter blades will actually slow the shutter down and eventually render the shutter inoperable. UNDER NO CIRCUMSTANCES SHOULD ANY TYPE OF LUBRICANT BE APPLIED TO THE SHUTTER BLADE AREA.

PRODUCT OPTIONS

LS2 T 2 -100


| Aperture Size | Blade Finish | Housing | Mounting Options |
|-------------------------------------|--|--|---|
| LS2 - 2mm LS3 - 3mm LS6 - 6mm | T - Teflon [®] Coated S.S. Blades ZM - AlMgF2 Coated BeCu Blades* Z - AlSiO Coated BeCu Blades* | 2 - #2 Housing (Electronic Synchronization is Included). | -21 Zeiss Axiocvert Type -22 Nikon SBX type -23 Olympus BH/MT type -24 Olympus BX/IX type -26 Leica Type -27 Nikon Type -28 Olympus IX Transmitted Type -29 Nikon TE Type -30 Leica DM/DMIR/DMIRB Type -31 Nikon Confocal Type -32 Nikon 80i Type -100 Mounting Ring -105 C-Mount Adapter (Male) -106 C-Mount Adapter (Female) -110 T-Mount Adapter |

¹Voltage level required across actuator coil when being hold in the open position.

²CONTinuous frequency rating specified at shutter's minimum exposure pulse. BURST frequency rating specified for (4) four seconds maximum with (1) one minute minimum between bursts. Frequency measurements are taken in free air, 25° C ambient, actuator coil equipped with heat sink. For additional information on maximum sustained frequencies obtainable, please contact one of our technical representatives.

*Input side only, Teflon[®] coating is on opposite side. Intended to protect the shutter blade surface, light source must be input to the reflective side only.


HOUSED STYLE



NOTES:
 1. (3) 2-56 MOUNTING HOLES ON A Ø1.204 BOLT CIRCLE, 120° APART.
 (3) 2-56 MOUNTING HOLES ON A Ø1.578 BOLT CIRCLE, 120° APART.
 ALL DIMENSIONS MAXIMUM [MM] INCH

The LS #2 housing style allows a number of mounting configurations. A 1/4-20 threaded hole is provided for post mounting. The 1.625 inch x 40TPI external thread located on the rear side, and the six 2-56 threaded holes located on the front side (see Figure 1 and Figure 2) can be interfaced directly into your application or fitted with a variety of specific mounting options. See "MICROSCOPE, VIDEO and UNIVERSAL MOUNTING SYSTEMS" data sheets for additional information. The unit terminates with a 7-pin male

HOUSING/CONNECTOR LAYOUT



This drawing illustrates 7-pin connector and 1/4-20 threaded hole layout for the LS2/3/6 series #2 housed style.

Due to our ongoing product development program, Vincent Associates reserves the right to discontinue or change specifications or designs at any time, without incurring any obligations. Teflon is a registered trade mark of E.I. DuPont. U. S. Pat. No. 3,427,576; 3,595,553; 3,967,293; 6,652,165. Drawing shown for illustrative purposes only. Updated 07/2004



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com