

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

VERSALOGIC CORPORATION

CHEETAH

PC/104-*Plus* Single Board Computer



- 1.0 GHz Pentium M processor
- Extreme Graphics 2 video
- High-speed DDR RAM
- CompactFlash socket
- 10/100 Ethernet
- Extended temp. operation
- RoHS-compliant

Highlights

High-performance Processor
Pentium M 1.0 GHz performance with low power draw.

Extreme Graphics 2 Video
Very high speed rendering and MPEG-2 support.

SO-DIMM Memory Socket
Accommodates up to 1 GB of DDR RAM.

On-board I/O
Two USB 2.0 ports, two COM ports (one 232/422/485 configurable), IDE interface, LPT port, audio.

TVS Protection
Enhanced ESD resistance.

CompactFlash Socket
Removable storage device has no moving parts.

Watchdog Timer
Provides hardware-level safety control for application run-away conditions.

400 MHz processor-side bus
Improved system throughput.

Embedded BIOS
OEM embedded features. Field-upgradeable. Customization available.

PC/104-*Plus* Form Factor
Compact module is ideal for space-constrained applications.

RoHS-compliant
Meet EU Directive 2002/95/EC.

Overview

The Cheetah single board computer reaches a new level of sophistication for embedded product technology, integrating very high performance with an expanded feature set on the compact and rugged PC/104-*Plus* form factor. The advanced design of the Pentium M processor makes it suitable for a wide range of higher-end applications such as security systems, telematics, UAVs, and sophisticated communications equipment.

An impressive amount of functionality is packed into the 2-board set, including 10/100 Ethernet, two USB 2.0 ports, two COM ports, LPT, IDE, audio, and high-resolution video output. It includes a CompactFlash socket for on-board bootable media storage, TVS devices on the user I/O for enhanced ESD protection, and a watchdog timer to control application run-away conditions. The Cheetah accommodates up to 1 GB DDR system RAM in a high-retention SO-DIMM socket.

Like all VersaLogic products, this small, powerful SBC is designed to support OEM applications where high reliability and long-term availability are required. From application design-in to 5+ years production life, its quality and longevity provide a cost-effective, long-term solution. The Cheetah is manufactured and tested to the highest quality standards and is backed by a two-year limited warranty. Customization is available in as few as 100 pieces.

Details

The Cheetah's Pentium M processor provides outstanding performance of 1.0 GHz while drawing less than 12 watts of power. The processor and chipset solution relies on three separate chips: the processor, a graphics and memory controller hub that provides fast RAM access and video output, and an I/O hub that provides PCI, IDE, USB, and audio functionality.

The Extreme Graphics 2 video built into the chipset offers outputs for LVDS flat panels and analog (CRT) monitors at resolutions up to 2048 x 1536. It supports 24-bit color, very fast rendering, and MPEG-2 decoding for full motion video. Video RAM is allocated from system memory (up to 64 MB).

With two COM ports, two USB ports (2.0), 10/100 Ethernet, LPT port, and IDE interface, the Cheetah offers more I/O options than other similar-sized SBCs. In addition, PC/104 and PC/104-*Plus* connectors provide support for many off-the-shelf expansion boards for added system functionality with minimal space requirements. The Cheetah also includes a number of reliability-enhancing features such as a watchdog timer and TVS devices.

VERSALOGIC CORPORATION


RoHS

VersaLogic Corporation • 4211 West 11th Ave., Eugene, OR 97402 • (541) 485-8575 • Fax (541) 485-5712 • info@VersaLogic.com • www.VersaLogic.com

CHEETAH

PC/104-*Plus* Single Board Computer

The Cheetah features a General Software Embedded BIOS with OEM enhancements. The field-reprogrammable BIOS supports custom defaults and CMOS settings. Optional firmware and firmbase applications for security processes, remote booting, and other pre-OS software functions are supported. The Cheetah is compatible with a variety of popular operating systems, including Windows, QNX, VxWorks, and Linux.



Ordering Information

VL-EPM-32t ..... Intel Pentium M 1.0 GHz, Extended Temp. (RoHS)

Accessories

VL-CBR-0501 ..... USB transition cable (RoHS)*
VL-CBR-0803 ..... Audio cable, stereo in/out (RoHS)*
VL-CBR-1008 ..... ATX power adapter cable (RoHS)*
VL-CBR-1201 ..... SVGA connector cable (RoHS)*
VL-CBR-2010 ..... LVDS Cable, HIROSE style (RoHS)
VL-CBR-2011 ..... LVDS Cable, JAE style (RoHS)
VL-CBR-2501 ..... Floppy connector converter (RoHS)
VL-CBR-4405 ..... 2 mm to 0.1" IDE adapter (RoHS)*
VL-CBR-4406 ..... 2.5" IDE drive cable (RoHS)*
VL-CBR-8001 ..... Primary user I/O breakout cable (RoHS)*
VL-CKR-CHEE ..... Development cable kit (RoHS)
VL-CDD-IDE1 ..... IDE CD-RW, DVD-ROM drive
VL-CFM-xxx ..... CompactFlash module
VL-CF-CLIP1 ..... CompactFlash retention clip
VL-ENCL-4 ..... VersaTainer Ruggedized enclosure
VL-ENCL-5 ..... Development enclosure
VL-FDD-144U ..... USB floppy drive
VL-HDD35-xxx ..... 3.5" IDE hard drive
VL-HDW-101 ..... Mounting standoffs, metric thread*
VL-MM5D-xxx ..... DDR RAM module
VL-DEV-CD-L2 ..... Debian Linux Board Support Package

** Included in VL-CKR-CHEE cable kit*

Specifications

General	Processor	Intel Pentium M
	Chipset	855GME
	Power Requirements	+5.0V only: 12W (EPM-32t)
	System Reset	Watchdog timeout VCC sensing (resets below 4.70V typ.)
	Bus Speed	CPU PSB: 400 MHz PCI, PC/104-*Plus*: 33 MHz PC/104: 8 MHz
	Compatibility	PC/104: footprint compatible. PC/104-*Plus*: supports 3.3V PCI signaling (2.2 compliant).
Mechanical	Board Size	Dual board set, 3.55" x 3.78" (90 mm x 96 mm) with 0.2" (5 mm) overhangs in the designated connector areas.
	Storage Temperature	-40° to +85°C
	Operating Temperature	-40° to +85°C (EPM-32t)
	Vibration, Sinusoidal Sweep	2g constant acceleration from 5 to 500Hz, 20 minutes per axis, MIL-STD-202G, Method 204, Modified Condition A
	Vibration, Random	$.02g^2$/Hz (5.35g rms), 15 minutes per axis, MIL-STD-202G, Method 214A, Condition A
	Mechanical Shock	30g half-sine, 11 ms duration per axis, MIL-STD-202G, Method 213B, Condition J
	Humidity	Less than 95%, noncondensing.
Memory	System RAM Interface	One 200-pin SO-DIMM socket. Up to 1 GB of 266 MHz PC2100 or 333 MHz PC2700 compatible DDR RAM.
	Flash Interface	CompactFlash socket (type I or II) with DMA support.
Video	General	Extreme Graphics 2 chip set. Uses up to 64 MB system memory. Full motion video, MPEG-2 decoder, 3-D, edge smoothing and ultra-fast rendering.
	Desktop Display Interface*	Standard analog display interface supports 24-bit color and resolutions up to 2048 x 1536.
	OEM Flat Panel Interface	LVDS flat panel interface supports 24-bit color and resolutions up to 1024 x 768.
Network Interface	Ethernet*	10/100 Ethernet port. Auto-detect.
	Network Boot Option	Argon Managed Boot Agent. Supports PXE, RPL, NetWare, TCP/IP (DHCP, BOOTP) remote boot protocols.
Device I/O	USB*‡	Two ports USB 2.0/1.1 protocol.
	IDE Interface	Single channel PCI-based. Up to 2 IDE devices. ATA 100 compatible. (CompactFlash is on a separate channel)
	COM 1 Interface*	RS-232, 16C550 compatible. 115K baud max.
	COM 2 Interface*	RS-232/422/485,16C550 compatible, 460K baud max.
	LPT Interface*	Bi-directional/EPP/ECP/floppy mode compatible.
	Audio	AC'97 PCI compatible. Stereo line in. Stereo line out.
	Other*	Keyboard and PS/2 mouse port.
Software	Operating Systems	Compatible with most x86 operating systems, including WinCE/XP/XPe, QNX, VxWorks, and Linux.
	BIOS	General Software's Embedded BIOS with OEM Enhancements. Field reprogrammable. Support for USB keyboard/mouse and USB boot.

**TVS protected port (Enhanced ESD protection).*
‡ Power pins on this port are protected with a self-resetting fuse.

Data represents standard operation at 25°C with 5.0V supply unless otherwise noted. Specifications are subject to change without notice. PC/104 is a trademark of the PC/104 Consortium.

06-08-10

VersaLogic Corporation • 4211 West 11th Ave., Eugene, OR 97402 • (541) 485-8575 • Fax (541) 485-5712 • info@VersaLogic.com • www.VersaLogic.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP