ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Versalogic VCM-DAS-2* at our website: ***Click HERE***

VCM-DAS-1

PC/104 Data Acquisition & Control Module

100 kHz Analog Input, Analog Output and Digital I/O Module.



Analog Input

- **16 channels**
- **16-bit input resolution**
- **Single ended, high impedance inputs**
- **Electronic digital calibration**
- **Up to 100K samples/second**
- **±5V and ±10V input ranges**
- **On board timer for periodic readings**
- **Auto retrigger mode**
- **Auto Channel Increment Mode**
- **DMA support**
- **Compatible with industry standard 5B01 series signal conditioners**

Analog Output

- **2 channels**
- **12-bit resolution**
- **Electronic digital calibration**
- **0-5V and 0-10V output range**
- **40 µS update time**
- **Short circuit proof, 5 ma output current**

Digital I/O

- **Two 8-bit ports**
- **±24 ma output drive**
- **Programmable read-only or read/write**
- **Opto 22 compatible**
- **EEPROM storage for user data**

Description

The VCM-DAS-1 module provides a combination of analog I/O, digital I/O, and non-volatile storage, which makes it ideal for data acquisition and control applications. All of its functions are provided on a single 3.8 x 3.6" PC/104 module.

The analog input section features 16 single-ended input channels with 16-bit resolution, fast 10 µS conversion, and a ±5V or ±10V input range (153µV or 305µV resolution). Throughput of up to 100 kHz may be realized with conversions on one channel and up to 67 kHz when scanning between channels. A variety of automatic channel scanning and triggering modes are available, including DMA support.

The analog output section includes two 12-bit analog output channels. Each may be jumpered independently for 0-5V or 0-10V output.

Both sections feature simplified calibration using programmable digital pots. In addition, the on-board EEPROM which is used to store the calibration values has free space available for user data. The digital pots power up and reset to mid-scale, and can be set to any calibration value during system initialization.

VERSALOGIC CORPORATION

3888 Stewart Road, Eugene, OR 97402 • (541) 485-8575 • Fax (541) 485-5712 • info@versalogic.com • www.versalogic.com

VCM-DAS-1

100 kHz 16-bit Data Acquisition & Control Module

The digital I/O section provides 16 digital I/O lines which feature high current TTL drivers. The two 8-bit ports are byte configurable as inputs only or outputs with readback. The digital interface is plug compatible with Opto 22 type modular I/O racks.

Software Support

Complete C Language source code drivers are included. Also includes DOS-based diagnostic and calibration routines.

Ordering Information

VCM-DAS-1 . . . . . 100 kHz Analog I/O Module
VL-HDW-100. . . . . Standoff Pkg. English Thread
VL-HDW-101. . . . . Standoff Pkg. Metric Thread
VL-CBL-2602. . . . . 1.5' 26-pin/26-pin socket

Specifications

Specifications are typical at 25°C with 5.0V and ±12.0V supplies unless otherwise noted.

Board Size:
3.8" x 3.6" (PC/104 standard)
0.6" component height
Storage Temperature:
–40°C to 85°C
Free Air Operating Temperature:
0°C to +60°C
Power Requirements:
+5V @ 510 ma typical
±12V @ ±20 ma typical
Analog Input:
Channels: 16 channels
Resolution: 16 bits, no missing codes
Accuracy: ±0.003% (±3 LSBs)
Input Mode: Single ended
Range: ±5V or ±10V (jumper selectable, all channels the same)
Conversion Time: 10 µS
Settling Time: 5 µS (applies only when switching channels)
Protection: ±35V overvoltage protection
Impedance: $>10^{10}\Omega$, 20pF
Retrigger Timer: Programmable 20 µS, 50 µS, 100 µS, 250 µS, 500 µS, 1 mS
Interrupt Channel: IRQ 10, 11, or 12
DMA Channel: DMA 5, 6, or 7
Analog Output:
Channels: 2 channels
Range: 0 to 5V or 0 to 10V (jumper selectable, each channel independent)
Resolution: 12 bits
Accuracy: ±1.5 LSB
Update/Settling Time: 40 µS
Output Drive: 5 ma, 200 pF (each channel)
Access: Bitwise serial
Digital I/O:
Channels: 16 (non-inverting)
Input Threshold: TTL compatible
Output Drive (H): –24 ma @ 2.4V
Output Drive (L): +24 ma @ 0.55V
Signal Direction: Byte programmable as input or output with readback
Short Protection: Short circuit to ground, indefinite duration
I/O Interface: Occupies 16 ports on any 16-bit boundary
EEPROM:
Organization: Sixty-four 16-bit words
Allocation: Two words used for digital pots, 62 words available for general purpose storage
Access: Bitwise serial
External Connectors:
Analog In/Out: 26-pin .1" header
Opto 22: 34-pin .1" header
Compatibility:
PC/104: Full compliance, 16-bit data bus

Specifications are subject to change without notice. PC/104 and the PC/104 logo are trademarks of the PC/104 Consortium.

VERSALOGIC CORPORATION

3888 Stewart Road, Eugene, OR 97402 • (541) 485-8575 • Fax (541) 485-5712 • info@versalogic.com • www.versalogic.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP