



Artisan Scientific

QUALITY INSTRUMENTATION ... GUARANTEED

Looking for more information?

Visit us on the web at <http://www.artisan-scientific.com> for more information:

- Price Quotations
- Drivers
- Technical Specifications, Manuals and Documentation

Artisan Scientific is Your Source for Quality New and Certified-Used/Pre-owned Equipment

- Tens of Thousands of In-Stock Items
- Hundreds of Manufacturers Supported
- Fast Shipping and Delivery
- Leasing / Monthly Rentals
- Equipment Demos
- Consignment

Service Center Repairs

Experienced Engineers and Technicians on staff in our State-of-the-art Full-Service In-House Service Center Facility

InstraView™ Remote Inspection

Remotely inspect equipment before purchasing with our Innovative InstraView™ website at <http://www.instraview.com>

We buy used equipment! We also offer credit for Buy-Backs and Trade-Ins

Sell your excess, underutilized, and idle used equipment. Contact one of our Customer Service Representatives today!

Talk to a live person: 888-88-SOURCE (888-887-6872) | Contact us by email: sales@artisan-scientific.com | Visit our website: <http://www.artisan-scientific.com>

PBTM-315 PMC - PCI Bus Analyzer

Specifications

[PCI Analysis](#) [Anomaly Timing Exerciser](#) [Products](#) [Support](#) [Applications](#) [HOME](#)

[PMC Analyzer](#) [PCI Analyzer](#)

Trace Memory:	64K x 128 bits (Model B) 256K x 128 bits (Model C)
Input channels:	91 PCI signals, plus 8 ext. inputs on pin header.
PCI clock requirements:	Max. 33MHz, min. 20MHz, Min. 5ns low or high pulse width. 1ms PLL lock time.
PCI signal levels:	5V or 3.3V
PCI loading:	Max. 10pF (One load + max 1.5"/3.8cm of trace length). Satisfies PCI specifications.
PCI signals:	AD[31::0], AD[63::32], C/BE[3::0]#, C/BE[7::4]#, FRAME#, TRDY#, IRDY#, STOP#, DEVSEL#, PAR, PAR64, PERR#, SERR#, RST#, SDONE, SBO#, INTA#, INTB#, INTC#, INTD#, LOCK#, ACK64#, REQ64#. (Plus GNT3:0#, REQ3:0#, IDSEL via pin headers).
Trigger:	4 word recognizers covering all 91PCI signals and 8 Ext. inputs. RANGE & NOT operator on Address/Data.
Range:	Four A64/A32 address ranges, Four D32 data ranges. Inside/Outside.
Sequencer:	16 levels with If, Else, Elsif, Goto, Count, Delay, Trigger, Store, Sampling mode, Halt.
Trigger position:	0%, 25%, 50%, 75%, 100%
Occurrence counters:	Four 20-bits (in Sequencer).
Delay counters:	Three 20-bits (in Sequencer).
Event counters:	Four 20-bits (for Statistics).
Time Tag: Range:	30ns-2hrs15m@33MHz
Resolution:	30ns@33MHz
Latency Tag:	Counts latency (wait states) from FRAME# to TRDY# asserted. Max count: 128clks.
Trigger Output:	TTL level trigger output with programmable polarity, level or pulse. May pulse on each stored sample. Available on pin header on front panel.
External Inputs:	Eight TTL level inputs on pin header on front panel.
Processor:	MC68EC020 16,67 MHz 512KByte RAM w/battery backup for Setup 512KByte Flash EPROM, Up to 64KByte UV EPROM. Storage.
Interfaces:	Two RS232C serial ports, both in one micro-DB9 female connector. Converter to standard DB9 included.

Baud rates: 1200-38400b/s, aut. adjusted.

Power supply requirements : +5VDC +/-5% from PMC host or from ext. power supply via front panel inlet.
Current: 1,3A typ. idle, 2,5A typ. sampling @ 33MHz.

Dimensions: 74.0 x 149.0mm
(Single-wide PMC card).

Compatibility: PCI Rev. 2.1

WARRANTY All VMETRO analyzer products have one year warranty.

Specifications subject to change without notice. V1.96



Artisan Scientific

QUALITY INSTRUMENTATION ... GUARANTEED

Looking for more information?

Visit us on the web at <http://www.artisan-scientific.com> for more information:

- Price Quotations
- Drivers
- Technical Specifications, Manuals and Documentation

Artisan Scientific is Your Source for Quality New and Certified-Used/Pre-owned Equipment

- Tens of Thousands of In-Stock Items
- Hundreds of Manufacturers Supported
- Fast Shipping and Delivery
- Leasing / Monthly Rentals
- Equipment Demos
- Consignment

Service Center Repairs

Experienced Engineers and Technicians on staff in our State-of-the-art Full-Service In-House Service Center Facility

InstraView™ Remote Inspection

Remotely inspect equipment before purchasing with our Innovative InstraView™ website at <http://www.instraview.com>

We buy used equipment! We also offer credit for Buy-Backs and Trade-Ins

Sell your excess, underutilized, and idle used equipment. Contact one of our Customer Service Representatives today!

Talk to a live person: 888-88-SOURCE (888-887-6872) | Contact us by email: sales@artisan-scientific.com | Visit our website: <http://www.artisan-scientific.com>