ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Abaco Systems / VMIC VMIVME-Repeat S-485/32* at our website: *Click HERE*

VMIVME-REPEAT L-485
Long-Line VMEbus Repeater Link


- Differential line drivers and receivers provide ±7 V noise rejection
- Software transparent link
- Supports up to 2,000-foot cables
- Supports all seven interrupt levels
- Allows expansion to 19 x 19 slots using 20-slot backplanes in a star configuration
- Supports 8- and 16-bit data transfers
- Supports 16- and 24-bit addressing
- Double Eurocard form factor
- Link includes one model REPEAT M-485, one model REPEAT S-485, and a wide variety of cable length options
- DIN-type I/O connectors
- Supports VMEbus slaves on a "slave-only" VMEbus

REPEATER LINK OVERVIEW — The VMIC Repeater Link is a two-board set which allows VMEbus slave I/O boards residing in one VMEbus chassis to be controlled by a VMEbus master residing in another chassis. The VMEbus chassis in which VMEbus masters reside is referred to as a master chassis, while the VMEbus slave boards reside in a slave chassis. The two-board set is configured as shown in Figure 1 with one board designated for the master chassis while the other board is designated for the slave chassis. A master VMEbus chassis can communicate with several slave chassis by using multiple Repeater Links as shown in Figure 2.

The REPEATER Link supports all seven interrupt levels. Interrupts are acknowledged by the IACKIN*/IACKOUT* daisy chain which is routed through all of the slave chassis slots before going on to the next VMEbus master chassis slot, as shown in Figures 3 and 4. This design concept allows any slave board mounted in a slave chassis to generate an interrupt.

SPECIFICATIONS

- Maximum cable length 2,000 ft
- Supports 8- and 16-bit data transfers
- Supports 16- and 24-bit addressing
- Supports all seven interrupt levels
- Propagation delay is approximately 400 ns with 5-foot cables (add 4 ns per foot for longer cables)
- Supports bus slaves and interrupters in slave chassis
- Allows expansion to 19 x 19 slots using 20-slot backplanes in a star expansion configuration
- DIN format connectors (optional keying capability)
- Inexpensive ribbon-cable interconnects
- Double Eurocard form factor



- The VMIVME-Repeat S-485 board must be installed in slot 1 of the VMEbus slave chassis

PHYSICAL/ENVIRONMENTAL

Temperature Range: 0 to 55 °C, operating
-20 to 85 °C, storage

Relative Humidity Range: 20 to 80 percent, noncondensing

Cooling: Convection

Power Requirements: +5 V at 2.5 A (maximum) - REPEAT M-485
+5 V at 2.0 A (maximum) - REPEAT S-485

Ordering Options

October 28, 1994 800-00RL85-000 B

VMIVME-REPEAT L-485

Cable Requirements

The VMIVME-REPEAT L-485 requires two cables each. Cables may be ordered from VMIC according to the following model numbers.

Item	Description	Model Number
1.	Cable Assembly - 5 ft	VMIVME-000-64-005
2.	Cable Assembly -10 ft	VMIVME-000-64-010
3.	Cable Assembly - 25 ft	VMIVME-000-64-025
4.	Cable Assembly - 50 ft	VMIVME-000-64-050
5.	Cable Assembly -100 ft	VMIVME-000-64-100
6.	Cable Assembly -150 ft	VMIVME-000-64-150
7.	Cable Assembly - 200 ft	VMIVME-000-64-200
8.	Cable Assembly -250 ft	VMIVME-000-64-250

Connector Data

Compatible Connector	120-964-435E
Strain Relief	100-000-032
PC Board Connector	120-964-033A

For Ordering Information, Call:
1-800-322-3616 or 1-256-880-0444 • FAX (256) 882-0859
E-mail: info@vmic.com Web Address: www.vmic.com
Copyright © January 1986 by VMIC
Specifications subject to change without notice.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

The VMIVME-REPEAT Link regenerates the following VMEbus signals:

D00 to D15LWORD*
A01 to A23IACK*
DS0* IACKOUT*
DS1*SYSFAIL*
AS*BERR*
AM0 to AM5DTACK*
WRITE*IRQ1* to IRQ7*
SYSRESET*GND
SYSCLKIACKIN* (see Note)

Note: IACKIN is daisy chained through the slave chassis and back to the master bus.

TRADEMARKS

The VMIC logo is a registered trademark of VMIC. Other registered trademarks are the property of their respective owners.




Figure 1. Typical VMEbus Configuration Using the VMIC VMIVME-Repeater Link

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com




Figure 2. Multiple Slave I/O Chassis





Figure 3. Interrupt Daisy Chain Structure

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Install wire jumper between P1, A22 and P1, B22 if an interrupter resides in the last slot of the chassis. Install a jumper between P1, A21 and P1, B22 if an interrupter is not present.

Figure 4. Interrupt Configuration Jumpers

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP