



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)

## VT6065-4 4-channel C-size Serial Interface Module VT6065-8 8-channel C-size Serial Interface Module

### Overview

The VT6065 is a C-size VXIbus compatible serial interface module, available in four or eight channels, and is an ideal general purpose serial communications module for applications with baud rates under 125 kbaud. For applications that require faster baud rates, DLC protocols or custom serial interfaces, the VM6068 module should be considered.

### Configuration

The VT6065 is available in two versions: Model VT6065-4 4-channel and Model VT6065-8 8-channel. Each individual channel can be configured under software control to be an RS-232, RS-422, RS-423 or RS-485 interface. Any combination of interface standards can be user-configured on the same card without opening the unit.

Software handshaking (XON/XOFF) or hardware handshaking with RTS/CTS is selectable under program control. Data Terminal Ready (DTR)/Data Set Ready (DSR) control lines are also provided.

In addition, each individual channel can be looped back on itself at the line driver/receiver level under program control in order to perform a full self test of the Model VT6065.

### Software Control

The Model VT6065 is a message-based module that can accommodate transmitting and receiving on all eight channels simultaneously.

All key protocol parameters (baud rate, word length, parity checking and handshaking) are software-programmable on each channel. The baud rate is programmable to standard and custom baud rates up to 125 kbaud. The VT6065 supports baud rates to 38400 with no "dead" time. These configurations can then be stored in non-volatile memory for added flexibility and ease of setup. Device-dependent commands meet Standard Commands for Programmable Instruments (SCPI) specifications.

### Flexible Memory Eases Data Throughput

512 kB of transmit and receive memory may be allocated by user among the eight channels, allowing complete flexibility for all interface applications. Transmit buffers can be unloaded under program control in either a repetitive loop mode controlled by an internal timer or in a burst mode.

Each receive buffer is supported by a programmable input buffer to prevent overflow conditions.



## Features

Single-slot VXIbus Module  
Message-based Control

Four or Eight Serial Interface  
Channels Configurable as  
RS-232, RS-422, RS-423, or RS-485

512 kB of Memory can be Allocated  
to Input and Output Buffers

Programmable to any Baud Rate  
from 1.7 Baud to 125 kBaud

Ideal for Interfacing the VXIbus  
to Other Peripherals

Easy SCPI Software Setup and  
Control

## VT6065-4 4-channel C-size Serial Interface Module VT6065-8 8-channel C-size Serial Interface Module

### Specifications

<b>Buffer Size:</b>	512 kB input and/or output
<b>Serial Port Baud Rate (Programmable):</b>	From 1.7 baud to 125 kbaud
<b>Minimum Receive Jitter Tolerance:</b>	±4.5%
<b>Data Length:</b>	5, 6, 7, 8
<b>Parity:</b>	None, odd, even, and mark or space
<b>Stop Bits:</b>	1, 2
<b>Handshaking:</b>	
Software	XON/XOFF
Hardware	DSR and CTS for output pacing
<b>Power Requirements (Ipm):</b>	
+5 V	2 A
±12 V	100 mA
±24 V	200 mA
<b>Weight:</b>	2.20 lb (1 kg)
<b>Dimensions:</b>	Single-slot, C-size
<b>VXIbus:</b>	Message-based , Revision 1.4

### Ordering Information

<b>VT6065 - 4</b>	4-channel Serial Interface Module
<b>VT6065 - 8</b>	8-channel Serial Interface Module

VT6065-4/6065-8



## Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

### SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

### *InstraView*<sup>SM</sup> REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at [www.instraview.com](http://www.instraview.com) ↗

### WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. [www.artisanng.com/WeBuyEquipment](http://www.artisanng.com/WeBuyEquipment) ↗

### LOOKING FOR MORE INFORMATION?

Visit us on the web at [www.artisanng.com](http://www.artisanng.com) ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

**Contact us:** (888) 88-SOURCE | [sales@artisanng.com](mailto:sales@artisanng.com) | [www.artisanng.com](http://www.artisanng.com)