

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Thermometers,Digital
General-Purpose

VWR®Total-Range Digital Thermometer



Fast-reading, easy-to-use thermometer switches from °C to °F at the touchof abutton. Largedisplaywith1.6cm (5/8") highdigits is legible from3m (10') away. Backlightingbutton permits reading indark areas. Unit features a holdbutton that captures current reading.Microprocessor updates display twiceper second.

Thermometer recallsminimum andmaximum readings from any timeperiod. Alarm function may beprogrammed in1° increments to sound when temperature rises above or falls below set points. Count-up timer alarmmay be set from23hours, 59minutes, to1minute. Unit is constructedof shock-resistant ABS plastic.Water-resistant PVCprotective case stops water, fumes, dirt, anddust. Uses all Type-K thermocoupleprobes. Batteries power unit for one year of routine use.

All Type-Kprobesmay be usedwith liquids, air/gas, and semi-solids. Stainless steel probe has a22.9cm (9") stemwith a3mm (1/8") diameter and a102cm (40 1/8") cable. Beadedprobe is 1.5mm (1/16") indiameter and features a1.2m (4') fluoropolymer resin cable. The low-temperature stainless steel probe has adiameter of 4.3mm (3/16") and features a30.5cm (12") stemwith a12.7cm (5") handle. Low-temperature probe is suppliedwith a2.4m (8') expandable cable.

A serial numbered certificate is provided from an ISO17025 calibration laboratory accreditedbyA2LA to indicate thermometer traceability to standards providedby the National Institute of Standards and Technology.

Ordering Information: Suppliedwith aPVCprotective casingwithflip-out stand, a fast-response Type-Kbeadedprobe (61161-372), and threeAAA alkalinebatteries.

Cable Length	1.2m (4')
Dimensions	8.3W x 17.8H x 3.8D cm (3 1/4 x 7 x 1 1/2")
TemperatureAccuracy	±1°C from –50 to 740°C, ±2°C at ends of range
Temp. atureResolution	0.1° from –199.9° to 1369.9°C (–327.8 to 2497.8°F), 1° rest of range
Weight	0.2 kg (0.5 lbs.)

Description	Range	Cat.No.	Price
Total-RangeDigital Thermometer	–200 to1370°C (–328 to2498°F) whenusedwithappropriateprobe	23609-232	Ea.

Accessories

Description	Cat.No.	Price
Low-TemperatureType-KProbe	23609-238	Ea.
Beaded, FastResponse Type-KProbe	61161-372	Ea.
High-TemperatureType-KProbe	77776-728	Ea.
StainlessSteel Type-KProbe	61161-281	Ea.

VWR®Traceable ™ Big-Digit Thermometer



Use outdoors and in storerooms, fume hoods, labs, cleanrooms, refrigerators, andplant areas. Thermometermay be attached to the outside of awindow to viewoutdoor temperatures. Features a transparent displaywith3.2cm (1 1/4") highdigits to show current andminimum/maximum temperatures, which are automatically cleared andupdateddaily.

A serial-numbered certificate is provided from an ISO17025 calibration laboratory accreditedbyA2LA to indicate traceability to standards providedby theNational Institute of Standards and Technology.

Ordering Information: Suppliedwithmounting tape, pre-cut Velcro® squares, andAAAbattery.

Accuracy	±1°C
Resolution	0.1°
W xH xD	8.9 x 10.8 x 1.9 cm (3 1/2 x 4 1/4 x 3/4")
Weight	227 g (8 oz.)

Range	Cat.No.	Price
–25 to70°C	36934-158	Ea.

VWR®Traceable®Big-Digit Type-KThermometer



Wide-range thermometer has shock-resistant ABS plastic casing. Features include °Cor °F display,maximum temperature recall, andholdbutton to capture current reading. Themicroprocessor updates thedisplay 2.5 times per second. The 1.6cm (5/8") digits are readable from4.6m (15').

A serial numbered certificate is provided from an ISO17025 calibration laboratory accreditedbyA2LA to indicate instrument traceability to standards providedby theNational Institute of Standards and Technology.

Ordering Information: Suppliedwith9-volt battery, carrying case, and fast-response type-Kbeadedprobewith1.2m (4') cable. See the 61161-372 series for other type-Kprobes.

Dimensions	7.6 x 18.4 x 3.2 cm (3 x 7 1/4 x 1 1/4")
Meter Accuracy	±0.3% of reading plus 1°C (2°F) from –50 to 1000°C (–58 to 1832°F), ±0.5% of reading plus 1°C (2°F) above 1000°C (1832°F)
Resolution	0.1° from –200 to 650°C, 0.1° from –328 to 999°F, 1° for all other temperatures
Weight	198.5 g (7 oz.)

Range	Cat.No.	Price
–50 to1300°C (–58 to2372°F)	89094-740	Ea.

VWR®Traceable ™ KangarooThermometer



Easy-to-use, portable unit automatically captures and recallsminimum andmaximum temperature readings over any periodof time. The high/low alarm canbeprogrammed in1° increments and sounds everyminute until the temperature returns tonon-alarm conditions. The hold button freezes thedisplay to record a current reading. Unit features largedigital displaywith1.9cm (3/4") digits that are readable from6m (20') away. Unit includes stainless steel probewith106.7cm (42") cable that canbe stored in rear reel-compartment pouch. Theprobe canbe used in most chemicals.

A serial numbered certificate is provided from an ISO17025 calibration laboratory accreditedbyA2LA to indicate instrument traceability to standards providedby theNational Institute of Standards and Technology.

Ordering Information: Suppliedwith silver-oxidebattery that runs continuously for one year.

Accuracy	±1°C between –30 to 250°C, ±2°C rest of range
ProbeDimensions	19.1L x 0.4dia. cm (7 1/2 x 5/32")
Resolution	0.1° between –19.9 to 199.9°, 1° rest of range

Continuedonnextpage

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP