

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Printed from VWR Website
User: [Anonymous]
Date: 09-13-2021 Time: 16:53

VWR® Traceable® Bench/Portable Conductivity Meter









Designed to measure conductivity in water analysis, biology, chromatography, food, electronics, dairies, and PC-board rinsing, the conductivity meter provides results in conductivity (micromhos/cm and microsiemens/cm), resistivity (megohms), and dissolved solids (parts per million).

- Traceable®

The tough, chemical-resistant ABS housing withstands the harshest environments. The 12.7 mm (1/2") high 4-digit LCD readout shows temperature in °C or °F. Recorder jack allows continuous monitoring and a permanent record. The epoxy conductivity probe has a range of 1.0–200000 Micromhos.

Certifications: Meets all accreditation requirements and U.S. Government specifications. Measures reagent grade water for CAP, ASTM, NCCLS, and ACS. A serial numbered certificate is provided from an ISO 17025 calibration laboratory to indicate instrument traceability to standards provided by the National Institute of Standards and Technology.

Ordering information: Unit complete with glass probe and 9 V alkaline battery.

SPECIFICATIONS

Accuracy	0.3%
Temperature Range	–30.0 to 130.0°C (–22 to 266°F)
Probe Dimensions	1.27 dia. x 13.3L cm ($^{1}/_{2}$ x $5^{1}/_{4}$")
Weight	453.6 g (16 oz.)
Dimensions	9.5L x 3.8D x 17.1H cm ($3^{3}/_{4}$ x $1^{1}/_{2}$ x $6^{3}/_{4}$")
Conductivity Range	0.01–20 µS, 0.1–200 µS, 1–2000 µS, 10–20,000 µS, 100–200,000 µS, 0.001–2 megohms, 0.01–20 megohms, 0.1–20 ppm dissolved solids, 1–200 ppm dissolved solids, 10–2000 ppm dissolved solids, 100–20,000 ppm dissolved solids

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP