ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *VX Instruments A5710* at our website: ***Click HERE***

A5710
AC Current Source

VXI instruments
the test solutions provider



TECHNICAL DATA SHEET

PXI
VXI
LAN
cPCI
PXIe
GPIB
USB
RS232
485
external
PCIe

Features

- Modern switching technology
- Output current up to 1,600 A_{eff}
- Variable output frequency between 45 and 65 Hz (option FREQ)
- Continous data acquisition (option DAQ)
- Readback of output current (option MEAS)
- Digital regulation loop with the integrated digital processing unit
- Digital calibration

Product Information

The A5710 AC Current Source is a high current AC source in a 3U 19" chassis.

In combination with a separate special power supply (3U 19") the A5710 supplies currents up to 1,600 A_{eff}.

Benefits of modern switching technology:

- Much lower power dissipation
- Much lower heat generation
- Much lower weight and size
- Much lower fan noise

Various output ratings available

This AC current source is available with output currents from 125 A_{eff} to 1,600 A_{eff}. With the option FREQ the output sine frequency is programmable between 45 and 65 Hz. The maximum output voltage depends on the device variant.

Digital signal processing unit


The A5710 contains a digital signal processing unit which provides the following advantages:

- Digital current regulation guarantees stable regulation even with long load-lines
- Open circuit detection provides high operation security
- Continous current sampling for waveform recording (option DAQ)

Controller interface

The A5710 is equipped with a GPIB interface.

Ordering Option	Comment
Option FREQ	Frequency changeable (45 ... 65 Hz)
Option MEAS	RMS output-current measurement
Option DAQ	Data acquisition for waveform recording
Option RMK	19" rack mounting kit



General	Specification	Comment
AC line voltage	230 V_{AC} ±10%	
AC line frequency	47 Hz ... 53 Hz	
Power consumption	<(50 W + up to 4,000 W)	A5710 + external power supply
Operating temperature	0 ... 40°C	
Operating altitude	<2,000 m	
Relative Humidity	Up to 85% at 35°C	
Storage temperature range	-25 ... 70°C	
Electrical safety	According EN61010-1	
Isolation output to PE	50 V CAT I, Pollution Degree 2	

Device Specification	A5710-125-17V0	A5710-160-3V0	A5710-200-11V0
Output Ratings Output current (RMS) Output voltage (Peak)	 1 ... 125 A_{eff} 17.0 V, 1 Phase AC	 2 ... 160 A_{eff} 3.0 V, 1 Phase AC	 5 ... 200 A_{eff} 11.0 V, 1 Phase AC
Output frequency	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)
Output current gain error	<1% of full scale	<1% of full scale	<1% of full scale
Measurement gain error	<1% of full scale	<1% of full scale	<1% of full scale
Size (+ext. power supply)	19" 12U	19" 6U	19" 12U
Weight (+ext. power supply)	≈65 kg	≈42 kg	≈65 kg

Device Specification	A5710-250-2V5	A5710-400-2V0
Output Ratings Output current (RMS) Output voltage (Peak)	 5 ... 250 A_{eff} 2.5 V, 1 Phase AC	 10 ... 400 A_{eff} 2.0 V, 1 Phase AC
Output frequency	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)
Output current gain error	<1% of full scale	<1% of full scale
Measurement gain error	<1% of full scale	<1% of full scale
Size (+ext. power supply)	19" 6U	19" 6U
Weight (+ext. power supply)	≈44 kg	≈46 kg

Notes: All product data are specified for 1 year at an ambient temperature of 23°C ±5°C (after 1 hour warm-up time).
Product specification and description in this document are subject to change without notice.

Device Specification	A5710-630-1V5	A5710-630-3V5	A5710-630-5V0
Output Ratings Output current (RMS) Output voltage (Peak)	 20 ... 630 A_{eff} 1.5 V, 1 Phase AC	 20 ... 630 A_{eff} 3.5 V, 1 Phase AC	 20 ... 630 A_{eff} 5.0 V, 1 Phase AC
Output frequency	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)
Output current gain error	<1% of full scale	<1% of full scale	<1% of full scale
Measurement gain error	<1% of full scale	<1% of full scale	<1% of full scale
Size (+ext. power supply)	19" 6U	19" 12U	19" 12U
Weight (+ext. power supply)	≈50 kg	≈85 kg	≈87 kg

Device Specification	A5710-1600-1V0	A5710-1600-2V0
Output Ratings Output current (RMS) Output voltage (Peak)	 40 ... 1,600 A_{eff} 1.0 V, 1 Phase AC	 40 ... 1,600 A_{eff} 2.0 V, 1 Phase AC
Output frequency	50 Hz (45 ... 65 Hz optional)	50 Hz (45 ... 65 Hz optional)
Output current gain error	<1% of full scale	<1% of full scale
Measurement gain error	<1% of full scale	<1% of full scale
Size (+ext. power supply)	19" 6U	19" 12U
Weight (+ext. power supply)	≈60 kg	≈80 kg

VX Instruments GmbH
Phone: +49 871 93 15 55-0
E-Mail: sales@vxinstruments.com

Revision Date: 2018-01-10

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP