ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *VX Instruments AXR7510* at our website: ***Click HERE***

AXR7510
Relay Switching Unit

VXI instruments
the test solutions provider



TECHNICAL DATA SHEET

PXI
VXI
LAN
cPCI
PXIe
GPIB
USB
RS232 485
external PCIe

Features

- Flexible relay switching unit allows powerful and flexible signal routing
- Currents up to 2,000 A (pulse)
- Voltages up to 3,000 V
- High density cards with up to 96 relays
- Various interfaces available (LAN, USB, GPIB)
- Highly reliable operation due to optical data interface

Product Information

The AXR7510 is a powerful switching unit. It allows flexible signal routing from any instrument pin to any DUT pin.

The AXR7510 Relay Switching Unit consists of two separate parts. The first unit (interface) is for communication via GPIB, USB or LAN.

The second part contains the matrix cards and is connected to the interface unit via fiber. This guarantees a high data transfer security even on high pulse currents within the matrix.

High Current Relay Cards (up to 10 cards each up to 18 relays)	**Specification**	**Comment**
Maximum current per card Number of parallelized cards	200 A 10	With duty cycle D ≤1/50 and t_{PULSE} ≤10 ms
Maximum standoff voltage	2,500 V	
Maximum switching voltage	250 V	
Typical path resistance	20 mΩ	

High Voltage Relay Cards (up to 10 cards each up to 48 relays)	**Specification**	**Comment**
Maximum current per path	1 A	
Maximum standoff voltage	3,000 V	
Maximum switching voltage	1,000 V	
Typical input capacitance	200 pF	

General Relay Cards (up to 20 cards each up to 96 relays)	**Specification**	**Comment**
Maximum current per path	5 A	
Maximum standoff voltage	2,500 V	
Maximum switching voltage	250 V	

Notes: All product data are specified for 1 year at an ambient temperature of 23°C ±5°C (after 1 hour warm-up time).
Product specification and description in this document are subject to change without notice.

VX Instruments GmbH
Phone: +49 871 93 15 55-0
E-Mail: sales@vxinstruments.com

Revision Date: 2018-03-14

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP