ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Ametek / VTI Instruments / VXI Technology VM7004* at our website: *Click HERE*

VM7004

4 channel Programmable Resistor (VMIP™)

- Up to 12 Channels per Single VXIbus C-size Slot
- Message or Register-based Control
- Several Resistance Ranges from 0Ω to 16MΩ
- On-board Scan Lists and Triggering
- Four Modes of Operation
- Ideal for RTD or Other Sensor Simulation
- SCPI Compatible
- VXI*plug&play* Drivers



Overview

The VM7004 provides four independent channels of programmable resistors. It is designed for applications such as RTD or other sensor simulation, process control, and ATE calibration. Three VM7004s can be accommodated in a single C-size card slot, giving the user up to 12 independent channels in a very small footprint.

The VM7004 is part of the VMIP™ family of instruments and can be combined with up to two other modules to form a high-density VXIbus instrument that fully utilizes the capabilities of the VMIP™. For example, when combined with the VM2716A Scanning Voltmeter, current measurements can be made.

Each resistance channel has a four-wire connection which eliminates connector and wiring resistance from critical measurements, maintaining the high accuracy of the VM7004. A four-wire monitor bus is provided giving access to any one of the four resistors at a single port. This feature can be used for station calibration and self-test, allowing the test station to make a four-wire resistance measurement of the programmed value. The monitor bus can also be paralleled across a large number of VM7004s, eliminating the need to add multiplexer switching to measure the resistors.

Word Serial Message-based Data Access: In this mode, the functions are accessed via the VXI message-based interface. The commands are SCPI and IEEE-STD-488.2 compatible. This method of programming and data access is the easiest for the end user.

Programming

Register-based Data Access: This mode offers the fastest data throughput. The data is directly mapped into the VXI user-definable registers, and up to 500 value changes per second can be made (includes 2ms relay setting times).

To reduce programming overhead and improve ease of use, on-board scan lists are provided per channel, along with extensive triggering and programmable delays, thus enabling the VM7004 to scan through resistance values at programmed intervals, simulating transducers with respect to time. The VM7004 can also trigger an external device or another VXIbus card after a channel has been programmed, synchronizing resistance changes to user-defined solutions.

For programming ease, VXI*plug&play* drivers are provided.

Modes of Operation

The VM7004 can be software programmed to operate in four different modes to ease integration by the user.

1. Individual channels. Each channel is programmed individually for a given resistance between 0Ω and 16,383Ω in the standard resistance range.

2. Potentiometer. Two or four channels can be tied externally and programmed to operate as a potentiometer.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

VM7004
4 channel Programmable Resistor (VMIP™)

3. Parallel mode. Two or more channels can be connected externally in parallel, increasing the accuracy and reducing step size. With two channels in parallel the VM7004 can be programmed between 0Ω and 8192Ω in 0.5Ω steps, and with four channels in parallel, between 0Ω and 4096Ω in 0.25Ω steps, in the standard resistance range.

4. Series mode. Two or more channels can be connected in series, increasing the range. With two channels in series the VM7004 can be programmed between 0Ω and 32,768Ω, and with four channels in series, between 0Ω and 65,536Ω in the standard resistance range.

Specifications

Resistance:	0 Ω to16,383 Ω	Standard
	0 Ω to163,830 Ω	Option 5
	0 Ω to1,638,300 Ω	Option 6
	0 Ω to16,383,000 Ω	Option 7
Resolution:	1 Ω step size	Standard
	10 Ω step size	Option 5
	100 Ω step size	Option 6
	1000 Ω step size	Option 7
Accuracy:	±0.02% of programmed value ± 0.5 Ω in standard range	
Maximum Power:	0.5 Watts to 40° Celsius	
Thermal Offset:	≤ ±25µV	
Scan List:	256 values per channel	
Programming Speed:	500 settings/second	
Programmable Delay:	0 to 655 ms	
User Connector:	The user connector is a standard 25 pin female high-density DSUB connector. A mating connector is provided with each unit	

Ordering Information

VM7004	4-channel Programmable Resistor (must be configured with VM9000 host module)
Option 5:	Resistance values on all channels range from 0 to 163,830 Ω
Option 6:	Resistance values on all channels range from 0 to 1,638,300 Ω
Option 7:	Resistance values on all channels range from 0 to 16,383,000 Ω

Online at www.vxitech.com
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com
949 955 1894

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP