

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*



PRODUCTS

PTR-200 Series

ARL Module

Fully Automatic Recoater wit
Integral Linear Proof Teste



The PTR-200-ARL combines both the fully automatic fiber recoater and the linear fiber proof tester into one single module. Since the same set of fiber holding blocks is used to hold the fiber for both recoating and proof testing, only one fiber loading step is required. Once the fiber is loaded, the entire process is automatic. This makes PTR-200-ARL is an ideal recoating / proof testing system for repetitive, high volume optical fiber production processing. The standard recoat mold size on the PTR-200-ARL is 280µm for nominal 250µm coating. Custom mold sizes are available from 200µm and up. The maximum recoat length is two inches (50mm).

Link to: ARL Product Suppo

Other Module Configurations (Link to detailed information n module configurations).

- **MRC** - Manual Fiber Recoater with Auto Injection
- **XLR** - Extended Length Recoater with Auto Injection
- **ARC** - Fully Automated Fiber Recoater
- **RPT** - Rotary Proof Tester / Tension Tester
- **LPT** - Linear Proof Tester
- **MRL**- Combination Manual Recoater & Linear Proof Tester
- **MRR**- Combination Manual Recoater & Rotary Proof Tester
- **ARL** - Combination Automatic Recoater & Linear Proof Tester

PTR-200 SPECIFICATIONS

General Dimensions

Base Module:	H: 5.0" (127mm), W: 10.25" (260mm), D: 5.0" (127mm).
Control Panel:	H: 5.0" (127mm), W: 8.0" (203mm), D: 1.0" (25mm).
External Power Supply:	H: 2.4" (60mm), W: 4.1" (105mm), L: 12.5" (320mm).

Electrical Requirements

Base Module:	12.5 VDC, 13 A. (Provided by external powers supply)
Control Panel:	12.5 VDC, 500 mA. (Provided from base module)
External Power Supply:	Voltage: 100-120 / 200-240 VAC. Current: 4.5 / 2.2 A. Frequency: 47-63 Hz.

Supply Requirements

All Modules Except RPT:	Vacuum for fiber holding blocks. (External vacuum pump available)
Automatic Recoat Modules:	80-120 psi dry compressed air or gas for pneumatic gripper.

Interface

Base Module:	RS-232 Serial Communication.

Recoating	Manual	Automatic
Modules:	MRC, XLR.	ARC, ARL.
Recoat Mold:	Quartz.	Quartz.
Recoat Diameter:	260μm std. for nominal 250μm fiber. Custom sizes from 200μm and up.	280μm std. for nominal 250μm fiber. Custom sizes are available.
Maximum Recoat Length:	2" (50 mm) for MRC Module. 4" (100 mm) for XLR Module.	2" (50 mm) for both Modules.
Recoat Material:	UV Curable Arcylate. DSM 950-200 recommended.	UV Curable Acrylate. DSM 950-200 recommended.
UV Source:	Four 10 W halogen lamps, for MRC. Eight 10 W halogen lamps, for XLR.	Twelve 10 W halogen lamps, ARC/ARL.
Recoat Injection:	Automatic, direct from 1 oz. bottle.	Automatic, direct from 1 oz. bottle.
Recoat Volume:	Programmable in microliters, 5μl typ..	Programmable in microliters, 1.5μl typ..
Recoat Inject Rate:		

	Programmable, up to 1.8µl/s.	Programmable, up to 1.8µl/s.
Inject/Lamp-on Delay Time:	Programmable, 5s typ..	Programmable, 5s typ..
Cure Time:	Programmable, 17s typical.	Programmable, 17s typical.
Mold Cleaning Requirement:	After every recoat.	Start-up and shut-down only.
Mold Open/Close Method:	Manual.	Automatic. (pneumatic gripper)
Total Cycle Time:	60s typ..	45s typ..

Proof Testing	**Rotary**	**Linear**
Modules:	RPT.	LPT, ARL.
Load Application:	Rotating Mandrel.	Linear Fiber Clamp.
Mandrel Diameter:	2" (51mm).	N/A.
Fiber Clamp Length:	N/A.	1.5" (38mm).
Fiber Spacing:	5" (127mm).	2.9" (74mm).
Min. Fiber Length Req.:	17" (432mm).	6" (150mm).
Maximum Load:	20 lbs., 9.1 kg.. >800 kpsi (5.5 Gpa) for 125µm fiber.	4.5 lbs., 2.1 kg.. 235 kpsi (1.6 Gpa) for 125µm fiber.
Accuracy:	+/- 2%.	+/- 2%.
Ramp Rate:	Manual adjust up to 5 lbs/s (2.3 kg/s).	Programmable, up to 5 lbs/s (2.3 kg/s).
Hold Time:	N/A.	Programmable.
Display Units:	lbs, kg, N, kpsi, GPa.	lbs, kg, N, kpsi, GPa.

Back to Main Product Page

VYTRAN CORPORATION

1400 Campus Drive West Morganville, NJ 07751 USA
Tel.: (732) 972-2880 Fax: (732) 972-6229 Email: info@vytran.com

[COMPANY INFO.] [PRODUCTS] [CONTACT US] [PRODUCT SUPPORT] [HOME]

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP