ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Watanabe AM-147-DV-11-1* at our website: ***Click HERE***

✻ RS232C output



■ Features

- Conversion rate 12.5times/sec(50Hz) or 15times/sec(60Hz)
- Four setpoint(Can display two setpoint)
- Maltiple range
- Scaling value and setting value stored 8 pattern
- Peak hold, Valley hold, Peak-valley hold, Digital zero, Moving average(standard)
- Power supply for sensor 24VDC 40mA
- Direct setting function
- Power supply 90 to 264VAC

■ DC Voltage Measurement

Input	Range	Measuring Range	Display Adjustable	Input Impedance	Input Protection
DV	11	±99.9mV	Offset ±9999 Fullscale ±0 to 9999	100MΩ	±250V
	12	±999.9V		100MΩ	±250V
	13	±9.999V		1MΩ	±250V
	14	±99.99V		10MΩ	±500V
	15	±700.0V		10MΩ	±700V
	IV	1 to 5V		1MΩ	±250V

Accuracy: ±(0.03% of rdg + 2 digit)(23°C±5°C 45 to 75% RH)

■ DC Current Measurement

Input	Range	Measuring Range	Display Adjustable	Internal Resistance	Input Protection
DA	23	±9.999mA	Offset ±9999 Fullscale ±0~9999	10Ω	±150mA
	24	±99.99mA		1Ω	±500mA
	25	±999.9mA		0.1Ω	±3A
	2A	4 to 20mA		10Ω	±150mA

Accuracy: ±(0.1% of rdg +2 digit)(23°C±5°C 45 to 75% RH)
±(0.3% rdg +2 digit) for 25 range

■ General specifications

●Measurement block

Input configuration: Single ended
Operation method: Dual slope
Conversion rate: 12.5 time/sec (50 Hz), 15 time/sec (60 Hz)
Noise rejection ratio: NMR more than 50 dB (50/60 Hz)
Temp. coefficient: ±(0.005% of rdg +0.3 digit)/°C
Display: Red LED, 14.2 mm height
Green LED, 8 mm height for setpoint
Polarity display: Automatic "–" display when the computation result is minus
Overrange warning: When input exceeds the maximum display, display 0L or –0L
Maximum display: 0 to ±9999 (4 digit)
Decimal poin: Settable to any digit position (by front sheet switch)
Zero display: Leading zero suppression

●External control block

Hold: Shorted COM terminal and S/H terminal or level "0"
Start: Shorted COM terminal and S/H terminal or level "1"
Digital zero: Shorted COM terminal and DZ terminal or level "0" (displayed zero and that value is stored)

Peak hold
Valley hold: Shorted COM terminal and PH terminal or level "0"
Peak Valley hold
Pattern selection: Any one of 8 patterns is settable in combination of COM terminal and P.SEL terminal 0, 1 and 2
Level "0" : 0 to 1.5V
Level "1" : 3.5 to 5 V
Input current : less than -2 mA

●Comparison block

Control method: Computation by microcomputer
Setting range: -9999 to 0 to +9999 (Including polarity)
Setting condition:

Comparison condition:

Comparison condition	Comparison result
High high limit set value < Measured value	HH
High limit set value < Measured value	HI
High high limit set value Low low limit set value ≧ Measured value ≧ High limit set value Low limit set value	GO
Measured value < Low limit set value	LO
Measured value < Low low limit set value	LL

Comparison relay output: Contact capacity
250 V AC 0.2 A Resistive load
120 V AC 0.5 A Resistive load
28 V DC 1 A Resistive load
Photo coupler output: (NPN) Voltage = Max. 30 V
Current = Max. 50 mA
Saturation voltage = less than 1.2 V at 50 mA
Hysteresis: 1 to 999 digit for each set point
External control: Relay reset
Shorted COM terminal and R.RE terminal or level "0"
Level "0" : 0 to 1.5 V
Level "1" : 3.5 to 5 V
Input current : less than -2 mA

●Common block

Memory backup: EEPROM (rewrite 100,000 times) back up 10 years
Operating temp: 0 to 50°C 35 to 85% RH (No condensation)
Storage temp: -10 to 70°C less than 60% RH
Power supply: 90 to 264 V AC (50 Hz/60 Hz)
Power consumption: Approx 10 VA typ (at 100 V AC)
Dimensions: 96 mm(W) X 348 mm(H) X 3148 mm(D) DIN size
Weight (unit only): Approx 450 g
Dielectric strength: Input/COM, EXC (0 V), comparative output, 500 V DC/1 min.
Input/COM of each output (BCD:FD.COM, ANALOG:-, RS-232C:SG, RS-485)
500 V DC/1 min.
Power supply terminal/input terminal, COM, EXC (0 V), case, comparative output, 1500 V AC/1 min.
Power supply terminal/COM of each output (BCD:D.COM, ANALOG:-, RS-232C:SG, RS-485) 1500 V AC/1 min.
Insulation resistance: 500 V DC more than 100 MΩ at the above terminals
Dielectric noise: Power supply terminal normal/common mode ±1500 V
Power supply for sensor: 24 V DC±10% 40 mA ripple 100 mVp-p
Accessories: Instruction manual
quick manual, setting list, unit label, terminal cover

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

■ Output specifications

●BCD data output (isolated input (Lo))

• At TTL

Measured data:	Tri-stage parallel BCD, Positive logic, latch output
Polarity signal:	Level "1" at minus input
Over signal:	Level "1" at overflow input
Printing command signal:	Positive pulse approx. 20 ms at every measurement completion (available negative logic the above signals)

TTL level, funout 2, CMOS 5V

• At open collector (NPN)

Measured data:	Negative logic transistor "ON" at logic 1
Polarity signal:	Transistor "ON" at minus input
Over signal:	Transistor "ON" at overflow input
Printing command signal:	Transistor "ON" during a period of approx. 20 ms at every measurement completion
Transistor output capacity:	Applied voltage, max. 30V current max. 10 mA saturated output voltage less than 1.2 V at 10 mA
ENABLE:	Shorted ENABLE terminal and D.COM terminal or level "0", Transistor output are OFF (TTL output is high impedance status) Level "0" : 0 to 1.5 V Level "1" : 3.5 to 5 V Input current : less than - 2 mA

●RS-485 (Isolated input (Lo))

Electrical characteristics:	Conforming to EIA RS-485
Communication method:	2-wires system half-duplex (Polling and selecting)
Transmission speed:	2400/4800/9600/19200 bps
Start bit:	1 bit
Data length:	7 bits
Error detection:	Even parity (BCC)
Stop bit:	2 bits
Character code:	ASCII code
Transmission control:	No protocol

Signal name used:

Signal name	Signal	Signal direction
Non-reversible output	+	Input/output
Reversible output	–	Input/output

No. of connectable meter:	Up to 31 meters
Line length:	Up to 500 m in total

●RS-232C (Isolated input (Lo))

Electrical characteristics:	Conforming to EIA RS-232C
Communication method:	Full duplex
Synchronous method:	Start and stop
Transmission speed:	2400/4600/9600/19200 bps
Start bit:	1 bit
Data length:	7 bits
Error detection:	Even parity
Stop bit:	2 bits
Character code:	ASCII code

●Analog output (Isolated input (Lo))

Resolution:	13 bits
Output response:	Less than 0.5S (0 to 90%)

Output	Resistive load	Accuracy (23°C ± 5°C)	Ripple
0 to 10 V	More than 10 kΩ	±0.5% FS	50 mV P-P
4 to 20 mA	0 to 550Ω	±0.5% FS	Less than 0.5%

* Ripple for 4 to 20 mA at resistive load 250Ω, 20 mA


■ Ordering Code

AM-147-□□-□□-□


- Comparator Output { 1. Relay / 2. Photo Coupler
- Output { 1. None / 2. BCD(Open collector) / 3. BCD(TTL) / 4. RS-485 / 5. RS-232C / 6. ANALOG(4 to 20mA) / 7. ANALOG(0 to 10V)
- Power Supply 1. 90 to 264VAC
- Input Range { DV(11,12,13,14,15,1V) / DA(23,24,25,2A)

■ Dimensions


Front



Side




Panel Cutout




Panel thickness 0.8 to 5.0mm

■ Connection Diagram


Upper




Lower



BCD output



RS232C output



ASAHI KEIKI CO.,LTD
Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP