



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Belt Driven Oil-Seal Design Lowers RPM and Maintenance

- Freeze Drying
- Concentrating
- Vacuum Manifold / Schlenk Line
- Degassing
- Vacuum Distillations
- Vacuum Drying



1399N



1400



1405/1402

Specifications

Two - Stage Vacuum Pumps¹

Welch Model	1400	1405	1402	1376	1397
Free Air Displacement					
cfm	0.9	3.2	5.6	10.6	17.7
l/min.	25	90	160	300	500
Ult. Pressure, torr(mbar) ¹	1 x 10 ⁻⁴ (0.00013)	1 x 10 ⁻⁴ (0.00013)	1 x 10 ⁻⁴ (0.00013)	1 x 10 ⁻⁴ (0.00013)	1 x 10 ⁻⁴ (0.00013)
Gas Ballast	Yes	Yes	Yes	Yes	Yes
Pump RPM	580	525	525	525	400
Motor Horsepower (watts)	1/3(250)	1/2(370)	1/2(370)	1(750)	1(750)
Oil Capacity, qt.(liters)	0.62(0.59)	2.25(2.1)	2.25(2.1)	2.5(2.4)	1.25(1.2)
Tubing Needed, I.D. in.	7/16(11)	7/16(11)	13/16(21)	13/16(21)	1-5/8(41)
Intake, Nipple Thread	3/4-20	1-20	1-20	1-20	1.75-20
Exhaust, Thread Type	3/4-20	1-20	1-20	1-20	1.75-20
Weight, lbs. (kg)	58(26)	112(51)	112(51)	156(71)	205(93)
Overall Dimensions					
L in.(cm)	17.8(45.1)	20(51)	20(51)	20(51)	26(66)
W in.(cm)	9(22.9)	12(30.5)	12(30.5)	14.1(35.9)	13.7(34.8)
H in.(cm)	12.6(32.1)	15(38.1)	15(38.1)	15.4(39)	18.8(47.6)
Ship Weight, lbs.(kg)	70(31.8)	132(60)	132(60)	180(81.8)	213(96.8)
Shipping Carton Dimensions LxWxH in.(cm)	20.5x13.8x14.5 (52.1x35.1x36.8)	22.5x15.5x19.5 (57.2x39.4x49.5)	22.5x15.5x19.5 (57.2x39.4x49.5)	22x18x19 (55.9x45.7x48.3)	27.3x18x22 (69.3x45.7x55.9)

Ordering Information^{4, 5, 6.}

Wired for 115V, 60Hz, 1 Ph with N. American 115V Plug	1400B-01 ^{6.}	1405B-01 ^{6.}	1402B-01 ^{6.}	1376B-01	1397B-01
Wired for 230V, 60Hz, 1 Ph with N. American 230V Plug	1400C-01	1405C-01	1402C-01	---	---
Wired for 220V, 50Hz, 1 Ph w/Cont. Euro. (Schuko) Plug	1400C-02	1405C-02	1402C-02	1376C-03	1397C-03
Explosion Proof Motor, 115V, 60 Hz	1400W-01 ^{5.}	1405W-01 ^{5.}	1402W-01 ^{5.}	---	---
3-Phase Motor 230V, 460V, 60Hz	---	---	1402M-01	1376M-01	1397M-01

Notes:

1. Two-stage pumps should not be operated continuously at pressures above 10torr. Ultimate pressure measured with a trapped McCleod gauge.
2. One-stage pumps should not be operated continuously at pressures above 50torr.

3. All 115V and 230V single phase motors include thermal overload protection.
4. Models 1400C-02, 1405C-02 and 1402C-02 provided with CE marking.



1376



1397/1374

	One - Stage Vacuum Pumps ⁵	
	w/o plate	w/bell jar plate
1374	1399	1399N
23	1.2	1.2
650	35	35
1 x 10 ⁻⁴ (0.00013)	1.5 x 10 ⁻² (0.019)	1.5 x 10 ⁻² (0.019)
Yes	No	No
510	750	750
1-1/2(1120)	1/3(250)	1/3(250)
1.25(1.2)	0.5(0.47)	0.5(0.47)
1-5/8(41)	7/16(11)	7/16(11)
1.75-20	3/4-20	3/4-20
1.75-20	3/4-20	3/4-20
220(100)	51(23)	63(28.6)
26(66)	17(43.2)	17(43.2)
13.7(34.8)	9(22.9)	9(22.9)
18.8(47.6)	10(25.4)	10(25.4)
215(97.7)	62(28.2)	74(33.6)
27.3x18x22 (69.3x45.7x55.9)	20.5x13.8x14.5 (52.1x35.1x36.8)	20.5x13.8x14.5 (52.1x35.1x36.8)
1374B-01 ⁵	1399B-01	1399N-01
---	---	---
---	1399C-02	---
---	---	---
1374M-01	---	---

5. Conduit wiring installation required. No cord, plug or switch provided.
6. CSA approved models are 1400B-80, 1405B-80 and 1402B-80.

Exhaust Filter

A replaceable filter element captures oil mist from the exhaust port of the pump and reduces pump noise.



Pump Model	CAT. No.
1399, 1400	1417
1376, 1402, 1405	1417P-10
1397, 1374	1417P-20

(See p. 43 for a complete list of filters)

Exhaust Oil Recycler

Use when pumping continuously above 1 torr. Captures oil mist from the pump, and returns collected oil to the pump via a gas ballast connection.



Pump Model	CAT. No.	CFM
1400	1416H-01	3
1376, 1402, 1405	1416C-01	8

(See p. 43 for a complete list of filters)

Dry Ice/Liquid Nitrogen Trap

Recommended to protect pump from condensable vapors. Use either dry ice slurry or LN2 in the 3 quart center well.



Pump Model	CAT. No.
8890, 8905, 8907, 8912, 8917, 8920, 8925	1420H-14

(See p. 40 for Trap Selection Table)

DuoSEAL™ Vacuum Pump Oil

Tested to high vacuum levels, this oil meets rigid requirements for vapor pressure, stability and viscosity.



Size	CAT. No.
Quart	1407K-11
Gallon	1407K-15
5 Gallon	1407K-20

Gold Vacuum Pump Oil

Specially formulated oil for challenging applications. This highly saturated synthetic oil is resistant to breakdown at higher temperature and is highly stable in chemical environments.



Size	CAT. No.
Liter	8995G-11
Gallon	8995G-15
5 Gallon	8995G-20



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com