

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

WF 3144

C-Series Programmable Resistor Module


The WF 3144 from WireFlow is a 4-channel, 16 bit, programmable resistor module for Compact RIO. Each channel is galvanically isolated, making it ideal for sensor simulation.

The 16 bit resolution is non-linear with finer steps at lower resistance values. It could, for example, be used to emulate a PT100 sensor with a range of 40–180Ω/-150–+200°C with a resolution of 0.1°C.



Application areas

- Resistive sensor simulation;
  Pressure sensors, Thermistors, RTDs etc.
- ATE (Automatic Test Equipment)
- HiL testing (Hardware in the Loop)
- Laboratory testing of electronic control units
- Automated calibration and alignment
- Automation of manual controls



Features

- Four independent, galvanically isolated channels
- Entirely solid-state simulation
- High resolution with non-linear scaling
- Wide resistance range
- Enhanced accuracy mode
- On-board calibration memory
- LabVIEW driver included
- Compatible with NI VeriStand
- Combines permutations of real resistors to achieve desired value

Specifications

Number of channels	4	
Max Voltage	60 V	
Max Power	100 mW/channel	
Range	16 Ω – 160 kΩ	
Max error in Normal mode	R < 100 Ω	0.03%
	R < 1 kΩ	0.1%
	R < 10 kΩ	1%
	R < 160 kΩ	10%
Max error in Enhanced mode	32 Ω < R < 160 kΩ	0,25%
Max update rate	200 Hz	

Isolation Voltages (rated working voltage)

Channel-to-channel, continuous	250 Vrms
Channel-to-earth ground, continuous	250 Vrms

WireFlow AB

Theres Svenssons gata 10
SE-417 55 Göteborg
Sweden

www.wireflow.se

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP