ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Xenotronix HPX60* at our website: *Click HERE*

Xenotronix HPX60 Sealed Lead-Acid Battery Charger

The HPX60 is a two stage, temperature compensated, constant voltage battery charger with current limiting. It is designed to automatically switch to a float charge after the battery is charged. It is protected against reversing the output terminals on a battery and short circuits. Standard models are available for charging 12 V and 24 V batteries and they can be easily modified to charge batteries between 4 V and 48V. The standard voltages will work with most AGM and Gel Cell batteries and can also be custom calibrated to your exact specification. The output current can be adjusted to match your specific battery size. A single stage version is available for charging batteries in applications where there may be a parallel load. A switch is provided for selecting between 115 or 230 V input voltage. Please call or email our technical sales department if you have any questions.

Technical Specifications @ 25 °C (77 °F)

Input Power Requirements
115 or 230 VAC, 50-60 Hz, 0.98 A

Available Charge Current Range
2 A – 4 A for 12 V models
1 A – 2 A for 24 V models

Battery Recommendations
Up to 40 Ah for 12 V, 4 A models
Up to 20 Ah for 24 V, 2 A models

Standard Charge Voltage
14.4 V for 12 V models
28.8 V for 24 V models

Standard Float Voltage
13.6 V for 12 V models
27.2 V for 24 V models

Change from Charge to Float
When current drops to 13% of maximum

Dimensions
6.65” W x 5.3” D x 3.4” H

Weight
7.4 lbs.

Operating Temperature
0 to 35 °C or 32 to 95 °F

Storage Temperature
-40 to 80 °C or -40 to 176 °F

Additional Features:

IEC-60320 power inlet accepts detachable power cords

6’ Power cord with Nema 5-15P plug provided standard

115/230 Volts input selection switch

3’ output cable with insulated battery clips provided standard

User replaceable fuse holder with integral spare fuse

Full metal enclosure to ensure field reliability

Temperature compensated

Custom charge voltages and currents available

Custom output cables available

Single tri-color LED indicator (power/charge/fault)

Private labeling available

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP