



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



DTP41 Series II AutoScan Spectrophotometer

Fast, Affordable,
Versatile, Accurate
Measurement
Solution



Unsurpassed Accuracy

Whether your need is for color calibration, color process control or color management, the DTP41 Series II autoscan spectrophotometer gives exact color measurements. Utilizing spectral technology to measure color with unsurpassed accuracy, the DTP41 Series II provides the most precise and detailed description of color.

Offers Density and Colorimetry Functions

By measuring color with spectral technology, the DTP41 is able to offer a host of functions including density or colorimetry functions. It's wide flexibility has made the DTP41 an instrument of choice by all the major proofing systems, color management software and digital printing manufacturers.

Completely Automated and Widely Supported

Convenience and versatility are synonymous with the DTP41 Series II. It's fully automated to quickly measure a whole row of color information from a color target. It automatically sends the measurement data directly to your color software. Scans take only a few seconds allowing a typical ICC profile target to be scanned in under 10 minutes.

UV, Transmission and Wide Options

The DTP41 Series II offers a UV model to help deal with fluorescent paper brighteners commonly found in proofing papers. Reducing the fluorescent effect from the brighteners, the UV model will assure accurate color measurement on these medias. The transmission model offers dual reflection and transmission capability which is an extremely versatile tool for a variety of applications including photo transparencies, research and testing. Or, extend your reach with our wide version, which accommodates larger media sizes than the standard model.



With the press of a single button, the fully automated DTP41 scans a printed test image. Each scan takes only about 20 seconds, so in just a few minutes you can do everything from verifying color quality to creating full color ICC profiles.

Measure Quickly And Accurately With The DTP4I

With the DTP4I strip-reading spectrophotometer, you get high-end versatility and accuracy without sacrificing speed. In fact, the DTP4I is one of the fastest color measurement instruments on the market—up to 10 times faster than hand-held instruments or expensive robotic measurement devices.

The DTP4I measures an entire row from a printed test image in about 20 seconds. A single scan verifies the quality of your digital or conventional proofing system. Two or three scans usually completes a typical color calibration. And five or six scans is often enough to create a full color management profile.

Designed For Years Of Reliable, User-Friendly Performance

We packed the DTP4I with plenty of features. We also made it extremely easy to use. The instrument arrives ready to go, as there are no menus or difficult set-up procedures. The small footprint fits well in prepress and desktop environments. Plus, our rugged design absorbs those inevitable bumps and jolts without incident.

The true-tracking drive system aboard the DTP4I accepts a variety of media from lightweight copy papers to polyester printing plates. And the entire instrument is easy to troubleshoot and service for years of hassle-free operation.

The DTP4I Works As Part Of A Team

The DTP4I already supports many of today's color management systems. Just plug it into nearly any third-party color management application for colorimetric calibration, profile creation, profile tweaking, and color testing. And it is fully compatible with all major computing platforms, including Macintosh®, Windows, Sun®, and SGI®. With connectivity options including serial or USB, the DTP4I Series II has unbeatable connectivity. Support continues to grow as compatibility is currently being written into even more color software applications.

To ensure color control of your monitor, consider teaming your DTP4I with X-Rite's Monitor Optimizer to control your complete color imaging system. Also fully-compatible with most every color management software solution, it delivers all the accuracy you need to complement the color functionality of the DTP4I.

Specifications

Measuring Geometry

Reflection 45°/0° per ANSI/ISO 5-4 (IT2.17)
Transmission 180°/0° (DTP4I/T model) per ANSI/ISO 5-2 (IT2.19)

Spot Size At Sample

1.8mm (.070 in) in scan direction x 2.5mm (.097 in) wide

Light Source

Gas Pressure @ 2850°K

Spectral Sensor

DRS Technology, 24 point engine, 31 point reporting

Spectral Range

400nm to 700nm

Illuminant Types

A, C, D50, D55, D65, D75, F2, F7, F11 & F12

Standard Observers

2° & 10°

Density Responses

Status T, E, I, & A (plus Status M on DTP4I/T model)

Measurement Time

Approx. 0.25 sec/patch (7mm patch)

Reflection Measurement (DTP4I & DTP4I/T)

Inter-Instrument Agreement

0.3 ΔE cmc avg, typical
(avg. based on 12 BCRA tiles)

Measurement Range

0.00D to 2.50D; 0 to 160% R (reflection)

Repeatability On White

0.2 ΔE max.; ±0.01D max

Linearity

±.01D or 1%

Transmission Measurement (DTP4I/T)

Inter-Instrument Agreement

0.02D or 2% typical, 0 to 3.0D

Measurement Range

0.00D to 5.00D; 0 to 110% T (transmission)

Repeatability

± 0.01D or 1%, 0 to 3.5D (visual)

Media Thickness

0.08mm (0.003 in) to 0.6mm (.025 in) for optimum scanning

Maximum Length Of Sheet

1400mm (55 in) (scanning direction)

Measuring Location (From Edge)

Columns of patches must fall within 100mm (4 in) insertable area on standard model, and within 225mm (9 in) insertable area on DTP4I/W9 model. Built-in guide for 35mm film

Minimum Patch Dimensions

7.0mm (.28 in) high in scan direction
12mm (.47 in) width recommended

Patch Quantities

1 minimum, 100 maximum per pass

Recommended Leader Length

38mm (1.5 in)

Minimum Footer Length

Greater of 30mm or 2 patch + 2 gap heights

Data Interface

RS-232 serial interface with baud rates from 1200 to 57.6k
communication USB

Power Required

12v DC, Universal 100–240 VAC;
50–60 Hz adapter; 30W

Calibration

Calibration strips as needed

Environmental

+10° (50°F) to +40°C (104°F) operating
30% to 85% RH non condensing

Warm-up Time

None

Physical Dimensions

Height: 88mm (3.45 in)
Width: 184mm (7.25 in)
Depth: 114mm (4.5 in)

Weight

890g (1.96 lb), DTP4I/T 1090g (2.40 lb)

Accessories Provided

Calibration Reference
Interface Cable: DB9 RS-232 and/or USB
AC Adapter

X-Rite calibration references are traceable to the National Institute of Standards and Technology through Munsell Color Science Laboratory RT.

This product is covered by U.S. and foreign Patents and Patents Pending. Specifications and design subject to change without notice.

ISO 9001
Certified

INFORMATION PROVIDED IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. The user assumes the entire risk as to the accuracy and the use of this information. All text must be copied without modification and all pages must be included. All components of this information must be distributed together. This information may not be distributed for profit. X-Rite® are registered trademarks of X-Rite, Incorporated. Other brand and product names are trademarks of their respective holders. All trademarks may be registered in the United States and/or other countries. Product design and specifications subject to change without notice.
© X-Rite, Incorporated 2006.

X-RITE GLOBAL HEADQUARTERS

Grandville, Michigan USA • +1 616 534-7663 • +1 800 248-9748 • FAX +1 616 534-8960

L11-044 (07/06)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisanTG.com



xrite.com



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com