

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Yamaha DP-5F* at our website: ***Click HERE***

DP-F standard pump series : Air switching type

DP-F Series

The DP-F Series pump range offers 5 different sized models of clean room menufactured process pumps suitable for high purity and corrosive applications. Utilizing the patented Yamada C-Spool these pumps are simple and easily installed into a process system.

DP-5F



DP-10F



DP-20F

DP-25F



DP-38F

Specification

Model name		DP-5F※1	DP-10F		DP-20F		DP-25F ※2	DP-38F ※2
Nominal port size		1/4″(8A)	3/8″（10A）		3/4″（20A）		1″（25A）	1″（25A）
Connection to liquid	Inlet	Rc1/4（F）	Rc3/8（F） ※3	JIS 10A flange or equivalent	Rc3/4（F） ※3	JIS 20A flange or equivalent	JIS 25A flange or equivalent	
	Outlet							
（）※5	Inlet （）	Rc1/4（F）					Rc3/8（F）	Rc1/2（F）
	Exhaust	Rc3/8（F） (silencer contained)	Rc3/8（F） (silencer contained)				Rc3/4（F） (silencer contained)	
	Wetted body	Fluoric resin （PTFE（PFA）						
	Diaphragm,	Fluoric resin						

Material	Valve, Seat	□PTFE□						
	Non Wetted body	PPS resin	Polypropylene □PP□			High-density polyethylene □HDPE□		
Air supply pressure range		0.2□0.5MPa				0.2□0.7MPa		
Max discharge pressure		0.5MPa				0.7MPa		
Discharge volume/cycle※4		13□L	65□L		150□L	300□L	700□L	
Max discharge volume※6		11L/min	27L/min		54L/min	64L/min	95L/min	
Max air consumption		170 L/min(ANR)	250 L/min(ANR)		350 L/min(ANR)	900 L/min(ANR)	1500 L/min(ANR)	
Max slurry diameter※7		—	1mm or smaller		2mm or smaller	3mm or smaller		
Viscosity limit		0.5Pa-s or lower	1Pa-s or lower		2Pa-s or lower	2.5Pa-s or lower		
Environmental temperature range	Ambient temperature range	0□70℃						
	Liquid temperature range	0□80℃						
Noise level		71□B	82□B		85□B	88□B	90□B	
Weight		3.4□□	6.7□□	7.2□□	14.6□□	15.5□□	32□□	52□□

※1□The DP-5F valve is a flat (plate) type.

※2□Since a DP-25F and a DP-38F are to be produced on orders, be sure to check the delivery date.

※3□The suction inlet or discharge outlet of a DP-10F/20F pump can be connected with an NPT screw orANSI flange (custom-designed) as well as a standard RC screw or flange.

※4□The maximum discharged liquid amount and/or self-suction capability are based on the test datameasured with using fresh water at the room temperature (20oC). In addition, the amount of dis-charged liquid varies depending on the supplied air pressure or pump head. Please check the per-formance curve for details.

※5□Use the clean air that has passed through a 1-μm filter or nitrogen gas (N2) as air to be supplied tothe pump.

□When you use a resin pump, it may not offer the designed performance due to significant change oftemperature. To maintain its performance, be careful to install the pump or store its parts.

□Any flat valve type of pumps cannot handle slurry.

Exploded view and Parts list

Valve type	Connection		
	Pump size	Screw□PT□	Flange
Ball	5	—	—
	10	853620	853622
	20	853621	853623
	25	—	853601
	38	—	853606
Flat	5	853656	—
	10	853628	853630
	20	853629	853631
	25	—	853614
	38	—	853617

Dimensions□Performance Curve

Dimensions □PDF)	**Performance Curve □PDF□**

DP-5F	DP-5F□FH
DP-5FH	
DP-10F(Rc)	DP-10F
DP-10F(Flange)	
DP-20F(Rc)	DP-20F
DP-20F(Flange)	
DP-25F	DP-25F
DP-38F	DP-38F

Manuals, CAD datas

Model	Operation manual (PDF)	Maintenance manual (PDF)	CAD data □DXF□
DP-5F	NDP 209U-12	NDP 032M-14	DP-5F(PT)
DP-5FH			DP-5FH
DP-10F			DP-10F(PT) DP-10F(FL)
DP-20F			DP-20F(PT) DP-20F(FL)
DP-25F			DP-25F(FL)
DP-38F			DP-38F(FL)

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP